

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Drone Shadow Wing 15.85inch operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 5.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 5.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 103.2dB μ V/m at 3m in the frequency 2440MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = 7.97dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 99.1dB μ V/m at 3m in the frequency 2468MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = 3.87dBm
which is within the production variation.

The maximum conducted output power specified is 8dBm= 6.310mW

The source- based time-averaging conducted output power
=6.310mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt (2.468) mW
= 9.55 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: R6Z202501B2R