

TEST REPORT

FCC RULES Part 90, Part 2

Class II Permissive Change

Report File No. : STROR-05-052

Date of Issue : Dec. 15, 2005

Kind of Product : FM Handheld Transceiver

Model Name : IS100

Manufacturer : E-TECH Co., Ltd.

Serial No. : -

Test Result : Complied

Note: This report shall not be reproduced except in full, without the written approval of SGS Testing Korea Co., Ltd. This document may be altered or revised by SGS Testing Korea Co., Ltd. Personnel only, and shall be noted in the revision section of the document

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435 -040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

VERIFICATION OF COMPLIANCE

Applicant : E-TECH Co., Ltd.
Kind of Product : FM Handheld Transceiver
Brand Name : Iris
Model Name : IS100
Model Difference : -
Report File No. : STROR-05-052
Date of test : Nov. 28, 2005 ~ Dec. 15, 2005
Receiver EUT : -

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC RULES Part 90, Part2	Complied

The above equipment was tested by SGS Testing Korea Co., Ltd. for compliance with the requirements set forth in the FCC RULES PARTS Part90, Part2. The results of testing in this report apply to the product system that was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Date

Dec. 15, 2005

Feel Jeong

Approved By



Date

Dec. 15, 2005

Albert Lim

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

INDEX

<u>CONTENTS</u>	<u>Page</u>
1. General Description of EUT - - - - -	<u>4</u>
2. General Information of EUT - - - - -	<u>4</u>
3. Item of the Modification - - - - -	<u>4</u>
4. Test Procedure - - - - -	<u>5</u>
 Test Results	
5. Radiated Spurious Emissions - - - - -	<u>6</u>
6. Attachment A ? Photos of the Test Setup - - - - -	<u>18</u>
7. Attachment B ? Photos of the EUT - - - - -	<u>19</u>

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

1. General Description of EUT

IS100 has a compact size with a various features in range of 136.025-173.975 MHz. IS100 has a various features shown as below

IS100 constructed with a microprocessor controlled, temperature compensated Phase Locked Loop (PLL) frequency synthesizer. A special integrated circuit provides supports to sub-audible signaling(CTCSS & DCS) and most of the receiving parts are switched off periodically in the power save mode to battery current drain standby.

2. General Information of EUT

Transceiver

Power Supply	DC 7.5V (lithium type of battery)
Operating Frequency	136.025 MHz –173.975 MHz
Transmit Power	1 W(low)/5 W(high)
Modulation of Channels	FM
Channel spacing	12.5 kHz and 25 kHz
Emission	8K5F3E/ 16K 0F3E
Communication method	Simplex
Number of Channels	255channels
Antenna Type	External

3. Modifications to made

Following modifications are made from IP100 model(FCC ID: R72IP100).

- External button SW604 and SW606 was deleted.
- Enclosure structure was little bit changed because external function button is changed from 6 button to 4 button.
- PCB artwork of Button part of Logic board is changed to assist 4 button.
- Pull-up resistor R652 (390K) of Logic board was deleted.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

4. Test Procedure


The test procedure are performed following the test stands ANSI/EIA -603, if applicable.

4.1 Radiated Spurious Emissions FCC 2.1053, FCC 90.210

Radiated spurious emissions are emissions from the EUT when transmitting in non-radiating load on frequencies outside the operating band.

ERP measurement of spurious emission the general substitution method as described at 2.4.2.

In order to suppress inter-modulation products in the spectrum analyzer a notch filter is used, if applicable.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

5. Radiated Spurious Emissions FCC 2.1053(a), FCC 90.210

TX FREQ=136.025 MHz

Low Power Setting

Channel Spacing 12.5 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
272.05	V	< -30	-20	>10
408.08	V	< -30	-20	>10
544.10	H	< -30	-20	>10
680.13	H	< -30	-20	>10
816.15	V	< -30	-20	>10
952.18	V	< -30	-20	>10
1088.2	V	< -30	-20	>10
1224.23	V	< -30	-20	>10
1360.25	V	< -30	-20	>10

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 136.025 MHz

High Power Setting

Channel Spacing 12.5 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
272.05	V	< -30	-20	>10
408.08	H	< -30	-20	>10
544.10	V	< -30	-20	>10
680.13	H	< -30	-20	>10
816.15	H	< -30	-20	>10
952.18	V	< -30	-20	>10
1088.2	H	< -30	-20	>10
1224.23	V	< -30	-20	>10
1360.25	V	< -30	-20	>10

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE =136.025 MHz Low Power Setting

Channel Spacing 25 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
272.05	V	< -30	-13	>17
408.08	V	< -30	-13	>17
544.10	V	< -30	-13	>17
680.13	H	< -30	-13	>17
816.15	V	< -30	-13	>17
952.18	V	< -30	-13	>17
1088.2	V	< -30	-13	>17
1224.23	V	< -30	-13	>17
1360.25	V	< -30	-13	>17

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE =136.025 MHz High Power Setting

Channel Spacing 25 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
272.05	V	< -30	-13	>17
408.08	V	< -30	-13	>17
544.10	V	< -30	-13	>17
680.13	H	< -30	-13	>17
816.15	H	< -30	-13	>17
952.18	V	< -30	-13	>17
1088.2	V	< -30	-13	>17
1224.23	V	< -30	-13	>17
1360.25	V	< -30	-13	>17

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 155.025 MHz

Low Power Setting

Channel Spacing 12.5 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
310.05	H	< -30	-20	>10
465.08	V	< -30	-20	>10
620.10	V	< -30	-20	>10
775.13	H	< -30	-20	>10
930.15	V	< -30	-20	>10
1085.18	V	< -30	-20	>10
1240.20	V	< -30	-20	>10
1395.23	V	< -30	-20	>10
1550.25	V	< -30	-20	>10

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 155.025 MHz

High Power Setting

Channel Spacing 12.5 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
310.05	H	< -30	-20	>10
465.08	V	< -30	-20	>10
620.10	V	< -30	-20	>10
775.13	H	< -30	-20	>10
930.15	V	< -30	-20	>10
1085.18	V	< -30	-20	>10
1240.20	V	< -30	-20	>10
1395.23	V	< -30	-20	>10
1550.25	V	< -30	-20	>10

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 155.025 MHz

Low Power Setting

Channel Spacing 25 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
310.05	V	< -30	-13	>17
465.08	V	< -30	-13	>17
620.10	H	< -30	-13	>17
775.13	H	< -30	-13	>17
930.15	V	< -30	-13	>17
1085.18	V	< -30	-13	>17
1240.20	V	< -30	-13	>17
1395.23	V	< -30	-13	>17
1550.25	H	< -30	-13	>17

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 155.025 MHz

High Power Setting

Channel Spacing 25 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
310.05	H	< -30	-13	>17
465.08	V	< -30	-13	>17
620.10	V	< -30	-13	>17
775.13	H	< -30	-13	>17
930.15	V	< -30	-13	>17
1085.18	V	< -30	-13	>17
1240.20	V	< -30	-13	>17
1395.23	V	< -30	-13	>17
1550.25	V	< -30	-13	>17

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 173.975 MHz

Low Power Setting

Channel Spacing 12.5 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
347.95	H	< -30	-20	>10
521.93	H	< -30	-20	>10
695.90	H	< -30	-20	>10
869.88	V	< -30	-20	>10
1043.85	V	< -30	-20	>10
1217.83	V	< -30	-20	>10
1391.80	V	< -30	-20	>10
1565.78	V	< -30	-20	>10
1739.75	V	< -30	-20	>10

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 173.975 MHz

High Power Setting

Channel Spacing 12.5 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
347.95	V	< -30	-20	>10
521.93	V	-27.9	-20	7.9
695.90	V	-29.6	-20	9.6
869.88	V	< -30	-20	>10
1043.85	V	< -30	-20	>10
1217.83	V	< -30	-20	>10
1391.80	V	< -30	-20	>10
1565.78	V	< -30	-20	>10
1739.75	V	< -30	-20	>10

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 173.975 MHz

Low Power Setting

Channel Spacing 25 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
347.95	V	< -30	-13	>17
521.93	V	< -30	-13	>17
695.90	V	< -30	-13	>17
869.88	V	< -30	-13	>17
1043.85	H	< -30	-13	>17
1217.83	H	< -30	-13	>17
1391.80	V	< -30	-13	>17
1565.78	V	< -30	-13	>17
1739.75	V	< -30	-13	>17

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

TX FREQE = 173.975 MHz

High Power Setting

Channel Spacing 25 kHz

Frequency [MHz]	Polarization	Max. Power Value [dBm]	Specification Limit [dBm]	Margin [dB]
347.95	V	< -30	-13	>17
521.93	V	-28.4	-13	15.4
695.90	H	-28.9	-13	15.9
869.88	V	< -30	-13	>17
1043.85	V	< -30	-13	>17
1217.83	H	< -30	-13	>17
1391.80	V	< -30	-13	>17
1565.78	V	< -30	-13	>17
1739.75	V	< -30	-13	>17

Test Equipment Used

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum analyzer	H/P	8593E	Sep. 2006
Signal Generator	Agilent	8648D	May 2006
Dipole Antenna	Schwarzbeck Mess	VHAP	May 2006
Amplifier	Sonoma Instrument	305	Jun.2006
Dummy Load	BIRD	8404	Dec. 2006
Horn Antenna	Schwarzbeck	9120D	Sep. 2006
Horn Antenna	Electro-Metrics	RGA-60	Apr. 2006
Biconical Antenna	Schwarzbeck	VHA9103	Mar. 2006
Log-periodic Antenna	Schwarzbeck	UHALP9107	May 2006
Anechoic Chamber	Seo Young EMC	-	-


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr

6. Attachment A – Photos of the test setup



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd. 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.sgstesting.co.kr