



Certification Exhibit

FCC ID: R7PNG1R1S1

FCC Rule Part: 47 CFR Part 2.1091

Project Number: 72127440

Manufacturer: Landis+Gyr Technology, Inc.
Model: NIC AM

RF Exposure

General Information:

Applicant: Landis+Gyr
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Whip
 Antenna Gain: 5 dBi
 Maximum Transmitter Conducted Power: 29.13 dBm, 818.46 mW
 Maximum System EIRP: 34.13 dBm, 2588.21 mW
 Exposure Conditions: 28 centimeters or greater

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm ²)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm ²)
902.3	29.13	0.60	818.46	5	3.162	28	0.263