

Würth Elektronik eiSos GmbH & Co. KG
Wireless Connectivity
Max-Eyth-Straße 1
74638 Waldenburg



SAR Test exclusion documentation according to FCC KDB 44798, RSS-102 and EN 62479

2621011024000

September 3, 2025

Certification numbers and labeling requirements	
IC number	5136A-2101102
HVIN (Hardware Version Identification Number)	2101102
PMN (Product Marketing Name)	2101102
FVIN (Firmware Version Identification Number)	-
HMN (Host Marketing Name)	-

Information how the EIRP was derived is demonstrated in the test reports referenced in this filing.

EUT technologies:

Technologies:	Max. power: (AVG)	Max. gain:	Min. pathloss:
Bluetooth LE	Declared 8 dBm Measured: +4.5 dBm	Measured: -3.4 dBi	0 dB (if applicable)

Bluetooth LE test results see Test Report Reference 1-9394-25-03-10_TR1-R01

FCC: SAR test exclusion according to KDB447498 General RF Exposure Guidance v06

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff. a)
For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, it must hold that

$$\frac{P_{(\text{mW})}}{d_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

for 1-g SAR and

$$\frac{P_{(\text{mW})}}{d_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 7.5$$

for 10-g extremity SAR, where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- $P_{(\text{mW})}$ is the power which is rounded to the nearest mW before calculation
- $d_{(\text{mm})}$ is distance which is rounded to the nearest mm before calculation

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

f [MHz]	d separation [mm]	Threshold 1-g	Powerlimit [mW]	P max-measured [mW]	Exclusion
2450	5	3	9.58	6.456	yes

ISED: SAR test exclusion according to RSS-102 Issue 6

Section 6.3 Table 11

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

f [MHz]	d separation [mm]	Tissue volume	Powerlimit [mW]	P max-measured [mW]	Exclusion
2450	10	1 g	7	6.456	yes

FCC: SAR test exclusion according to EN 62479

Compliance is given according to EN 62479 because the output power of the DUT is smaller than 20 mW.