

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

**Test Report acc. to FCC Title 47 CFR Part 15
Relating to
AMBER wireless GmbH
AMB9625**

**Title 47 - Telecommunication
Part 15 - Radio Frequency Devices
Subpart C – Intentional Radiators
Measurement Procedure:
ANSI C63.4-2014
ANSI C63.10-2013**



EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

MANUFACTURER	
Manufacturer name	AMBER Wireless
Manufacturer's grantee code	R7T
Manufacturer's address	Rudi-Schillings-Str. 31
Phone	+49 (0) 651 99355 0
Fax	+49 (0) 651 99355 69
Email	gudrun.eckhardt@amber-wireless.de

TESTING LABORATORY	
Test engineer	Mr. Ralf Trepper
Testing laboratory name	m. dudde hochfrequenz-technik
Testing laboratory address	Rottland 5a, 51429 Bergisch Gladbach, Germany
Phone	+49 (0) 2207 96890
Fax	+49 (0) 2207 968920
Email	m.duddelabor@dudde.com

RELEVANT STANDARD	
Title	47 - Telecommunication
Part	15 - Radio Frequency Devices
Subpart	Subpart C – Intentional Radiators – Section 15.249
Measurement procedure	ANSI C63.4-2014 & ANSI C63.10-2013

EQUIPMENT UNDER TEST (EUT)	
Equipment category	Intentional Radiator
Trade name	---
Type designation	AMB9625
Serial no. of Module	086006391 086006395 086006394
Variants	---
Hosts	ART No. RMS-MLOG-T-915 ART No. RMS-GW-915 ART No. RMS-LOG-915

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

1. Test results

Clause	Requirements headline	Test result			Page number
8.1	Antenna requirement	Pass	Fail	N.t.*	9
8.2	Conducted limits	Pass	Fail	N.t. ³	10 – 12
8.3	Restricted bands of operation	Pass	Fail	N.t.*	13 – 14
8.4	Radiated emission limits, general requirements	Pass	Fail	N.t.*	15 – 19
8.5	Field strength limits of fundamental frequencies and harmonics	Pass	Fail	N.t.*	20 – 23
8.6	Bandwidth	Pass	Fail	N.t.*	24 – 25

* Not tested

The equipment passed all the conducted tests	Yes	No
--	-----	----

Signature		
Name	Mr. Ralf Trepper	Mr. Manfried Dudde
Designation	RF Test Engineer	Laboratory-Manager
Date of issue	2017-08-25	2017-08-25

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Table of contents

1. Test results	3
2. Introduction.....	5
3. Testing laboratory	5
4. Applicant	6
5. Product and product documentation	6
6. Conclusions, observations and comments	7
7. Operational description.....	8
8. Compliance assessment	9
8.1 Antenna requirement	9
8.1.1 Regulation	9
8.1.2 Result	9
8.2 Conducted limits	10
8.2.1 Regulation	10
8.2.2 Test procedures.....	11
8.2.3 Result	11
8.3 Restricted bands of operation	13
8.3.1 Regulation	13
8.3.2 Result	14
8.4 Radiated emission limits, general requirements	15
8.4.1 Regulation	15
8.4.2 Test procedure.....	16
8.4.3 Calculation of the field strength	17
8.4.4 Result	18
8.5 Field strength limits of fundamental frequencies and harmonics	20
8.5.1 Regulation	20
8.5.2 Test procedure.....	21
8.5.3 Calculation of the average correction factor	22
8.5.4 Calculation of the field strengths.....	22
8.5.5 Result	23
8.6 Bandwidth (20 dB)	27
8.6.1 Regulation	27
8.6.2 Test procedure.....	27
8.6.3 Result	28
9. Additional information to the test report	29
10. List of test equipment	30
11. List of test cables.....	31

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

2. Introduction

This test report **is not an expert opinion** and consists of:

- Test result summary
- List of contents
- Introduction and further information
- Performance assessment
- Detailed test information

All pages have been numbered consecutively and bear the m. dudde hochfrequenz-technik logo, the test report number, the date, the test specification in its current version as well as the type designation of the EUT. The total numbers of pages in this report is **32**.

The tests were carried out in a representative assembly and in accordance with the test methods and/or requirements stated in:

FCC Title 47 CFR Part 15 Subpart C Section 15.249 & ANSI C63.4-2014 & ANSI C63.10-2013

The sample of the product was received on:

- 2017-07-07

The tests were carried out in the following period of time:

- 2017-07-31 - 2017-08-08

3. Testing laboratory

m. dudde hochfrequenz-technik,
Rottland 5a,
D-51429 Bergisch Gladbach
Germany

Phone: +49 - (0) 22 07 / 96 89-0
Fax: +49 - (0) 22 07 / 96 89-20

FCC Registration Number: 699717

Accredited by:

DAkkS Deutsche Akkreditierungsstelle GmbH
DAkkS accreditation number: D-PL-12053-01-00

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

4. Applicant

Company name : AMBER wireless GmbH
 Address : Rudi-Schillings-Str. 31
 54296 Trier
 Country : Germany
 Telephone : +49 (0) 651 99355 0
 Fax : +49 (0) 651 99355 69
 Email : Gudrun.eckhardt@amber-wireless.de
 Date of order : 2017-06-07
 References : Ms. Gudrun Eckhardt

5. Product and product documentation

Samples of the following apparatus were submitted for testing:

Manufacturer : AMBER wireless
 Trademark : ---
 Type designation : AMB9625
 Serial number of Module : 086006391 || 086006395 || 086006394
 Serial number of Host Device : 915000022 || 915000001 || 915000014
 Hardware versions : ---
 Variants : ---
 Software release : ---
 Type of equipment : Intentional Radiator
 Power used : 3.3 V DC (RMS-LOG-915 and RMS-GW-915)
 : 3.6 V DC (RMS-MLOG-T-915)
 Frequency used : 902.5 MHz – 927.5 MHz
 Generated or used frequencies : 32.769 kHz, 40 MHz (crystal),
 902.5 MHz, 915.0 MHz and 927.5 MHz (carrier)
 ITU emission class : 79K3F1D
 FCC ID : R7TAMB9625

For issuing this report the following product documentation was used:

Title	Description	Version
---	---	---

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

For issuing this report the following product documentation was used:

Description	Date	Identifications
External photographs of the Equipment Under Test (EUT)	2017-08-25	Annex no. 1
Internal photographs of the Equipment Under Test (EUT)	2017-08-25	Annex no. 2
Channel occupancy / bandwidth	2017-08-25	Annex no. 3
Label sample	2017-08-25	Annex no. 4
Functional description / User Manual	2017-08-25	Annex no. 5
Test setup photos	2017-08-25	Annex no. 6
Block diagram	2017-08-25	Annex no. 7
Operational description	2017-08-25	Annex no. 8
Schematics	2017-08-25	Annex no. 9
Parts list	2017-08-25	Annex no. 10

6. Conclusions, observations and comments

The test report will be filed at m. dudde hochfrequenz-technik for a period of 10 years following the issue of this report. It may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of m. dudde hochfrequenz-technik.

The results of the tests as stated in this report are exclusively applicable to the EUT as identified in this report. m. dudde hochfrequenz-technik cannot be held liable for properties of the EUT that have not been observed during these tests.

m. dudde hochfrequenz-technik assumes the sample to comply with the requirements of FCC Title 47 CFR Part 15 for the respective test sector, if the test results turn out positive.

Comments: ---

Date	: 2017-08-25	Date	: 2017-08-25
Name	: Ralf Trepper	Name	: Manfried Dudde
Function	: RF Test Engineer	Function	: Laboratory Manager
Signature	: 	Signature	: 

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

7. Operational description

7.1 EUT details

The module is designed as radio sub module for wireless communication between devices such as control systems, remote controls, sensors etc. It offers several addressing modes and relieves the host system of radio-specific tasks.

7.2 EUT configuration

The EUT is connected to typical voltage as declared by the customer and then connected to laptop via USB cable provided by customer. The EUT is then configured to the required frequency using the test software (**HTerm 0.8.1beta**) provided by the customer.

7.3 EUT measurement description

Radiated measurements

The EUT was tested in a typical fashion. During preliminary emission tests the EUT was operated in the continuous measuring mode for worst case emission mode investigation. Therefore, the final qualification testing was completed with the EUT operated in continuous measuring mode. All tests were performed with the EUT's typical voltage: 3.3 V DC and 3.6 V DC, depending on which host device is tested.

In order to establish the maximum radiation, firstly, there have been viewed all orthogonal adjustments of the test samples, secondly the test ample have been rotated at all adjustments around the own axis between 0° and 360°, and thirdly, the antenna polarization between horizontal and vertical had been varied.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8. Compliance assessment

8.1 Antenna requirement

8.1.1 Regulation

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

8.1.2 Result

Antenna Type	Frequency	Gain	Number of Antennas
Wire Antenna ^{*1}	902.5 – 927.5 MHz	2.15 dBi	1
Helical Antenna ^{*2}	902.5 – 927.5 MHz	2.00 dBi	1

^{*1} RMS-MLOG-T-915

^{*2} RMS-GW-915 and RMS-LOG-915

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.:2
---	-----	----	-------------

N.t.* see clause: 9

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.2 Conducted limits

8.2.1 Regulation

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H /50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Conducted Limits		
Frequency of Emission	Quasi-Peak (QP)	Average (AV)
MHz	dB μ V	dB μ V
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 -30	60	50

*Limit Decreases with the logarithm of the frequency

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

- 1) For carrier current system containing their fundamental emission within the frequency band 535–1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.
- (2) For all other carrier current systems: 1000 μ V within the frequency band 535–1705 kHz, as measured using a 50 μ H /50 Ω LISN.
- (3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.2.2 Test procedures

The EUT and the additional equipment (if required) are connected to the main power through a line impedance stabilization network (LISN). The LISN must be appropriate to ANSI C63.4-2014 Section 7.

Additional equipment must also be connected to a second LISN with the same specifications described in the above section (if required).

8.2.3 Result

Conducted emissions (Section 15.207) - Tested with external AC power supply								
Tested Line	Frequency	Bandwidth	QP Value	QP Limit	Margin	AV Value	AV Limit	Margin
L1 / N	MHz	kHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
Measurement uncertainty < \pm 2 dB								

Test Cables used	---
Test equipment used	---

The equipment passed the conducted tests	Yes	No	N.t. ³
--	-----	----	-------------------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	-----	----	------------

N.t.* see clause: 9

Date: 2017-01-16

Created: P6

Reviewed: P9

Released: P1

Vers. no. 1.17

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Conducted emissions (Section 15.207) - Tested with a Laptop over USB / LAN port								
Tested Line	Frequency	Bandwidth	QP Value	QP Limit	Margin	AV Value	AV Limit	Margin
L1 / N	MHz	kHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
		9						
Measurement uncertainty < \pm 2 dB								

Test Cables used	---
Test equipment used	---

The equipment passed the conducted tests	Yes	No	N.t. ³
--	-----	----	-------------------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	-----	----	------------

N.t.* see clause: 9

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.3 Restricted bands of operation

8.3.1 Regulation

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Restricted bands of operation			
Frequency Band	Frequency Band	Frequency Band	Frequency Band
MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	² (²)
13.36 - 13.41	---	---	---

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR Quasi-Peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e), regardless of the field strength limits specified elsewhere in this Subpart, the provisions of this Section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this Section:

(1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a), the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a), and the fundamental emission is outside of the bands listed in paragraph (a) more than 99% of the time the device is actively transmitting, without compensation for duty cycle.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

(2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.

(3) Cable locating equipment operated pursuant to Section 15.213.

(4) Any equipment operated under the provisions of § 15.253, § 15.255 or § 15.256 in the frequency band 75-85 GHz, or § 15.257 of this part

(5) Biomedical telemetry devices operating under the provisions of Section 15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.

(6) Transmitters operating under the provisions of Subpart D or F of this part.

(7) Devices operated pursuant to § 15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.

(8) Devices operated in the 24.075-24.175 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in § 15.245(b).

(9) Devices operated in the 24.0-24.25 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in § 15.245(b).

(10) White space devices operating under subpart H of this part are exempt from complying with the requirements of this section for the 608-614 MHz band.

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of Section 15.245 shall not exceed the limits specified in Section 15.245(b).

8.3.2 Result

Test Cables used	K1a, K40, K56, K83, K84, K51, K52		
Test equipment used	103, 166a, 171a, 406, 23, 445a		

The equipment passed the conducted tests	Yes**	No	N.t.*
--	-------	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	-----	----	------------

**All emissions fall under restricted band are included in clause 8.4 and 8.5, and are marked blue!

N.t.* see clause: 9

8.4 Radiated emission limits, general requirements

8.4.1 Regulation

(a) Emissions radiated outside of the specified frequency bands in this part, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation. The general radiated emission limits are specified in the following table:

Intentional radiator- radiated emission limits		
Frequency	Field Strength	Measurement distance
MHz	µV / m	m
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 ^{**}	3
88-216	150 ^{**}	3
216-960	200 ^{**}	3
above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

(b) In the emission table above, the tighter limit applies at the band edges.

(c) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

(e) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(f) In accordance with Section 15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in Section 15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in Section 15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in Section 15.109 that are applicable to the incorporated digital device.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.4.2 Test procedure

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8 m above the ground. The turn table would be allowed to rotate 360° to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna is changed in horizontal and vertical polarization; the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4-2014 Section 8 “Radiated Emissions Testing”

Measurement procedures for electric field radiated emissions from 9kHz - 1 GHz & 1 GHz - 40 GHz are covered in Clause 8 of ANSI C63.4-2014. The ANSI C63.4-2014 measurement procedure consists of both an exploratory test and a final measurement. The exploratory test is critical to determine the frequency of all significant emissions. For each mode of operation required to be tested, the frequency spectrum is monitored. Variations in antenna height, antenna orientation, antenna polarization, EUT azimuth, and cable or wire placement is explored to produce the emission that has the highest amplitude relative to the limit.

The final measurements are made based on the findings in the exploratory testing. When making exploratory and final measurements it is necessary to maximize the measured radiated emission. Sub clause 8.3.2 of ANSI C63.4-2014 states that the measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” We consider the “cone of radiation” to be the 3 dB beam width of the measurement antenna.

While the “bore-sighting” technique is not explicitly mentioned in ANSI C63.4-2014, it is a useful technique for measurements using a directional antenna, such as a double-ridged waveguide antenna. Several precautions must be observed, including: knowledge of the beam width of the antenna and the resulting illumination area relative to the size of the EUT, estimation for source of the emission and general location within larger EUTs, measuring system sensitivity, etc.

ANSI C63.4-2014 requires that the measurement antenna is kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. That means that if the directional radiation pattern of the EUT results in a maximum emission at an upwards angle from the EUT, when a directional antenna is used to make the measurement it will be necessary for it to be pointed towards the source of the emission within the EUT. This can be done by either pointing the antenna at an angle towards the source of the emission, or by rotating the EUT, in both height and polarization, to maximize the measured emission. The emission must be kept within the illumination area of the 3 dB beamwidth of the antenna so that the maximum emission from the EUT is measured.

The measurement procedure for harmonics and spurious emissions above 40 GHz is taken from ANSI C63.10-2013.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Radiated emissions test characteristics	
Frequency range	9 kHz – Above 960 MHz
Test distance	3 m*
Test instrumentation minimum resolution bandwidth	9 kHz (Below 30 MHz) 120 kHz (30 MHz - 1,000 MHz) 1 MHz (Above 1000 MHz)
Detector Type	Quasi peak and Average based on frequency range
Receive antenna scan height	1 m - 4 m
Receive antenna polarization	Vertical/horizontal

* According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

8.4.3 Calculation of the field strength

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors
 Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μ V. The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91 dB μ V/m. The 35.91 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

Level in μ V/m = Common Antilogarithm (35.91/20) = 62.44

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.4.4 Result

Transmitter spurious radiation below 30 MHz (Section 15.205, 15.209 and 15.249)												
f	Detct	BW	Rx Level	MD	CF	DEF	LC	Limit	Margin	EP	Antenna	
											Pol	H
MHz	Type	kHz	dB μ V	m	dB	dB	dB μ V/m	dB μ V/m	dB	°	H/V	m
	QP	9	**	3			**					
	QP	9	**	3			**					
	QP	9	**	3			**					
	QP	9	**	3			**					
	QP	9	**	3			**					

Measurement uncertainty: ± 4 dB

**No emissions detected

f: Frequency | Detct : Detector type | BW: Bandwidth | Rx Level : Receiver level | MD: Measurement distance | CF : Correction factor | DEF: Distance extrapolation factor | LC : Level corrected | EP: EUT Position | Pol:Antenna polarization | H: Antenna height

Remark: *¹ Noise level of the measuring instrument ≤ 4.0 dB μ V@10m distance (0.009 MHz –30 MHz)

Remark: * Peak Limit according to Section 15.35 (b).

The above measurement is performed for all host devices, in lower, middle and highest channels!

Test Cables used	K1a, K56, K83
Test equipment used	103, 171a, 23

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	-----	----	------------

N.t.* see clause: 9

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Transmitter spurious radiation above 30 MHz (Section 15.205, 15.209 and 15.249)													
f	Detct	BW	Rx Level	MD	CF	DEF	AVC	LC	Limit	Margin	EP	Antenna	
												Pol	H
MHz	Type	kHz	dB μ V	m	dB	dB	dB	dB μ V/m	dB μ V/m	dB	°	H / V	m
30	QP	120	$\leq 3.5^{**}$	3	-2.6 ⁵	0	0	0.9	40.0	39.1	0-360	H / V	1-4
88	QP	120	$\leq 3.5^{**}$	3	-10.8 ⁵	0	0	-7.3	40.0	47.3	0-360	H / V	1-4
216	QP	120	$\leq 3.5^{**}$	3	-10.3 ⁵	0	0	-6.8	43.5	50.3	0-360	H / V	1-4
960	QP	120	$\leq 3.5^{**}$	3	8.5 ⁵	0	0	12.0	43.5	31.5	0-360	H / V	1-4
1700	Av	1000	$\leq 4.5^{**}$	3	3.8 ⁶	0	0	8.3	54.0	45.7	0-360	H / V	1-4
1805	Av	1000	$\leq 10^{**}$	3	9.5 ⁶	0	0	19.5	54.0	34.5	0-360	H / V	1-4
2250	Av	1000	$\leq 10^{**}$	3	8.0 ⁶	0	0	18.0	54.0	36.0	0-360	H / V	1-4
4000	Av	1000	$\leq 10^{**}$	3	8.4 ⁶	0	0	18.4	54.0	35.6	0-360	H / V	1-4
5000	Av	1000	$\leq 10^{**}$	3	9.1 ⁶	0	0	19.4	54.0	34.6	0-360	H / V	1-4
7500	Av	1000	$\leq 14^{**}$	3	12.9 ⁶	0	0	26.9	54.0	27.1	0-360	H / V	1-4
8300	Av	1000	$\leq 14^{**}$	3	14.8 ⁶	0	0	28.8	54.0	25.2	0-360	H / V	1-4

Measurement uncertainty: ± 4 dB

**** All other emissions are lower than the noise level of the measuring equipment!**
The noise level is noted in the above table!
The blue marked frequencies fall into the restricted bands of operation

f: Frequency | Detct : Detector type | BW: Bandwidth | Rx Level : Receiver level | MD: Measurement distance | CF : Correction factor | DEF : Distance extrapolation factor | AVC : Averaging Correction factor | LC : Level corrected | EP: EUT Position | Pol:Antenna polarization | H: Antenna height |

Remark: ¹ noise floor noise level of the measuring instrument ≤ 3.5 dB μ V @ 3m distance (30 – 1,000 MHz)
 Remark: ² noise floor noise level of the measuring instrument ≤ 4.5 dB μ V @ 3m distance (1,000 – 2,000 MHz)
 Remark: ³ noise floor noise level of the measuring instrument ≤ 10 dB μ V @ 3m distance (2,000 – 5,500 MHz)
 Remark: ⁴ noise floor noise level of the measuring instrument ≤ 14 dB μ V @ 3m distance (5,500 – 14,500 MHz)
 Remark: ⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: ⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

The above measurement is performed for all host devices, in lower, middle and highest channels!

Test Cables used	K1a, K83, K84, K40, K56, K51, K52
Test equipment used	103, 171a, 166a, 345, 406, 445a

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	-----	----	------------

N.t.* see clause: 9

Date: 2017-01-16

Created: P6

Reviewed: P9

Released: P1

Vers. no. 1.17

8.5 Field strength limits of fundamental frequencies and harmonics

8.5.1 Regulation

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Intentional radiator- Fundamental frequencies / Field strength limits		
Frequency	Field strength of fundamental	Field strength of harmonics
MHz	mV / m	µV / m
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24.0-24.25	250	2500

Fixed, point-to-point operation as referred to in this paragraph shall be limited to systems employing a fixed transmitter transmitting to a fixed remote location. Point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information are not allowed. Fixed, point-to-point operation is permitted in the 24.05-24.25 GHz band subject to the following conditions:

- (1) The field strength of emissions in this band shall not exceed 2500 millivolts/meter.
- (2) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.001\%$ of the operating frequency over a temperature variation of $-20\text{ }^{\circ}\text{C}$ to $+50\text{ }^{\circ}\text{C}$ at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of $20\text{ }^{\circ}\text{C}$. For battery operated equipment, the equipment tests shall be performed using a new battery.

Field strength limits are specified at a distance of 3 meters.

As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits mentioned above are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.5.2 Test procedure

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8m above the ground. The turn table would be allowed to rotate 360° to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna are changed in horizontal and vertical polarization, the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4-2014 Section 8 “Radiated Emissions Testing”

Measurement procedures for electric field radiated emissions from 9kHz - 1 GHz & 1 GHz - 40 GHz are covered in Clause 8 of ANSI C63.4-2014. The ANSI C63.4-2014 measurement procedure consists of both an exploratory test and a final measurement. The exploratory test is critical to determine the frequency of all significant emissions. For each mode of operation required to be tested, the frequency spectrum is monitored. Variations in antenna height, antenna orientation, antenna polarization, EUT azimuth, and cable or wire placement is explored to produce the emission that has the highest amplitude relative to the limit.

The final measurements are made based on the findings in the exploratory testing. When making exploratory and final measurements it is necessary to maximize the measured radiated emission. Sub clause 8.3.2 of ANSI C63.4-2014 states that the measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” We consider the “cone of radiation” to be the 3 dB beam width of the measurement antenna.

While the “bore-sighting” technique is not explicitly mentioned in ANSI C63.4-2014, it is a useful technique for measurements using a directional antenna, such as a double-ridged waveguide antenna. Several precautions must be observed, including: knowledge of the beam width of the antenna and the resulting illumination area relative to the size of the EUT, estimation for source of the emission and general location within larger EUTs, measuring system sensitivity, etc.

ANSI C63.4-2014 requires that the measurement antenna is kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. That means that if the directional radiation pattern of the EUT results in a maximum emission at an upwards angle from the EUT, when a directional antenna is used to make the measurement it will be necessary for it to be pointed towards the source of the emission within the EUT. This can be done by either pointing the antenna at an angle towards the source of the emission, or by rotating the EUT, in both height and polarization, to maximize the measured emission. The emission must be kept within the illumination area of the 3 dB beamwidth of the antenna so that the maximum emission from the EUT is measured.

The measurement procedure for harmonics and spurious emissions above 40 GHz is taken from ANSI C63.10-2013.

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Radiated emissions test characteristics	
Test distance	10m, 3 m*
Test instrumentation resolution bandwidth	9 kHz (Below 30 MHz) 120 kHz (30 MHz - 1,000 MHz) 1 MHz (Above 1000 MHz)
Receive antenna height	1 m (20 kHz – 30 MHz)
Receive antenna polarization	0° - 90° (20 kHz – 30 MHz)
Receive antenna scan height	1 m - 4 m (30 MHz - 15,000 MHz) 1 m – 2.5 m (18,000 MHz - 40,000 MHz)
Receive antenna polarization	vertical/horizontal (Above 30 MHz)

*According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

8.5.3 Calculation of the average correction factor

The average correction factor is computed by analyzing the "worst case" on time in any 100msec time period and using the formula: Corrections Factor + 20*log (worst case on time/100msec). Analysis of the remote transmitter worst case on time in any 100msec time period is an on time of 50msec, therefore the correction factor is 20*log (50/100) = - 6 dB. The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules.

8.5.4 Calculation of the field strengths

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-Amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μ V. The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB μ V/m.

The 35.91dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

Level in μ V/m = Common Antilogarithm (35.91/20) = 62.44

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.5.5 Result

Transmitter Field Strengths - Fundamental Emissions & Harmonics (Section 15.249)											
EUT: RMS-MLOG-T-915											
f	Detct	BW	Rx Level	MD	CF	DEF	LC	Limit	Marg in	EP	Antenna
MHz	Type	kHz	dB μ V	m	dB	dB	dB μ V/m	dB μ V/m	dB	°	Pol H / V m
Lowest channel – 902.5 MHz											
902.5	QP	120	72.9	3	6.8	0	79.7	94.0	14.3	0°	H 1.14
1805.0	AV	1000	25.0	3	8.3	0	33.3	54.0	20.7	15	H 2.13
2707.5	AV	1000	25.2	3	13.0	0	38.2	54.0	15.8	210°	H 1.37
3610.0	AV	1000	22.0	3	16.6	0	38.6	54.0	15.4	0°-360°	H 1-4
4512.5	AV	1000	24.0	3	19.9	0	43.9	54.0	10.1	0°-360°	H 1-4
5415.0	AV	1000	21.6	3	24.1	0	45.7	54.0	8.3	0°-360°	H 1-4
6317.5	AV	1000	22.5	3	25.3	0	47.8	54.0	6.2	0°-360°	V 1-4
Middle channel – 915.0 MHz											
915.0	QP	120	72.8	3	7.0	0	79.8	94.0	14.2	0°	H 1.17
1830.0	AV	1000	24.8	3	8.3	0	33.1	54.0	20.9	15°	H 2.21
2745.0	AV	1000	23.9	3	13.0	0	36.9	54.0	17.1	210°	H 1.55
3660.0	AV	1000	22.0	3	16.6	0	38.6	54.0	15.4	0°-360°	H 1-4
4575.0	AV	1000	24.0	3	19.9	0	43.9	54.0	10.1	0°-360°	H 1-4
5490.0	AV	1000	22.0	3	24.1	0	46.1	54.0	7.9	0°-360°	H 1-4
6405.0	AV	1000	22.5	3	25.3	0	47.8	54.0	6.2	0°-360°	V 1-4
Highest Channel – 927.5 MHz											
927.5	QP	120	72.5	3	7.4	0	79.9	94.0	14.1	0°	H 1.22
1855.0	AV	1000	25.1	3	8.3	0	33.4	54.0	20.6	15°	H 2.17
2782.5	AV	1000	23.7	3	13.0	0	36.7	54.0	17.3	210°	H 1.61
3710.0	AV	1000	22.0	3	16.6	0	38.6	54.0	15.4	0°-360°	H 1-4
4637.5	AV	1000	24.0	3	19.9	0	43.9	54.0	10.1	0°-360°	H 1-4
5565.0	AV	1000	23.0	3	24.1	0	47.1	54.0	6.9	0°-360°	V 1-4
6492.5	AV	1000	22.0	3	25.3	0	47.3	54.0	6.7	0°-360°	H 1-4
Measurement uncertainty: ± 4 dB											
The blue marked frequencies fall into the restricted bands of operation!											
f: Frequency Detct : Detector type BW: Bandwidth Rx Level : Receiver level MD: Measurement distance CF : Correction factor DEF : Distance extrapolation factor LC : Level corrected EP: EUT Position Pol: Antenna polarization H: Antenna height											
Remark: * ¹ noise floor	noise level of the measuring instrument ≤ 3.5dB μ V @ 3m distance (30 – 1,000 MHz)										
Remark: * ² noise floor	noise level of the measuring instrument ≤ 4.5dB μ V @ 3m distance (1,000 – 2,000 MHz)										
Remark: * ³ noise floor	noise level of the measuring instrument ≤ 10dB μ V @ 3m distance (2,000 – 5,500 MHz)										
Remark: * ⁴ noise floor	noise level of the measuring instrument ≤ 14dB μ V @ 3m distance (5,500 – 14,500 MHz)										
Remark: * ⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz											
Remark: * ⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz											
Remark: * ⁷ for periodic operated transmitter											

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Test Cables used	K1a, K40, K83, K50, K51, K56, K83, K84		
Test equipment used	103, 166a, 171a, 406, 345, 445a		

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.: 6
---	-----	----	--------------

N.t.* see clause: 9

Date: 2017-01-16

Created: P6

Reviewed: P9

Released: P1

Vers. no. 1.17

dudde hochfrequenz-technik

Rottland 5a

D-51429 Bergisch Gladbach/ Germany

Tel: +49 2207-96890

Fax +49 2207-968920

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Transmitter Field Strengths - Fundamental Emissions & Harmonics (Section 15.249)

EUT: RMS-LOG-915

f	Detct	BW	Rx Level	MD	CF	DEF	LC	Limit	Marg in	EP	Antenna	
											Pol	H
MHz	Type	kHz	dB μ V	m	dB	dB	dB μ V/m	dB μ V/m	dB	°	H / V	m
Lowest channel – 902.5 MHz												
902.5	QP	120	85.6	3	8.4	0	92.4	94.0	1.6	125°	V	1.40
1805.0	AV	1000	23.4	3	8.3	0	31.7	54.0	22.3	60°	V	1.94
2707.5	AV	1000	25.9	3	13.0	0	38.9	54.0	15.1	270°	V	1.55
Middle channel – 915.0 MHz												
915.0	QP	120	85.2	3	7.0	0	92.2	94.0	1.8	125°	V	1.43
1830.0	AV	1000	23.0	3	8.3	0	31.3	54.0	22.7	60°	V	1.97
2745.0	AV	1000	24.9	3	13.0	0	37.9	54.0	16.1	270°	V	1.66
Highest Channel – 927.5 MHz												
927.5	QP	120	85.0	3	7.4	0	92.4	94.0	1.6	125°	V	1.47
1855.0	AV	1000	21.5	3	8.3	0	29.8	54.0	24.2	95°	V	2.07
2782.5	AV	1000	24.8	3	13.0	0	37.8	54.0	16.2	210°	V	1.98
Measurement uncertainty: ± 4 dB												
The blue marked frequencies fall into the restricted bands of operation!												
f: Frequency Detct : Detector type BW : Bandwidth Rx Level : Receiver level MD : Measurement distance CF : Correction factor DEF : Distance extrapolation factor LC : Level corrected EP : EUT Position Pol : Antenna polarization H : Antenna height												
Remark: * ¹ noise floor noise level of the measuring instrument ≤ 3.5dB μ V @ 3m distance (30 – 1,000 MHz) Remark: * ² noise floor noise level of the measuring instrument ≤ 4.5dB μ V @ 3m distance (1,000 – 2,000 MHz) Remark: * ³ noise floor noise level of the measuring instrument ≤ 10dB μ V @ 3m distance (2,000 – 5,500 MHz) Remark: * ⁴ noise floor noise level of the measuring instrument ≤ 14dB μ V @ 3m distance (5,500 – 14,500 MHz) Remark: * ⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz Remark: * ⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz Remark: * ⁷ for periodic operated transmitter												

Test Cables used	K1a, K40, K83, K50, K51, K56, K83, K84
Test equipment used	103, 166a, 171a, 406, 345, 445a

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.:6
---	-----	----	-------------

N.t.* see clause: 9

Date: 2017-01-16

Created: P6

Reviewed: P9

Released: P1

Vers. no. 1.17

dudde hochfrequenz-technik

Rottland 5a

D-51429 Bergisch Gladbach/ Germany

Tel: +49 2207-96890

Fax +49 2207-968920

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

Transmitter Field Strengths - Fundamental Emissions & Harmonics (Section 15.249)

EUT: RMS-GW-915

f	Detct	BW	Rx Level	MD	CF	DEF	LC	Limit	Marg in	EP	Antenna	
											Pol	H
MHz	Type	kHz	dB μ V	m	dB	dB	dB μ V/m	dB μ V/m	dB	°	H / V	m
Lowest channel – 902.5 MHz												
902.5	QP	120	85.5	3	6.8	0	92.3	94.0	1.7	120°	V	1.67
1805.0	AV	1000	23.0	3	8.3	0	31.3	54.0	22.7	65°	V	1.90
2707.5	AV	1000	25.1	3	13.0	0	38.1	54.0	15.9	270°	V	1.61
Middle channel – 915.0 MHz												
915.0	QP	120	85.4	3	7.0	0	92.4	94.0	1.6	120°	V	1.69
1830.0	AV	1000	22.5	3	8.3	0	30.8	54.0	23.2	65°	V	1.94
2745.0	AV	1000	25.0	3	13.0	0	38.0	54.0	16.0	270°	V	1.87
Highest Channel – 927.5 MHz												
927.5	QP	120	85.0	3	7.4	0	92.4	94.0	1.6	120°	V	1.74
1855.0	AV	1000	22.0	3	8.3	0	30.3	54.0	23.7	65°	V	1.99
2782.5	AV	1000	24.6	3	13.0	0	37.6	54.0	16.4	270°	V	2.05

Measurement uncertainty: ± 4 dB

The blue marked frequencies fall into the restricted bands of operation!

f: Frequency | Detct : Detector type | BW: Bandwidth | Rx Level : Receiver level | MD: Measurement distance | CF : Correction factor |
 DEF : Distance extrapolation factor | LC : Level corrected | EP: EUT Position | Pol: Antenna polarization | H: Antenna height

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5 dB μ V @ 3m distance (30 – 1,000 MHz)Remark: *² noise floor noise level of the measuring instrument ≤ 4.5 dB μ V @ 3m distance (1,000 – 2,000 MHz)Remark: *³ noise floor noise level of the measuring instrument ≤ 10 dB μ V @ 3m distance (2,000 – 5,500 MHz)Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14 dB μ V @ 3m distance (5,500 – 14,500 MHz)Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHzRemark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHzRemark: *⁷ for periodic operated transmitter

Test Cables used	K1a, K40, K83, K50, K51, K56, K83, K84		
Test equipment used	103, 166a, 171a, 406, 345, 445a		

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.: 6
---	-----	----	--------------

N.t.* see clause: 9

Date: 2017-01-16

Created: P6

Reviewed: P9

Released: P1

Vers. no. 1.17

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

8.6 Bandwidth (20 dB)

8.6.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.6.2 Test procedure

ANSI C63.10-2013 Section 6.9.3 Occupied bandwidth measurements.

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

h) Determine the “-xx dB down amplitude” using [(reference value) – xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “- xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.6.3 Result

Intentional radiator- Maximum Measured 20 dB Bandwidth – RMS-MLOG-T-915		
Operating Frequency	Maximum Measured 20 dB Bandwidth	20 dB Bandwidth limit
MHz	kHz	kHz
902.5	79.09	500
915.0	79.30	500
927.5	78.88	500

The results above are the worst case values!

Test Cables used	K22		
Test equipment used	144, 226, 502, test-fixture		

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no.:3
---	-----	----	-------------

N.t.* see clause: 9

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

9. Additional information to the test report

Remarks	Description
N.t. ¹	Not tested, because the antenna is part of the PCB
N.t. ²	Not tested, because the EUT is directly battery powered
N.t. ³	Not tested, because not applicable to the EUT
N.t. ⁴	Not tested, because not ordered

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

10. List of test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration	Calibration executed by
Test fixture	Dudde	---	---	---	---
Magnetic loop antenna (9 kHz - 30 MHz)	Schwarzbeck FMZB 1516 (23)	---	05/2016	05/2019	Seibersdorf
OATS	Dudde (103)	---	06/2016	06/2018	Dudde
Digital Multimeter	GW GDM-8045G (144)	0090256	08/2016	08/2019	Testo
Pre-amplifier (100kHz - 1.3GHz)	Hewlett Packard 8447 E (166a)	1726A00705	07/2016	07/2018	Dudde
Hornantenna (2.0-14.0 GHz)	Schwarzbeck BBHA 9120 C (169)	305	09/2016	09/2020	Seibersdorf
Receiver (9 kHz –18.0 GHz)	Rohde & Schwarz Spectrum Analyzer FSL 18 (171a)	100.117	03/2016	03/2018	Rohde & Schwarz
Pre-amplifier (1GHz - 18GHz)	Narda (345)	---	02/2016	02/2018	Dudde
Bilog-antenna (30- 1000 MHz)	Schwarzbeck VULP 9168 (406)	---	04/2016	04/2019	Seibersdorf
Log. Per, Antenne (1- 18 GHz)	Schwarzbeck STLP 9148 (445a)	---	03/2016	03/2019	Seibersdorf
Signal Analyzer (9 kHz –30.0 GHz)	Rohde & Schwarz FSV 30 (502)	100932	06/2016	06/2019	Rohde & Schwarz

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

11. List of test cables

Type	Manufacturer/ Model no.	Cable no.	Last calibration	Next calibration	Calibration executed by
RF- cable	Kabelmetal 18m [N]	K1a	10/2016	10/2017	Dudde
RF- cable	Aircell 0.5m [BNC]	K40	10/2016	10/2017	Dudde
RF- cable	Sucoflex 104 Suhner [N] 1 m	K50	10/2016	10/2017	Dudde
RF- cable	Aircell 1m [BNC/N]	K56	10/2016	10/2017	Dudde
RF- cable	Sucoflex 100 Suhner [N] 1 m	K51	10/2016	10/2017	Dudde
RF- cable	Sucoflex 106 Suhner 6,4m [N]	K83	10/2016	10/2017	Dudde
RF- cable	Sucoflex 106 Suhner 6,4m [N]	K84	10/2016	10/2017	Dudde
RF- cable	Sucoflex Suhner 13 m [N]	K144	10/2016	10/2017	Dudde
RF- cable	Sucoflex Suhner 8m [SMA]	K145	10/2016	10/2017	Dudde
RF- cable	Sucoflex Suhner 8m [SMA]	K146	10/2016	10/2017	Dudde

EUT: AMB9625

FCC ID: R7TAMB9625

FCC Title 47 CFR Part 15

Date of issue: 2017-08-25

End of test report