



Test Report

Test Report No.:	KTI04EF06002		
Registration No.:	99058		
Applicant:	Zilliontek Co., Ltd.		
Applicant Address:	Suite 603, Magicplaza Bldg, 1009-6, Youngtong-Dong, Youngtong-Ku, Suwon-City, Kyungki-Do, Korea 442-813		
Product:	Door Lock		
FCC ID:	R8EVG-300L	Model No.	VG-300L
Receipt No.:	04-0313	Date of receipt:	March 10, 2004
Date of Issue:	June 22, 2004		
Testing location	Korea Technology Institute Co., Ltd. 51-19, Sanglim3-Ri, Docheok-Myeun, Gwangju-Shi, Gyeungki-Do, Korea		
Test Standards:	FCC/ANSI. C63.4: 2001		
Rule Parts: FCC	Part 15, Subpart C		
Equipment Class:	Remote Control/Security Device Transceiver		
Test Result:	The above-mentioned product has been tested with compliance.		

Tested by: Hyun, Kim
/ Engineer

Approved by: G. C. Min
/President

Signature Date

Signature Date

Other Aspects:	
----------------	--

Abbreviations:	* OK, Pass=passed * Fail=failed * N/A=not applicable
----------------	--

- This test report is not permitted to copy partly without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of one sample of the above mentioned.
- This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.
- We certify this test report has been based on the measurement standards that is traceable to the national or international standards.



Contents

Contents	2
List of Tables	2
List of Figures	2
List of Photographs	2
1. General	3
2. Test Site	3
2.1 Location	3
2.2 List of Test and Measurement Instruments	4
2.3 Test Date	4
2.4 Test Environment	4
3. Description of the tested samples	5
3.1 Rating and Physical characteristics	5
3.2 Submitted documents	5
4. Measurement conditions	6
4.1 Modes of operation	6
4.2 Additional Equipment	6
4.3 Uncertainty	6
4.4 Test Setup	7
5. Definition and limit	8
5.1 Definition	8
5.2 Restricted Bands of Operation	8
5.3 Limitation	8
5.4 Labeling Requirement	9
5.5 User Information	9
6. Conducted Emissions Measurement	10
7. Radiated Emission Measurement	11
8. Emission Bandwidth Measurement	13
Bandwidth Ploted Data	14
Annex1 Photographs of the Test Set-up	14
Annex2 Label	15~16
Photographs of EUT	17~26

List of Tables

Table 1	List of test and measurement equipment	4
Table 2	Test Data. Radiated Emissions	12

List of Figures

List of Photographs

Photograph 1	Setup for Radiated Emissions
--------------	------------------------------

15



1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. Korea Technology Institute Co., Ltd. performed all measurements reported herein. And were made under Chief Engineer's supervisor.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. Test Site

Korea Technology Institute Co., Ltd.

2.1 Location

51-19, Sanglim3-Ri, Docheok-Myeon, Gwangju-Shi, Gyeungki-Do, Korea

The Test Site is in compliance with ANSI C63.4/2001 for measurement of radio Interference.



2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

- Conducted Emissions

Kind of Equipment	Type	S/N	Calibrated until
Spectrum Analyzer	R3261C	61720417	11.2004
Field Strength Meter	ESPC	832827/011	9.2004
LISN	KNW407	8-1157-2	10.2004
LISN	EM-7823	115019	4.2005
Conducted Cable	N/A	N/A	11.2004

- Radiated Emissions

Kind of Equipment	Type	S/N	Calibrated until
Field Strength Meter	ESIB40	100093	3.2005
Spectrum Analyzer	R3261C	61720417	11.2004
Pre Amplifier	8447D	2944A06874	11.2004
BiconiLog Antenna	3142B	1705	2.2005
Horn Antenna	3115	6443	6.2005
Open Site Cable	N/A	N/A	11.2004
Antenna Mast	DETT-03	N/A	N/A
Antenna & Turntable controller	DETT-04	91X519	N/A

2.3 Test Date

Date of Application: March 10, 2004

Date of Test: June 7, 2004

2.4 Test Environment

See each test item's description.



3. Description of the tested samples

The EUT is Door Lock.

3.1. Rating and Physical Characteristics

operating Frequency : 447.35MHz FM

Power : DC 3V (AA size 4 ea)

Battery Hour : Min. 1 year

LED Display

Size(mm) : 190(W)x75(D)x43(H)

3.2. Submitted Documents

- User's Guide
- Block Diagram



4. Measurement Conditions

Testing Input Voltage: DC 3V battery

4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

The EUT was operated continuously in its normal operating mode for the purpose of the measurements.

In order to secure the continuous operation of the EUT, rewiring in the circuit was done by the manufacturer so as to affect its intended operation.

4.2 Additional Equipment

DEVICE TYPE	Manufacturer	M/N	S/N	FCC ID
-	-.	-	-	-

4.3 Uncertainty

1) Radiated disturbance

U_c (Combined standard Uncertainty) = $\pm 1.8\text{dB}$

Expanded uncertainty $U=KU_c$

$K = 2$

$U = \pm 3.6\text{dB}$


2) Conducted disturbance

$U_c = \pm 0.88\text{dB}$

$U = KU_c = 2 \times U_c = \pm 1.8\text{dB}$



4.4 Test Setup





5. Definition and Limits

5.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

5.2 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.25
0.495 – 0.505 **	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 21.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
5.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2655 – 2900	22.01 – 23.12
8.41425 – 8.41475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3360 – 4400	Abobe 38.6
13.36 – 13.41			

Remark “**” : Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz

5.3 Limitation

(1) Conducted Emission Limits :

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the conducted limit is the following:

Frequency(MHz)	Emission(dBuV)
0.15 – 0.5	66dBuV – 56dBuV
0.5 – 5.0	56 dBuV
5.0 – 30.0	60 dBuV



(2) Radiated Emission Limits :

According to 15.231 the field strength of emissions from intentional radiators operated under these frequency bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental	
	uV/meter	dBuV/meter
40.66-40.70	2,250	67.04
70-130	1,250	61.94
130-174	1,250 to 3,750**	61.94 to 71.48**
174-260	3,750	71.48
260-470	3,750 to 12,500**	71.48 to 81.94**
Above	12,500	81.94

** linear interpolations

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3meters=56.81818(F)-6136.3636; For the band 260-470 MHz, $\mu\text{V/m}$ at 3meters=41.6667(F)-7083.3333. The maximum permitted unwanted emission level is 20dB below the maximum permitted fundamental level.

(3) Emission Band Limits :

According to 15.231, The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

5.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

5.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



6. Conducted Emissions (Not Applicable)

This EUT is excused from investigation of conducted emission, for it is powered by DC Battery only.

According to §15.207(c), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.



7. Radiated Emission Measurement

Result:

Pass

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband Amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and Investigated. The system configurations, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 1GHz using BiconiLog Antenna. Above 1GHz, Double ridged horn Antenna was used.

Final measurements were made outdoors at 3-meter test range using EMCO antennas. The test equipment was placed on a wooden table situated on a 4x4 meter area adjacent to the measurement area. Turntable was to protect from weather in the dome that made with Polyethylene film. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter (ESIB40). The detector function was set to CISPR quasi-peak or peak mode as appropriate and the bandwidth of the receiver was set to 120kHz or 1 MHz depending on the frequency or type or signal.

The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8meter high non-metallic 1 x 1.5 meter table.

The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed, and/or support equipment, if applicable; and changing the polarity of the antenna and rotating the EUT in turns with three orthogonal axes for portable devices, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of radiated emission test.

Each EME reported was calibrated using self-calibrating mode.



Table 2. Test Data, Radiated Emissions

A. 447.35MHz

Frequency (MHz)	Height [m]	Angle [°]	(1) Reading Peak (dB μ V)		(2) AFCL (dB/m)	(3) Actual (dB μ V/m)		(4) Limit (dB μ V/m)	(5) Margin (dB)	
			H	V		H	V		H	V
447.35	1.8	5	51.8	52.3	20.76	72.56	73.06	81.26	8.7	8.2
894.70	-	-	-	-	-	-	-	-	-	-
1342.05	-	-	-	-	-	-	-	-	-	-
1789.40	-	-	-	-	-	-	-	-	-	-
2236.75	-	-	-	-	-	-	-	-	-	-
2684.10	-	-	-	-	-	-	-	-	-	-
3131.45	-	-	-	-	-	-	-	-	-	-
3578.80	-	-	-	-	-	-	-	-	-	-
4026.15	-	-	-	-	-	-	-	-	-	-
4473.50	-	-	-	-	-	-	-	-	-	-

*Remark: “-“ means that the emission level is too low to be measured.

PK: Peak reading, QP: Quasi Peak reading, AV: Average reading

AFCL: Antenna factor + Cable loss

H: Horizontal, V: Vertical

Note :

1. Limit on the field strength of fundamental
447.35MHz: $41.6667(447.35)-7083.3333 = 11,556\mu$ V/m (81.26dB μ V/m)
2. Limit on the field strength of spurious less than limit value 20dB.
3. If the measured frequencies fall in the restricted frequency band, the limit employed is §15.209 general requirement when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function, no duty factor applied.

♦ Margin Calculation

$$(5) \text{ Margin} = (4) \text{ Limit} - (3) \text{ Actual}$$

$$[(3) \text{ Actual} = (1) \text{ Reading} + (2) \text{ AFCL}]$$



8. Emission Bandwidth Measurement

Result:

Pass

The -20dB bandwidth was checked to see that it was within 0.25% of the fundamental frequency for the EUT.

The emission bandwidth limit for this transmitter is

- A)** $447.35\text{MHz} * 0.25 = 111.837\text{kHz}$
- B)** Test result: $35.170\text{kHz} < 111.837\text{ KHz}$

Note : Please see appendix 1 for Plotted Data



Appendix 1 for Bandwidth plotted Data

