



FCC RF Test Report

APPLICANT : Guangdong OPPO Mobile Telecommunications Corp., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : OPPO
MODEL NAME : CPH2737
FCC ID : R9C-OP24321
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Mar. 14, 2025 ~ Apr. 08, 2025

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Test Software.....	7
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	18
3.6 AC Conducted Emission Measurement.....	22
3.7 Antenna Requirements.....	24
4 LIST OF MEASURING EQUIPMENT	25
5 MEASUREMENT UNCERTAINTY	26
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR521816C	Rev. 01	Initial issue of report	Apr. 22, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 30\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.12 dB at 2483.96 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.75 dB at 0.18 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

1.2 Manufacturer

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	OPPO
Model Name	CPH2737
FCC ID	R9C-OP24321
IMEI Code	Conducted: 869081070026695/869081070026687 Conduction: 869081070034053/869081070034046 Radiation: 869081070034574/869081070034566
HW Version	11
SW Version	ColorOS 15.0
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum Output Power to antenna	<MIMO Ant 7+12> 802.11b : 26.11 dBm (0.4083 W) 802.11g : 26.86 dBm (0.4853 W) 802.11ax HE20 : 26.91 dBm (0.4909 W) 802.11ax HE40 : 23.31 dBm (0.2143 W)
99% Occupied Bandwidth	<MIMO Ant 7+12> 802.11b : 12.735MHz 802.11g : 17.722MHz 802.11ax HE20 : 19.498MHz 802.11ax HE40 : 37.860MHz
Antenna Type / Gain	<Ant 7 > Metal-Frame Antenna type with gain 0.5 dBi <Ant 12 > Metal-Frame Antenna type with gain 0 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)

Note:

1. The device supports WLAN MIMO CDD mode.
2. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher normal output power.
3. For 802.11n/11ac/11ax mode, the whole testing have assessed only 802.11ax HE20/HE40 by referring to the higher output power.
4. 802.11ax support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power, the full RU power/PSD > partial RU, therefore the full RU perform full, and partial RU verify bandedge/spurious.
5. For RSE, the worse cases of partial RU are shown in this report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ CO02-SZ 03CH04-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


MIMO Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11ax HE20	MCS0
802.11ax HE40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable (Charging from Adapter1) + Battery 1
Remark: For Radiated Test Cases, The tests were performance with Adapter 1 and USB Cable.	

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.12 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 2.12+ 10 = 12.12 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup





3.2.5 Test Result of Average Output Power

2.4GHz Band MIMO																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant12	Ant7	SUM	Ant12	Ant7	Ant12	Ant7	Ant12	Ant7	Ant12	Ant7	
11b	1Mbps	2	1	2412	20.70	20.60	23.66	30.00		0.50		24.16		36.00		Pass
11b	1Mbps	2	6	2437	23.10	23.10	26.11	30.00		0.50		26.61		36.00		Pass
11b	1Mbps	2	11	2462	20.70	20.50	23.61	30.00		0.50		24.11		36.00		Pass
11g	6Mbps	2	1	2412	19.20	19.10	22.16	30.00		0.50		22.66		36.00		Pass
11g	6Mbps	2	2	2417	19.70	19.40	22.56	30.00		0.50		23.06		36.00		Pass
11g	6Mbps	2	3	2422	21.10	21.20	24.16	30.00		0.50		24.66		36.00		Pass
11g	6Mbps	2	6	2437	23.90	23.80	26.86	30.00		0.50		27.36		36.00		Pass
11g	6Mbps	2	9	2452	22.40	22.00	25.21	30.00		0.50		25.71		36.00		Pass
11g	6Mbps	2	10	2457	20.30	19.60	22.97	30.00		0.50		23.47		36.00		Pass
11g	6Mbps	2	11	2462	20.10	20.00	23.06	30.00		0.50		23.56		36.00		Pass

2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant12	Ant7	SUM	Ant12	Ant7	Ant12	Ant7	Ant12	Ant7	Ant12	Ant7	
HE20	MCS0	2	1	2412	Full	19.30	19.20	22.26	30.00		0.50		22.76		36.00		Pass
HE20	MCS0	2	2	2417	Full	19.20	19.20	22.21	30.00		0.50		22.71		36.00		Pass
HE20	MCS0	2	3	2422	Full	21.10	20.90	24.01	30.00		0.50		24.51		36.00		Pass
HE20	MCS0	2	6	2437	Full	24.00	23.80	26.91	30.00		0.50		27.41		36.00		Pass
HE20	MCS0	2	9	2452	Full	22.60	22.30	25.46	30.00		0.50		25.96		36.00		Pass
HE20	MCS0	2	10	2457	Full	20.40	19.70	23.07	30.00		0.50		23.57		36.00		Pass
HE20	MCS0	2	11	2462	Full	20.10	19.80	22.96	30.00		0.50		23.46		36.00		Pass
HE40	MCS0	2	3	2422	Full	19.10	19.40	22.26	30.00		0.50		22.76		36.00		Pass
HE40	MCS0	2	6	2437	Full	20.40	20.20	23.31	30.00		0.50		23.81		36.00		Pass
HE40	MCS0	2	7	2442	Full	19.50	19.30	22.41	30.00		0.50		22.91		36.00		Pass
HE40	MCS0	2	8	2447	Full	18.10	17.90	21.01	30.00		0.50		21.51		36.00		Pass
HE40	MCS0	2	9	2452	Full	17.30	17.10	20.21	30.00		0.50		20.71		36.00		Pass



Test Mode	Antenna	Freq (MHz)	Ru Size	Ru Index	Set Power	Average power [dBm]	Duty Cycle [%]	DC Factor [dBm]	Result [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11AX20MIMO	Ant12	2412	26Tone	RU0	8	8.50	96.23	0.17	8.67	≤30.00	0.00	8.67	≤36.00	PASS
			52Tone	RU37	11	11.68	96.23	0.17	11.85	≤30.00	0.00	11.85	≤36.00	PASS
			106Tone	RU53	14	14.66	96.23	0.17	14.83	≤30.00	0.00	14.83	≤36.00	PASS
	Ant7	2412	26Tone	RU0	8	7.33	95.28	0.21	7.54	≤30.00	0.50	8.04	≤36.00	PASS
			52Tone	RU37	11	10.55	95.28	0.21	10.76	≤30.00	0.50	11.26	≤36.00	PASS
			106Tone	RU53	14	14.23	95.28	0.21	14.44	≤30.00	0.50	14.94	≤36.00	PASS
	total	2412	26Tone	RU0	---	---	---	---	11.15	≤30.00	0.50	11.65	≤36.00	PASS
			52Tone	RU37	---	---	---	---	14.35	≤30.00	0.50	14.85	≤36.00	PASS
			106Tone	RU53	---	---	---	---	17.65	≤30.00	0.50	18.15	≤36.00	PASS
	Ant12	2462	26Tone	RU8	8	8.25	96.23	0.17	8.42	≤30.00	0.00	8.42	≤36.00	PASS
			52Tone	RU40	11	11.57	96.23	0.17	11.74	≤30.00	0.00	11.74	≤36.00	PASS
			106Tone	RU54	14	14.57	96.23	0.17	14.74	≤30.00	0.00	14.74	≤36.00	PASS
	Ant7	2462	26Tone	RU8	8	8.08	95.28	0.21	8.29	≤30.00	0.50	8.79	≤36.00	PASS
			52Tone	RU40	11	11.20	95.28	0.21	11.41	≤30.00	0.50	11.91	≤36.00	PASS
			106Tone	RU54	14	12.88	95.28	0.21	13.09	≤30.00	0.50	13.59	≤36.00	PASS
	total	2462	26Tone	RU8	---	---	---	---	11.37	≤30.00	0.50	11.87	≤36.00	PASS
			52Tone	RU40	---	---	---	---	14.59	≤30.00	0.50	15.09	≤36.00	PASS
			106Tone	RU54	---	---	---	---	17.00	≤30.00	0.50	17.50	≤36.00	PASS

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01:

Method (a): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 7	Ant. 12	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	0.50	0.00	0.50	3.26	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Mar. 14, 2025~ Apr. 03, 2025	Apr. 08, 2025	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA24440A	11707	50MHz~40GHz	Jan. 02, 2025	Mar. 14, 2025~ Apr. 03, 2025	Jan. 01, 2026	Conducted (TH01-SZ)
Thermo meter	Anymetre	JR593	#7	- 10°C ~ 50°C 10%RH~99%RH	Apr. 09, 2024	Mar. 14, 2025~ Apr. 03, 2025	Apr. 08, 2025	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 03, 2024	Mar. 14, 2025	Jul. 02, 2025	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2024	Mar. 14, 2025	Jul. 02, 2025	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002 470	100Vac~250Vac	Dec. 25, 2024	Mar. 14, 2025	Dec. 24, 2025	Conduction (CO02-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 14, 2024	Mar. 19, 2025~ Apr. 08, 2025	Oct. 13, 2025	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 13	10Hz~44GHz	Jul. 03, 2024	Mar. 19, 2025~ Apr. 08, 2025	Jul. 02, 2025	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Mar. 19, 2025~ Apr. 08, 2025	Dec. 27, 2025	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May 09, 2024	Mar. 19, 2025~ Apr. 08, 2025	May 08, 2025	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-147 4	1GHz~18GHz	Jul. 07, 2023	Mar. 19, 2025~ Apr. 08, 2025	Jul. 06, 2025	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 04, 2024	Mar. 19, 2025~ Apr. 08, 2025	Jul. 03, 2025	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2024	Mar. 19, 2025~ Apr. 08, 2025	Oct. 17, 2025	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101 800-30-10P-R	1943528	1GHz~18GHz	Oct. 14, 2024	Mar. 19, 2025~ Apr. 08, 2025	Oct. 13, 2025	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-H G	1871923	18GHz~40GHz	Jul. 03, 2024	Mar. 19, 2025~ Apr. 08, 2025	Jul. 02, 2025	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY572801 36	500MHz~26.5G Hz	Jul. 03, 2024	Mar. 19, 2025~ Apr. 08, 2025	Jul. 02, 2025	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F11905001 9	N/A	Oct. 14, 2024	Mar. 19, 2025~ Apr. 08, 2025	Oct. 13, 2025	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 19, 2025~ Apr. 08, 2025	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 19, 2025~ Apr. 08, 2025	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.9 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 24-26 °C, 45-55 %RH

Test Date: 2025.03.14~2025.4.3

Test Engineer: Chen ZhiQiang


DTS Bandwidth



Test Result



TestMode	Antenna	Freq (MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-CDD	Ant12	2412	8.04	2407.96	2416.00	0.5	PASS
	Ant7	2412	8.08	2407.96	2416.04	0.5	PASS
	Ant12	2437	7.56	2432.96	2440.52	0.5	PASS
	Ant7	2437	8.04	2432.96	2441.00	0.5	PASS
	Ant12	2462	8.04	2457.96	2466.00	0.5	PASS
	Ant7	2462	8.08	2457.96	2466.04	0.5	PASS
11G-CDD	Ant12	2412	15.72	2403.84	2419.56	0.5	PASS
	Ant7	2412	16.08	2404.08	2420.16	0.5	PASS
	Ant12	2437	15.32	2429.24	2444.56	0.5	PASS
	Ant7	2437	16.04	2428.84	2444.88	0.5	PASS
	Ant12	2462	15.12	2454.44	2469.56	0.5	PASS
	Ant7	2462	15.88	2454.24	2470.12	0.5	PASS
11AX20MIMO	Ant12	2412	17.04	2403.00	2420.04	0.5	PASS
	Ant7	2412	17.72	2403.72	2421.44	0.5	PASS
	Ant12	2437	16.64	2428.24	2444.88	0.5	PASS
	Ant7	2437	17.88	2428.44	2446.32	0.5	PASS
	Ant12	2462	16.92	2452.92	2469.84	0.5	PASS
	Ant7	2462	15.12	2454.44	2469.56	0.5	PASS
11AX40MIMO	Ant12	2422	35.04	2404.48	2439.52	0.5	PASS
	Ant7	2422	33.92	2405.68	2439.60	0.5	PASS
	Ant12	2437	36.32	2418.28	2454.60	0.5	PASS
	Ant7	2437	35.04	2419.48	2454.52	0.5	PASS
	Ant12	2452	36.16	2433.36	2469.52	0.5	PASS
	Ant7	2452	35.12	2434.40	2469.52	0.5	PASS







Test Graphs










































Occupied Channel Bandwidth



Test Result



TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
11B-CDD	Ant12	2412	12.435	2405.7166	2418.1514
	Ant7	2412	12.735	2405.7326	2418.4674
	Ant12	2437	12.615	2430.6006	2443.2154
	Ant7	2437	12.639	2430.6926	2443.3314
	Ant12	2462	12.611	2455.6046	2468.2154
	Ant7	2462	12.707	2455.6726	2468.3794
11G-CDD	Ant12	2412	17.254	2403.4369	2420.6911
	Ant7	2412	17.39	2403.5808	2420.9711
	Ant12	2437	17.722	2428.0409	2445.7631
	Ant7	2437	16.97	2428.4729	2445.4432
	Ant12	2462	17.158	2453.2849	2470.4432
	Ant7	2462	16.902	2453.5848	2470.4872
11AX20MIMO	Ant12	2412	18.91	2402.5289	2421.4391
	Ant7	2412	18.894	2402.6329	2421.5270
	Ant12	2437	19.498	2427.1370	2446.6350
	Ant7	2437	19.122	2427.4850	2446.6070
	Ant12	2462	19.058	2452.3770	2471.4351
	Ant7	2462	19.058	2452.4570	2471.5150
11AX40MIMO	Ant12	2422	37.668	2403.0979	2440.7661
	Ant7	2422	37.7	2403.2419	2440.9421
	Ant12	2437	37.86	2417.9859	2455.8461
	Ant7	2437	37.86	2418.0499	2455.9101
	Ant12	2452	37.66	2433.0579	2470.7181
	Ant7	2452	37.788	2433.0419	2470.8301







Test Graphs









































Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B-CDD	Ant12	2412	-1.84	≤8.00	PASS
	Ant7	2412	-2.14	≤8.00	PASS
	total	2412	1.02	≤8.00	PASS
	Ant12	2437	2.20	≤8.00	PASS
	Ant7	2437	1.93	≤8.00	PASS
	total	2437	5.08	≤8.00	PASS
	Ant12	2462	-1.58	≤8.00	PASS
	Ant7	2462	-1.73	≤8.00	PASS
	total	2462	1.36	≤8.00	PASS
11G-CDD	Ant12	2412	-4.58	≤8.00	PASS
	Ant7	2412	-4.19	≤8.00	PASS
	total	2412	-1.37	≤8.00	PASS
	Ant12	2437	0.69	≤8.00	PASS
	Ant7	2437	0.61	≤8.00	PASS
	total	2437	3.66	≤8.00	PASS
	Ant12	2462	-3.08	≤8.00	PASS
	Ant7	2462	-4.30	≤8.00	PASS
	total	2462	-0.64	≤8.00	PASS
11AX20MIMO	Ant12	2412	-5.82	≤8.00	PASS
	Ant7	2412	-5.93	≤8.00	PASS
	total	2412	-2.86	≤8.00	PASS
	Ant12	2437	-0.08	≤8.00	PASS
	Ant7	2437	-0.25	≤8.00	PASS
	total	2437	2.85	≤8.00	PASS
	Ant12	2462	-4.58	≤8.00	PASS
	Ant7	2462	-4.42	≤8.00	PASS
	total	2462	-1.49	≤8.00	PASS
11AX40MIMO	Ant12	2422	-8.55	≤8.00	PASS
	Ant7	2422	-8.44	≤8.00	PASS
	total	2422	-5.48	≤8.00	PASS
	Ant12	2437	-5.88	≤8.00	PASS
	Ant7	2437	-5.97	≤8.00	PASS
	total	2437	-2.91	≤8.00	PASS
	Ant12	2452	-9.47	≤8.00	PASS
	Ant7	2452	-10.39	≤8.00	PASS
	total	2452	-6.90	≤8.00	PASS



Test Graphs

