

Giant Telecom Ltd.

Application
For
Class II Permissive Change

2.4GHz Frequency Hopping Spread Spectrum Cordless Network (VoIP) Phone
with Router Base

(FCC ID: RAQVP1000X)

06008741
TL/Ann Choy
March 14, 2006

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2741 1693 Website: www.hk.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labelling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Security Code Information
<i>EXHIBIT 10:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Giant Telecom Ltd. - MODEL: VP1000SBR

FCC ID: RAQVP1000X

This report concerns (check one) Original Grant _____ Class II Change X _____

Equipment Type: DSS-Part 15 Spread Spectrum Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No X _____

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No X _____

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-04 Edition] provision.

Report prepared by:

Tommy Leung
Intertek Testing Services Hong Kong Ltd.
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone: 852-2173-8538
Fax: 852-2741-1693

INTERTEK TESTING SERVICES

Table of Contents

1.0 <u>Summary of test results</u>	2
2.0 <u>General Description</u>	4
2.1 Product Description	4
2.2 Purpose of Application	4
2.3 Related Submittal(s) Grants	5
2.4 Test Methodology	5
2.5 Test Facility	5
3.0 <u>System Test Configuration</u>	7
3.1 Justification	7
3.2 EUT Exercising Software	7
3.3 Support Equipment List and Description	8
3.4 Measurement Uncertainty	9
3.5 Equipment Modification	9
4.0 <u>Measurement Results</u>	11
4.1 Out of Band Conducted Emissions	11
4.2 Out of Band Radiated Emissions	12
4.3 Transmitter Radiated Emissions in Restricted Bands	13
4.4 Field Strength Calculation	14
4.5 Radiated Emission Configuration Photograph - Base Unit	15
4.6 Radiated Emission Data - Base Unit	16
4.7 AC Line Conducted Emission	20
4.8 Line Conducted Configuration Photograph - Base Unit	21
4.9 Line Conducted Emission Configuration Data	22
4.10 Radiated Emission from Digital Section of Transceiver	23
4.11 Transmitter Duty Cycle Calculation and Measurements	26
5.0 <u>Equipment Photographs</u>	28
6.0 <u>Product Labelling</u>	30
7.0 <u>Technical Specifications</u>	32
8.0 <u>Instruction Manual</u>	34
9.0 <u>Security Code Information</u>	36
10.0 <u>Confidentiality Request</u>	38

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Test Report	Confidentiality Request	request.pdf
Test Report	Test Report	report.pdf
Cover Page	Purpose of Application	product change.pdf
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	config photos.doc
Test Setup Photo	Conducted Emission	config photos.doc
Test Report	Out Band Antenna Conducted Emission Plot	obantcon.pdf
Test Report	Duty Cycle Calculation and Measurement	dcc.pdf
Test Report	Conducted Emission Test Result	conduct.pdf
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
User Manual	FCC Information	FCC information.pdf
Operation Description	Security Code Information	security code information.pdf

EXHIBIT 1
SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test

Giant Telecom Ltd. - MODEL: VP1000SBR

FCC ID: RAQVP1000X

TEST	REFERENCE	RESULTS
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Radiated Emission from Digital Part	15.109	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses a permanently attached antenna which, in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

EXHIBIT 2
GENERAL DESCRIPTION

2.0 **General Description**

2.1 Product Description

The VP1000SBR is a 2.4GHz Frequency Hopping Spread Spectrum Cordless Network (VoIP) Phone with Router Base. It operates at frequency range of 2401.056MHz to 2482.272MHz with 95 hopping frequencies.

The system includes a base unit and handset unit.

The base unit consists of a page key and a LAN and a WAN interface.

The handset unit consists of a keypad with twelve standard keys (0,...9, *, #), nine function keys (V.Mail, PROG/Cancel, Int., Clear, Flash/spk, Redial, Call return, Info, repeat dial). A phone key is provided to control pick/release telephone line in a toggle base.

The antennas used in base unit and handset are integral, and the test sample is a prototype.

The circuit description and frequency hopping algorithm is saved with filename: descri.pdf

2.2 Purpose of Application

The purpose of application is saved with filename: product change.pdf.

As the RF module and FHSS mechanism of the base unit remained unchanged and they have the same handset, only the out of band conducted emission results, radiated emission results, and AC line conducted emission results of the base unit were included in this report.

INTERTEK TESTING SERVICES

2.3 Related Submittal(s) Grants

This is an application for Certification of a DSS-Part 15 Spread Spectrum Cordless VoIP Phone system. The computer peripherals device portion is subject to declaration of conformity.

2.4 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

EXHIBIT 3
SYSTEM TEST CONFIGURATION

3.0 **System Test Configuration**

3.1 Justification

For emissions testing, the units were setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. The base unit attaches to a Notebook computer and a VoIP phone (model: VP1000). They are connected by RJ45 Cat 5 unshielded cable and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1MHz or greater for frequencies above 1000MHz.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9kHz to 25GHz.

3.2 EUT Exercising Software

The EUT exercise program (TCP/IP protocol) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

HARDWARE:

The unit was operated standalone. An AC adaptor and a battery (provided with the unit) were used to power the device. Their description are listed below.

- (1) Base Unit: An AC adaptor (120VAC to 9VDC 700mA, Model: SA41-118A)
- (2) Handset: A "Ni-MH" type rechargeable battery (3.6V 600mAh, Model: 60AAAH3BMXZ)
- (3) Non-removeable adaptor for extra charger (120VAC to 9VDC 200mA, Model: MA132-090020).

CABLES:

- (1) 1 x serial cable with 1 meter long
- (2) 1 x parallel cable with 1 meter long
- (3) 2 x unshielded CAT 5 LAN cable with 3 meter long (Supplied by Client)

OTHERS:

- (1) A headset for telephone use with 1.2m unshielded cable permanently affixed.
- (2) VoIP Phone, Model: VP1000, FCC ID: RAQVP1000X (Supplied by Client)
- (3) Toshiba Notebook, Model: PT810L-21CE2, S/N: 30013417J, DOC Product
- (4) HP Mouse, Model: M-S34, S/N: LZC84609205, FCC ID: DZL211029
- (5) HP Printer, Model: C2642A, S/N: 6121702C, FCC ID: B94C2642X
Model: C6431D, S/N: CN23B680ZP, DOC Product
- (6) Hayes Modem, Model: 6800CN, S/N: A00900153317, FCC ID: BFJD907-00038
- (7) Genius Modem, Model: GM56EX, S/N: ZT5505000355, DOC Product

INTERTEK TESTING SERVICES

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification


Any modifications installed previous to testing by Giant Telecom Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

Confirmed by:

*Tommy Leung
Assistant Manager
Intertek Testing Services Hong Kong Ltd.
Agent for Giant Telecom Ltd.*



Signature

Mar 21, 2006 Date

EXHIBIT 4
MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.0 Measurement Results

4.1 Out of Band Conducted Emissions, FCC Rule 15.247(d):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Plot B6A.1 - B6A.2: Low Channel Emissions
Plot B6B.1 - B6B.2: Middle Channel Emissions
Plot B6C.1 - B6C.2: High Channel Emissions
Plot B6D.1 - B6D.2: Modulation Products Emissions*

The plots showed the 2nd harmonic and modulation products at the band edges of 2400MHz and 2483.5MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Furthermore, delta measurement technique for measuring bandedge emissions was incorporated in the test of the edge at 2483.5MHz.

*These 2 plots are shown the worst-case which has been already considered between enable and disable the hopping function of the EUT.

For electronic filing, the above plots are saved with filenames: obantcon.pdf

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.2 Out of Band Radiated Emissions (for emissions in 4.1 above that are less than 20 dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☒ Not required, all emissions more than 20dB below fundamental
- ☐ See attached data sheet

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.3 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.4 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.5 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission
at
19858.176 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR


Date of Test: January 19-March 6, 2006

4.6 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 26.7 dB margin compare with the peak limit

TEST PERSONNEL:



Tester Signature

Kenneth C. C. Lam, Senior Lead Engineer
Typed/Printed Name

March 14, 2006
Date

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR
Mode : TX-Channel 0

Date of Test: January 19-March 6, 2006

Table 1, Base Unit

Radiated Emissions

Polari- zation	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (-dB)	Calculated at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	*1200.528	53.1	34	26.1	45.2	29.6	15.6	54	-38.4
V	*4802.112	44.5	34	34.9	45.4	29.6	15.8	54	-38.2
V	*12005.280	39.1	34	40.5	45.6	29.6	16.0	54	-38.0
V	*19208.448	41.6	34	37.7	45.3	29.6	15.7	54	-38.3

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Kenneth C. C. Lam

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR
Mode : TX-Channel 47

Date of Test: January 19-March 6, 2006

Table 2, Base unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (-dB)	Calculated at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	*1220.832	53.3	34	26.1	45.4	29.6	15.8	54	-38.2
V	*4883.328	44.8	34	34.9	45.7	29.6	16.1	54	-37.9
V	*7324.992	42.1	34	37.9	46.0	29.6	16.4	54	-37.6
V	*12208.320	39.9	34	40.5	46.4	29.6	16.8	54	-37.2
V	*19533.312	42.3	34	37.8	46.1	29.6	16.5	54	-37.5

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Kenneth C. C. Lam

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR
Mode : TX-Channel 94

Date of Test: January 19-March 6, 2006

Table 3, Base unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (-dB)	Calculated at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	**2482.272	123.8	34	29.4	119.2	29.6	89.6	---	---
V	*4964.544	45.0	34	34.9	45.9	29.6	16.3	54	-37.7
V	*7446.816	42.4	34	37.9	46.3	29.6	16.7	54	-37.3
V	*12411.360	40.3	34	40.5	46.8	29.6	17.2	54	-36.8
V	*19858.176	43.5	34	37.8	47.3	29.6	17.7	54	-36.3
V	*22340.448	42.9	34	38.2	47.1	29.6	17.5	54	-36.5

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 26.7dB margin at 19858.176MHz.
- ** Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Kenneth C. C. Lam

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.7 AC Line Conducted Emission, FCC Rule 15.207:

☐ Not required; battery operation only

☒ Test data attached

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.8 Line Conducted Configuration Photograph - Base

Worst Case Line-Conducted Configuration
at
29.235MHz

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.9 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by 15.2 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Kenneth C. C. Lam, Senior Lead Engineer
Typed/Printed Name

March 14, 2006
Date

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.10 Radiated Emissions from Digital Section of Transceiver (Transmitter), FCC Ref: 15.109

☐ Not required - No digital part

☒ Test results are attached

☐ Included in the separated DOC report.

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR
Mode: VoIP Online

Date of Test: January 19-March 6, 2006

Table 4, Base Unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	50.004	34.3	16	11.0	29.3	40.0	-10.7
V	75.004	39.1	16	6.0	29.1	40.0	-10.9
V	100.004	37.6	16	12.0	33.6	43.5	-9.9
V	125.004	36.7	16	14.0	34.7	43.5	-8.8
H	150.004	31.0	16	14.0	29.0	43.5	-14.5
H	175.004	26.3	16	19.0	29.3	43.5	-14.2
H	200.004	29.9	16	16.0	29.9	43.5	-13.6
H	225.004	32.8	16	18.0	34.8	46.0	-11.2
H	250.004	32.4	16	20.0	36.4	46.0	-9.6
H	275.004	24.4	16	22.0	30.4	46.0	-15.6
H	300.004	30.8	16	22.0	36.8	46.0	-9.2
V	400.004	28.1	16	24.0	36.1	46.0	-9.9
V	500.004	25.6	16	26.0	35.6	46.0	-10.4

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Kenneth C. C. Lam

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR
Mode: PC Online

Date of Test: January 19-March 6, 2006

Table 5, Base Unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	50.004	34.3	16	11.0	29.3	40.0	-10.7
V	75.004	39.1	16	6.0	29.1	40.0	-10.9
V	100.004	37.4	16	12.0	33.4	43.5	-10.1
V	125.004	36.3	16	14.0	34.3	43.5	-9.2
H	150.004	31.1	16	14.0	29.1	43.5	-14.4
H	175.004	26.7	16	19.0	29.7	43.5	-13.8
H	200.004	30.1	16	16.0	30.1	43.5	-13.4
H	225.004	32.7	16	18.0	34.7	46.0	-11.3
H	250.004	32.2	16	20.0	36.2	46.0	-9.8
H	275.004	24.8	16	22.0	30.8	46.0	-15.2
H	300.004	30.9	16	22.0	36.9	46.0	-9.1
V	400.004	27.8	16	24.0	35.8	46.0	-10.2
V	500.004	25.0	16	26.0	35.0	46.0	-11.0

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Kenneth C. C. Lam

INTERTEK TESTING SERVICES

Company: Giant Telecom Ltd.
Model: VP1000SBR

Date of Test: January 19-March 6, 2006

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Base Unit:

Duty cycle (DC) = Maximum ON time in 100ms/100ms
= (0.82ms x 4)/100ms for 4 handsets operation

Duty cycle correction, dB = $20 \times \log(\text{DC})$
= $20 \times \log(0.0328)$
= -29.6 dB

X	See attached spectrum analyzer chart (s) for transmitter timing Base Unit: Plot B7
	See transmitter timing diagram provided by manufacturer
	Not applicable, duty cycle was not used.

For electronic filing, the above plots are saved with filenames: dcc.pdf

EXHIBIT 5
EQUIPMENT PHOTOGRAPHS

5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc

EXHIBIT 6
PRODUCT LABELLING

6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename:
label.pdf

EXHIBIT 7
TECHNICAL SPECIFICATIONS

7.0 **Technical Specifications**

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 8
INSTRUCTION MANUAL

8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

Please note that the required FCC Information to the User is saved with filename: FCC information.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 9
SECURITY CODE INFORMATION

9.0 **Security Code Information**

For electronic filing, a security code information is saved with filename: security code information.pdf

EXHIBIT 10
CONFIDENTIALITY REQUEST

10.0 **Confidentiality Request**

For electronic filing, a confidentiality request is saved with filename: request.pdf