



Engineering Analysis MPE for ERM1, 4.9-5.9 GHz Transceiver

FCC ID: RAR20021001

BelAir Networks

This analysis was performed as part of the FCC certification requirements for spread spectrum devices, according to the requirements of: FCC part 15, and FCC OET Bulletin 65 “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”.

- Module RAR20021001 will be mounted in BelAir Networks host units and will be professionally installed (Fixed) to provide a minimum separation distance from all persons as detailed in co-location compliance tables below.
- Module RAR20021001 may be co-located with other modules in BelAir Networks products as shown in the co-location compliance tables below. Worst-case configurations are shown below.
- This device will only be operated according to the exposure conditions described in this application.
- End users and installers will be provided with antenna installation and transmitter operating conditions for satisfying RF exposure compliance.

The measured worst-case transmit power yielding the worst-case EIRP were used for the MPE calculations. Calculations were performed based on FCC OET Bulletin 65. The calculations are performed based on the following formula provided in OET 65:

$$S = \text{EIRP} / (4\pi R^2).$$

Co-location compliance for multiple frequency exposure criteria to the power density exposure limit is detailed in the table below. This calculation is a worst-case analysis since it assumes all devices are continuously transmitting. The device utilizes the 802.11 WLAN protocol which operates in time-division duplex (TDD) mode, so the transmit duty cycle can never be 100% in normal operation. It is also assumed that all directional antennas are aligned to point in the same direction so that power from all radios adds together.



The following tables outlines the MPE analysis for various combinations of radios and antenna the RAR200021001 can be used with:

Notes:

1. Cases I-VI are for the BelAir200 which supports a single ERM1 or multiple ERM2 radios. The BelAir200 does not support multiple ERM1 radios.
2. For ease of reading, the ERM1 cases below are highlighted in yellow.
3. All BelAir100 cases with a single ERM radio use ERM1, and the case with 2 ERM radios uses ERM2.

BelAir200

Case I: 3 X RAR20031001 (ERM2) 5.725 - 5.850 GHz 19 dBi or less antennas-1 X RAR20000003 (ARM3)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios								
Safety Distance:			65 cm		(25.6 inches)			
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Total Density for co-located radios [mW/cm^2]	Limit: General Population / Uncontrolled Exposure [mW/cm^2]	Result
RAR20000003 (ARM3)			RAR20031001 (ERM2)					
35.5	0.067	1	42	0.299	3	0.962	1	Complies

Case II: 3 X RAR20031001 (ERM2) 5.725 - 5.850 GHz with 23, 28, 30 dBi antennas and 1 X RAR20000003 (ARM3)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios								
Safety Distance:			156 cm		(61.4 inches)			
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Total Density for co-located radios [mW/cm^2]	Limit: General Population / Uncontrolled Exposure [mW/cm^2]	Result
RAR20000003 (ARM3)			RAR20031001 (ERM2)					
35.5	0.012	1	50	0.327	3	0.993	1	Complies



Case IIIa: 2 X RAR20031001 (ERM2) 5.725 - 5.850 GHz with 19 dBi or less antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20004001 (PSM1) or 1 X RAR20008001 (PSM2) (10 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.11a Public Service Radios										Result				
Safety Distance:			42 cm			(16.5 inches)				Result				
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Total Density for co-located radios [mW/cm^2]					
RAR20000003 (ARM3)	RAR20031001 (ERM2)	RAR20008001 (PSM2)	35.5	0.160	1	39	0.358	2	34	0.113	1	0.990	1	Complies

Case IIIb: 2 X RAR20031001 (ERM2) 5.725 - 5.850 GHz with 19 dBi or less antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20004001 (PSM1) or 1 X RAR20008001 (PSM2) (25 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.11a Public Service Radios										Result				
Safety Distance:			89 cm			(35.0 inches)				Result				
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Total Density for co-located radios [mW/cm^2]					
RAR20000003 (ARM3)	RAR20031001 (ERM2)	RAR20008001 (PSM2)	35.5	0.036	1	39	0.080	2	49	0.798	1	0.993	1	Complies

Case IVa: 2 X RAR20031001 (ERM2) 5.725 - 5.850 GHz with 23, 28, 30 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20004001 (PSM1) or 1 X RAR20008001 (PSM2) (10dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.11a Public Service Radios										Result				
Safety Distance:			129 cm			(50.8 inches)				Result				
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Total Density for co-located radios [mW/cm^2]					
RAR20000003 (ARM3)	RAR20031001 (ERM2)	RAR20008001 (PSM2)	35.5	0.017	1	50	0.478	2	34	0.012	1	0.985	1	Complies

Case IVb: 2 X RAR20031001 (ERM2) 5.725 - 5.850 GHz with 23, 28, 30 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20004001 (PSM1) or 1 X RAR20008001 (PSM2) (25dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.11a Public Service Radios										Result				
Safety Distance:			151 cm			(59.4 inches)				Result				
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Total Density for co-located radios [mW/cm^2]					
RAR20000003 (ARM3)	RAR20031001 (ERM2)	RAR20008001 (PSM2)	35.5	0.012	1	50	0.349	2	49	0.277	1	0.988	1	Complies



Case Va: 1 X RAR20021001 (ERM1) 5.725-5.850 GHz with 19 dBi or less antennas and 1 X RAR20000003 (ARM3) and 2 X RAR20006001 (WRM1) or 2 X RAR20007001 (WRM2) (15 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios										Result
Safety Distance:			47 cm (18.5 inches)						Total Density for co-located radios [mW/cm^2]	Limit: General Population / Uncontrolled Exposure [mW/cm^2]
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios		
RAR20000003 (ARM3)	RAR20021001 (ERM1)			RAR20006001 (WRM1)						Complies
35.5	0.128	1	42	0.571	1	36	0.143	2	0.986	1

Case Vb: 1 X RAR20021001 (ERM1) 5.725-5.850 GHz with 23 dBi or less antennas and 1 X RAR20000003 (ARM3) and 2 X RAR20006001 (WRM1) or 2 X RAR20007001 (WRM2) (25dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios										Result
Safety Distance:			99 cm (39.0 inches)						Total Density for co-located radios [mW/cm^2]	Limit: General Population / Uncontrolled Exposure [mW/cm^2]
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios		
RAR20000003 (ARM3)	RAR20021001 (ERM1)			RAR20006001 (WRM1)						Complies
35.5	0.029	1	46	0.323	1	46	0.323	2	0.999	1

Case VIa: 2 X RAR20031001 (ERM2) 5.725-5.850 GHz with 23, 28, 30 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20006001 (WRM1) or 1 X RAR20007001 (WRM2)(15 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios										Result
Safety Distance:			129 cm (50.8 inches)						Total Density for co-located radios [mW/cm^2]	Limit: General Population / Uncontrolled Exposure [mW/cm^2]
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios		
RAR20000003 (ARM3)	RAR20031001 (ERM2)			RAR20006001 (WRM1)						Complies
35.5	0.017	1	50	0.478	2	36	0.019	1	0.992	1

Case VIIb: 2 X RAR20031001 (ERM2) 5.725-5.850 GHz with 23, 28, 30 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20006001 (WRM1) or 1 X RAR20007001 (WRM2)(25dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios										Result
Safety Distance:			140 cm (55.1 inches)						Total Density for co-located radios [mW/cm^2]	Limit: General Population / Uncontrolled Exposure [mW/cm^2]
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios		
RAR20000003 (ARM3)	RAR20031001 (ERM2)			RAR20006001 (WRM1)						Complies
35.5	0.014	1	50	0.406	2	46	0.162	1	0.988	1

**BelAir100**

Case VIIa: 1X RAR20021001 (ERM1) 5.725 - 5.850 GHz with 19 dBi or less antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20008001 (PSM2) (10 dBi)

Safety Distance:			42 cm (16.5 inches)								
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Total Density for co-located radios	Limit: General Population / Uncontrolled Exposure	Result
RAR20000003 (ARM3)											
35.5	0.160	1	42	0.715	1	34	0.113	1	0.988	1	Complies

Case VIIb: 1X RAR20021001 (ERM1) 5.725 - 5.850 GHz with 19 dBi or less antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20008001 (PSM2) (25 dBi)

Safety Distance:			89 cm (35.0 inches)								
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Total Density for co-located radios	Limit: General Population / Uncontrolled Exposure	Result
RAR20000003 (ARM3)											
35.5	0.036	1	42	0.159	1	49	0.798	1	0.993	1	Complies

Case VIIa: 1X RAR20021001 (ERM1) 5.725 - 5.850 GHz with 23 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20008001 (PSM2) (10 dBi)

Safety Distance:			61 cm (24.0 inches)								
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Total Density for co-located radios	Limit: General Population / Uncontrolled Exposure	Result
RAR20000003 (ARM3)											
35.5	0.076	1	46	0.851	1	34	0.054	1	0.981	1	Complies

Case VIIib: 1X RAR20021001 (ERM1) 5.725 - 5.850 GHz with 23 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20008001 (PSM2)(25dBi)

Safety Distance:			99 cm (39.0 inches)								
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Density for co-located radios	Population / Uncontrolled Exposure	Result
RAR20000003 (ARM3)											
35.5	0.029	1	46	0.323	1	49	0.645	1	0.997	1	Complies



Case IXa: 1X RAR20021001 (ERM1) 5.725-5.850 GHz with 19 dBi or less antennas and 1 X RAR20008001 (PSM2) and 1 X RAR20006001 (WRM1) or 1 X RAR20007001 (WRM2) (15 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios														
Safety Distance:			43 cm (16.9 inches)											
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios						
RAR20008001 (PSM2)	RAR20021001 (ERM1)	RAR20006001 (WRM1)	34	0.108	1	42	0.682	1	36	0.171	1	0.962	1	Complies

Case IXb: 1X RAR20021001 (ERM1) 5.725-5.850 GHz with 19 dBi or less antennas and 1 X RAR20008001 (PSM2) and 1 X RAR20006001 (WRM1) or 1 X RAR20007001 (WRM2) (25 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios														
Safety Distance:			69 cm (27.2 inches)											
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios						
RAR20008001 (PSM2)	RAR20021001 (ERM1)	RAR20006001 (WRM1)	34	0.042	1	42	0.265	1	46	0.665	1	0.972	1	Complies

Case Xa: 1X RAR20021001 (ERM1) 5.725-5.850 GHz with 23 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20006001 (WRM1) or 1 X RAR20007001 (WRM2)(15 dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios														
Safety Distance:			62 cm (24.4 inches)											
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios						
RAR20000003 (ARM3)	RAR20021001 (ERM1)	RAR20006001 (WRM1)	35.5	0.073	1	46	0.824	1	36	0.082	1	0.980	1	Complies

Case Xb: 1X RAR20021001 (ERM1) 5.725-5.850 GHz with 23 dBi antennas and 1 X RAR20000003 (ARM3) and 1 X RAR20006001 (WRM1) or 1 X RAR20007001 (WRM2)(25dBi)

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios														
Safety Distance:			82 cm (32.3 inches)											
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Number of Radios						
RAR20000003 (ARM3)	RAR20021001 (ERM1)	RAR20006001 (WRM1)	35.5	0.042	1	46	0.471	1	46	0.471	1	0.984	1	Complies



Case XIa: 2X RAR20031001 (ERM2) 5.725-5.850 GHz with 19 dBi or less antennas and 1 X RAR20008001 (PSM2) with 10 dBi

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios												
Safety Distance:		39 cm		(15.4 inches)								
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Density for co-located	Population / Uncontrolled Exposure [mW/cm^2]	Result	
RAR20008001 (PSM2) 34	0.131	1	RAR20031001 (ERM2) 39	0.416	2	0	0.000	0	0.963	1	Complies	

Case XIb: 2X RAR20031001 (ERM2) 5.725-5.850 GHz with 30 dBi or less antennas and 1 X RAR20008001 (PSM2) with 25 dBi

Co-location Compliance for Integrated 802.11b/g & 802.11a Radios & 802.16 WCS band Radios												
Safety Distance:		150 cm		(59.1 inches)								
Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Worst-case Total EIRP [dBm]	Max Power Density [mW/cm^2]	Maximum Number of Radios	Total Density for co-located radios	Limit: General Population / Uncontrolled Exposure [mW/cm^2]	Result	
RAR20008001 (PSM2) 49	0.281	1	RAR20031001 (ERM2) 50	0.354	2	RAR20006001 (WRM1) 0	0.000	0	0.988	1	Complies	

The equipment therefore fulfills the requirements on power density for general population/uncontrolled exposure and therefore complies with the requirements of FCC Bulletin 65.



The following worst case summary table will be incorporated in BelAir Networks installation procedures.

Product	Minimum Safety Distances									
	Standard Antennas (up to 19 dBi)					High Gain Antennas (up to 30 dBi)				
RF boards: All valid combinations	ERM1	ERM2	ARM3C	PSM1 PSM2	WRM1 WRM2	ERM1	ERM2	ARM3C	PSM1 PSM2	WRM1 WRM2
BelAir100, BelAir100C, BelAir100T, BelAir100S, BelAir100M, BelAir100D	up to 19 dBi	up to 19 dBi	Any	10 dBi	15 dBi	up to 23 dBi	up to 30 dBi	Any	25 dBi	25 dBi
Distance	43 cm (16.5 in)					150 cm (59.1 in)				
BelAir200, BelAir200D	up to 19 dBi	up to 19 dBi	Any	10 dBi	15 dBi	up to 23 dBi	up to 30 dBi	Any	25 dBi	25 dBi
Distance	65 cm (25.6 in)					156 cm (61.4 in)				
RAR20000003 (ARM3); RAR20004001 (PSM1); RAR20008001 (PSM2); RAR20021001 (ERM1); RAR20031001 (ERM2); RAR20006001 (WRM1); RAR20007001 (WRM2)										