

# SAR Test Report

**Report No.** : SF190628E01J  
**Applicant** : MediaTek Inc.  
**Address** : No.1, Duxing 1st Rd., East District, Hsinchu City 300, Taiwan (R.O.C.)  
**Product** : 2TX 11ac + BLE Combo Card  
**FCC ID** : RAS-MT7663  
**Brand** : MTK  
**Model No.** : MT7663  
**Standards** : FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013  
KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 248227 D01 v02r02,  
KDB 447498 D01 v06  
**Sample Received Date** : Jun. 28, 2019  
**Date of Testing** : Oct. 25, 2019 ~ Nov. 08, 2019 / Jul. 14, 2020  
**Lab Address** : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
**Test Location** : No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch–Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is issued as a supplementary report to BV CPS report no.: SF190628E01B. The differences compared with original report are adding Ch. 10 ~ Ch. 13 of WLAN 2.4GHz

Prepared By :



Shelly Hsueh / Specialist

Approved By :



Gordon Lin / Manager



FCC Accredited No.: TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|                                                                                        |    |
|----------------------------------------------------------------------------------------|----|
| Release Control Record .....                                                           | 3  |
| 1. Summary of Maximum SAR Value .....                                                  | 4  |
| 2. Description of Equipment Under Test .....                                           | 5  |
| 3. SAR Measurement System .....                                                        | 6  |
| 3.1 Definition of Specific Absorption Rate (SAR) .....                                 | 6  |
| 3.2 SPEAG DASY6 System .....                                                           | 6  |
| 3.2.1 Robot .....                                                                      | 7  |
| 3.2.2 Probes .....                                                                     | 8  |
| 3.2.3 Data Acquisition Electronics (DAE) .....                                         | 8  |
| 3.2.4 Phantoms .....                                                                   | 8  |
| 3.2.5 Device Holder .....                                                              | 9  |
| 3.2.6 System Validation Dipoles .....                                                  | 10 |
| 3.2.7 Power Source .....                                                               | 10 |
| 3.2.8 Tissue Simulating Liquids .....                                                  | 11 |
| 3.3 SAR System Verification .....                                                      | 13 |
| 3.4 SAR Measurement Procedure .....                                                    | 14 |
| 3.4.1 Area & Zoom Scan Procedure .....                                                 | 14 |
| 3.4.2 Volume Scan Procedure .....                                                      | 14 |
| 3.4.3 Power Drift Monitoring .....                                                     | 15 |
| 3.4.4 Spatial Peak SAR Evaluation .....                                                | 15 |
| 3.4.5 SAR Averaged Methods .....                                                       | 15 |
| 4. SAR Measurement Evaluation .....                                                    | 16 |
| 4.1 EUT Configuration and Setting .....                                                | 16 |
| 4.2 EUT Testing Position .....                                                         | 18 |
| 4.2.1 Body Exposure Conditions .....                                                   | 18 |
| 4.3 Tissue Verification .....                                                          | 19 |
| 4.4 System Validation .....                                                            | 19 |
| 4.5 System Verification .....                                                          | 20 |
| 4.6 Maximum Output Power .....                                                         | 21 |
| 4.6.1 Maximum Target Conducted Power .....                                             | 21 |
| 4.6.2 Measured Conducted Power Result .....                                            | 25 |
| 4.7 SAR Testing Results .....                                                          | 26 |
| 4.7.1 SAR Test Reduction Considerations .....                                          | 26 |
| 4.7.2 SAR Results for Body Exposure Condition (Test Separation Distance is 5 mm) ..... | 27 |
| 4.7.3 SAR Measurement Variability .....                                                | 29 |
| 4.7.4 Simultaneous Multi-band Transmission Evaluation .....                            | 30 |
| 5. Calibration of Test Equipment .....                                                 | 31 |
| 6. Measurement Uncertainty .....                                                       | 32 |
| 7. Information of the Testing Laboratories .....                                       | 33 |
| Appendix A. SAR Plots of System Verification                                           |    |
| Appendix B. SAR Plots of SAR Measurement                                               |    |
| Appendix C. Calibration Certificate for Probe and Dipole                               |    |
| Appendix D. Photographs of EUT and Setup                                               |    |

## Release Control Record

| Report No.   | Reason for Change | Date Issued   |
|--------------|-------------------|---------------|
| SF190628E01J | Initial release   | Aug. 19, 2020 |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |
|              |                   |               |

## SAR Test Report

### 1. Summary of Maximum SAR Value

| Equipment Class | Mode      | Highest SAR-1g Body<br>Tested at 5 mm<br>(W/kg) |
|-----------------|-----------|-------------------------------------------------|
| DTS             | 2.4G WLAN | 0.33                                            |
| NII             | 5.3G WLAN | 0.42                                            |
|                 | 5.6G WLAN | 0.64                                            |
|                 | 5.8G WLAN | 0.79                                            |
| DSS             | Bluetooth | 0.12                                            |

| Highest Simultaneous Transmission SAR | Highest SAR-1g Body<br>Tested at 5 mm<br>(W/kg) |
|---------------------------------------|-------------------------------------------------|
|                                       | 0.68                                            |

**Note:**

- The SAR criteria (**Head & Body: SAR-1g 1.6 W/kg, and Extremity: SAR-10g 4.0 W/kg**) for general population/uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

## SAR Test Report

### 2. Description of Equipment Under Test

|                                                |                                                                                                   |
|------------------------------------------------|---------------------------------------------------------------------------------------------------|
| EUT Type                                       | 2TX 11ac + BLE Combo Card                                                                         |
| FCC ID                                         | RAS-MT7663                                                                                        |
| Brand Name                                     | MTK                                                                                               |
| Model Name                                     | MT7663                                                                                            |
| Tx Frequency Bands<br>(Unit: MHz)              | WLAN : 2412 ~ 2472, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5720, 5745 ~ 5825<br>Bluetooth : 2402 ~ 2480 |
| Uplink Modulations                             | 802.11b : DSSS<br>802.11a/g/n/ac : OFDM<br>Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK               |
| Maximum Tune-up Conducted Power<br>(Unit: dBm) | Please refer to section 4.6.1 of this report                                                      |
| Antenna Type                                   | Fixed Internal Antenna                                                                            |
| EUT Stage                                      | Engineering Sample                                                                                |

#### Note:

- The EUT contains two samples are listed as below.

| Sample | Description    |
|--------|----------------|
| 1      | PCIe interface |
| 2      | SDIO interface |

#### Note:

PCIe and SDIO interface signal switch by IC bonding on the same pin, Most of the layout including RF, PMU, and the control signal is the same.

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

#### List of Antenna:

|         |                |                                                            |
|---------|----------------|------------------------------------------------------------|
| Antenna | Brand Name     | PSA                                                        |
|         | Model Name     | Chain 0: RFMTA340718EMLB301<br>Chain 1: RFMTA340718EMLB301 |
|         | Antenna Type   | PIFA                                                       |
|         | Connector Type | i-pex (MHF)                                                |

#### Report Issue History Record:

| Issue No.    | Description                           | Date Issued   |
|--------------|---------------------------------------|---------------|
| SA190628E01B | Original release.                     | Nov. 18, 2019 |
| SF190628E01J | Adding Ch. 10 ~ Ch. 13 of WLAN 2.4GHz | Aug. 19, 2020 |

### **3. SAR Measurement System**

#### **3.1 Definition of Specific Absorption Rate (SAR)**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

#### **3.2 SPEAG DASY6 System**

DASY6 system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY6 software defined. The DASY6 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.



**Fig-3.1 SPEAG DASY6 System Setup**

## 3.2.1 Robot

The DASY6 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version of CS8c from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



**Fig-3.2 SPEAG DASY6 System**

## SAR Test Report

### 3.2.2 Probes


The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

|                      |                                                                                                                                                          |                                                                                     |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>         | EX3DV4                                                                                                                                                   |  |
| <b>Construction</b>  | Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |                                                                                     |
| <b>Frequency</b>     | 4 MHz to 10 GHz<br>Linearity: $\pm 0.2$ dB                                                                                                               |                                                                                     |
| <b>Directivity</b>   | $\pm 0.1$ dB in TSL (rotation around probe axis)<br>$\pm 0.3$ dB in TSL (rotation normal to probe axis)                                                  |                                                                                     |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)                                                                   |                                                                                     |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                     |                                                                                     |


### 3.2.3 Data Acquisition Electronics (DAE)

|                             |                                                                                                                                                                                                                                                     |                                                                                      |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>                | DAE3, DAE4                                                                                                                                                                                                                                          |  |
| <b>Construction</b>         | Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop. |                                                                                      |
| <b>Measurement Range</b>    | -100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)                                                                                                                                                                              |                                                                                      |
| <b>Input Offset Voltage</b> | $< 5\mu$ V (with auto zero)                                                                                                                                                                                                                         |                                                                                      |
| <b>Input Bias Current</b>   | $< 50$ fA                                                                                                                                                                                                                                           |                                                                                      |
| <b>Dimensions</b>           | 60 x 60 x 68 mm                                                                                                                                                                                                                                     |                                                                                      |

### 3.2.4 Phantoms

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>           | SAM-Twin Phantom                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |  |
| <b>Construction</b>    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE Std 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. |                                                                                       |
| <b>Material</b>        | Vinylester, fiberglass reinforced (VE-GF)                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       |
| <b>Shell Thickness</b> | $2 \pm 0.2$ mm ( $6 \pm 0.2$ mm at ear point)                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                       |
| <b>Dimensions</b>      | Length: 1000 mm<br>Width: 500 mm<br>Height: adjustable feet                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                       |
| <b>Filling Volume</b>  | approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                       |

## SAR Test Report

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>           | ELI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |
| <b>Construction</b>    | The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. |                                                                                     |
| <b>Material</b>        | Vinylester, fiberglass reinforced (VE-GF)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                     |
| <b>Shell Thickness</b> | 2.0 ± 0.2 mm (bottom plate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                     |
| <b>Dimensions</b>      | Major axis: 600 mm<br>Minor axis: 400 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                     |
| <b>Filling Volume</b>  | approx. 30 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                     |

### 3.2.5 Device Holder

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>        | MD4HHTV5 - Mounting Device for Hand-Held Transmitters                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |
| <b>Construction</b> | In combination with the Twin SAM or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). |                                                                                      |
| <b>Material</b>     | Polyoxymethylene (POM)                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                      |

|                     |                                                                                                                                                                          |                                                                                       |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>        | MDA4WTV5 - Mounting Device Adaptor for Ultra Wide Transmitters                                                                                                           |  |
| <b>Construction</b> | An upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm. |                                                                                       |
| <b>Material</b>     | Polyoxymethylene (POM)                                                                                                                                                   |                                                                                       |

|                     |                                                                                                                                          |                                                                                       |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>        | MDA4SPV6 - Mounting Device Adaptor for Smart Phones                                                                                      |  |
| <b>Construction</b> | The solid low-density MDA4SPV6 adaptor assuring no impact on the DUT radiation performance and is conform with any DUT design and shape. |                                                                                       |
| <b>Material</b>     | ROHACELL                                                                                                                                 |                                                                                       |

## SAR Test Report

|                     |                                                                                                                                                                                                                                              |                                                                                     |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>        | MD4LAPV5 - Mounting Device for Laptops and other Body-Worn Transmitters                                                                                                                                                                      |  |
| <b>Construction</b> | In combination with the Twin SAM or ELI phantoms, the Mounting Device (Body-Worn) enables testing of transmitter devices according to IEC 62209-2 specifications. The device holder can be locked for positioning at a flat phantom section. |                                                                                     |
| <b>Material</b>     | Polyoxymethylene (POM), PET-G, Foam                                                                                                                                                                                                          |                                                                                     |

### 3.2.6 System Validation Dipoles

|                         |                                                                                                                                                                      |                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>            | D-Serial                                                                                                                                                             |  |
| <b>Construction</b>     | Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions. |                                                                                      |
| <b>Frequency</b>        | 750 MHz to 5800 MHz                                                                                                                                                  |                                                                                      |
| <b>Return Loss</b>      | > 20 dB                                                                                                                                                              |                                                                                      |
| <b>Power Capability</b> | > 100 W (f < 1GHz), > 40 W (f > 1GHz)                                                                                                                                |                                                                                      |


### 3.2.7 Power Source

|                              |                                                           |                                                                                       |
|------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>                 | Powersource1                                              |  |
| <b>Signal Type</b>           | Continuous Wave                                           |                                                                                       |
| <b>Operating Frequencies</b> | 600 MHz to 5850 MHz                                       |                                                                                       |
| <b>Output Power</b>          | -5.0 dBm to +17.0 dBm                                     |                                                                                       |
| <b>Power Supply</b>          | 5V DC, via USB jack                                       |                                                                                       |
| <b>Power Consumption</b>     | <3 W                                                      |                                                                                       |
| <b>Applications</b>          | System performance check and validation with a CW signal. |                                                                                       |

## SAR Test Report

### 3.2.8 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 10 % are listed in Table-3.1.



**Table-3.1 Targets of Tissue Simulating Liquid**

| Frequency (MHz) | Target Permittivity | Range of $\pm 10\%$ | Target Conductivity | Range of $\pm 10\%$ |
|-----------------|---------------------|---------------------|---------------------|---------------------|
| 450             | 43.5                | 39.2 ~ 47.9         | 0.87                | 0.78 ~ 0.96         |
| 750             | 41.9                | 37.7 ~ 46.1         | 0.89                | 0.80 ~ 0.98         |
| 835             | 41.5                | 37.4 ~ 45.7         | 0.90                | 0.81 ~ 0.99         |
| 900             | 41.5                | 37.4 ~ 45.7         | 0.97                | 0.87 ~ 1.07         |
| 1450            | 40.5                | 36.5 ~ 44.6         | 1.20                | 1.08 ~ 1.32         |
| 1500            | 40.4                | 36.4 ~ 44.4         | 1.23                | 1.11 ~ 1.35         |
| 1640            | 40.2                | 36.2 ~ 44.2         | 1.31                | 1.18 ~ 1.44         |
| 1750            | 40.1                | 36.1 ~ 44.1         | 1.37                | 1.23 ~ 1.51         |
| 1800            | 40.0                | 36.0 ~ 44.0         | 1.40                | 1.26 ~ 1.54         |
| 1900            | 40.0                | 36.0 ~ 44.0         | 1.40                | 1.26 ~ 1.54         |
| 2000            | 40.0                | 36.0 ~ 44.0         | 1.40                | 1.26 ~ 1.54         |
| 2100            | 39.8                | 35.8 ~ 43.8         | 1.49                | 1.34 ~ 1.64         |
| 2300            | 39.5                | 35.6 ~ 43.5         | 1.67                | 1.50 ~ 1.84         |
| 2450            | 39.2                | 35.3 ~ 43.1         | 1.80                | 1.62 ~ 1.98         |
| 2600            | 39.0                | 35.1 ~ 42.9         | 1.96                | 1.76 ~ 2.16         |
| 3000            | 38.5                | 34.7 ~ 42.4         | 2.40                | 2.16 ~ 2.64         |
| 3500            | 37.9                | 34.1 ~ 41.7         | 2.91                | 2.62 ~ 3.20         |
| 4000            | 37.4                | 33.7 ~ 41.1         | 3.43                | 3.09 ~ 3.77         |
| 4500            | 36.8                | 33.1 ~ 40.5         | 3.94                | 3.55 ~ 4.33         |
| 5000            | 36.2                | 32.6 ~ 39.8         | 4.45                | 4.01 ~ 4.90         |
| 5200            | 36.0                | 32.4 ~ 39.6         | 4.66                | 4.19 ~ 5.13         |
| 5400            | 35.8                | 32.2 ~ 39.4         | 4.86                | 4.37 ~ 5.35         |
| 5600            | 35.5                | 32.0 ~ 39.1         | 5.07                | 4.56 ~ 5.58         |
| 5800            | 35.3                | 31.8 ~ 38.8         | 5.27                | 4.74 ~ 5.80         |
| 6000            | 35.1                | 31.6 ~ 38.6         | 5.48                | 4.93 ~ 6.03         |

## SAR Test Report

The dielectric properties of the tissue simulating liquids are defined in IEC 62209-1 and IEC 62209-2. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Since the range of  $\pm 10\%$  of the required target values is used to measure relative permittivity and conductivity, the SAR correction procedure is applied to correct measured SAR for the deviations in permittivity and conductivity. Only positive correction has been used to scale up the measured SAR, and SAR result would not be corrected if the correction  $\Delta$  SAR has a negative sign.


The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid**

| Tissue Type | Bactericide | DGBE | HEC | NaCl | Sucrose | Triton X-100 | Water | Diethylene Glycol Mono-hexylether |
|-------------|-------------|------|-----|------|---------|--------------|-------|-----------------------------------|
| H750        | 0.2         | -    | 0.2 | 1.5  | 56.0    | -            | 42.1  | -                                 |
| H835        | 0.2         | -    | 0.2 | 1.5  | 57.0    | -            | 41.1  | -                                 |
| H900        | 0.2         | -    | 0.2 | 1.4  | 58.0    | -            | 40.2  | -                                 |
| H1450       | -           | 43.3 | -   | 0.6  | -       | -            | 56.1  | -                                 |
| H1640       | -           | 45.8 | -   | 0.5  | -       | -            | 53.7  | -                                 |
| H1750       | -           | 47.0 | -   | 0.4  | -       | -            | 52.6  | -                                 |
| H1800       | -           | 44.5 | -   | 0.3  | -       | -            | 55.2  | -                                 |
| H1900       | -           | 44.5 | -   | 0.2  | -       | -            | 55.3  | -                                 |
| H2000       | -           | 44.5 | -   | 0.1  | -       | -            | 55.4  | -                                 |
| H2300       | -           | 44.9 | -   | 0.1  | -       | -            | 55.0  | -                                 |
| H2450       | -           | 45.0 | -   | 0.1  | -       | -            | 54.9  | -                                 |
| H2600       | -           | 45.1 | -   | 0.1  | -       | -            | 54.8  | -                                 |
| H3500       | -           | 8.0  | -   | 0.2  | -       | 20.0         | 71.8  | -                                 |
| H5G         | -           | -    | -   | -    | -       | 17.2         | 65.5  | 17.3                              |

## 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



**Fig-3.3 System Verification Setup**

The SPEAG Powersource1 is a portable and very stable RF source providing a continuous wave (CW) signal. It is designed for conducting SAR system checks and SAR system validation of DASY and is compatible with IEC 62209-1, IEC 62209-2 and IEEE Std 1528 standards. The Powersource1 has been calibrated by SPEAG's ISO/IEC 17025-accredited calibration center. When using Powersource1, the setup can be simplified, as shown in Fig-3.3. The signal purity is warranted by design. Since the Powersource1 is calibrated, no additional equipment is needed and the Powersource1 can directly be connected to the SMA connector of the dipole without a cable as all separate components (signal generator, amplifier, coupler and power meter) are built into the unit.

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The Powersource1 is adjusted for the desired forward power of 17 dBm at the dipole connector and the RF output power would be turned on. After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

## SAR Test Report

### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664D01, the resolution for Area and Zoom scan is specified in the table below.

| Items                              | $\leq 2$ GHz | 2-3 GHz      | 3-4 GHz      | 4-5 GHz      | 5-6 GHz      |
|------------------------------------|--------------|--------------|--------------|--------------|--------------|
| Area Scan ( $\Delta x, \Delta y$ ) | $\leq 15$ mm | $\leq 12$ mm | $\leq 12$ mm | $\leq 10$ mm | $\leq 10$ mm |
| Zoom Scan ( $\Delta x, \Delta y$ ) | $\leq 8$ mm  | $\leq 5$ mm  | $\leq 5$ mm  | $\leq 4$ mm  | $\leq 4$ mm  |
| Zoom Scan ( $\Delta z$ )           | $\leq 5$ mm  | $\leq 5$ mm  | $\leq 4$ mm  | $\leq 3$ mm  | $\leq 2$ mm  |
| Zoom Scan Volume                   | $\geq 30$ mm | $\geq 30$ mm | $\geq 28$ mm | $\geq 25$ mm | $\geq 22$ mm |

#### Note:

When zoom scan is required and report SAR is  $\leq 1.4$  W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz:  $\leq 8$  mm, 3-4GHz:  $\leq 7$  mm, 4-6GHz:  $\leq 5$  mm) may be applied.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## **4. SAR Measurement Evaluation**

### **4.1 EUT Configuration and Setting**

#### **<Considerations Related to WLAN for Setup and Testing>**

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

#### **Initial Test Configuration**

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

#### **Subsequent Test Configuration**

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for that subsequent test configuration.

### SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

### Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

### <Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

## SAR Test Report

The Bluetooth call box has been used during SAR measurement and the EUT was set to DH5 mode at the maximum output power. Its duty factor was calculated as below and the measured SAR for Bluetooth would be scaled to the 100% transmission duty factor to determine compliance.



Time-domain plot for Bluetooth transmission signal

The duty factor of Bluetooth signal has been calculated as following.

$$\text{Duty Factor} = \text{Pulse Width} / \text{Total Period} = (8.582 \text{ ms} - 5.614 \text{ ms}) / (10.54 \text{ ms} - 5.614 \text{ ms}) = 60.3 \%$$

## 4.2 EUT Testing Position

### 4.2.1 Body Exposure Conditions

SAR evaluation was tested in six positions. It is the Front Face, Rear Face, Left Side, Right Side, Top Side, and Bottom Side of WLAN antenna. In these positions, the air gap between the WLAN antenna and the phantom is 5 mm.

## SAR Test Report

### 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

| Frequency (MHz) | Liquid Temp. (°C) | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Target Conductivity ( $\sigma$ ) | Target Permittivity ( $\epsilon_r$ ) | Conductivity Deviation (%) | Permittivity Deviation (%) | Test Date     |
|-----------------|-------------------|------------------------------------|----------------------------------------|----------------------------------|--------------------------------------|----------------------------|----------------------------|---------------|
| 2450            | 23.3              | 1.852                              | 38.607                                 | 1.8                              | 39.2                                 | 2.89                       | -1.51                      | Oct. 25, 2019 |
| 2450            | 23.2              | 1.824                              | 38.456                                 | 1.8                              | 39.2                                 | 1.33                       | -1.90                      | Nov. 04, 2019 |
| 2450            | 23.2              | 1.866                              | 38.343                                 | 1.8                              | 39.2                                 | 3.67                       | -2.19                      | Nov. 05, 2019 |
| 5250            | 23.3              | 4.604                              | 35.76                                  | 4.71                             | 35.9                                 | -2.25                      | -0.39                      | Oct. 29, 2019 |
| 5250            | 23.2              | 4.693                              | 37.651                                 | 4.71                             | 35.9                                 | -0.36                      | 4.88                       | Nov. 06, 2019 |
| 5600            | 23.3              | 4.966                              | 35.251                                 | 5.07                             | 35.5                                 | -2.05                      | -0.70                      | Oct. 29, 2019 |
| 5600            | 23.5              | 5.031                              | 37.232                                 | 5.07                             | 35.5                                 | -0.77                      | 4.88                       | Nov. 06, 2019 |
| 5600            | 23.5              | 5.124                              | 35.657                                 | 5.07                             | 35.5                                 | 1.07                       | 0.44                       | Nov. 07, 2019 |
| 5750            | 23.3              | 5.33                               | 35.546                                 | 5.22                             | 35.4                                 | 2.11                       | 0.41                       | Oct. 28, 2019 |
| 5750            | 23.6              | 5.121                              | 36.517                                 | 5.22                             | 35.4                                 | -1.90                      | 3.16                       | Nov. 08, 2019 |

#### Note:

The dielectric properties of the tissue simulating liquid have been measured within 24 hours before the SAR testing and within  $\pm 10$  % of the target values. Liquid temperature during the SAR testing has kept within  $\pm 2$  °C.

### 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

| Test Date     | Probe S/N | Calibration Point | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Validation for CW |                 |                | Validation for Modulation |             |      |
|---------------|-----------|-------------------|------------------------------------|----------------------------------------|-------------------|-----------------|----------------|---------------------------|-------------|------|
|               |           |                   |                                    |                                        | Sensitivity Range | Probe Linearity | Probe Isotropy | Modulation Type           | Duty Factor | PAR  |
| Oct. 25, 2019 | 7375      | 2450              | 1.852                              | 38.607                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Nov. 04, 2019 | 7472      | 2450              | 1.824                              | 38.456                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Nov. 05, 2019 | 7472      | 2450              | 1.866                              | 38.343                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Oct. 29, 2019 | 7472      | 5250              | 4.604                              | 35.76                                  | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Nov. 06, 2019 | 7472      | 5250              | 4.693                              | 37.651                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Oct. 29, 2019 | 7472      | 5600              | 4.966                              | 35.251                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Nov. 06, 2019 | 7472      | 5600              | 5.031                              | 37.232                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Nov. 07, 2019 | 7472      | 5600              | 5.124                              | 35.657                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Oct. 28, 2019 | 7537      | 5750              | 5.33                               | 35.546                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Nov. 08, 2019 | 7472      | 5750              | 5.121                              | 36.517                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |

## SAR Test Report

### 4.5 System Verification

The measuring result for system verification is tabulated as below.

| Test Date     | Frequency (MHz) | 1W Target SAR-1g (W/kg) | Measured SAR-1g (W/kg) | Normalized to 1W SAR-1g (W/kg) | Deviation (%) | Dipole S/N | Probe S/N | DAE S/N |
|---------------|-----------------|-------------------------|------------------------|--------------------------------|---------------|------------|-----------|---------|
| Oct. 25, 2019 | 2450            | 52.70                   | 13.6                   | 54.40                          | 3.23          | 737        | 7375      | 1277    |
| Nov. 04, 2019 | 2450            | 52.70                   | 13.2                   | 52.80                          | 0.19          | 737        | 7472      | 579     |
| Nov. 05, 2019 | 2450            | 52.70                   | 12.9                   | 51.60                          | -2.09         | 737        | 7472      | 579     |
| Oct. 29, 2019 | 5250            | 80.70                   | 8.66                   | 86.60                          | 7.31          | 1019       | 7472      | 579     |
| Nov. 06, 2019 | 5250            | 80.70                   | 8.55                   | 85.50                          | 5.95          | 1019       | 7472      | 579     |
| Oct. 29, 2019 | 5600            | 85.80                   | 8.36                   | 83.60                          | -2.56         | 1019       | 7472      | 579     |
| Nov. 06, 2019 | 5600            | 85.80                   | 8.39                   | 83.90                          | -2.21         | 1019       | 7472      | 579     |
| Nov. 07, 2019 | 5600            | 85.80                   | 8.42                   | 84.20                          | -1.86         | 1019       | 7472      | 579     |
| Oct. 28, 2019 | 5750            | 81.50                   | 7.66                   | 76.60                          | -6.01         | 1019       | 7537      | 1585    |
| Nov. 08, 2019 | 5750            | 81.50                   | 7.68                   | 76.80                          | -5.77         | 1019       | 7472      | 579     |

**Note:**

Comparing to the reference SAR value provided by SPEAG in dipole calibration certificate, the deviation of system check results is within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots please refer to Appendix A of this report.

## SAR Test Report

### 4.6 Maximum Output Power

#### 4.6.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

#### <WLAN 2.4G>

| Mode             | Channel | Frequency (MHz) | Tune-up Power (Ant-0) | Tune-up Power (Ant-1) | Tune-up Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11b          | 1       | 2412            | 12.0                  | 12.0                  | 15.0                          |
|                  | 6       | 2437            | 12.0                  | 12.0                  | 15.0                          |
|                  | 11      | 2462            | 12.0                  | 12.0                  | 15.0                          |
|                  | 12      | 2467            | 12.0                  | 12.0                  | 15.0                          |
|                  | 13      | 2472            | 10.0                  | 10.0                  | 13.0                          |
| 802.11g          | 1       | 2412            | 12.0                  | 12.0                  | 15.0                          |
|                  | 6       | 2437            | 12.0                  | 12.0                  | 15.0                          |
|                  | 11      | 2462            | 12.0                  | 12.0                  | 15.0                          |
|                  | 12      | 2467            | 12.0                  | 12.0                  | 15.0                          |
|                  | 13      | 2472            | 8.0                   | 8.0                   | 11.0                          |
| 802.11n (HT20)   | 1       | 2412            | 12.0                  | 12.0                  | 15.0                          |
|                  | 6       | 2437            | 12.0                  | 12.0                  | 15.0                          |
|                  | 11      | 2462            | 12.0                  | 12.0                  | 15.0                          |
|                  | 12      | 2467            | 12.0                  | 12.0                  | 15.0                          |
|                  | 13      | 2472            | 7.0                   | 7.0                   | 10.0                          |
| 802.11n (HT40)   | 3       | 2422            | 12.0                  | 12.0                  | 15.0                          |
|                  | 6       | 2437            | 12.0                  | 12.0                  | 15.0                          |
|                  | 9       | 2452            | 12.0                  | 12.0                  | 15.0                          |
|                  | 10      | 2457            | 12.0                  | 12.0                  | 15.0                          |
|                  | 11      | 2462            | 7.0                   | 7.0                   | 10.0                          |
| 802.11ac (VHT20) | 1       | 2412            | 12.0                  | 12.0                  | 15.0                          |
|                  | 6       | 2437            | 12.0                  | 12.0                  | 15.0                          |
|                  | 11      | 2462            | 12.0                  | 12.0                  | 15.0                          |
|                  | 12      | 2467            | 12.0                  | 12.0                  | 15.0                          |
|                  | 13      | 2472            | 7.0                   | 7.0                   | 10.0                          |
| 802.11ac (VHT40) | 3       | 2422            | 12.0                  | 12.0                  | 15.0                          |
|                  | 6       | 2437            | 12.0                  | 12.0                  | 15.0                          |
|                  | 9       | 2452            | 12.0                  | 12.0                  | 15.0                          |
|                  | 10      | 2457            | 12.0                  | 12.0                  | 15.0                          |
|                  | 11      | 2462            | 7.0                   | 7.0                   | 10.0                          |

## SAR Test Report

### <WLAN 5.2G>

| Mode             | Channel | Frequency (MHz) | Tune-up Power (Ant-0) | Tune-up Power (Ant-1) | Tune-up Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11a          | 36      | 5180            | 10.5                  | 10.5                  | 13.5                          |
|                  | 40      | 5200            | 10.5                  | 10.5                  | 13.5                          |
|                  | 44      | 5220            | 10.5                  | 10.5                  | 13.5                          |
|                  | 48      | 5240            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT20)   | 36      | 5180            | 10.5                  | 10.5                  | 13.5                          |
|                  | 40      | 5200            | 10.5                  | 10.5                  | 13.5                          |
|                  | 44      | 5220            | 10.5                  | 10.5                  | 13.5                          |
|                  | 48      | 5240            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT40)   | 38      | 5190            | 10.5                  | 10.5                  | 13.5                          |
|                  | 46      | 5230            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT20) | 36      | 5180            | 10.5                  | 10.5                  | 13.5                          |
|                  | 40      | 5200            | 10.5                  | 10.5                  | 13.5                          |
|                  | 44      | 5220            | 10.5                  | 10.5                  | 13.5                          |
|                  | 48      | 5240            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT40) | 38      | 5190            | 10.5                  | 10.5                  | 13.5                          |
|                  | 46      | 5230            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT80) | 42      | 5210            | 10.5                  | 10.5                  | 13.5                          |

### <WLAN 5.3G>

| Mode             | Channel | Frequency (MHz) | Tune-up Power (Ant-0) | Tune-up Power (Ant-1) | Tune-up Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11a          | 52      | 5260            | 10.5                  | 10.5                  | 13.5                          |
|                  | 56      | 5280            | 10.5                  | 10.5                  | 13.5                          |
|                  | 60      | 5300            | 10.5                  | 10.5                  | 13.5                          |
|                  | 64      | 5320            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT20)   | 52      | 5260            | 10.5                  | 10.5                  | 13.5                          |
|                  | 56      | 5280            | 10.5                  | 10.5                  | 13.5                          |
|                  | 60      | 5300            | 10.5                  | 10.5                  | 13.5                          |
|                  | 64      | 5320            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT40)   | 54      | 5270            | 10.5                  | 10.5                  | 13.5                          |
|                  | 62      | 5310            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT20) | 52      | 5260            | 10.5                  | 10.5                  | 13.5                          |
|                  | 56      | 5280            | 10.5                  | 10.5                  | 13.5                          |
|                  | 60      | 5300            | 10.5                  | 10.5                  | 13.5                          |
|                  | 64      | 5320            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT40) | 54      | 5270            | 10.5                  | 10.5                  | 13.5                          |
|                  | 62      | 5310            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT80) | 58      | 5290            | 10.5                  | 10.5                  | 13.5                          |

## SAR Test Report

### <WLAN 5.6G>

| Mode             | Channel | Frequency (MHz) | Tune-up Power (Ant-0) | Tune-up Power (Ant-1) | Tune-up Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11a          | 100     | 5500            | 10.5                  | 10.5                  | 13.5                          |
|                  | 116     | 5580            | 10.5                  | 10.5                  | 13.5                          |
|                  | 120     | 5600            | 10.5                  | 10.5                  | 13.5                          |
|                  | 124     | 5620            | 10.5                  | 10.5                  | 13.5                          |
|                  | 132     | 5660            | 10.5                  | 10.5                  | 13.5                          |
|                  | 140     | 5700            | 10.5                  | 10.5                  | 13.5                          |
|                  | 144     | 5720            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT20)   | 100     | 5500            | 10.5                  | 10.5                  | 13.5                          |
|                  | 116     | 5580            | 10.5                  | 10.5                  | 13.5                          |
|                  | 120     | 5600            | 10.5                  | 10.5                  | 13.5                          |
|                  | 124     | 5620            | 10.5                  | 10.5                  | 13.5                          |
|                  | 132     | 5660            | 10.5                  | 10.5                  | 13.5                          |
|                  | 140     | 5700            | 10.5                  | 10.5                  | 13.5                          |
|                  | 144     | 5720            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT40)   | 102     | 5510            | 10.5                  | 10.5                  | 13.5                          |
|                  | 110     | 5550            | 10.5                  | 10.5                  | 13.5                          |
|                  | 118     | 5590            | 10.5                  | 10.5                  | 13.5                          |
|                  | 126     | 5630            | 10.5                  | 10.5                  | 13.5                          |
|                  | 134     | 5670            | 10.5                  | 10.5                  | 13.5                          |
|                  | 142     | 5710            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT20) | 100     | 5500            | 10.5                  | 10.5                  | 13.5                          |
|                  | 116     | 5580            | 10.5                  | 10.5                  | 13.5                          |
|                  | 120     | 5600            | 10.5                  | 10.5                  | 13.5                          |
|                  | 124     | 5620            | 10.5                  | 10.5                  | 13.5                          |
|                  | 132     | 5660            | 10.5                  | 10.5                  | 13.5                          |
|                  | 140     | 5700            | 10.5                  | 10.5                  | 13.5                          |
|                  | 144     | 5720            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT40) | 102     | 5510            | 10.5                  | 10.5                  | 13.5                          |
|                  | 110     | 5550            | 10.5                  | 10.5                  | 13.5                          |
|                  | 118     | 5590            | 10.5                  | 10.5                  | 13.5                          |
|                  | 126     | 5630            | 10.5                  | 10.5                  | 13.5                          |
|                  | 134     | 5670            | 10.5                  | 10.5                  | 13.5                          |
|                  | 142     | 5710            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT80) | 106     | 5530            | 10.5                  | 10.5                  | 13.5                          |
|                  | 122     | 5610            | 10.5                  | 10.5                  | 13.5                          |
|                  | 138     | 5690            | 10.5                  | 10.5                  | 13.5                          |

## SAR Test Report

### <WLAN 5.8G>

| Mode             | Channel | Frequency (MHz) | Tune-up Power (Ant-0) | Tune-up Power (Ant-1) | Tune-up Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11a          | 149     | 5745            | 10.5                  | 10.5                  | 13.5                          |
|                  | 153     | 5765            | 10.5                  | 10.5                  | 13.5                          |
|                  | 157     | 5785            | 10.5                  | 10.5                  | 13.5                          |
|                  | 161     | 5805            | 10.5                  | 10.5                  | 13.5                          |
|                  | 165     | 5825            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT20)   | 149     | 5745            | 10.5                  | 10.5                  | 13.5                          |
|                  | 153     | 5765            | 10.5                  | 10.5                  | 13.5                          |
|                  | 157     | 5785            | 10.5                  | 10.5                  | 13.5                          |
|                  | 161     | 5805            | 10.5                  | 10.5                  | 13.5                          |
|                  | 165     | 5825            | 10.5                  | 10.5                  | 13.5                          |
| 802.11n (HT40)   | 151     | 5755            | 10.5                  | 10.5                  | 13.5                          |
|                  | 159     | 5795            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT20) | 149     | 5745            | 10.5                  | 10.5                  | 13.5                          |
|                  | 153     | 5765            | 10.5                  | 10.5                  | 13.5                          |
|                  | 157     | 5785            | 10.5                  | 10.5                  | 13.5                          |
|                  | 161     | 5805            | 10.5                  | 10.5                  | 13.5                          |
|                  | 165     | 5825            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT40) | 151     | 5755            | 10.5                  | 10.5                  | 13.5                          |
|                  | 159     | 5795            | 10.5                  | 10.5                  | 13.5                          |
| 802.11ac (VHT80) | 155     | 5775            | 10.5                  | 10.5                  | 13.5                          |

### <Bluetooth>

| Mode          | Channel | Frequency (MHz) | Tune-up Power |
|---------------|---------|-----------------|---------------|
| Bluetooth BDR | 0       | 2402            | 7.5           |
|               | 39      | 2441            | 7.5           |
|               | 78      | 2480            | 7.5           |
| Bluetooth LE  | 0       | 2402            | 7.5           |
|               | 19      | 2440            | 7.5           |
|               | 39      | 2480            | 7.5           |

## SAR Test Report

### 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

#### <WLAN 2.4G>

| Mode    | Channel | Frequency (MHz) | Average Power (Ant-0) | Average Power (Ant-1) | Average Power (Ant-0 + Ant-1) |
|---------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11b | 1       | 2412            | 11.83                 | 11.81                 | 14.51                         |
|         | 6       | 2437            | 11.81                 | 11.96                 | 14.64                         |
|         | 11      | 2462            | 11.98                 | 11.97                 | 14.73                         |
|         | 12      | 2467            | 11.50                 | 11.48                 | 14.50                         |
|         | 13      | 2472            | 9.10                  | 8.72                  | 11.92                         |

#### <WLAN 5.3G>

| Mode             | Channel | Frequency (MHz) | Average Power (Ant-0) | Average Power (Ant-1) | Average Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11ac (VHT80) | 58      | 5290            | 10.47                 | 10.43                 | 12.83                         |

#### <WLAN 5.6G>

| Mode             | Channel | Frequency (MHz) | Average Power (Ant-0) | Average Power (Ant-1) | Average Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11ac (VHT80) | 106     | 5530            | 10.37                 | 10.41                 | 13.13                         |
|                  | 122     | 5610            | 10.33                 | 10.36                 | 13.07                         |
|                  | 138     | 5690            | 10.43                 | 10.43                 | 13.18                         |

#### <WLAN 5.8G>

| Mode             | Channel | Frequency (MHz) | Average Power (Ant-0) | Average Power (Ant-1) | Average Power (Ant-0 + Ant-1) |
|------------------|---------|-----------------|-----------------------|-----------------------|-------------------------------|
| 802.11ac (VHT80) | 155     | 5775            | 10.46                 | 10.38                 | 12.96                         |

#### <Bluetooth EDR>

| Mode          | Channel | Frequency (MHz) | Average Power |
|---------------|---------|-----------------|---------------|
| Bluetooth BDR | 0       | 2402            | 6.14          |
|               | 39      | 2441            | 6.27          |
|               | 78      | 2480            | 6.01          |

#### <Bluetooth LE>

| Mode         | Channel | Frequency (MHz) | Average Power |
|--------------|---------|-----------------|---------------|
| Bluetooth LE | 0       | 2402            | 6.10          |
|              | 19      | 2440            | 6.03          |
|              | 39      | 2480            | 6.10          |

## **4.7 SAR Testing Results**

### **4.7.1 SAR Test Reduction Considerations**

#### **<KDB 447498 D01, General RF Exposure Guidance>**

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1)  $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
- (2)  $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3)  $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz

When SAR is not measured at the maximum power level allowed for production units, the measured SAR will be scaled to the maximum tune-up tolerance limit to determine compliance. The scaling factor for the tune-up power is defined as maximum tune-up limit (mW) / measured conducted power (mW). The reported SAR would be calculated by measured SAR x tune-up power scaling factor.

The SAR has been measured with highest transmission duty factor supported by the test mode tools for WLAN and/or Bluetooth. When the transmission duty factor could not achieve 100%, the reported SAR will be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up power. The scaling factor for the duty factor is defined as 100% / transmission duty cycle (%). The reported SAR would be calculated by measured SAR x tune-up power scaling factor x duty cycle scaling factor.

#### **<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>**

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is  $\leq 0.4$  W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is  $\leq 0.8$  W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is  $\leq 1.2$  W/kg.
- (3) For WLAN 5GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is  $> 0.8$  W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is  $\leq 1.2$  W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is  $\leq 1.2$  W/kg.

## SAR Test Report

- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

### 4.7.2 SAR Results for Body Exposure Condition (Test Separation Distance is 5 mm)

| Plot No. | Band     | Mode           | Test Position | Ch. | Sample | TX Antenna | Duty Cycle | Crest Factor | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|----------------|---------------|-----|--------|------------|------------|--------------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | WLAN2.4G | 802.11b        | Front Face    | 11  | 1      | Ant 0      | 99.90      | 1.00         | 12.0                     | 11.98                          | 1.00           | -0.08            | 0.218                  | 0.22                 |
|          | WLAN2.4G | 802.11b        | Rear Face     | 11  | 1      | Ant 0      | 99.90      | 1.00         | 12.0                     | 11.98                          | 1.00           | 0.02             | 0.112                  | 0.11                 |
|          | WLAN2.4G | 802.11b        | Left Side     | 11  | 1      | Ant 0      | 99.90      | 1.00         | 12.0                     | 11.98                          | 1.00           | 0.01             | 0.254                  | 0.25                 |
|          | WLAN2.4G | 802.11b        | Right Side    | 11  | 1      | Ant 0      | 99.90      | 1.00         | 12.0                     | 11.98                          | 1.00           | 0.07             | 0.266                  | 0.27                 |
|          | WLAN2.4G | 802.11b        | Top Side      | 11  | 1      | Ant 0      | 99.90      | 1.00         | 12.0                     | 11.98                          | 1.00           | -0.15            | 0.259                  | 0.26                 |
|          | WLAN2.4G | 802.11b        | Bottom Side   | 11  | 1      | Ant 0      | 99.90      | 1.00         | 12.0                     | 11.98                          | 1.00           | 0.03             | 0.319                  | 0.32                 |
|          | WLAN2.4G | 802.11b        | Front Face    | 11  | 1      | Ant 1      | 99.90      | 1.00         | 12.0                     | 11.97                          | 1.01           | -0.02            | 0.159                  | 0.16                 |
|          | WLAN2.4G | 802.11b        | Rear Face     | 11  | 1      | Ant 1      | 99.90      | 1.00         | 12.0                     | 11.97                          | 1.01           | 0.01             | 0.097                  | 0.10                 |
|          | WLAN2.4G | 802.11b        | Left Side     | 11  | 1      | Ant 1      | 99.90      | 1.00         | 12.0                     | 11.97                          | 1.01           | -0.14            | 0.248                  | 0.25                 |
|          | WLAN2.4G | 802.11b        | Right Side    | 11  | 1      | Ant 1      | 99.90      | 1.00         | 12.0                     | 11.97                          | 1.01           | -0.08            | 0.249                  | 0.25                 |
|          | WLAN2.4G | 802.11b        | Top Side      | 11  | 1      | Ant 1      | 99.90      | 1.00         | 12.0                     | 11.97                          | 1.01           | 0.06             | 0.246                  | 0.25                 |
|          | WLAN2.4G | 802.11b        | Bottom Side   | 11  | 1      | Ant 1      | 99.90      | 1.00         | 12.0                     | 11.97                          | 1.01           | 0.01             | 0.257                  | 0.26                 |
|          | WLAN2.4G | 802.11b        | Front Face    | 11  | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | 0.11             | 0.148                  | 0.16                 |
|          | WLAN2.4G | 802.11b        | Rear Face     | 11  | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | -0.05            | 0.099                  | 0.10                 |
|          | WLAN2.4G | 802.11b        | Left Side     | 11  | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | 0.03             | 0.264                  | 0.28                 |
|          | WLAN2.4G | 802.11b        | Right Side    | 11  | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | 0.07             | 0.301                  | 0.32                 |
|          | WLAN2.4G | 802.11b        | Top Side      | 11  | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | 0.12             | 0.248                  | 0.26                 |
| 01       | WLAN2.4G | 802.11b        | Bottom Side   | 11  | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | -0.06            | 0.308                  | 0.33                 |
|          | WLAN2.4G | 802.11b        | Bottom Side   | 1   | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.51                          | 1.12           | 0.05             | 0.209                  | 0.23                 |
|          | WLAN2.4G | 802.11b        | Bottom Side   | 6   | 1      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.64                          | 1.09           | 0.01             | 0.218                  | 0.24                 |
|          | WLAN2.4G | 802.11b        | Bottom Side   | 11  | 2      | Ant 0+1    | 99.90      | 1.00         | 15.0                     | 14.73                          | 1.06           | -0.06            | 0.296                  | 0.31                 |
|          | WLAN5.3G | 802.11ac VHT80 | Front Face    | 58  | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.47                          | 1.01           | 0.08             | 0.244                  | 0.25                 |
|          | WLAN5.3G | 802.11ac VHT80 | Rear Face     | 58  | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.47                          | 1.01           | 0.01             | 0.151                  | 0.15                 |
|          | WLAN5.3G | 802.11ac VHT80 | Left Side     | 58  | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.47                          | 1.01           | -0.09            | 0.292                  | 0.29                 |
|          | WLAN5.3G | 802.11ac VHT80 | Right Side    | 58  | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.47                          | 1.01           | -0.07            | 0.122                  | 0.12                 |
|          | WLAN5.3G | 802.11ac VHT80 | Top Side      | 58  | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.47                          | 1.01           | 0.03             | 0.161                  | 0.16                 |
|          | WLAN5.3G | 802.11ac VHT80 | Bottom Side   | 58  | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.47                          | 1.01           | -0.01            | 0.251                  | 0.25                 |
|          | WLAN5.3G | 802.11ac VHT80 | Front Face    | 58  | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.02             | 0.157                  | 0.16                 |
|          | WLAN5.3G | 802.11ac VHT80 | Rear Face     | 58  | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.04             | 0.141                  | 0.14                 |
|          | WLAN5.3G | 802.11ac VHT80 | Left Side     | 58  | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.08            | 0.310                  | 0.32                 |
|          | WLAN5.3G | 802.11ac VHT80 | Right Side    | 58  | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.06            | 0.053                  | 0.05                 |
|          | WLAN5.3G | 802.11ac VHT80 | Top Side      | 58  | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.05             | 0.155                  | 0.16                 |
|          | WLAN5.3G | 802.11ac VHT80 | Bottom Side   | 58  | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.03            | 0.294                  | 0.30                 |
|          | WLAN5.3G | 802.11ac VHT80 | Front Face    | 58  | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | -0.11            | 0.151                  | 0.18                 |
|          | WLAN5.3G | 802.11ac VHT80 | Rear Face     | 58  | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | 0.05             | 0.162                  | 0.19                 |
| 02       | WLAN5.3G | 802.11ac VHT80 | Left Side     | 58  | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | -0.12            | 0.361                  | 0.42                 |
|          | WLAN5.3G | 802.11ac VHT80 | Right Side    | 58  | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | 0.12             | 0.085                  | 0.10                 |
|          | WLAN5.3G | 802.11ac VHT80 | Top Side      | 58  | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | 0.08             | 0.228                  | 0.27                 |
|          | WLAN5.3G | 802.11ac VHT80 | Bottom Side   | 58  | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | -0.06            | 0.334                  | 0.39                 |
|          | WLAN5.3G | 802.11ac VHT80 | Left Side     | 58  | 2      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.83                          | 1.17           | -0.12            | 0.337                  | 0.39                 |

# SAR Test Report

| Plot No. | Band     | Mode           | Test Position | Ch. | Sample | TX Antenna | Duty Cycle | Crest Factor | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|----------------|---------------|-----|--------|------------|------------|--------------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | WLAN5.6G | 802.11ac VHT80 | Front Face    | 138 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.02             | 0.501                  | 0.51                 |
|          | WLAN5.6G | 802.11ac VHT80 | Rear Face     | 138 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.07             | 0.403                  | 0.41                 |
|          | WLAN5.6G | 802.11ac VHT80 | Left Side     | 138 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.06            | 0.600                  | 0.61                 |
|          | WLAN5.6G | 802.11ac VHT80 | Right Side    | 138 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.15            | 0.251                  | 0.26                 |
|          | WLAN5.6G | 802.11ac VHT80 | Top Side      | 138 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.03             | 0.331                  | 0.34                 |
|          | WLAN5.6G | 802.11ac VHT80 | Bottom Side   | 138 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.10            | 0.515                  | 0.53                 |
|          | WLAN5.6G | 802.11ac VHT80 | Front Face    | 138 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.08            | 0.291                  | 0.30                 |
|          | WLAN5.6G | 802.11ac VHT80 | Rear Face     | 138 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.15             | 0.284                  | 0.29                 |
|          | WLAN5.6G | 802.11ac VHT80 | Left Side     | 138 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.05            | 0.575                  | 0.59                 |
|          | WLAN5.6G | 802.11ac VHT80 | Right Side    | 138 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.04             | 0.098                  | 0.10                 |
|          | WLAN5.6G | 802.11ac VHT80 | Top Side      | 138 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | 0.10             | 0.287                  | 0.29                 |
|          | WLAN5.6G | 802.11ac VHT80 | Bottom Side   | 138 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.43                          | 1.02           | -0.12            | 0.545                  | 0.56                 |
|          | WLAN5.6G | 802.11ac VHT80 | Front Face    | 138 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | -0.01            | 0.248                  | 0.27                 |
|          | WLAN5.6G | 802.11ac VHT80 | Rear Face     | 138 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | 0.19             | 0.255                  | 0.28                 |
| 03       | WLAN5.6G | 802.11ac VHT80 | Left Side     | 138 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | -0.03            | 0.597                  | 0.64                 |
|          | WLAN5.6G | 802.11ac VHT80 | Right Side    | 138 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | -0.02            | 0.141                  | 0.15                 |
|          | WLAN5.6G | 802.11ac VHT80 | Top Side      | 138 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | 0.07             | 0.377                  | 0.41                 |
|          | WLAN5.6G | 802.11ac VHT80 | Bottom Side   | 138 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | 0.03             | 0.553                  | 0.60                 |
|          | WLAN5.6G | 802.11ac VHT80 | Left Side     | 106 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.13                          | 1.09           | -0.08            | 0.574                  | 0.63                 |
|          | WLAN5.6G | 802.11ac VHT80 | Left Side     | 122 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.07                          | 1.10           | 0.03             | 0.564                  | 0.62                 |
|          | WLAN5.6G | 802.11ac VHT80 | Left Side     | 138 | 2      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 13.18                          | 1.08           | -0.03            | 0.584                  | 0.63                 |
|          | WLAN5.8G | 802.11ac VHT80 | Front Face    | 155 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.46                          | 1.01           | -0.10            | 0.272                  | 0.27                 |
|          | WLAN5.8G | 802.11ac VHT80 | Rear Face     | 155 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.46                          | 1.01           | 0.06             | 0.254                  | 0.26                 |
|          | WLAN5.8G | 802.11ac VHT80 | Left Side     | 155 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.46                          | 1.01           | -0.16            | 0.421                  | 0.43                 |
|          | WLAN5.8G | 802.11ac VHT80 | Right Side    | 155 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.46                          | 1.01           | 0.03             | 0.176                  | 0.18                 |
|          | WLAN5.8G | 802.11ac VHT80 | Top Side      | 155 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.46                          | 1.01           | 0.01             | 0.232                  | 0.23                 |
|          | WLAN5.8G | 802.11ac VHT80 | Bottom Side   | 155 | 1      | Ant 0      | 99.90      | 1.00         | 10.5                     | 10.46                          | 1.01           | -0.08            | 0.361                  | 0.36                 |
|          | WLAN5.8G | 802.11ac VHT80 | Front Face    | 155 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.38                          | 1.03           | 0.02             | 0.221                  | 0.23                 |
|          | WLAN5.8G | 802.11ac VHT80 | Rear Face     | 155 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.38                          | 1.03           | 0.07             | 0.196                  | 0.20                 |
|          | WLAN5.8G | 802.11ac VHT80 | Left Side     | 155 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.38                          | 1.03           | -0.01            | 0.438                  | 0.45                 |
|          | WLAN5.8G | 802.11ac VHT80 | Right Side    | 155 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.38                          | 1.03           | -0.09            | 0.075                  | 0.08                 |
|          | WLAN5.8G | 802.11ac VHT80 | Top Side      | 155 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.38                          | 1.03           | 0.11             | 0.219                  | 0.23                 |
|          | WLAN5.8G | 802.11ac VHT80 | Bottom Side   | 155 | 1      | Ant 1      | 99.90      | 1.00         | 10.5                     | 10.38                          | 1.03           | 0.02             | 0.415                  | 0.43                 |
|          | WLAN5.8G | 802.11ac VHT80 | Front Face    | 155 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | -0.03            | 0.289                  | 0.33                 |
|          | WLAN5.8G | 802.11ac VHT80 | Rear Face     | 155 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | 0.06             | 0.248                  | 0.28                 |
| 04       | WLAN5.8G | 802.11ac VHT80 | Left Side     | 155 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | 0.03             | 0.696                  | 0.79                 |
|          | WLAN5.8G | 802.11ac VHT80 | Right Side    | 155 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | -0.09            | 0.165                  | 0.19                 |
|          | WLAN5.8G | 802.11ac VHT80 | Top Side      | 155 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | 0.13             | 0.441                  | 0.50                 |
|          | WLAN5.8G | 802.11ac VHT80 | Bottom Side   | 155 | 1      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | 0.05             | 0.643                  | 0.73                 |
|          | WLAN5.8G | 802.11ac VHT80 | Left Side     | 155 | 2      | Ant 0+1    | 99.90      | 1.00         | 13.5                     | 12.96                          | 1.13           | 0.03             | 0.674                  | 0.76                 |
|          | BT       | BDR            | Front Face    | 39  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | 0.08             | 0.038                  | 0.08                 |
|          | BT       | BDR            | Rear Face     | 39  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | 0.03             | 0.019                  | 0.04                 |
|          | BT       | BDR            | Left Side     | 39  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | -0.11            | 0.043                  | 0.09                 |
|          | BT       | BDR            | Right Side    | 39  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | 0.05             | 0.046                  | 0.10                 |
|          | BT       | BDR            | Top Side      | 39  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | -0.07            | 0.045                  | 0.10                 |
| 05       | BT       | BDR            | Bottom Side   | 39  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | -0.01            | 0.055                  | 0.12                 |
|          | BT       | BDR            | Bottom Side   | 0   | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.14                           | 1.37           | 0.01             | 0.049                  | 0.11                 |
|          | BT       | BDR            | Bottom Side   | 78  | 1      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.01                           | 1.41           | 0.09             | 0.050                  | 0.12                 |
|          | BT       | BDR            | Bottom Side   | 39  | 2      | Ant 0      | 60.30      | 1.66         | 7.5                      | 6.27                           | 1.33           | -0.01            | 0.049                  | 0.11                 |

### 4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Since all the measured SAR are less than 0.8 W/kg, the repeated measurement is not required.

## SAR Test Report

### 4.7.4 Simultaneous Multi-band Transmission Evaluation

#### <Possibilities of Simultaneous Transmission>

The simultaneous transmission possibilities for this device are listed as below.

| Simultaneous TX Combination | Capable Transmit Configurations | Body Exposure Condition |
|-----------------------------|---------------------------------|-------------------------|
| 1                           | WLAN 2.4G Ant-1 + BT            | Yes                     |
| 2                           | WLAN 5G Ant-1 + BT              | Yes                     |

**Note :** The WLAN 2.4G and WLAN 5G cannot transmit simultaneously.

#### <SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR<sub>1g</sub> of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR<sub>1g</sub> is greater than the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

| Position    | 1g SAR W/kg       |                 |          | Summing Result 1g SAR W/kg |             |
|-------------|-------------------|-----------------|----------|----------------------------|-------------|
|             | A                 | B               | C        | A+C                        | B+C         |
|             | WLAN 2.4GHz Ant 1 | WLAN 5GHz Ant 1 | BT Ant 0 |                            |             |
| Front Face  | 0.16              | 0.30            | 0.08     | 0.24                       | 0.38        |
| Rear Face   | 0.10              | 0.29            | 0.04     | 0.14                       | 0.33        |
| Left Side   | 0.25              | 0.59            | 0.09     | 0.34                       | <b>0.68</b> |
| Right Side  | 0.25              | 0.10            | 0.10     | 0.35                       | 0.20        |
| Top Side    | 0.25              | 0.29            | 0.10     | 0.35                       | 0.39        |
| Bottom Side | 0.26              | 0.56            | 0.12     | 0.38                       | <b>0.68</b> |

**Test Engineer :** Eric Wu, and Kevin Yao

## SAR Test Report

### 5. Calibration of Test Equipment

| Equipment                    | Manufacturer | Model   | SN         | Cal. Date     | Cal. Interval |
|------------------------------|--------------|---------|------------|---------------|---------------|
| System Validation Dipole     | SPEAG        | D2450V2 | 737        | Aug. 26, 2019 | 1 Year        |
| System Validation Dipole     | SPEAG        | D5GHzV2 | 1019       | Mar. 21, 2019 | 1 Year        |
| Dosimetric E-Field Probe     | SPEAG        | EX3DV4  | 7375       | Dec. 13, 2018 | 1 Year        |
| Dosimetric E-Field Probe     | SPEAG        | EX3DV4  | 7472       | Aug. 30, 2019 | 1 Year        |
| Dosimetric E-Field Probe     | SPEAG        | EX3DV4  | 7537       | Jun. 18, 2019 | 1 Year        |
| Data Acquisition Electronics | SPEAG        | DAE3    | 579        | Aug. 27, 2019 | 1 Year        |
| Data Acquisition Electronics | SPEAG        | DAE4    | 1277       | Jan. 24, 2019 | 1 Year        |
| Data Acquisition Electronics | SPEAG        | DAE4    | 1585       | Jun. 07, 2019 | 1 Year        |
| Spectrum Analyzer            | R&S          | FSL6    | 102006     | Mar. 26, 2019 | 1 Year        |
| ENA Series Network Analyzer  | Agilent      | E5071C  | MY46214281 | Jun. 17, 2019 | 1 Year        |
| MXG Analog Signal Generator  | Agilent      | N5181A  | MY50143868 | Jun. 27, 2019 | 1 Year        |
| Power Meter                  | Anritsu      | ML2495A | 1218009    | Jun. 28, 2019 | 1 Year        |
| Power Sensor                 | Anritsu      | MA2411B | 1207252    | Jun. 28, 2019 | 1 Year        |
| Thermometer                  | YFE          | YF-160A | 130504591  | Mar. 22, 2019 | 1 Year        |

## **6. Measurement Uncertainty**

According to KDB 865664 D01, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq 1.5$  W/kg for 1-g SAR, and  $\geq 3.75$  W/kg for 10-g SAR. The procedures described in IEEE Std 1528-2013 should be applied. The expanded SAR measurement uncertainty must be  $\leq 30\%$ , for a confidence interval of  $k = 2$ . When the highest measured SAR within a frequency band is  $< 1.5$  W/kg for 1-g and  $< 3.75$  W/kg for 10-g, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. Hence, the measurement uncertainty analysis is not required in this SAR report because the test result met the condition.

## SAR Test Report

---

### 7. Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Taiwan Huaya Lab:**

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan

Tel: +886-(0)3-318-3232

Fax: +886-(0)3-211-5834

**Taiwan Linkou Lab:**

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan

Tel: +886-(0)2-2605-2180

Fax: +886-(0)2-2605-2943

**Taiwan Hsinchu Lab1:**

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan

Tel: +886-(0)3-666-8565

Fax: +886-(0)3-666-8323

**Taiwan Hsinchu Lab2:**

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan

Tel: +886-(0)3-512-0595

Fax: +886-(0)3-512-0568

**Taiwan Xindian Lab:**

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel: +886-(0)2-8914-5882

Fax: +886-(0)2-8914-5840

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** <https://ee.bureauveritas.com.tw/BVInternet/Default>

The road map of all our labs can be found in our web site also.

---END---

### Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

## System Check\_H2450\_191025

**DUT: Dipole 2450 MHz; Type: D2450V2; SN: 737**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: H19T27N1\_1025 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.852$  S/m;  $\epsilon_r = 38.607$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7375; ConvF(7.64, 7.64, 7.64); Calibrated: 2018/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2019/01/24
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 22.6 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 28.2 W/kg

**SAR(1 g) = 13.6 W/kg; SAR(10 g) = 6.34 W/kg**

Maximum value of SAR (measured) = 22.7 W/kg



## System Check\_H5250\_191029

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: H34T60N1\_1029 Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.604$  S/m;  $\epsilon_r = 35.76$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(5.67, 5.67, 5.67); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2019/08/27
- Phantom: Twin SAM Phantom\_1496; Type: QD000P40CB;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.5 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 68.56 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 27.9 W/kg

**SAR(1 g) = 8.66 W/kg; SAR(10 g) = 2.19 W/kg**

Maximum value of SAR (measured) = 17.9 W/kg



## System Check\_H5600\_191029

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: H34T60N1\_1029 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.966$  S/m;  $\epsilon_r = 35.251$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2019/08/27
- Phantom: Twin SAM Phantom\_1496; Type: QD000P40CB;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 20.3 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 63.86 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 36.3 W/kg

**SAR(1 g) = 8.36 W/kg; SAR(10 g) = 2.38 W/kg**

Maximum value of SAR (measured) = 21.8 W/kg



## System Check\_H5750\_191028

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: H34T60N1\_1028 Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.33$  S/m;  $\epsilon_r = 35.546$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7537; ConvF(4.99, 4.99, 4.99); Calibrated: 2019/06/18
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1585; Calibrated: 2019/06/07
- Phantom: SAM Phantom\_1982; Type: QD 000 P41 Ax; Serial: 1982
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.7 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 67.94 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 34.5 W/kg

**SAR(1 g) = 7.66 W/kg; SAR(10 g) = 2.19 W/kg**

Maximum value of SAR (measured) = 20.2 W/kg



## **Appendix B. SAR Plots of SAR Measurement**

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

**P01 WLAN2.4G\_802.11b\_Bottom Side\_5mm\_Ch11\_Sample1\_Ant0+1****DUT: 190628E06**

Communication System: WLAN\_2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: H19T27N1\_1025 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.867$  S/m;  $\epsilon_r = 38.595$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7375; ConvF(7.64, 7.64, 7.64); Calibrated: 2018/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2019/01/24
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**- Area Scan (71x171x1):** Interpolated grid:  $dx=1.200$  mm,  $dy=1.200$  mm

Maximum value of SAR (interpolated) = 0.601 W/kg

**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 14.68 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.811 W/kg

**SAR(1 g) = 0.308 W/kg; SAR(10 g) = 0.131 W/kg**

Maximum value of SAR (measured) = 0.563 W/kg


**- Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 14.68 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.756 W/kg

**SAR(1 g) = 0.292 W/kg; SAR(10 g) = 0.120 W/kg**

Maximum value of SAR (measured) = 0.537 W/kg



**P02 WLAN5.3G\_802.11ac VHT80\_Left Side\_5mm\_Ch58\_Sample1\_Ant0+1****DUT: 190628E06**

Communication System: WLAN\_5G; Frequency: 5290 MHz; Duty Cycle: 1:1

Medium: H34T60N1\_1029 Medium parameters used:  $f = 5290$  MHz;  $\sigma = 4.7$  S/m;  $\epsilon_r = 36.874$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(5.67, 5.67, 5.67); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2019/08/27
- Phantom: Twin SAM Phantom\_1496; Type: QD000P40CB;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**- Area Scan (81x201x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.788 W/kg

**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 12.67 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.27 W/kg

**SAR(1 g) = 0.361 W/kg; SAR(10 g) = 0.118 W/kg**

Maximum value of SAR (measured) = 0.776 W/kg


**- Zoom Scan (6x6x12)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 12.67 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.13 W/kg

**SAR(1 g) = 0.311 W/kg; SAR(10 g) = 0.106 W/kg**

Maximum value of SAR (measured) = 0.663 W/kg



**P03 WLAN5.6G\_802.11ac VHT80\_Left Side\_5mm\_Ch138\_Sample1\_Ant0+1****DUT: 190628E06**

Communication System: WLAN\_5G; Frequency: 5690 MHz; Duty Cycle: 1:1

Medium: H34T60N1\_1029 Medium parameters used:  $f = 5690$  MHz;  $\sigma = 5.106$  S/m;  $\epsilon_r = 36.082$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(5.23, 5.23, 5.23); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2019/08/27
- Phantom: Twin SAM Phantom\_1496; Type: QD000P40CB;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**- Area Scan (81x201x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.66 W/kg

**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 14.72 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.49 W/kg

**SAR(1 g) = 0.597 W/kg; SAR(10 g) = 0.198 W/kg**

Maximum value of SAR (measured) = 1.42 W/kg


**- Zoom Scan (6x6x12)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 14.72 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.18 W/kg

**SAR(1 g) = 0.545 W/kg; SAR(10 g) = 0.187 W/kg**

Maximum value of SAR (measured) = 1.24 W/kg



**P04 WLAN5.8G\_802.11ac VHT80\_Left Side\_5mm\_Ch155\_Sample1\_Ant0+1****DUT: 190628E06**

Communication System: WLAN\_5G; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium: H34T60N1\_1028 Medium parameters used:  $f = 5775$  MHz;  $\sigma = 5.309$  S/m;  $\epsilon_r = 35.467$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7537; ConvF(4.99, 4.99, 4.99); Calibrated: 2019/06/18
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1585; Calibrated: 2019/06/07
- Phantom: SAM Phantom\_1982; Type: QD 000 P41 Ax; Serial: 1982
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**- Area Scan (81x201x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.70 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 15.68 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 2.84 W/kg

**SAR(1 g) = 0.696 W/kg; SAR(10 g) = 0.273 W/kg**

Maximum value of SAR (measured) = 1.61 W/kg



**P05 BT\_BDR\_Bottom Side\_5mm\_Ch39\_Sample1\_Ant0****DUT: 190628E06**

Communication System: BT; Frequency: 2441 MHz; Duty Cycle: 1:1.66

Medium: H19T27N1\_1025 Medium parameters used:  $f = 2441$  MHz;  $\sigma = 1.842$  S/m;  $\epsilon_r = 38.637$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7375; ConvF(7.64, 7.64, 7.64); Calibrated: 2018/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2019/01/24
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**- Area Scan (71x171x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.116 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.839 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.144 W/kg

**SAR(1 g) = 0.055 W/kg; SAR(10 g) = 0.022 W/kg**

Maximum value of SAR (measured) = 0.113 W/kg



## **Appendix C. Calibration Certificate for Probe and Dipole**

The SPEAG calibration certificates are shown as follows.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **B.V. ADT (Auden)**

Certificate No: **D2450V2-737\_Aug19**

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN:737**

Calibration procedure(s) **QA CAL-05.v11**  
**Calibration Procedure for SAR Validation Sources between 0.7-3 GHz**

Calibration date: **August 26, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards               | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|---------------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP                 | SN: 104778         | 03-Apr-19 (No. 217-02892/02893)   | Apr-20                 |
| Power sensor NRP-Z91            | SN: 103244         | 03-Apr-19 (No. 217-02892)         | Apr-20                 |
| Power sensor NRP-Z91            | SN: 103245         | 03-Apr-19 (No. 217-02893)         | Apr-20                 |
| Reference 20 dB Attenuator      | SN: 5058 (20k)     | 04-Apr-19 (No. 217-02894)         | Apr-20                 |
| Type-N mismatch combination     | SN: 5047.2 / 06327 | 04-Apr-19 (No. 217-02895)         | Apr-20                 |
| Reference Probe EX3DV4          | SN: 7349           | 29-May-19 (No. EX3-7349_May19)    | May-20                 |
| DAE4                            | SN: 601            | 30-Apr-19 (No. DAE4-601_Apr19)    | Apr-20                 |
| Secondary Standards             | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B              | SN: GB39512475     | 30-Oct-14 (in house check Feb-19) | In house check: Oct-20 |
| Power sensor HP 8481A           | SN: US37292783     | 07-Oct-15 (in house check Oct-18) | In house check: Oct-20 |
| Power sensor HP 8481A           | SN: MY41092317     | 07-Oct-15 (in house check Oct-18) | In house check: Oct-20 |
| RF generator R&S SMT-06         | SN: 100972         | 15-Jun-15 (in house check Oct-18) | In house check: Oct-20 |
| Network Analyzer Agilent E8358A | SN: US41080477     | 31-Mar-14 (in house check Oct-18) | In house check: Oct-19 |

Calibrated by: **Michael Weber** **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** **Technical Manager**

Issued: August 26, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                        |             |
|-------------------------------------|------------------------|-------------|
| <b>DASY Version</b>                 | DASY5                  | V52.10.2    |
| <b>Extrapolation</b>                | Advanced Extrapolation |             |
| <b>Phantom</b>                      | Modular Flat Phantom   |             |
| <b>Distance Dipole Center - TSL</b> | 10 mm                  | with Spacer |
| <b>Zoom Scan Resolution</b>         | dx, dy, dz = 5 mm      |             |
| <b>Frequency</b>                    | 2450 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 37.8 $\pm$ 6 % | 1.83 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 250 mW input power | 13.4 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>52.7 W/kg <math>\pm</math> 17.0 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 250 mW input power | 6.20 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>24.5 W/kg <math>\pm</math> 16.5 % (k=2)</b> |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $54.3 \Omega + 4.5 j\Omega$ |
| Return Loss                          | - 24.5 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.162 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |       |
|-----------------|-------|
| Manufactured by | SPEAG |
|-----------------|-------|

## DASY5 Validation Report for Head TSL

Date: 26.08.2019

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:737**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.83$  S/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.9, 7.9, 7.9) @ 2450 MHz; Calibrated: 29.05.2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2019
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.2(1504); SEMCAD X 14.6.12(7470)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 117.9 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 26.7 W/kg


**SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.2 W/kg**

Maximum value of SAR (measured) = 22.1 W/kg



0 dB = 22.1 W/kg = 13.44 dBW/kg

Impedance Measurement Plot for Head TSL





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Client **B.V. ADT (Auden)**

Certificate No: **D5GHzV2-1019\_Mar19**

## CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1019**

Calibration procedure(s) **QA CAL-22.v4**  
**Calibration Procedure for SAR Validation Sources between 3-6 GHz**

Calibration date: **March 21, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards               | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|---------------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP                 | SN: 104778         | 04-Apr-18 (No. 217-02672/02673)   | Apr-19                 |
| Power sensor NRP-Z91            | SN: 103244         | 04-Apr-18 (No. 217-02672)         | Apr-19                 |
| Power sensor NRP-Z91            | SN: 103245         | 04-Apr-18 (No. 217-02673)         | Apr-19                 |
| Reference 20 dB Attenuator      | SN: 5058 (20k)     | 04-Apr-18 (No. 217-02682)         | Apr-19                 |
| Type-N mismatch combination     | SN: 5047.2 / 06327 | 04-Apr-18 (No. 217-02683)         | Apr-19                 |
| Reference Probe EX3DV4          | SN: 3503           | 31-Dec-18 (No. EX3-3503_Dec18)    | Dec-19                 |
| DAE4                            | SN: 601            | 04-Oct-18 (No. DAE4-601_Oct18)    | Oct-19                 |
| Secondary Standards             | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B              | SN: GB41293874     | 06-Apr-16 (in house check Jun-18) | In house check: Jun-20 |
| Power sensor HP 8481A           | SN: US37292783     | 07-Oct-15 (in house check Oct-18) | In house check: Oct-20 |
| Power sensor HP 8481A           | SN: MY41092317     | 07-Oct-15 (in house check Oct-18) | In house check: Oct-20 |
| RF generator R&S SMT-06         | SN: 100972         | 15-Jun-15 (in house check Oct-18) | In house check: Oct-20 |
| Network Analyzer Agilent E8358A | SN: US41080477     | 31-Mar-14 (in house check Oct-18) | In house check: Oct-19 |

Calibrated by: **Jeton Kastrati** Function: **Laboratory Technician** Signature:

Approved by: **Katja Pokovic** Technical Manager Signature:

Issued: March 25, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.7 ± 6 %   | 4.85 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

## SAR result with Head TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.64 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>85.8 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.47 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>24.5 W/kg ± 19.5 % (k=2)</b> |

## Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.4         | 5.22 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.5 ± 6 %   | 5.00 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

## SAR result with Head TSL at 5750 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 8.21 W/kg                       |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>81.5 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.34 W/kg                       |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>23.2 W/kg ± 19.5 % (k=2)</b> |

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                                     |                                                                      |                                  |
|-------------------------------------|----------------------------------------------------------------------|----------------------------------|
| <b>DASY Version</b>                 | DASY5                                                                | V52.10.2                         |
| <b>Extrapolation</b>                | Advanced Extrapolation                                               |                                  |
| <b>Phantom</b>                      | Modular Flat Phantom V5.0                                            |                                  |
| <b>Distance Dipole Center - TSL</b> | 10 mm                                                                | with Spacer                      |
| <b>Zoom Scan Resolution</b>         | dx, dy = 4.0 mm, dz = 1.4 mm                                         | Graded Ratio = 1.4 (Z direction) |
| <b>Frequency</b>                    | 5250 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5750 MHz $\pm$ 1 MHz |                                  |

## Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

|                                                | Temperature         | Permittivity   | Conductivity         |
|------------------------------------------------|---------------------|----------------|----------------------|
| <b>Nominal Head TSL parameters</b>             | 22.0 °C             | 35.9           | 4.71 mho/m           |
| <b>Measured Head TSL parameters</b>            | (22.0 $\pm$ 0.2) °C | 35.2 $\pm$ 6 % | 4.50 mho/m $\pm$ 6 % |
| <b>Head TSL temperature change during test</b> | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL at 5250 MHz

|                                                             |                    |                                                |
|-------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b> | Condition          |                                                |
| SAR measured                                                | 100 mW input power | 8.12 W/kg                                      |
| SAR for nominal Head TSL parameters                         | normalized to 1W   | <b>80.7 W/kg <math>\pm</math> 19.9 % (k=2)</b> |

|                                                               |                    |                                                |
|---------------------------------------------------------------|--------------------|------------------------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b> | condition          |                                                |
| SAR measured                                                  | 100 mW input power | 2.34 W/kg                                      |
| SAR for nominal Head TSL parameters                           | normalized to 1W   | <b>23.2 W/kg <math>\pm</math> 19.5 % (k=2)</b> |

### Body TSL parameters at 5250 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.36 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.8 ± 6 %   | 5.45 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5250 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.54 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>74.8 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.11 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>20.9 W/kg ± 19.5 % (k=2)</b> |

### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.2 ± 6 %   | 5.92 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5600 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.80 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>77.3 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.18 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.5 W/kg ± 19.5 % (k=2)</b> |

## Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.3         | 5.94 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.0 ± 6 %   | 6.13 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

## SAR result with Body TSL at 5750 MHz

|                                                             |                    |                                 |
|-------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b> | Condition          |                                 |
| SAR measured                                                | 100 mW input power | 7.62 W/kg                       |
| SAR for nominal Body TSL parameters                         | normalized to 1W   | <b>75.5 W/kg ± 19.9 % (k=2)</b> |

|                                                               |                    |                                 |
|---------------------------------------------------------------|--------------------|---------------------------------|
| <b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b> | condition          |                                 |
| SAR measured                                                  | 100 mW input power | 2.12 W/kg                       |
| SAR for nominal Body TSL parameters                           | normalized to 1W   | <b>21.0 W/kg ± 19.5 % (k=2)</b> |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL at 5250 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.3 $\Omega$ - 5.8 j $\Omega$ |
| Return Loss                          | - 24.3 dB                      |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 56.8 $\Omega$ - 1.1 j $\Omega$ |
| Return Loss                          | - 23.8 dB                      |

### Antenna Parameters with Head TSL at 5750 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 58.3 $\Omega$ + 3.2 j $\Omega$ |
| Return Loss                          | - 21.7 dB                      |

### Antenna Parameters with Body TSL at 5250 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.5 $\Omega$ - 3.7 j $\Omega$ |
| Return Loss                          | - 27.3 dB                      |

### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 58.1 $\Omega$ - 1.2 j $\Omega$ |
| Return Loss                          | - 22.4 dB                      |

### Antenna Parameters with Body TSL at 5750 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 58.7 $\Omega$ + 4.8 j $\Omega$ |
| Return Loss                          | - 20.8 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.204 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |       |
|-----------------|-------|
| Manufactured by | SPEAG |
|-----------------|-------|

## DASY5 Validation Report for Head TSL

Date: 21.03.2019

Test Laboratory: SPEAG, Zurich, Switzerland

### DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1019

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.5$  S/m;  $\epsilon_r = 35.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>,

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.85$  S/m;  $\epsilon_r = 34.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>,

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5$  S/m;  $\epsilon_r = 34.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.4, 5.4, 5.4) @ 5250 MHz, ConvF(4.95, 4.95, 4.95) @ 5600 MHz, ConvF(4.98, 4.98, 4.98) @ 5750 MHz; Calibrated: 31.12.2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.10.2018
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

#### **Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 78.16 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 28.1 W/kg

**SAR(1 g) = 8.12 W/kg; SAR(10 g) = 2.34 W/kg**

Maximum value of SAR (measured) = 18.1 W/kg

#### **Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 77.63 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 32.2 W/kg

**SAR(1 g) = 8.64 W/kg; SAR(10 g) = 2.47 W/kg**

Maximum value of SAR (measured) = 19.7 W/kg

#### **Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:**


Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 74.85 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 32.4 W/kg


**SAR(1 g) = 8.21 W/kg; SAR(10 g) = 2.34 W/kg**

Maximum value of SAR (measured) = 19.1 W/kg



0 dB = 19.1 W/kg = 12.81 dBW/kg

## Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 20.03.2019

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1019**

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 5.45$  S/m;  $\epsilon_r = 46.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>,

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.92$  S/m;  $\epsilon_r = 46.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>,

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 6.13$  S/m;  $\epsilon_r = 46$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503testing; ConvF(5.26, 5.26, 5.26) @ 5250 MHz, ConvF(4.7, 4.7, 4.7) @ 5600 MHz, ConvF(4.59, 4.59, 4.59) @ 5750 MHz; Calibrated: 31.12.2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.10.2018
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.09 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 29.2 W/kg

**SAR(1 g) = 7.54 W/kg; SAR(10 g) = 2.11 W/kg**

Maximum value of SAR (measured) = 17.2 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 68.10 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 33.4 W/kg

**SAR(1 g) = 7.8 W/kg; SAR(10 g) = 2.18 W/kg**

Maximum value of SAR (measured) = 18.5 W/kg


**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.59 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 34.1 W/kg


**SAR(1 g) = 7.62 W/kg; SAR(10 g) = 2.12 W/kg**

Maximum value of SAR (measured) = 18.3 W/kg



0 dB = 17.2 W/kg = 12.36 dBW/kg

## Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Auden**

Certificate No: **EX3-7375\_Dec18**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7375**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **December 13, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|------------------|-----------------------------------|------------------------|
| Power meter NRP            | SN: 104778       | 04-Apr-18 (No. 217-02672/02673)   | Apr-19                 |
| Power sensor NRP-Z91       | SN: 103244       | 04-Apr-18 (No. 217-02672)         | Apr-19                 |
| Power sensor NRP-Z91       | SN: 103245       | 04-Apr-18 (No. 217-02673)         | Apr-19                 |
| Reference 20 dB Attenuator | SN: S5277 (20x)  | 04-Apr-18 (No. 217-02682)         | Apr-19                 |
| Reference Probe ES3DV2     | SN: 3013         | 30-Dec-17 (No. ES3-3013_Dec17)    | Dec-18                 |
| DAE4                       | SN: 660          | 21-Dec-17 (No. DAE4-660_Dec17)    | Dec-18                 |
| Secondary Standards        | ID               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B         | SN: GB41293874   | 06-Apr-16 (in house check Jun-18) | In house check: Jun-20 |
| Power sensor E4412A        | SN: MY41498087   | 06-Apr-16 (in house check Jun-18) | In house check: Jun-20 |
| Power sensor E4412A        | SN: 000110210    | 06-Apr-16 (in house check Jun-18) | In house check: Jun-20 |
| RF generator HP 8648C      | SN: US3642U01700 | 04-Aug-99 (in house check Jun-18) | In house check: Jun-20 |
| Network Analyzer E8358A    | SN: US41080477   | 31-Mar-14 (in house check Oct-18) | In house check: Oct-19 |

|                |                                |                                          |               |
|----------------|--------------------------------|------------------------------------------|---------------|
| Calibrated by: | Name<br><b>Claudio Leubler</b> | Function<br><b>Laboratory Technician</b> | Signature<br> |
| Approved by:   | <b>Katja Pokovic</b>           | <b>Technical Manager</b>                 |               |

Issued: December 15, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

## Glossary:

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\varphi$   | $\varphi$ rotation around probe axis                                                                                                                    |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |
| Connector Angle          | information used in DASY system to align probe sensor X to the robot coordinate system                                                                  |

## Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

# Probe EX3DV4

## SN:7375

Manufactured: April 13, 2015  
Calibrated: December 13, 2018

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7375

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.50     | 0.42     | 0.46     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 99.7     | 99.5     | 99.8     |               |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 162.8    | $\pm 3.3 \%$              |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 162.4    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 176.7    |                           |

Note: For details on UID parameters see Appendix.

### Sensor Model Parameters

|   | C1<br>fF | C2<br>fF | $\alpha$<br>$\text{V}^{-1}$ | T1<br>$\text{ms}\cdot\text{V}^{-2}$ | T2<br>$\text{ms}\cdot\text{V}^{-1}$ | T3<br>ms | T4<br>$\text{V}^{-2}$ | T5<br>$\text{V}^{-1}$ | T6    |
|---|----------|----------|-----------------------------|-------------------------------------|-------------------------------------|----------|-----------------------|-----------------------|-------|
| X | 49.17    | 370.4    | 36.49                       | 10.04                               | 0.092                               | 5.100    | 1.852                 | 0.214                 | 1.010 |
| Y | 33.20    | 261.0    | 38.89                       | 2.699                               | 0.121                               | 5.052    | 0.000                 | 0.162                 | 1.015 |
| Z | 41.99    | 314.1    | 35.78                       | 7.410                               | 0.109                               | 5.054    | 1.240                 | 0.205                 | 1.005 |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.