



Test report No.: 24B0011R-SAUSV01S-A

SAR Test Report (Class II Permissive Change)

Product Name	2TX 11ax (WiFi6) BW80 + BT/BLE Combo Card
Trademark	MediaTek
Model and /or type reference	MT7920
Applicant's name / address	MediaTek Inc. No.1, Dusing 1st Rd., Hsinchu Science Park, Hsinchu City 30078, Taiwan
Manufacturer's name	MediaTek Inc.
FCC ID	RAS-MT7920
Applicable Standard	IEEE 1528-2013 KDB 447498 D01 v06 KDB 865664 D01 v01r04
Test Result	Max. SAR Measurement (1g) 2.4 GHz: 1.155 W/kg 5 GHz: 1.185 W/kg
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / April Chen)	
Tested By (Senior Engineer / Luke Cheng)	
Approved By (Assistant Manager / San Lin)	
Date of Receipt	2024/11/01
Date of Issue	2024/12/13
Report Version	V1.0

INDEX

	Page
1. General Information	5
1.1 EUT Description	5
1.2 Antenna List	6
1.3 SAR Test Exclusion Calculation	7
1.4 Test Environment.....	8
1.5 Measurement procedures.....	9
2. SAR Measurement System	10
2.1 DASY System Description.....	10
2.2 Area Scans.....	11
2.3 DASY E-Field Probe.....	12
2.4 DATA Acquisition Electronics (DAE) and Measurement Server	13
2.5 Robot.....	14
2.6 Device Holder.....	14
2.7 Phantom	15
3. Tissue Simulating Liquid	16
3.1 The composition of the tissue simulating liquid	16
3.2 Tissue Calibration Result.....	16
3.3 Tissue Dielectric Parameters for Phantoms	17
4. Measurement Procedure.....	18
4.1 SAR System Check	18
4.2 SAR Measurement Procedure.....	19
5. RF Exposure Limits	20
6. Test Equipment List	21
7. Measurement Uncertainty.....	22
8. Conducted Power Measurement (Including tolerance allowed for production unit)	24
9. Test Results	29
9.1 Test Results Summary	29
9.2 Simultaneous Transmission.....	32
10. SAR measurement variability.....	33
Appendix A. System Check Data	
Appendix B. Highest measurement Data	
Appendix C. Test Setup Photographs	
Appendix D. Probe Calibration Data	
Appendix E. Dipole & Source Calibration	
Appendix F. Product Photos-Please refer to the file: 24B0011R-Product Photos	

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
24B0011R-SAUSV01S-A	V1.0	Initial issue of report.	2024/12/13

1. General Information

1.1 EUT Description

Product Name	2TX 11ax (WiFi6) BW80 + BT/BLE Combo Card
Trademark	MediaTek
Model and /or type reference	MT7920
FCC ID	RAS-MT7920
Frequency Range	WLAN 2.4GHz: 2412-2472MHz WLAN 5GHz: 5180-5240MHz, 5260-5320MHz, 5500-5720MHz, 5745-5825MHz, 5845-5885MHz BT: 2402-2480MHz
Type of Modulation	802.11b: DSSS 802.11a/g/n/ac/ax: OFDM, OFDMA GFSK(1Mbps) / π /4DQPSK(2Mbps) / 8DPSK(3Mbps)
Antenna Type	PIFA
Device Category	Portable
RF Exposure Environment	Uncontrolled

Summary of test result – Reported 1g SAR (W/kg)			
Test configuration	DTS	NII	DSS(BT)
Standalone	1.155	1.185	0.258
Simultaneous	1.916 (SPLSR=0.01)	2.495 (SPLSR=0.02)	2.495 (SPLSR=0.02)

Note:

Host information			
Brand	Product Name	Model No.	Difference
ASUS	Notebook PC	M1407K	All models are electrically identical, different model names are for marketing purpose.
		D1407K	
The representative test sample is M1407.			

1.2 Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	ICT	6036B0372401 (LA9RF589-NB-H) (Main)	PIFA	2.34 dBi for 2400MHz 2.74 dBi for 5150~5250MHz 2.8 dBi for 5250~5350MHz 3.5 dBi for 5470~5725MHz 3.89 dBi for 5725~5850MHz
		6036B0372301 (LA9RF590-NB-H) (Aux)		2.18 dBi for 2400MHz 1.84 dBi for 5150~5250MHz 1.84 dBi for 5250~5350MHz 2.23 dBi for 5470~5725MHz 2.4 dBi for 5725~5850MHz
2	Pulse	6036B0372201 (TZ2950D) (Main)	PIFA	2.84 dBi for 2400MHz 3.26 dBi for 5150~5250MHz 3.57 dBi for 5250~5350MHz 4.43 dBi for 5470~5725MHz 4.43 dBi for 5725~5850MHz
		6036B0372101 (TZ2950E) (Aux)		2.81 dBi for 2400MHz 2.97 dBi for 5150~5250MHz 3.49 dBi for 5250~5350MHz 4.36 dBi for 5470~5725MHz 4.06 dBi for 5725~5850MHz


Note: 1. The above EUT information by host manufacturer.

2. Pulse antenna was tested and recorded in this report since it represents worst case gain.
3. There are the same antennas only difference in Manufacturer.

1.3 SAR Test Exclusion Calculation

According to KDB Publication 616217 D04, SAR evaluation is required for the bottom surface of the laptop keyboard.

The laptop does not support flip to PAD mode, the antenna is installed on the keyboard, the distance from the bottom is 9.83 mm, and considering that the antenna distance from the front edge is 5 mm, was tested the bottom and front edge of the keyboard.



1.4 Test Environment

Ambient conditions in the laboratory:

Test Date: 2024/11/29 - 2024/12/01

Items	Required	Actual
Temperature (°C)	18-25	23 ± 2
Humidity (%RH)	30-70	50 ± 20

USA	FCC Designation Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd. Linkou Laboratory
Address	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

1.5 Measurement procedures

IEEE 1528-2013

47CFR § 2.1093

KDB 248227 D01 v02r02

KDB 447498 D01 v06


KDB 616217 D04 v01r02

KDB 865664 D01 v01r04

2. SAR Measurement System

2.1 DASY System Description

SAR Configurations is shown below:



The DASY system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7/8/10 and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

2.2 Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for utilize a 10mm² step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing.

2.2.1 Zoom Scan (Cube Scan Averaging)

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications utilize a physical step of 5x5x7 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 30mm in the Z axis.

2.2.2 SAR measurement drifts

Before an area scan and after the zoom scan, single point SAR measurements are performed at defined locations to estimate the SAR measurement drift due to device output power variations. If a device is known to drift randomly, additional single point drift reference measurements should be performed at regular intervals throughout the area and zoom scan test durations. The SAR drift shall be kept within $\pm 5\%$, whether there are substantial drifts or not. The field difference will be calculated in dB units in the DASY software.

2.2.3 Uncertainty of Inter-/Extrapolation and Averaging

In order to evaluate the uncertainty of the interpolation, extrapolation and averaged SAR calculation algorithms of the Postprocessor, DASY allows the generation of measurement grids which are artificially predefined by analytically based test functions. Therefore, the grids of area scans and zoom scans can be filled with uncertainty test data, according to the SAR benchmark functions.


2.3 DASY E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

SPEAG conducts the probe calibration in compliance with international and national standards under ISO 17025. The calibration data are in Appendix D.

Isotropic E-Field Probe Specification

Model	Ex3DV4
Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Frequency	4 MHz – 10 GHz Linearity: ± 0.2 dB (30 MHz to 10 GHz)
Directivity	± 0.1 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



E-Field mm-Wave Probe Specification

Model	EUmmWVx
Construction	Two dipoles optimally arranged to obtain pseudo-vector information Minimum three measurements/point, 120° rotated around probe axis Sensors (0.8 mm length) printed on glass substrate protected by high density foam
Frequency	750 MHz to 110 GHz
Dynamic Range	< 20 V/m to 10000 V/m with PRE-10 (min < 20 V/m to 2000 V/m)
Position Precision	< 0.2 mm
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: encapsulation 8 mm (internal sensor < 1mm) Distance from probe tip to dipole centers: < 2 mm Sensor displacement to probe's calibration point: < 0.3 mm
Application	E-field measurements of 5G devices and other mm-wave transmitters operating above 10GHz in < 2 mm distance from device (free-space) Power density, H-field, and far-field analysis using total field reconstruction

2.4 DATA Acquisition Electronics (DAE) and Measurement Server

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit.

Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE4 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



2.5 Robot

The DASY system uses the high precision robots TX90 XL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY system, the CS8C robot controller version from Stäubli is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller



2.6 Device Holder

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.




2.7 Phantom

2.7.1 SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm).

It has three measurement areas:


- Left head
- Right head
- Flat phantom



The device holder positions are adjusted to the standard measurement positions in the three sections. A cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

2.7.2 mmWave Phantom

The mmWave Phantom approximates free-space conditions, allowing to evaluate not only the antenna side of the device but also the front (screen) side or any opposite-radiating side of wireless devices operating above 10 GHz without distorting the RF field. It consists of a 40 mm thick Rohacell plate used as a test bed, which has a loss tangent ($\tan \delta$) ≤ 0.05 and a relative permittivity (ϵ_r) ≤ 1.2 . High-performance RF absorbers are placed below the foam.



3. Tissue Simulating Liquid

3.1 The composition of the tissue simulating liquid

Description: Aqueous solution with surfactants and inhibitors

Declarable, or hazardous components:

CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28-0000	Ethanediol STOT RE 2, H373; Acute Tox. 4, H302	< 5.2%
CAS: 68608-26-4 EINECS: 271-781-5 Reg.nr.: 01-2119527859-22-0000	Sodium petroleum sulfonate Eye Irrit. 2, H319	< 2.9%
CAS: 107-41-5 EINECS: 203-489-0 Reg.nr.: 01-2119539582-35-0000	Hexylene Glycol / 2-Methyl-pentane-2,4-diol Skin Irrit. 2, H315; Eye Irrit. 2, H319	< 2.9%
CAS: 68920-66-1 NLP: 500-236-9 Reg.nr.: 01-2119489407-26-0000	Alkoxylated alcohol, > C₁₆ Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319	< 2.0%

3.2 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using Dielectric Probe Kit and Vector Network Analyzer.

Date	Tissue Type	Frequency (MHz)	Relative Permittivity (εr)			Conductivity (σ)			Tissue Temp. (°C)
			Measured	Target	Delta (%)	Measured	Target	Delta (%)	
2024/12/1	Head	2450	39.17	39.20	-0.08	1.77	1.80	-1.67	21.9
	Head	2412	39.32	39.28	0.10	1.73	1.77	-2.26	
	Head	2437	39.22	39.23	-0.03	1.76	1.79	-1.68	
	Head	2442	39.21	39.22	-0.03	1.76	1.79	-1.68	
	Head	2462	39.13	39.18	-0.13	1.79	1.81	-1.10	
2024/11/30	Head	5250	36.35	35.95	1.11	4.73	4.71	0.42	22.2
	Head	5270	36.30	35.93	1.03	4.76	4.73	0.63	
	Head	5310	36.19	35.89	0.84	4.82	4.77	1.05	
	Head	5600	35.39	35.50	-0.31	5.21	5.07	2.76	
	Head	5530	35.57	35.61	-0.11	5.12	5.00	2.40	
	Head	5610	35.36	35.49	-0.37	5.22	5.08	2.76	
	Head	5690	35.15	35.41	-0.73	5.32	5.16	3.10	
	Head	5800	34.84	35.30	-1.30	5.47	5.27	3.80	
	Head	5775	34.91	35.33	-1.19	5.44	5.25	3.62	
2024/11/29	Head	5800	35.40	35.30	0.28	5.45	5.27	3.42	22.3
	Head	5855	35.26	35.25	0.03	5.22	5.33	-2.06	

3.3 Tissue Dielectric Parameters for Phantoms

The head tissue dielectric parameters recommended by the IEC/IEEE 62209-1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head tissue parameters that have not been specified are interpolated according to the head parameters specified in IEC/IEEE 62209-1528.

Target Frequency (MHz)	Head	
	ϵ_r	σ (S/m)
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1640	40.2	1.31
1750	40.1	1.37
1800 – 2000	40.0	1.40
2450	39.2	1.80
3000	38.5	2.40
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27
6000	35.1	5.48
6500	34.5	6.07
7000	33.9	6.65
7500	33.3	7.24

4. Measurement Procedure

4.1 SAR System Check

4.1.1 Dipoles



The SAR dipoles are optimized symmetrical dipole with $\lambda/4$ balun matched to a flat phantom section filled with tissue simulating liquids. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC signals. They are available for the variety of frequencies between 300MHz and 10 GHz. The provided tripod is used to hold the dipole below the phantom. As the distance between the dipole center and the TSL is critical, a spacer is placed between the dipole and the phantom. The spacing distance is frequency dependent.

4.1.2 SAR System Check Result

1. Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %.
2. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Delta 1g ± 10 (%)	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Delta 10g ± 10 (%)	Tissue Temp. (°C)
2024/12/1	2450	250	13.00	52.50	52	-0.95	6.23	24.70	24.92	0.89	21.9
2024/11/30	5250	100	7.67	78.10	76.7	-1.79	2.26	22.40	22.6	0.89	22.2
2024/11/30	5600	100	8.12	82.30	81.2	-1.34	2.35	23.50	23.5	0.00	22.2
2024/11/29	5800	100	8.14	80.20	81.4	1.50	2.33	22.80	23.3	2.19	22.3
2024/11/30	5800	100	8.05	80.20	80.5	0.37	2.29	22.80	22.9	0.44	22.2

4.2 SAR Measurement Procedure

The Dasy calculates SAR using the following equation,

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where :

σ : represents the simulated tissue conductivity

ρ : represents the tissue density

E :RMS electric field strength (V/m)

The SAR / APD measurements for the EUT should be performed on the channel that produces the highest rated output power of each transmitting antenna.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR / APD distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR / APD location (interpolated resolution set at 1mm²)which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm³).

5. RF Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, RSS-102 Issue 6, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg
Power density ¹	1 mW/cm²

Note: 1 mW/cm² = 10 W/m²

6. Test Equipment List

Instrument	Manufacturer	Model No.	Serial No.	Last Calibration	Next Calibration
Reference Dipole 2450MHz	Speag	D2450V2	1053	2024/02/19	2027/02/18
Reference Dipole 5GHz	Speag	D5GHzV2	1321	2024/03/12	2027/03/11
Device Holder	Speag	N/A	N/A	N/A	N/A
Data Acquisition Electronic	Speag	DAE4	1651	2024/02/15	2025/02/14
Data Acquisition Electronic	Speag	DAE4	1305	2024/04/18	2025/04/17
E-Field Probe	Speag	EX3DV4	7631	2024/02/21	2025/02/20
E-Field Probe	Speag	EX3DV4	3801	2024/06/20	2025/06/19
SAR Software	Speag	DASY52	V52.10.4.1535	N/A	N/A
SAR Software	Speag	cDASY6	V16.4.0.5005	N/A	N/A
Power Amplifier	Mini-Circuit	ZVE-8G+	447202211	N/A	N/A
Directional Coupler	Agilent	87300C	MY44300353	N/A	N/A ¹
Attenuator	Woken	WATT-218FS-10	N/A	N/A	N/A ¹
Attenuator	Mini-Circuit	BW-S20W2+	N/A	N/A	N/A ¹
Vector Network Analyzer	Agilent	E5071C	MY46108013	2024/03/19	2025/03/18
Signal Generator	Anritsu	MG3694A	041902	2024/08/20	2025/08/19
Power Meter	Anritsu	ML2487A	6K00001447	2024/10/19	2025/10/18
Power Sensor	Anritsu	MA2411B	1339194	2024/10/19	2025/10/18

Note: 1. System Check, the path loss measured by the network analyzer, includes the signal generator, amplifier, cable, attenuator and directional coupler.

7. Measurement Uncertainty

Measurement uncertainty for 300 MHz to 3 GHz							
Error Description	Uncert. value	Prob. Dist.	Div.	(c _i) 1g	(c _i) 10g	Std. Unc. (1g)	Std. Unc. (10g)
Measurement System Errors							
Probe Calibration	±12.0%	N	2	1	1	±6.0%	±6.0%
Probe Calibration Drift	±1.7%	R	1.732	1	1	±1.0%	±1.0%
Probe Linearity	±4.7%	R	1.732	1	1	±2.7%	±2.7%
Broadband Signal	±2.8%	R	1.732	1	1	±1.6%	±1.6%
Probe Isotropy	±7.6%	R	1.732	1	1	±4.4%	±4.4%
Other Probe+Electronic	±0.8%	N	1	1	1	±0.8%	±0.8%
RF Ambient	±1.8%	N	1	1	1	±1.8%	±1.8%
Probe Positioning	±0.006 mm	N	1	0.14	0.14	±0.1%	±0.1%
Data Processing	±1.2%	N	1	1	1	±1.2%	±1.2%
Phantom and Device Errors							
Conductivity (meas.)	±2.5%	N	1	0.78	0.71	±2.0%	±1.8%
Conductivity (temp.)	±3.3%	R	1.732	0.78	0.71	±1.5%	±1.4%
Phantom Permittivity	±14.0%	R	1.732	0	0	±0.0%	±0.0%
Distance DUT - TSL	±2.0%	N	1	2	2	±4.0%	±4.0%
Device Positioning	±1.0%	N	1	1	1	±1.0%	±1.0%
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%
DUT Modulation	±2.4%	R	1.732	1	1	±1.4%	±1.4%
Time-average SAR	±1.7%	R	1.732	1	1	±1.0%	±1.0%
DUT drift	±2.5%	N	1	1	1	±2.5%	±2.5%
Val Antenna Unc.	±0.0%	N	1	1	1	±0.0%	±0.0%
Unc. Input Power	±0.0%	N	1	1	1	±0.0%	±0.0%
Correction to the SAR results							
Deviation to Target	±1.9%	N	1	1	0.84	±1.9%	±1.6%
SAR scaling	±0.0%	R	1.732	1	1	±0.0%	±0.0%
Combined Uncertainty						±11.0%	±10.9%
Expanded Uncertainty						±21.9%	±21.7%

Measurement uncertainty for 3 GHz to 6 GHz							
Error Description	Uncert. value	Prob. Dist.	Div.	(c _i) 1g	(c _i) 10g	Std. Unc. (1g)	Std. Unc. (10g)
Measurement System Errors							
Probe Calibration	±14.0%	N	2	1	1	±7.0%	±7.0%
Probe Calibration Drift	±1.7%	R	1.732	1	1	±1.0%	±1.0%
Probe Linearity	±4.7%	R	1.732	1	1	±2.7%	±2.7%
Broadband Signal	±2.6%	R	1.732	1	1	±1.5%	±1.5%
Probe Isotropy	±7.6%	R	1.732	1	1	±4.4%	±4.4%
Other Probe+Electronic	±1.2%	N	1	1	1	±1.2%	±1.2%
RF Ambient	±1.8%	N	1	1	1	±1.8%	±1.8%
Probe Positioning	±0.005 mm	N	1	0.29	0.29	±0.2%	±0.2%
Data Processing	±2.3%	N	1	1	1	±2.3%	±2.3%
Phantom and Device Errors							
Conductivity (meas.)	±2.5%	N	1	0.78	0.71	±2.0%	±1.8%
Conductivity (temp.)	±3.4%	R	1.732	0.78	0.71	±1.5%	±1.4%
Phantom Permittivity	±14.0%	R	1.732	0.25	0.25	±2.0%	±2.0%
Distance DUT - TSL	±2.0%	N	1	2	2	±4.0%	±4.0%
Device Positioning	±1.0%	N	1	1	1	±1.0%	±1.0%
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%
DUT Modulation	±2.4%	R	1.732	1	1	±1.4%	±1.4%
Time-average SAR	±1.7%	R	1.732	1	1	±1.0%	±1.0%
DUT drift	±2.5%	N	1	1	1	±2.5%	±2.5%
Val Antenna Unc.	±0.0%	N	1	1	1	±0.0%	±0.0%
Unc. Input Power	±0.0%	N	1	1	1	±0.0%	±0.0%
Correction to the SAR results							
Deviation to Target	±1.9%	N	1	1	0.84	±1.9%	±1.6%
SAR scaling	±0.0%	R	1.732	1	1	±0.0%	±0.0%
Combined Uncertainty						±11.9%	±11.8%
Expanded Uncertainty						±23.8%	±23.6%

8. Conducted Power Measurement (Including tolerance allowed for production unit)

WLAN 2.4G 2TX SISO									
DSSS/OFDM mode specified maximum output power at an antenna port	Frequency	Mode	BW	SISO-Main(TX0)			SISO-Aux(TX1)		
				CH	Avg. Power	Tune-Up Power	CH	Avg. Power	Tune-Up Power
WLAN 2.4GHz	b	20	1	16.19	16.5	1	16.46	16.5	
			6	16.45	16.5	6	16.48	16.5	
		11	16.29	16.5	11	16.36	16.5		
		12	15.41	15.5	12	15.44	15.5		
		13	11.37	11.5	13	11.48	11.5		
	g	20	1	16.07	16.5	1	16.15	16.5	
			6	16.17	16.5	6	16.25	16.5	
		11	16.14	16.5	11	16.21	16.5		
		12	14.33	14.5	12	14.41	14.5		
		13	10.97	11	13	10.92	11		
	n (HT)	20	1	16.14	16.5	1	16.12	16.5	
			6	16.11	16.5	6	16.22	16.5	
			11	16.15	16.5	11	16.18	16.5	
			12	14.44	14.5	12	14.39	14.5	
			13	10.25	10.5	13	10.20	10.5	
		40	3	14.75	15	3	14.63	15	
			6	15.93	16.5	6	16.22	16.5	
			9	14.66	15	9	14.54	15	
			10	13.12	13.5	10	13.37	13.5	
			11	10.44	10.5	11	10.23	10.5	
	ax (HE)	20	1	16.14	16.5	1	16.21	16.5	
			6	16.12	16.5	6	16.25	16.5	
			11	16.11	16.5	11	16.24	16.5	
			12	14.36	14.5	12	14.41	14.5	
			13	10.31	10.5	13	10.37	10.5	
		40	3	14.75	15	3	14.55	15	
			6	16.24	16.5	6	16.12	16.5	
			9	14.93	15	9	14.77	15	
			10	13.37	13.5	10	13.34	13.5	
			11	10.15	10.5	11	10.24	10.5	

WLAN 5G 2TX SISO											
	Frequency	Mode	BW	SISO-Main(TX0)			SISO-Aux(TX1)				
				CH	Avg. Power	Tune-Up Power	CH	Avg. Power	Tune-Up Power		
U-NII-1 (5150~5250MHz)		a	20	36	14.03	14.5	36	13.99	14.5		
				40	14.06	14.5	40	14.02	14.5		
				44	14.08	14.5	44	14.12	14.5		
				48	14.06	14.5	48	14.01	14.5		
		n (HT)	20	36	14.05	14.5	36	13.96	14.5		
				40	14.14	14.5	40	14.01	14.5		
				44	14.09	14.5	44	14.09	14.5		
				48	14.04	14.5	48	13.95	14.5		
		40	40	38	14.41	14.5	38	14.21	14.5		
				46	14.45	14.5	46	14.23	14.5		
				ac(VHT)	80	42	13.17	13.5	42	13.32	13.5
				36	14.11	14.5	36	14.04	14.5		
	OFDM mode specified maximum output power at an antenna port		20	40	13.96	14.5	40	14.16	14.5		
				44	13.88	14.5	44	14.15	14.5		
				48	14.13	14.5	48	14.07	14.5		
				38	13.88	14.5	38	14.07	14.5		
			40	46	14.04	14.5	46	14.05	14.5		
				80	42	13.06	13.5	42	13.16	13.5	
		a	20	52	14.11	14.5	52	14.06	14.5		
				56	14.06	14.5	56	14.10	14.5		
	U-NII-2A (5250~5350MHz)			60	14.04	14.5	60	14.05	14.5		
				64	13.94	14.5	64	14.06	14.5		
	n (HT)	20	52	14.09	14.5	52	14.08	14.5			
			56	14.16	14.5	56	14.15	14.5			
			60	14.08	14.5	60	13.97	14.5			
			64	14.04	14.5	64	14.06	14.5			
	40	40	54	14.42	14.5	54	14.49	14.5			
			62	14.33	14.5	62	14.19	14.5			
	ac (VHT)	80	58	13.71	14	58	13.52	14			
			52	14.11	14.5	52	14.13	14.5			
	ax (HE)	20	56	13.94	14.5	56	14.16	14.5			
			60	13.98	14.5	60	14.06	14.5			
			64	14.08	14.5	64	13.96	14.5			
			54	14.12	14.5	54	13.97	14.5			
	40	80	62	13.79	14.5	62	14.01	14.5			
			58	13.78	14	58	13.84	14			

	Frequency	Mode	BW	SISO-Main(TX0)			SISO-Aux(TX1)		
				CH	Avg. Power	Tune-Up Power	CH	Avg. Power	Tune-Up Power
OFDM mode specified maximum output power at an antenna port U-NII-2C (5470~5725MHz)	a	n (HT)	20	100	14.09	14.5	100	14.14	14.5
				116	14.05	14.5	116	14.09	14.5
				124	14.09	14.5	124	14.11	14.5
				132	13.92	14.5	132	14.13	14.5
				140	13.95	14.5	140	14.08	14.5
				144	13.84	14.5	144	14.03	14.5
	n (HT)	20	40	100	14.06	14.5	100	13.99	14.5
				116	14.04	14.5	116	14.15	14.5
				124	14.13	14.5	124	13.99	14.5
				132	14.31	14.5	132	13.93	14.5
				140	14.08	14.5	140	14.09	14.5
				144	14.05	14.5	144	14.11	14.5
	ac (VHT)	80	20	102	14.19	14.5	102	14.18	14.5
				110	14.04	14.5	110	14.04	14.5
				126	13.79	14.5	126	13.95	14.5
				134	14.06	14.5	134	14.12	14.5
				142	14.10	14.5	142	14.09	14.5
				106	14.39	14.5	106	14.41	14.5
	ax (HE)	80	40	122	14.36	14.5	122	14.22	14.5
				138	14.29	14.5	138	14.28	14.5
				100	14.06	14.5	100	13.85	14.5
				116	14.13	14.5	116	14.13	14.5
				124	14.09	14.5	124	13.97	14.5
				132	14.08	14.5	132	14.02	14.5
	ax (HE)	80	20	140	14.09	14.5	140	14.01	14.5
				144	14.13	14.5	144	14.08	14.5
				102	14.03	14.5	102	14.03	14.5
				110	13.94	14.5	110	3.96	14.5
				126	14.09	14.5	126	13.82	14.5
				134	14.01	14.5	134	14.06	14.5
	ax (HE)	80	40	142	14.09	14.5	142	14.05	14.5
				106	14.06	14.5	106	13.93	14.5
				122	14.06	14.5	122	14.12	14.5
				138	14.11	14.5	138	14.07	14.5

	Frequency	Mode	BW	SISO-Main(TX0)			SISO-Aux(TX1)		
				CH	Avg. Power	Tune-Up Power	CH	Avg. Power	Tune-Up Power
OFDM mode specified maximum output power at an antenna port	U-NII-3 (5725~5850MHz)	a	20	149	13.87	14.5	149	14.12	14.5
				157	13.81	14.5	157	14.17	14.5
				165	14.11	14.5	165	14.10	14.5
		n (HT)	20	149	14.14	14.5	149	14.11	14.5
				157	14.15	14.5	157	14.19	14.5
				165	14.16	14.5	165	14.00	14.5
			40	151	14.08	14.5	151	14.03	14.5
				159	14.13	14.5	159	14.06	14.5
		ac(VHT)	80	155	14.35	14.5	155	14.40	14.5
		ax (HE)	20	149	14.06	14.5	149	14.09	14.5
				157	14.05	14.5	157	14.15	14.5
				165	14.12	14.5	165	14.11	14.5
			40	151	13.74	14.5	151	13.96	14.5
				159	13.89	14.5	159	14.06	14.5
			80	155	14.06	14.5	155	14.16	14.5
OFDM mode specified maximum output power at an antenna port	U-NII-4 (5850~5925MHz)	a	20	169	14.06	14.5	169	14.07	14.5
				173	13.91	14	173	13.82	14
				177	13.85	14	177	13.89	14
		n (HT)	20	169	14.09	14.5	169	14.02	14.5
				173	13.93	14.5	173	14.06	14.5
				177	14.07	14.5	177	13.96	14.5
			40	167	14.06	14.5	167	13.97	14.5
				175	14.11	14.5	175	13.88	14.5
		ac(VHT)	80	171	14.31	14.5	171	14.36	14.5
		ax (HE)	20	169	13.89	14.5	169	14.09	14.5
				173	14.01	14.5	173	14.09	14.5
				177	14.08	14.5	177	13.97	14.5
			40	167	14.06	14.5	167	13.77	14.5
				175	14.09	14.5	175	13.97	14.5
			80	171	14.08	14.5	171	14.15	14.5

BT Only Support Aux								
Bluetooth mode maximum output power	Frequency	Mode	Modulation	SISO-Aux(TX2)				
				CH	Avg. Power	Tune-Up Power		
				0	11.11	11.5		
	BT 2.4GHz	BR	GFSK	39	11.43	11.5		
				78	11.31	11.5		
		EDR	8DPSK	0	8.37	8.5		
	BLE			39	8.30	8.5		
				78	8.41	8.5		
	GFSK	GFSK	0	11.01	11.5			
			19	11.21	11.5			
			39	11.17	11.5			

9. Test Results

9.1 Test Results Summary

SAR MEASUREMENT								
Ambient Temperature (°C): 22.9±2					Relative Humidity (%): 54%			
Liquid Temperature (°C): 21.9±2					Depth of Liquid (cm): >15			
Test Position	Dist. (mm)	Frequency		Conducted Power (dBm)		SAR (W/kg)		Plot No.
		Ch.	MHz	Meas.	Tune-Up Limit	Meas-1g	Scaled-1g	
Test Mode: WLAN2.4GHz_802.11b-1M_Ant Main_Pluse								
Bottom of laptop	0	1	2412	16.19	16.5	1.010	1.096	
Bottom of laptop	0	6	2437	16.45	16.5	1.130	1.155	1
Bottom of laptop	0	11	2462	16.29	16.5	1.080	1.145	
Front edge of laptop	0	6	2437	16.45	16.5	0.232	0.237	
Test Mode: WLAN2.4GHz_802.11b-1M_Ant Aux_Pluse								
Bottom of laptop	0	6	2437	16.48	16.5	0.750	0.761	
Front edge of laptop	0	6	2437	16.48	16.5	0.356	0.361	
Test Mode: WLAN2.4GHz_802.11b-1M_Ant Main_ICT								
Bottom of laptop	0	6	2437	16.45	16.5	1.080	1.103	
Test Mode: Bluetooth_BT-1M_Ant Aux_Pluse								
Bottom of laptop	0	39	2441	11.43	11.5	0.198	0.258	33
Front edge of laptop	0	39	2441	11.43	11.5	0.098	0.128	

Note:

1. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required.
2. When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required in that exposure configuration.

SAR MEASUREMENT								
Ambient Temperature (°C): 23.2±2				Relative Humidity (%): 57%				
Liquid Temperature (°C): 22.2±2				Depth of Liquid (cm): >15				
Test Position	Dist. (mm)	Frequency		Conducted Power (dBm)		SAR (W/kg)		Plot No.
		Ch.	MHz	Meas.	Tune-Up Limit	Meas-1g	Scaled-1g	
Test Mode: WLAN5GHz_802.11n40-HT0_Ant Main_Pluse								
Bottom of laptop	0	54	5270	14.42	14.5	0.527	0.569	
Front edge of laptop	0	54	5270	14.42	14.5	1.020	1.117	15
Front edge of laptop	0	62	5310	14.33	14.5	0.994	1.111	
Test Mode: WLAN5GHz_802.11n40-HT0_Ant Aux_Pluse								
Bottom of laptop	0	54	5270	14.49	14.5	0.418	0.450	
Front edge of laptop	0	54	5270	14.49	14.5	0.659	0.710	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Main_Pluse								
Bottom of laptop	0	106	5530	14.39	14.5	0.798	0.909	
Bottom of laptop	0	122	5610	14.36	14.5	0.789	0.905	
Bottom of laptop	0	138	5690	14.29	14.5	0.817	0.953	
Front edge of laptop	0	106	5530	14.39	14.5	1.040	1.185	14
Front edge of laptop	0	122	5610	14.36	14.5	0.889	1.020	
Front edge of laptop	0	138	5690	14.29	14.5	0.833	0.971	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Aux_Pluse								
Bottom of laptop	0	106	5530	14.41	14.5	0.516	0.585	
Front edge of laptop	0	106	5530	14.41	14.5	0.641	0.727	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Main_Pluse								
Bottom of laptop	0	155	5775	14.35	14.5	0.881	1.013	
Front edge of laptop	0	155	5775	14.35	14.5	0.837	0.963	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Aux_Pluse								
Bottom of laptop	0	155	5775	14.40	14.5	0.447	0.508	
Front edge of laptop	0	155	5775	14.40	14.5	0.961	1.093	
Test Mode: WLAN5GHz_802.11n40-HT0_Ant Main_ICT								
Front edge of laptop	0	54	5270	14.42	14.5	0.973	1.051	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Main_ICT								
Front edge of laptop	0	106	5530	14.39	14.5	0.884	1.007	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Main_ICT								
Bottom of laptop	0	155	5775	14.35	14.5	0.711	0.818	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Aux_ICT								
Front edge of laptop	0	155	5775	14.40	14.5	0.942	1.071	

Note:

- When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required in that exposure configuration.
- When multiple transmission modes have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected.
- When the reported SAR of the highest measured maximum U-NII-2A for the exposure configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.

SAR MEASUREMENT								
Ambient Temperature (°C): 23.3±2				Relative Humidity (%): 57%				
Liquid Temperature (°C): 22.3±2				Depth of Liquid (cm): >15				
Test Position	Dist. (mm)	Frequency		Conducted Power (dBm)		SAR (W/kg)		Plot No.
		Ch.	MHz	Meas.	Tune-Up Limit	Meas-1g	Scaled-1g	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Main_Pluse								
Bottom of laptop	0	171	5855	14.31	14.5	0.997	1.157	
Front edge of laptop	0	171	5855	14.31	14.5	0.846	0.982	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Aux_Pluse								
Bottom of laptop	0	171	5855	14.36	14.5	0.452	0.519	
Front edge of laptop	0	171	5855	14.36	14.5	1.030	1.182	54
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Main_ICT								
Bottom of laptop	0	171	5855	14.31	14.5	0.799	0.927	
Test Mode: WLAN5GHz_802.11ac80-VHT0_Ant Aux_ICT								
Front edge of laptop	0	171	5855	14.36	14.5	0.993	1.139	

Note:

1. When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required in that exposure configuration.
2. When multiple transmission modes have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected.

9.2 Simultaneous Transmission

Simultaneous Transmission Configurations								
1	WLAN 2.4 GHz ANT Main + WLAN 2.4 GHz ANT Aux							
2	WLAN 2.4 GHz ANT Main + Bluetooth Aux							
3	WLAN 5 GHz ANT Main + WLAN 5 GHz ANT Aux + Bluetooth Aux							

9.2.1 Simultaneous transmission test exclusion considerations

Test Position	1	2	3	4	5	1 + 2	1 + 5	3 + 4 + 5
	WLAN2.4GHz ANT Main (W/kg)	WLAN2.4GHz ANT Aux (W/kg)	WLAN5GHz ANT Main (W/kg)	WLAN5GHz ANT Aux (W/kg)	Bluetooth ANT Aux (W/kg)	$\Sigma 1\text{-g SAR}$	$\Sigma 1\text{-g SAR}$	$\Sigma 1\text{-g SAR}$
Front edge of laptop at 0 mm	0.237	0.361	1.185	1.182	0.128	0.598	0.365	2.495
Bottom of laptop at 0 mm	1.155	0.761	1.157	0.585	0.258	1.916	1.413	2.000

When the sum of SAR is larger than the limit, The ratio is determined by $(\text{SAR1} + \text{SAR2})^{1.5}/R_i$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion. The estimation result as below:

Test Position	WLAN2.4GHz Ant Main SAR (W/kg)	WLAN2.4GHz Ant Aux SAR (W/kg)	Simultaneous Transmission (W/kg)	Antenna pair in mm	Peak location separation ratio
Bottom of laptop	1.155	0.761	1.916	187	0.01

The ratio of value is less than 0.04, thus simultaneous SAR testing is not needed.

Test Position	WLAN5GHz Ant Main SAR (W/kg)	WLAN5GHz Ant Aux SAR (W/kg)	Bluetooth Ant Aux SAR (W/kg)	Simultaneous Transmission (W/kg)	Antenna pair in mm	Peak location separation ratio
Front edge of laptop	1.185	1.182	0.128	2.495	187	0.02

The ratio of value is less than 0.04, thus simultaneous SAR testing is not needed.

Test Position	WLAN5GHz Ant Main SAR (W/kg)	WLAN5GHz Ant Aux SAR (W/kg)	Bluetooth Ant Aux SAR (W/kg)	Simultaneous Transmission (W/kg)	Antenna pair in mm	Peak location separation ratio
Bottom of laptop	1.157	0.585	0.258	2.000	187	0.02

The ratio of value is less than 0.04, thus simultaneous SAR testing is not needed.

10. SAR measurement variability

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Frequency		SAR 1g (W/kg)		
Channel	MHz	Original	First Repeated	
			Value	Ratio
6	2437	1.130	1.110	1.018
106	5530	1.040	0.948	1.097

Appendix

Appendix A. System Check Data

Appendix B. Highest measurement Data

Appendix C. Test Setup Photographs

Appendix D. Probe Calibration Data

Appendix E. Dipole Calibration Data

Appendix F. Product Photos-Please refer to the file: 24B0011R-Product Photos