

# ANTENNA INFORMATION

|                                                           |                          |
|-----------------------------------------------------------|--------------------------|
| OEM                                                       | DELL                     |
| ODM                                                       | Compal Corporation       |
| Platform model name                                       | P200G                    |
| Intel platform (ex: Yes, No or NA)                        | Yes                      |
| Platform type (ex: regular NB, convertible PC, AIO...etc) | Convertible PC (NB mode) |
| SAR minimum separation (mm)                               | 5 mm with bumper (3 mm)  |

|                      |                 |                                                                       |
|----------------------|-----------------|-----------------------------------------------------------------------|
| Antenna manufacturer | Company name    | Auden Techno Corp                                                     |
|                      | Address         | NO. 19, Lane 772, Heping Rd., Bade Dist, Taoyuan City, Taiwan (R.O.C) |
| Test location        | Company name    | SPORTON INTERNATIONAL INC                                             |
|                      | Address         | NO. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)   |
| Test Personnel       | Name(Full name) | Alex Weng                                                             |
|                      | E-mail          | <a href="mailto:Alex.weng@auden.com.tw">Alex.weng@auden.com.tw</a>    |
|                      | Tel/Mobile      | +886-3-3631901 #571                                                   |
| Testing date         |                 | 2024.08.29                                                            |

|                                       |      |                         |
|---------------------------------------|------|-------------------------|
| Antenna Part number                   | Main | A23300-30 (DC33002YB1L) |
|                                       | Aux  | A23300-30 (DC33002YB1L) |
| Antenna type (ex: PIFA, Dipole...etc) |      | PIFA                    |

| Antenna Peak gain w/ cable loss (dBi)* |                           |                        |                        |                        |                        |                        |                        |                        |                        |                         |
|----------------------------------------|---------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------------|
|                                        | 2.4GHz<br>2400-2483.5 MHz | 5.2GHz<br>5150-5250MHz | 5.3GHz<br>5250-5350MHz | 5.6GHz<br>5470-5725MHz | 5.8GHz<br>5725-5850MHz | 5.9GHz<br>5850-5895MHz | 6.2GHz<br>5925-6425MHz | 6.5GHz<br>6425-6525MHz | 6.7GHz<br>6525-6875MHz | 7.0 GHz<br>6875-7125MHz |
| Main                                   | -0.93                     | 1.32                   | 0.60                   | 0.69                   | 0.69                   | 0.46                   | 0.53                   | -1.06                  | 1.34                   | 3.99                    |
| Aux                                    | 0.25                      | 2.58                   | 2.48                   | 0.55                   | 0.99                   | 0.69                   | 0.70                   | 0.00                   | 1.78                   | 3.35                    |

| Cable Assembly Part Number and Information |               |                  |                    |                |                |
|--------------------------------------------|---------------|------------------|--------------------|----------------|----------------|
|                                            | Cable PN      | Cable length(mm) | Cable diameter(mm) | Impedance(ohm) | Connector type |
| Main                                       | SY113L/50-143 | 150              | 1.13               | 50             | 20565-001R-13  |
| Aux                                        | SY113L/50-118 | 153              | 1.13               | 50             | 20565-001R-13  |

\* 3D Antenna Peak Gain required being test in system basis.

| Cable loss (dBi) |                           |                        |                        |                        |                        |                        |                        |                        |                        |                         |
|------------------|---------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------------|
|                  | 2.4GHz<br>2400-2483.5 MHz | 5.2GHz<br>5150-5250MHz | 5.3GHz<br>5250-5350MHz | 5.6GHz<br>5470-5725MHz | 5.8GHz<br>5725-5850MHz | 5.9GHz<br>5850-5895MHz | 6.2GHz<br>5925-6425MHz | 6.5GHz<br>6425-6525MHz | 6.7GHz<br>6525-6875MHz | 7.0 GHz<br>6875-7125MHz |
| Main             | 0.33                      | 0.53                   | 0.54                   | 0.58                   | 0.59                   | 0.59                   | 0.63                   | 0.62                   | 0.65                   | 0.67                    |
| Aux              | 0.34                      | 0.54                   | 0.55                   | 0.59                   | 0.60                   | 0.60                   | 0.64                   | 0.63                   | 0.66                   | 0.66                    |

# Table of Contents

|                                                                             |          |
|-----------------------------------------------------------------------------|----------|
| <b>Cover page.....</b>                                                      | <b>1</b> |
| <b>1. Intel Reference Gain and Type.....</b>                                | <b>3</b> |
| <b>2. Document Revision History.....</b>                                    | <b>3</b> |
| <b>3. Test &amp; System Description</b>                                     |          |
| 3.1 Measurement Method and System.....                                      | 4        |
| 3.2 Test setup.....                                                         | 4        |
| 3.3 Equipment list.....                                                     | 5        |
| <b>4. Radiation characteristics of antenna loaded in Host Platform.....</b> | <b>6</b> |
| <b>Annex A. Photographs</b>                                                 |          |
| A.1 Setup Photo.....                                                        | 16       |
| A.2 Test sample.....                                                        | 17       |
| <b>Annex B. Antenna Location</b>                                            |          |
| B.1 Antenna Host Platform Location Information.....                         | 19       |
| B.2 Antenna dimensional information for SAR evaluation.....                 | 20       |

## 1. Intel Reference Gain and Type

| Antenna Peak gain w/ cable loss (dBi) |                         |                                  |                               |                               |                               |                               |                               |                               |                               |                               |                                |
|---------------------------------------|-------------------------|----------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|--------------------------------|
| Band/Frequency                        |                         | <b>2.4GHz</b><br>2400-2483.5 MHz | <b>5.2GHz</b><br>5150-5250MHz | <b>5.3GHz</b><br>5250-5350MHz | <b>5.6GHz</b><br>5470-5725MHz | <b>5.8GHz</b><br>5725-5850MHz | <b>5.9GHz</b><br>5850-5895MHz | <b>6.2GHz</b><br>5925-6425MHz | <b>6.5GHz</b><br>6425-6525MHz | <b>6.7GHz</b><br>6525-6875MHz | <b>7.0 GHz</b><br>6875-7125MHz |
| Design                                | EU/UK                   | 3.00                             | 5.00                          | 5.00                          | 5.00                          | 5.00                          | 5.00                          | 5.00                          | 5.00                          | 5.00                          | 5.00                           |
| PIFA                                  | For WiFi 6E and earlier | 3.24                             | 3.64                          | 3.73                          | 4.77                          | 4.97                          | 4.72                          | 4.83                          | 4.30                          | 5.37                          | 5.59                           |
|                                       | From WiFi 7             | 2.95                             | 5.11                          | 4.55                          | 5.15                          | 5.13                          | 4.45                          | 5.02                          | 5.02                          | 4.96                          | 4.96                           |
| Dipole                                | For WiFi 6E and earlier | 2.89                             | 2.92                          | 3.19                          | 4.41                          | 4.22                          | 4.22                          | 4.83                          | 4.30                          | 4.49                          | 5.34                           |
|                                       | From WiFi 7             | 2.95                             | 4.03                          | 4.11                          | 5.15                          | 5.13                          | 4.45                          | 5.02                          | 4.71                          | 4.49                          | 4.96                           |
| Monopole                              | From WiFi 7             | 2.83                             | 4.57                          | 4.44                          | 4.95                          | 4.95                          | 4.43                          | 4.87                          | 4.91                          | 4.91                          | 4.79                           |

### 3D Peak Antenna gain should be equal or greater than -2 dBi

If a host integrator plans to use a lower gain antenna of the same type, additional CBP(FCC)/EDT(EU) testing need to be performed while the module is installed in the host.


## 2. Document Revision History

| Revision # | Revision Details | Issued Date |
|------------|------------------|-------------|
| Rev. 00    | First Issue      |             |

### 3. Test & System Description

#### 3.1 Measurement Method and System

#### 3.2 Test setup



### 3.3 Equipment list


| Huaya-Sporton OTA03                                         |                       |            |               |             |           |
|-------------------------------------------------------------|-----------------------|------------|---------------|-------------|-----------|
| Name                                                        | Manufacturer          | Type/Model | Serial Number | Calibration |           |
|                                                             |                       |            |               | Last Cal.   | Due Date  |
| ENA Series Network Analyzer                                 | Keysight              | E5071C     | MY46100746    | 2023/9/15   | 2024/9/14 |
| RF Switch                                                   | Keysight              | 3499A      | MY42000955    | NCR         | NCR       |
| Multi-Axis Positioner Controller                            | ETS-Lindgren          | 2090       | N/A           | NCR         | NCR       |
| Medium-Duty Positioner                                      | ETS-Lindgren          | 2015       | N/A           | NCR         | NCR       |
| Measurement Horn Antenna                                    | EMCO                  | 3164-08    | 00086722      | NCR         | NCR       |
| Anechoic Chamber                                            | ETS-Lindgren          | AMS-8500   | N/A           | 2024/3/12   | 2025/3/11 |
| 12GHz SMA(M)-SMA(M)+20core for 60cm RG316DS Cable Assembly  | Woken Technology Inc. | RG316DS    | N/A           | N/A         | N/A       |
| 12GHz SMA(M)-SMA(M)+30core for 300cm RG316DS Cable Assembly | Woken Technology Inc. | RG316DS    | N/A           | N/A         | N/A       |
| Note: Chamber calibration included full set of implement.   |                       |            |               |             |           |

#### 4. Radiation characteristics of antenna loaded in Host Platform

##### Main Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 2400-2483.5     | -0.93                         |




Max Antenna 3D Radiation Pattern 5150-5250 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5150-5250       | 1.32                          |




## Max Antenna 3D Radiation Pattern 5250-5350 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5250-5350       | 0.60                          |




## Max Antenna 3D Radiation Pattern 5470-5725 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5470-5725       | 0.69                          |




## Max Antenna 3D Radiation Pattern 5725-5850 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5725-5850       | 0.69                          |



## Max Antenna 3D Radiation Pattern 5850-5895 MHz


| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5850-5895       | 0.46                          |






## Max Antenna 3D Radiation Pattern 5925-6425 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5925-6425       | 0.53                          |




## Max Antenna 3D Radiation Pattern 6425-6525 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 6425-6525       | -1.06                         |




## Max Antenna 3D Radiation Pattern 6525-6875 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 6525-6875       | 1.34                          |



## Max Antenna 3D Radiation Pattern 6875-7125 MHz


| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 6875-7125       | 3.99                          |



## Auxiliary Antenna


### Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 2400-2483.5     | 0.25                          |




### Max Antenna 3D Radiation Pattern 5150-5250 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5150-5250       | 2.58                          |




## Max Antenna 3D Radiation Pattern 5250-5350 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5250-5350       | 2.48                          |




## Max Antenna 3D Radiation Pattern 5470-5725 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5470-5725       | 0.55                          |




## Max Antenna 3D Radiation Pattern 5725-5850 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5725-5850       | 0.99                          |




## Max Antenna 3D Radiation Pattern 5850-5895 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5850-5895       | 0.69                          |




## Max Antenna 3D Radiation Pattern 5925-6425 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 5925-6425       | 0.70                          |




## Max Antenna 3D Radiation Pattern 6425-6525 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 6425-6525       | 0.00                          |




## Max Antenna 3D Radiation Pattern 6525-6875 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 6525-6875       | 1.78                          |



## Max Antenna 3D Radiation Pattern 6875-7125 MHz

| Frequency (MHz) | Peak Gain w/ Cable Loss (dBi) |
|-----------------|-------------------------------|
| 6875-7125       | 3.35                          |



# Annex A. Photographs

---

## A.1 Setup Photo


**Please refer to the photo file**



## A.2 Test sample



## Main Antenna

## Antenna Drawing





## Antenna Photo

## Front




## Back



**Note: antenna photo should include L type ruler**



## Aux Antenna

### Antenna Drawing





### Antenna Photo

#### Front



#### Back




Note: antenna photo should include L type ruler

# Annex B. Antenna Location


## B.1 Antenna Host Platform Location Information

Include a dimensioned photo(s) or dimensioned drawing(s) of Main and Aux antenna placements (measurements are not required for receive-only antenna).

Any antenna that transmits must show dimensions to bottom of laptop. Provide a description of the materials that are used for supporting or surrounding transmit antennas; for example, non-conductive plastics vs. conductive coated plastic or metallic materials.



| Minimum Separation Distance |           |                     |               |
|-----------------------------|-----------|---------------------|---------------|
| Item                        | Antenna   | Position            | Distance (mm) |
| A                           | WLAN-Aux  | to Top              | 214           |
| B                           | WLAN-Aux  | to Left             | 250           |
| C                           | WLAN-Aux  | to Right            | 20            |
| D                           | WLAN-Aux  | to Bottom           | 5             |
| E                           | WLAN-Aux  | Main Antenna Length | 40            |
| F                           | Main-Aux  | Main to Aux         | 190           |
| G                           | WLAN-main | to Top              | 214           |
| H                           | WLAN-main | to Left             | 20            |
| I                           | WLAN-main | to Right            | 250           |
| J                           | WLAN-main | to Bottom           | 5             |
| K                           | WLAN-main | Aux Antenna Length  | 40            |
| L                           | NB        | Bumper thickness    | 3             |
| X                           | WLAN-Aux  | to hinge            | 15            |
| Y                           | WLAN-Main | to hinge            | 15            |
| Z                           | NB        | Keyboard depth      | 223           |



| Minimum Separation Distance |           |          |               |
|-----------------------------|-----------|----------|---------------|
| Item                        | Antenna   | Position | Distance (mm) |
| P                           | WLAN-Main | to Front | 10            |
| Q                           | WLAN-Main | to Rear  | 0             |
| R                           | WLAN-Aux  | to Front | 10            |
| S                           | WLAN-Aux  | to Rear  | 0             |

## B.2 Antenna dimensional information for SAR evaluation

Include a dimensioned photo(s) or dimensioned drawing(s) showing the distance (mm) between the transmit antennas and the user. For notebook/laptop hosts show lapheld position (example below). For tablet hosts show all orientations including lapheld, primary & secondary portrait, primary & secondary landscape positions. Include a description of any proximity sensors or power throttling implementations that limit or exclude use of any host orientation.

Notebook Mode

