


FCC RADIO TEST REPORT

Applicant's company	Arcadyan Technology Corporation
Applicant Address	4F, No.9, Park Avenue II, Science-based Industrial Park, Hsinchu 300, Taiwan, R.O.C
FCC ID	RAX-WN8522B

Product Name	11n wireless USB module
Model Name	WN8522B-LF-ZZ, WN8522B-LF-FA
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Aug. 27, 2009
Final Test Date	Oct. 08, 2009
Submission Type	Original Equipment
Multiple Listing	Please refer to section 3.7



Statement

Test result included is only for the Draft n, 802.11b/g part and 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes.....	8
3.6. Table for Testing Locations.....	9
3.7. Table for Multiple Listing.....	10
3.8. Table for Supporting Units	10
3.9. Table for Parameters of Test Software Setting	10
3.10. Test Configurations	12
4. TEST RESULT	14
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. Maximum Conducted Output Power Measurement.....	18
4.3. Power Spectral Density Measurement	40
4.4. 6dB Spectrum Bandwidth Measurement	53
4.5. Radiated Emissions Measurement	67
4.6. Band Edge Emissions Measurement	113
4.7. Antenna Requirements	125
5. LIST OF MEASURING EQUIPMENTS	126
6. TEST LOCATION.....	127
7. TAF CERTIFICATE OF ACCREDITATION	128
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A4
APPENDIX B. TEST PHOTOS.....	B1 ~ B6
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~ C3

History of This Test Report

Original Issue Date: Apr. 15, 2010

Report No.: FR982208-02AB

- ☒ No additional attachment.
- ☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : 11n wireless USB module
Model Name : WN8522B-LF-ZZ, WN8522B-LF-FA
Applicant : Arcadyan Technology Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Aug. 27, 2009 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Jordan Hsiao 2010.4.15

Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	10.32 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	10.71 dB
4.3	15.247(e)	Power Spectral Density	Complies	14.26 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.14 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.32 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Draft n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	<For 2.4GHz Band>: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth <For 5GHz Band>: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	<For 2.4GHz Band>: MCS8 (20MHz): 17.68 MHz ; MCS8 (40MHz): 36.16 MHz <For 5GHz Band>: MCS8 (20MHz): 17.68 MHz ; MCS8 (40MHz): 36.16 MHz
Conducted Output Power	<For 2.4GHz Band>: MCS8 (20MHz): 19.29 dBm ; MCS8 (40MHz): 17.91 dBm <For 5GHz Band>: MCS8 (20MHz): 14.10 dBm ; MCS8 (40MHz): 14.40 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11a/b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 13.28 MHz ; 11g: 16.52 MHz ; 11a: 16.60 MHz
Conducted Output Power	11b: 16.41 dBm ; 11g: 18.41 dBm ; 11a: 14.82 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
802.11a	V	X	X	X
802.11b	V	X	X	X
802.11g	V	X	X	X
Draft n	X	X	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Accessories
USB Cable with Cradle

3.3. Table for Filed Antenna

<For 5GHz>:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
A	-	-	PCB Antenna	N/A	2
B	-	-	PCB Antenna	N/A	2

<For 2.4GHz>:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
A	-	-	PCB Antenna	N/A	2
B	-	-	PCB Antenna	N/A	2

Note: The EUT has two antennas.

For IEEE 802.11a/b/g Mode:

Ant. A can be used as transmitting antenna.

Ant. B can be used as receiving antenna.

For Draft n Mode:

Ant. A & Ant. B could transmit/receive simultaneously.



Ant. A: TX/RX



Ant. B: TX/RX

3.4. Table for Carrier Frequencies

<For 2.4GHz Band>

Frequency Allocation for 802.11b/g

There are two bandwidth systems for draft n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

<For 5GHz Band>

Frequency Allocation for 802.11a

There are two bandwidth systems for draft n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

<For 2.4GHz Band>

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Max. Peak Conducted Output Power	MCS8/20MHz	13Mbps	1/6/11	A / B / A+B
	MCS8/40MHz	27Mbps	3/6/9	A / B / A+B
	11b/CCK	1 Mbps	1/6/11	A / B / A+B
	11g/BPSK	6 Mbps	1/6/11	A / B / A+B
Power Spectral Density 6dB Spectrum Bandwidth	MCS8/20MHz	13Mbps	1/6/11	A+B
	MCS8/40MHz	27Mbps	3/6/9	A+B
	11b/CCK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	MCS8/20MHz	13Mbps	1/6/11	A+B
	MCS8/40MHz	27Mbps	3/6/9	A+B
	11b/CCK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Band Edge Emissions	MCS8/20MHz	13Mbps	1/11	A+B
	MCS8/40MHz	27Mbps	3/9	A+B
	11b/CCK	1 Mbps	1/11	A
	11g/BPSK	6 Mbps	1/11	A

<For 5GHz Band>

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Max. Peak Conducted Output Power	MCS8/20MHz	13Mbps	149/157/165	A / B / A+B
	MCS8/40MHz	27Mbps	151/159	A / B / A+B
	11a/BPSK	6 Mbps	149/157/165	A / B / A+B
Power Spectral Density 6dB Spectrum Bandwidth	MCS8/20MHz	13Mbps	149/157/165	A+B
	MCS8/40MHz	27Mbps	151/159	A+B
	11a/BPSK	6 Mbps	149/157/165	A
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	MCS8/20MHz	13Mbps	149/157/165	A+B
	MCS8/40MHz	27Mbps	151/159	A+B
	11a/BPSK	6 Mbps	149/157/165	A
Band Edge Emissions	MCS8/20MHz	13Mbps	149/157/165	A+B
	MCS8/40MHz	27Mbps	151/159	A+B
	11a/BPSK	6 Mbps	149/157/165	A

NOTE: All the test modes were illustrated as below.

Test Mode 1: EUT + USB Cable with Cradle

Test Mode 2: EUT

<For Conducted Emissions Test>:

Due to Mode 1 generated the worst test result, so it was recorded in this report.

<For Radiated Emissions Test Below 1GHz>:

Due to Mode 1 generated the worst test result, so it was recorded in this report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	480872	IC 4086	-
CO04-HY	Conduction	Hwa Ya	480872	IC 4086	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
WN8522B-LF-ZZ	All the models are identical, the difference model served as marketing strategy.
WN8522B-LF-FA	

3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	PP25L	E2K4965AGNM
Mouse	iCooky	AMS0706W	DoC
Wireless AP	Planex	GW-AP54SGX	N/A

3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

<For 2.4GHz Band>

Power Parameters of Draft n MCS8 20MHz Ant. A / Ant. B

Test Software Version	DOS		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n 20MHz	13	13	12

Power Parameters of Draft n MCS8 40MHz Ant. A / Ant. B

Test Software Version	DOS		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n 40MHz	11	13	11

Power Parameters of IEEE 802.11b/g Ant. A

Test Software Version	DOS		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	15	15	15
IEEE 802.11g	14	15	15

<For 5GHz Band>

Power Parameters of Draft n MCS8 20MHz Ant. A / Ant. B

Test Software Version	DOS		
Frequency	5745 MHz	5785 MHz	5825 MHz
Draft n 20MHz	11	11	11

Power Parameters of Draft n MCS8 40MHz Ant. A / Ant. B

Test Software Version	DOS	
Frequency	5755 MHz	5795 MHz
Draft n 40MHz	11	11

Power Parameters of IEEE 802.11a Ant. A

Test Software Version	DOS		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	16	16	16

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- Turn on the power of all equipment.
- The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.

During testing, the remote wireless network ancillary were connected by EUT.



At the same time, "DOS" was executed to control the EUT continuously transmit RF signal.

3.10. Test Configurations


3.10.1. Radiation Emissions Test Configuration

Test Configuration: 9kHz~1GHz

Test Mode: Mode 1




Test Configuration: Above 1GHz



3.10.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.



- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

There is no deviation with the original standard.


4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement


<For Test Mode 1>:

Temperature	24°C	Humidity	56%
Test Engineer	Peter Wu	Phase	Line
Configuration	Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.17787	54.26	-10.32	64.58	54.00	0.06	0.20	QP
2	0.17787	41.89	-12.69	54.58	41.63	0.06	0.20	AVERAGE
3	0.23402	32.34	-19.97	52.31	32.09	0.05	0.20	AVERAGE
4	0.23402	45.73	-16.58	62.31	45.48	0.05	0.20	QP
5	0.30188	37.00	-23.19	60.19	36.76	0.04	0.20	QP
6	0.30188	22.96	-27.23	50.19	22.72	0.04	0.20	AVERAGE
7	0.64740	26.54	-19.46	46.00	26.31	0.03	0.20	AVERAGE
8	0.64740	28.91	-27.09	56.00	28.68	0.03	0.20	QP
9	7.872	27.39	-32.61	60.00	26.71	0.28	0.40	QP
10	7.872	23.57	-26.43	50.00	22.89	0.28	0.40	AVERAGE
11	20.924	25.40	-24.60	50.00	24.01	0.89	0.50	AVERAGE
12	20.924	31.21	-28.79	60.00	29.82	0.89	0.50	QP

Temperature	24°C	Humidity	56%
Test Engineer	Peter Wu	Phase	Neutral
Configuration	Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1 @	0.17612	40.23	-14.44	54.67	39.94	0.09	0.20	AVERAGE
2 @	0.17612	53.38	-11.29	64.67	53.09	0.09	0.20	QP
3	0.23409	45.29	-17.02	62.30	45.01	0.08	0.20	QP
4	0.23409	31.19	-21.12	52.30	30.91	0.08	0.20	AVERAGE
5	0.29088	38.04	-22.45	60.50	37.77	0.07	0.20	QP
6	0.29088	23.07	-27.42	50.50	22.80	0.07	0.20	AVERAGE
7	0.35201	21.24	-27.67	48.91	20.97	0.07	0.20	AVERAGE
8	0.35201	34.02	-24.89	58.91	33.75	0.07	0.20	QP
9	7.921	27.05	-32.95	60.00	26.32	0.33	0.40	QP
10	7.921	25.23	-24.77	50.00	24.50	0.33	0.40	AVERAGE
11	20.594	30.24	-29.76	60.00	28.89	0.85	0.50	QP
12	20.594	24.16	-25.84	50.00	22.81	0.85	0.50	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1MHz
VB	3MHz
Detector	RMS
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	60%
Test Engineer	Jacky Ho	Configurations	Draft n

<For 2.4GHz Band>

Configuration Draft n MCS8 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	15.80	30.00	Complies
6	2437 MHz	16.01	30.00	Complies
11	2462 MHz	14.60	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.46	30.00	Complies
6	2437 MHz	16.53	30.00	Complies
11	2462 MHz	15.48	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.15	30.00	Complies
6	2437 MHz	19.29	30.00	Complies
11	2462 MHz	18.07	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	12.56	30.00	Complies
6	2437 MHz	14.25	30.00	Complies
9	2452 MHz	12.62	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	13.44	30.00	Complies
6	2437 MHz	15.46	30.00	Complies
9	2452 MHz	13.53	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	16.03	30.00	Complies
6	2437 MHz	17.91	30.00	Complies
9	2452 MHz	16.11	30.00	Complies

<For 5GHz Band>

Configuration Draft n MCS8 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	9.90	30.00	Complies
157	5785 MHz	10.22	30.00	Complies
165	5825 MHz	10.20	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	11.60	30.00	Complies
157	5785 MHz	11.49	30.00	Complies
165	5825 MHz	11.83	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	13.84	30.00	Complies
157	5785 MHz	13.91	30.00	Complies
165	5825 MHz	14.10	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	9.93	30.00	Complies
159	5795 MHz	10.45	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	11.86	30.00	Complies
159	5795 MHz	12.16	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	14.01	30.00	Complies
159	5795 MHz	14.40	30.00	Complies

Temperature	23°C	Humidity	60%
Test Engineer	Jacky Ho	Configurations	802.11a/b/g

Configuration IEEE 802.11b Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.19	30.00	Complies
6	2437 MHz	16.41	30.00	Complies
11	2462 MHz	16.11	30.00	Complies


Configuration IEEE 802.11g Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.08	30.00	Complies
6	2437 MHz	18.41	30.00	Complies
11	2462 MHz	18.13	30.00	Complies

Configuration IEEE 802.11a Ant. A


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	14.13	30.00	Complies
157	5785 MHz	14.32	30.00	Complies
165	5825 MHz	14.82	30.00	Complies

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 2412 MHz




Date: 12.SEP.2009 08:52:08

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 2437 MHz




Date: 12.SEP.2009 08:57:03

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 2462 MHz




Date: 12.SEP.2009 09:00:25

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. B / 2412 MHz




Date: 12.SEP.2009 08:51:16

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. B / 2437 MHz




Date: 12.SEP.2009 08:55:32

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. B / 2462 MHz




Date: 12.SEP.2009 09:01:28

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 2422 MHz




Date: 12.SEP.2009 09:15:20

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 2437 MHz




Date: 12.SEP.2009 09:09:27

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 2452 MHz




Date: 12.SEP.2009 09:14:08

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. B / 2422 MHz




Date: 12.SEP.2009 09:08:10

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. B / 2437 MHz




Date: 12.SEP.2009 09:10:41

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. B / 2452 MHz




Date: 12.SEP.2009 09:12:40

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. A / 5745 MHz




Date: 14.SEP.2009 14:14:58

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. A / 5785MHz




Date: 14.SEP.2009 14:16:28

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. A / 5825 MHz




Date: 14.SEP.2009 14:21:34

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. B / 5745 MHz




Date: 14.SEP.2009 14:13:17

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. B / 5785MHz




Date: 14.SEP.2009 14:17:30

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. B / 5825 MHz




Date: 14.SEP.2009 14:22:09

Channel Output Power Plot on Configuration 11a Draft n MCS8 40MHz Ant. A / 5755 MHz




Date: 12.SEP.2009 12:49:40

Channel Output Power Plot on Configuration 11a Draft n MCS8 40MHz Ant. A / 5795 MHz




Date: 12.SEP.2009 12:51:29

Channel Output Power Plot on Configuration 11a Draft n MCS8 40MHz Ant. B / 5755 MHz




Date: 12.SEP.2009 12:48:38

Channel Output Power Plot on Configuration 11a Draft n MCS8 40MHz Ant. B / 5795 MHz




Date: 12.SEP.2009 12:52:42

Conducted Output Power Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 12.SEP.2009 08:28:34

Conducted Output Power Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 12.SEP.2009 08:35:02

Conducted Output Power Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 12.SEP.2009 08:36:23

Conducted Output Power Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 12.SEP.2009 08:39:55

Conducted Output Power Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz




Date: 14.SEP.2009 16:42:12

Conducted Output Power Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz




Date: 12.SEP.2009 08:42:03

Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 8.OCT.2009 21:41:24

Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5785 MHz



Date: 8.OCT.2009 21:42:33

Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 8.OCT.2009 21:44:46

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.
5. Measuring multiple antennas, the connector is required to link with spectrum analyser through a combiner.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	60%
Test Engineer	Jacky Ho	Configurations	Draft n

<For 2.4GHz Band>

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm/ 3kHz)	Result
1	2412 MHz	-7.04	8.00	Complies
6	2437 MHz	-6.85	8.00	Complies
11	2462 MHz	-8.22	8.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
3	2422 MHz	-11.53	8.00	Complies
6	2437 MHz	-10.72	8.00	Complies
9	2452 MHz	-11.02	8.00	Complies

<For 5GHz Band>

Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
149	5745 MHz	-10.61	8.00	Complies
157	5785 MHz	-10.53	8.00	Complies
165	5825 MHz	-10.43	8.00	Complies

Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
151	5755 MHz	-12.08	8.00	Complies
159	5795 MHz	-10.96	8.00	Complies

Temperature	23°C	Humidity	60%
Test Engineer	Jacky Ho	Configurations	802.11a/b/g

Configuration IEEE 802.11b Ant. A

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
1	2412 MHz	-6.40	8.00	Complies
6	2437 MHz	-6.26	8.00	Complies
11	2462 MHz	-6.26	8.00	Complies


Configuration IEEE 802.11g Ant. A

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
1	2412 MHz	-9.05	8.00	Complies
6	2437 MHz	-8.17	8.00	Complies
11	2462 MHz	-8.36	8.00	Complies

Configuration IEEE 802.11a Ant. A


Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
149	5745 MHz	-11.63	8.00	Complies
157	5785 MHz	-11.53	8.00	Complies
165	5825 MHz	-10.02	8.00	Complies

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2412 MHz




Date: 12.SEP.2009 13:14:27

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2437 MHz




Date: 12.SEP.2009 13:17:16

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2462 MHz




Date: 12.SEP.2009 13:19:32

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2422 MHz




Date: 12.SEP.2009 13:40:36

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2437 MHz




Date: 12.SEP.2009 13:38:28

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2452 MHz




Date: 12.SEP.2009 13:42:26

Power Density Plot on Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B / 5745 MHz




Date: 14.SEP.2009 14:29:26

Power Density Plot on Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B / 5785 MHz




Date: 14.SEP.2009 14:34:39

Power Density Plot on Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B / 5825 MHz




Date: 14.SEP.2009 14:36:29

Power Density Plot on Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B / 5755 MHz




Date: 12.SEP.2009 14:22:10

Power Density Plot on Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B / 5795 MHz




Date: 12.SEP.2009 14:19:57

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 12.SEP.2009 08:32:08

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 12.SEP.2009 12:56:55

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 12.SEP.2009 12:59:08

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 14.SEP.2009 16:46:52

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz




Date: 12.SEP.2009 13:07:21

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz




Date: 12.SEP.2009 13:09:32

Power Density Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 8.OCT.2009 21:52:42

Power Density Plot on Configuration IEEE 802.11a Ant. A / 5785 MHz



Date: 8.OCT.2009 21:50:19

Power Density Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 8.OCT.2009 21:48:05

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	60%
Test Engineer	Jacky Ho	Configurations	Draft n
Test Date	Oct. 08, 2009		

<For 2.4GHz Band>

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.60	17.68	500	Complies
6	2437 MHz	17.60	17.68	500	Complies
11	2462 MHz	17.32	17.68	500	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.52	36.08	500	Complies
6	2437 MHz	35.52	36.08	500	Complies
9	2452 MHz	35.36	36.16	500	Complies

<For 5GHz Band>

Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.60	17.68	500	Complies
157	5785 MHz	17.56	17.68	500	Complies
165	5825 MHz	17.60	17.68	500	Complies

Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.36	36.16	500	Complies
159	5795 MHz	34.88	36.16	500	Complies

Temperature	23°C	Humidity	60%
Test Engineer	Jacky Ho	Configurations	802.11a/b/g
Test Date	Oct. 08, 2009		

Configuration IEEE 802.11b Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.08	13.12	500	Complies
6	2437 MHz	10.16	13.28	500	Complies
11	2462 MHz	10.16	13.16	500	Complies


Configuration IEEE 802.11g Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	16.52	500	Complies
6	2437 MHz	16.40	16.52	500	Complies
11	2462 MHz	16.40	16.48	500	Complies

Configuration IEEE 802.11a Ant. A


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.48	16.56	500	Complies
157	5785 MHz	16.40	16.56	500	Complies
165	5825 MHz	16.40	16.60	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A+ Ant. B / 2412 MHz




Date: 12.SEP.2009 13:13:00

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A+ Ant. B / 2437 MHz




Date: 12.SEP.2009 13:15:19

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A+ Ant. B / 2462 MHz




Date: 12.SEP.2009 13:18:04

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A+ Ant. B / 2422 MHz




Date: 12.SEP.2009 13:21:47

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A+ Ant. B / 2437 MHz




Date: 12.SEP.2009 13:24:13

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A+ Ant. B / 2452 MHz




Date: 12.SEP.2009 13:30:20

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5745 MHz




Date: 12.SEP.2009 14:24:43

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5785MHz




Date: 12.SEP.2009 14:26:55

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5825 MHz




Date: 12.SEP.2009 14:31:03

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B / 5755MHz




Date: 12.SEP.2009 14:14:13

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B / 5795 MHz




Date: 12.SEP.2009 14:18:17

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 12.SEP.2009 08:30:41

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 12.SEP.2009 12:55:27

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 12.SEP.2009 12:57:41

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 12.SEP.2009 16:28:17

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz




Date: 12.SEP.2009 13:05:52

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz




Date: 12.SEP.2009 13:08:05

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 8.OCT.2009 21:51:14

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5785 MHz



Date: 8.OCT.2009 21:48:52

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 8.OCT.2009 21:46:37

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)

<For Test Mode 1>:


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Normal Link / Mode 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	172.590	35.44	-8.06	43.50	48.14	12.97	1.56	27.23	Peak	100	0	HORIZONTAL
2 @	276.380	32.59	-13.41	46.00	44.45	13.08	2.01	26.95	Peak	100	0	HORIZONTAL
3 @	342.340	33.89	-12.11	46.00	44.39	14.51	2.18	27.20	Peak	100	0	HORIZONTAL
4 @	416.060	35.27	-10.73	46.00	44.24	16.32	2.40	27.68	Peak	100	0	HORIZONTAL
5 @	696.390	37.93	-8.07	46.00	43.54	19.08	3.32	28.00	Peak	100	0	HORIZONTAL
6 @	901.060	41.42	-4.58	46.00	44.68	20.54	3.60	27.39	QP	100	236	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	31.940	28.50	-11.50	40.00	38.11	17.69	0.50	27.80	Peak	400	0	VERTICAL
2 @	98.870	34.96	-8.54	43.50	50.59	10.79	1.18	27.61	Peak	400	0	VERTICAL
3 @	164.830	36.41	-7.09	43.50	49.77	12.39	1.52	27.27	Peak	400	0	VERTICAL
4 @	172.590	36.33	-7.17	43.50	49.03	12.97	1.56	27.23	Peak	100	124	VERTICAL
5 @	696.390	37.72	-8.28	46.00	43.33	19.08	3.32	28.00	Peak	400	0	VERTICAL
6 @	897.180	38.15	-7.85	46.00	41.46	20.51	3.59	27.41	Peak	400	0	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 20MHz Ch 1 / Ant. A+ Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4823.992	36.52	-17.48	54.00	36.33	32.46	3.00	35.26	AVERAGE	100	351	HORIZONTAL
2	4823.993	49.25	-24.75	74.00	49.06	32.46	3.00	35.26	PEAK	100	351	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4823.975	34.64	-19.36	54.00	34.44	32.46	3.00	35.26	AVERAGE	100	101	VERTICAL
2	4824.000	47.95	-26.05	74.00	47.75	32.46	3.00	35.26	PEAK	100	101	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 20MHz Ch 6 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.979	46.12	-27.88	74.00	45.69	32.56	3.01	35.15	PEAK	100	135	HORIZONTAL
2	4874.025	33.51	-20.49	54.00	33.08	32.56	3.01	35.15	AVERAGE	100	135	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.992	47.43	-26.57	74.00	47.00	32.56	3.01	35.15	PEAK	100	61	VERTICAL
2	4874.008	33.02	-20.98	54.00	32.59	32.56	3.01	35.15	AVERAGE	100	61	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 20MHz Ch11 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4923.975	35.67	-18.33	54.00	35.02	32.66	3.02	35.03	AVERAGE	100	349	HORIZONTAL
2	4924.022	49.96	-24.04	74.00	49.30	32.66	3.02	35.03	PEAK	100	349	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4923.994	46.06	-27.94	74.00	45.40	32.66	3.02	35.03	100	287	VERTICAL
2	4924.025	33.98	-20.02	54.00	33.32	32.66	3.02	35.03	100	287	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 40MHz Ch 3 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4843.992	32.25	-21.75	54.00	31.95	32.49	3.01	35.20	AVERAGE	100	31	HORIZONTAL
2	4844.003	49.15	-24.85	74.00	48.86	32.49	3.01	35.20	PEAK	100	31	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4843.992	32.69	-21.31	54.00	32.39	32.49	3.01	35.20	AVERAGE	100	103	VERTICAL
2	4844.022	49.13	-24.87	74.00	48.84	32.49	3.01	35.20	PEAK	100	103	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 40MHz Ch 6 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.979	44.61	-29.39	74.00	44.19	32.56	3.01	35.15	PEAK	100	88	HORIZONTAL
2	4874.008	32.64	-21.36	54.00	32.21	32.56	3.01	35.15	AVERAGE	100	88	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.992	32.33	-21.67	54.00	31.91	32.56	3.01	35.15	AVERAGE	100	178	VERTICAL
2	4874.008	44.66	-29.34	74.00	44.23	32.56	3.01	35.15	PEAK	100	178	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 40MHz Ch 9 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4903.975	31.91	-22.09	54.00	31.35	32.63	3.02	35.09	AVERAGE	100	224	HORIZONTAL
2	4903.990	43.62	-30.38	74.00	43.06	32.63	3.02	35.09	PEAK	100	224	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4903.992	32.93	-21.07	54.00	32.37	32.63	3.02	35.09	AVERAGE	100	111	VERTICAL
2	4903.998	48.64	-25.36	74.00	48.08	32.63	3.02	35.09	PEAK	100	111	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	11a Draft n MCS8 20MHz CH 149 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11490.020	50.50	-29.50	80.00	41.98	38.50	4.76	34.75	PEAK	100	162	HORIZONTAL
2	11490.030	38.20	-21.80	60.00	29.68	38.50	4.76	34.75	AVERAGE	100	162	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11489.970	37.02	-22.98	60.00	28.51	38.50	4.76	34.75	AVERAGE	4185	255	VERTICAL
2	11490.010	50.65	-29.35	80.00	42.14	38.50	4.76	34.75	PEAK	100	255	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	11a Draft n MCS8 20MHz CH 157 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11569.990	50.26	-29.74	80.00	41.66	38.51	4.91	34.82	PEAK	100	162	HORIZONTAL
2	11570.030	38.38	-21.62	60.00	29.78	38.51	4.91	34.82	AVERAGE	100	162	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11570.010	51.00	-29.00	80.00	42.40	38.51	4.91	34.82	PEAK	100	107	VERTICAL
2	11570.030	37.21	-22.79	60.00	28.61	38.51	4.91	34.82	AVERAGE	100	107	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	11a Draft n MCS8 20MHz CH 165 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11650.000	51.68	-28.32	80.00	43.02	38.53	5.03	34.90	PEAK	100	156	HORIZONTAL
2	11650.030	38.25	-21.75	60.00	29.59	38.53	5.03	34.90	AVERAGE	100	156	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11649.990	38.14	-21.86	60.00	29.48	38.53	5.03	34.90	AVERAGE	100	228	VERTICAL
2	11649.990	51.27	-28.73	80.00	42.60	38.53	5.03	34.90	PEAK	100	228	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	11a Draft n MCS8 40MHz CH 151 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11510.020	51.54	-28.46	80.00	43.01	38.50	4.78	34.75	PEAK	100	261	HORIZONTAL
2	11510.030	37.65	-22.35	60.00	29.12	38.50	4.78	34.75	AVERAGE	100	261	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11510.020	49.87	-30.13	80.00	41.34	38.50	4.78	34.75	PEAK	100	79	VERTICAL
2	11510.030	36.62	-23.38	60.00	28.09	38.50	4.78	34.75	AVERAGE	100	79	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	11a Draft n MCS8 40MHz CH 159 / Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11589.990	51.48	-28.52	80.00	42.87	38.52	4.91	34.82	PEAK	100	127	HORIZONTAL
2	11590.030	38.05	-21.95	60.00	29.44	38.52	4.91	34.82	AVERAGE	100	127	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11590.010	38.01	-21.99	60.00	29.41	38.52	4.91	34.82	AVERAGE	100	30	VERTICAL
2	11590.010	51.54	-28.46	80.00	42.94	38.52	4.91	34.82	PEAK	100	30	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11b CH 1 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	4823.980	50.86	-3.14	54.00	50.66	32.46	3.00	35.26	AVERAGE	134	26	HORIZONTAL
2	4824.036	53.86	-20.14	74.00	53.67	32.46	3.00	35.26	PEAK	134	26	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4823.960	47.02	-6.98	54.00	46.82	32.46	3.00	35.26	AVERAGE	104	109	VERTICAL
2	4824.044	51.02	-22.98	74.00	50.83	32.46	3.00	35.26	PEAK	104	109	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11b CH 6 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.952	51.82	-22.18	74.00	51.40	32.56	3.01	35.15	PEAK	138	30	HORIZONTAL
2	4874.000	48.29	-5.71	54.00	47.86	32.56	3.01	35.15	AVERAGE	138	30	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.900	49.60	-24.40	74.00	49.17	32.56	3.01	35.15	PEAK	100	108	VERTICAL
2	4874.040	44.94	-9.06	54.00	44.52	32.56	3.01	35.15	AVERAGE	100	108	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11b CH 11 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4923.912	51.37	-22.63	74.00	50.71	32.66	3.02	35.03	PEAK	133	29	HORIZONTAL
2	4924.000	47.35	-6.65	54.00	46.70	32.66	3.02	35.03	AVERAGE	133	29	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4923.952	50.29	-23.71	74.00	49.63	32.66	3.02	35.03	PEAK	102	74	VERTICAL
2	4923.960	45.55	-8.45	54.00	44.90	32.66	3.02	35.03	AVERAGE	102	74	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11g CH 1 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4823.980	46.19	-27.81	74.00	45.99	32.46	3.00	35.26	PEAK	100	76	HORIZONTAL
2	4823.999	33.66	-20.34	54.00	33.46	32.46	3.00	35.26	AVERAGE	100	76	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4824.024	48.51	-25.49	74.00	48.31	32.46	3.00	35.26	PEAK	100	110	VERTICAL
2	4824.025	33.68	-20.32	54.00	33.48	32.46	3.00	35.26	AVERAGE	100	110	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11g CH 6 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Preamp Loss Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	4874.000	48.27	-25.73	74.00	47.85	32.56	3.01 35.15	100	360	HORIZONTAL
2	4874.008	33.58	-20.42	54.00	33.15	32.56	3.01 35.15	100	360	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.992	49.82	-24.18	74.00	49.39	32.56	3.01	35.15	PEAK	100	110	VERTICAL
2	4874.008	34.91	-19.09	54.00	34.49	32.56	3.01	35.15	AVERAGE	100	110	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11g CH 11 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4924.018	49.00	-25.00	74.00	48.35	32.66	3.02	35.03	PEAK	100	360	HORIZONTAL
2	4924.025	35.22	-18.78	54.00	34.57	32.66	3.02	35.03	AVERAGE	100	360	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4924.008	35.35	-18.65	54.00	34.69	32.66	3.02	35.03	AVERAGE	100	277	VERTICAL
2	4924.016	47.71	-26.29	74.00	47.05	32.66	3.02	35.03	PEAK	100	277	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11a CH 149 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11490.020	64.19	-15.81	80.00	55.68	38.50	4.76	34.75	PEAK	100	167	HORIZONTAL
2	11490.030	49.80	-10.20	60.00	41.29	38.50	4.76	34.75	AVERAGE	100	167	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	11490.020	71.39	-8.61	80.00	62.88	38.50	4.76	34.75	PEAK	100	51	VERTICAL
2 @	11490.030	55.90	-4.10	60.00	47.38	38.50	4.76	34.75	AVERAGE	100	51	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11a CH 157 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11570.010	50.11	-9.89	60.00	41.51	38.51	4.91	34.82	AVERAGE	100	31	HORIZONTAL
2	11570.010	64.73	-15.27	80.00	56.13	38.51	4.91	34.82	PEAK	100	31	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	11569.990	56.76	-3.24	60.00	48.17	38.51	4.91	34.82	AVERAGE	100	61	VERTICAL
2 @	11570.020	70.45	-9.55	80.00	61.85	38.51	4.91	34.82	PEAK	100	61	VERTICAL


Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11a CH 165 / Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBUV	dB/m	dB	dB		cm	deg	
1	11650.010	65.23	-14.77	80.00	56.56	38.53	5.03	34.90	PEAK	100	245	HORIZONTAL
2 @	11650.030	50.45	-9.55	60.00	41.78	38.53	5.03	34.90	AVERAGE	100	245	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11649.980	66.00	-14.00	80.00	57.34	38.53	5.03	34.90	PEAK	100	358	VERTICAL
2 @	11650.030	54.19	-5.81	60.00	45.52	38.53	5.03	34.90	AVERAGE	100	358	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
- In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 20MHz Ch 1, 6, 11 / Ant. A + Ant. B
Test date	Sep. 10, 2009		

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2389.800	67.52	-6.48	74.00	37.60	27.87	2.05	0.00	PEAK	100	28	VERTICAL
2 !	2390.000	52.22	-1.78	54.00	22.30	27.87	2.05	0.00	AVERAGE	100	28	VERTICAL
3 @	2414.600	97.54			67.65	27.84	2.05	0.00	AVERAGE	100	28	VERTICAL
4 @	2414.800	110.08			80.19	27.84	2.05	0.00	PEAK	100	28	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2389.000	57.65	-16.35	74.00	27.75	27.87	2.04	0.00	PEAK	100	334	VERTICAL
2	2390.000	45.54	-8.46	54.00	15.62	27.87	2.05	0.00	AVERAGE	100	334	VERTICAL
3 @	2434.000	97.82			67.94	27.81	2.07	0.00	AVERAGE	100	334	VERTICAL
4 @	2444.000	111.28			81.42	27.78	2.08	0.00	PEAK	100	334	VERTICAL
5	2483.500	44.75	-9.25	54.00	14.93	27.73	2.10	0.00	AVERAGE	100	334	VERTICAL
6	2483.500	55.74	-18.26	74.00	25.92	27.73	2.10	0.00	PEAK	100	334	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2458.600	111.02			81.18	27.76	2.08	0.00	PEAK	100	37	VERTICAL
2 @	2458.600	97.63			67.80	27.76	2.08	0.00	AVERAGE	100	37	VERTICAL
3 !	2483.500	52.97	-1.03	54.00	23.15	27.73	2.10	0.00	AVERAGE	100	37	VERTICAL
4 !	2483.900	68.10	-5.90	74.00	38.28	27.73	2.10	0.00	PEAK	100	37	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	Draft n MCS8 40MHz Ch 3, 6, 9 / Ant. A + Ant. B
Test date	Sep. 10, 2009		

Channel 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	2386.400	69.02	-4.98	74.00	39.11	27.87	2.04	0.00 PEAK	100	333	VERTICAL
2 !	2390.000	52.59	-1.41	54.00	22.67	27.87	2.05	0.00 AVERAGE	100	333	VERTICAL
3	2405.200	88.10			58.20	27.84	2.05	0.00 AVERAGE	100	333	VERTICAL
4	2427.200	105.81			75.94	27.81	2.07	0.00 PEAK	100	333	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2390.000	64.13	-9.87	74.00	34.21	27.87	2.05	0.00 PEAK	100	35	VERTICAL
2 !	2390.000	48.24	-5.76	54.00	18.32	27.87	2.05	0.00 AVERAGE	100	35	VERTICAL
3 @	2451.000	90.28			60.41	27.78	2.08	0.00 AVERAGE	100	35	VERTICAL
4	2453.400	107.98			78.11	27.78	2.08	0.00 PEAK	100	35	VERTICAL
5 !	2483.500	49.78	-4.22	54.00	19.96	27.73	2.10	0.00 AVERAGE	100	35	VERTICAL
6	2485.100	65.06	-8.94	74.00	35.23	27.73	2.10	0.00 PEAK	100	35	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2456.000	89.56			59.73	27.76	2.08	0.00 AVERAGE	100	35	VERTICAL
2	2457.200	107.73			77.90	27.76	2.08	0.00 PEAK	100	35	VERTICAL
3 !	2483.500	53.63	-0.37	54.00	23.81	27.73	2.10	0.00 AVERAGE	100	35	VERTICAL
4	2485.900	66.47	-7.53	74.00	36.64	27.73	2.10	0.00 PEAK	100	35	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11b CH 1, 6, 11 / Ant. A
Test Date	Sep. 09, 2009		

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	2389.200	49.71	-4.29	54.00	19.80	27.87	2.04	0.00 AVERAGE	100	29	VERTICAL
2	2389.600	59.88	-14.12	74.00	29.97	27.87	2.04	0.00 PEAK	100	29	VERTICAL
3	2414.600	109.13			79.24	27.84	2.05	0.00 PEAK	100	29	VERTICAL
4 @	2414.600	105.46			75.57	27.84	2.05	0.00 AVERAGE	100	29	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2389.400	57.22	-16.78	74.00	27.32	27.87	2.04	0.00 PEAK	100	30	VERTICAL
2	2390.000	45.84	-8.16	54.00	15.92	27.87	2.05	0.00 AVERAGE	100	30	VERTICAL
3 @	2439.800	105.17			75.32	27.78	2.07	0.00 AVERAGE	100	30	VERTICAL
4	2440.600	108.74			78.89	27.78	2.07	0.00 PEAK	100	30	VERTICAL
5	2483.500	46.14	-7.86	54.00	16.32	27.73	2.10	0.00 AVERAGE	100	30	VERTICAL
6	2483.700	57.58	-16.42	74.00	27.76	27.73	2.10	0.00 PEAK	100	30	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2464.800	106.26			76.42	27.76	2.08	0.00 AVERAGE	100	33	VERTICAL
2 @	2465.800	109.61			79.77	27.76	2.08	0.00 PEAK	100	33	VERTICAL
3 !	2483.500	49.82	-4.18	54.00	19.99	27.73	2.10	0.00 AVERAGE	100	33	VERTICAL
4	2483.500	60.80	-13.20	74.00	30.98	27.73	2.10	0.00 PEAK	100	33	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	54%
Test Engineer	Allen Liu	Configurations	802.11g CH 1, 6, 11 / Ant. A
Test Date	Sep. 10, 2009		

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	2390.000	52.22	-1.78	54.00	22.30	27.87	2.05	0.00	AVERAGE	100	30	VERTICAL
2 !	2390.000	68.83	-5.17	74.00	38.91	27.87	2.05	0.00	PEAK	100	30	VERTICAL
3	2409.000	96.18			66.29	27.84	2.05	0.00	AVERAGE	100	30	VERTICAL
4 @	2414.800	111.79			81.90	27.84	2.05	0.00	PEAK	100	30	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2389.200	55.43	-18.57	74.00	25.52	27.87	2.04	0.00	PEAK	100	33	VERTICAL
2	2390.000	45.55	-8.45	54.00	15.63	27.87	2.05	0.00	AVERAGE	100	33	VERTICAL
3 @	2438.400	96.84			66.99	27.78	2.07	0.00	AVERAGE	100	33	VERTICAL
4 @	2442.000	112.10			82.23	27.78	2.08	0.00	PEAK	100	33	VERTICAL
5	2483.500	46.61	-7.39	54.00	16.79	27.73	2.10	0.00	AVERAGE	100	33	VERTICAL
6	2484.100	57.30	-16.70	74.00	27.48	27.73	2.10	0.00	PEAK	100	33	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.


Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2465.400	111.13			81.29	27.76	2.08	0.00	PEAK	100	327	VERTICAL
2 @	2466.200	97.57			67.73	27.76	2.08	0.00	AVERAGE	100	327	VERTICAL
3 !	2483.500	53.68	-0.32	54.00	23.86	27.73	2.10	0.00	AVERAGE	100	327	VERTICAL
4 !	2483.500	70.89	-3.11	74.00	41.07	27.73	2.10	0.00	PEAK	100	327	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2412 MHz




Date: 12.SEP.2009 13:14:36

High Band Edge Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2462 MHz




Date: 12.SEP.2009 13:19:40

Low Band Edge Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2422 MHz




Date: 12.SEP.2009 13:23:23

High Band Edge Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2452 MHz




Date: 12.SEP.2009 16:34:57

Low Band Edge Plot on Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B / 5745 MHz




Date: 12.SEP.2009 14:26:19

High Band Edge Plot on Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B / 5825 MHz




Date: 12.SEP.2009 14:32:38

Low Band Edge Plot on Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B / 5755 MHz



Date: 12.SEP.2009 14:15:49


High Band Edge Plot on Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B / 5795 MHz



Date: 12.SEP.2009 14:17:59


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 12.SEP.2009 08:32:17

High Band Edge Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 12.SEP.2009 12:59:16

Low Band Edge Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 12.SEP.2009 13:04:42

High Band Edge Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz




Date: 12.SEP.2009 13:09:40

Low Band Edge Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz



Date: 8.OCT.2009 21:52:50

High Band Edge Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 8.OCT.2009 21:48:12

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Apr. 15, 2009	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 23, 2009	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2009	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2009	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Jun. 11, 2009	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 07, 2009	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 23, 2009	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2009	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Apr. 06, 2009*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100305	9 kHz - 40 GHz	Feb. 03, 2009	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Sep. 26, 2009	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 28, 2009	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.16, 2009	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Oct. 28, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 31, 2009	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 30GHz	Aug. 05, 2009	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 31, 2009	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 12, 2009*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2009	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Aug. 06, 2009	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2008	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Feb. 13, 2009	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 25, 2009	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

* Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihsu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-091230

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : December 30, 2009

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix