



RADIO EXPOSURE TEST REPORT

FCC ID : RAXAIOS7

Equipment : HEOS 7.0 Platform Module, HEOS 7.0 Platform Module
Type DH

Brand Name : Arcadyan

Model Name : WN9722OAX22-DM (AIOS7.0), WN9722HAX22-DM
(AIOS7.0-DH)

Applicant : Arcadyan Technology Corporation
No.8, Sec.2, Guangfu Rd., Hsinchu, 30071 Taiwan

Manufacturer : Arcadyan Technology Corporation
No.8, Sec.2, Guangfu Rd., Hsinchu, 30071 Taiwan

Standard : 47 CFR Part 2.1091

The product was received on Feb. 02, 2023, and testing was started from Feb. 10, 2023 and completed on Jun. 26, 2025. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Antenna Information	6
1.3 Table for EUT Information	8
1.4 Source Table	8
1.5 Table for Permissive Change	9
1.6 Accessories	9
1.7 Applicable Standards	9
1.8 Testing Location	9
2 Maximum Permissible Exposure	10
2.1 Limit of Maximum Permissible Exposure	10
2.2 MPE Calculation Method	10
2.3 MPE Exemption	11
2.4 Calculated Result and Limit	12
Appendix A. Photographs of EUT	



History of this test report

TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A1_1 Ver1.1

Page Number : 3 of 14
Issued Date : Jul. 17, 2025
Report Version : 01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen

Report Producer: Vicky Huang



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
6GHz WLAN	5925-7125	5955-7115	802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: GFSK

1.2 Antenna Information

Set	Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)			
							2.4GHz	5GHz	6GHz	Bluetooth
1	1	1	WIESON	ARY196-0383-005-00	Dipole Antenna	I-PEX	-	-	-	2.1
	2	1	WIESON	ARY196-0383-006-00	Dipole Antenna	I-PEX	2.2	2.7	2.8	-
	3	2	WIESON	ARY196-0383-007-00	Dipole Antenna	I-PEX	1.7	1.6	1.7	-
2	1	1	WIESON	ARY196-0383-008-00	Dipole Antenna	I-PEX	-	-	-	1.7
	2	1	WIESON	ARY196-0383-009-00	Dipole Antenna	I-PEX	2.0	2.2	2.3	-
	3	2	WIESON	ARY196-0383-010-00	Dipole Antenna	I-PEX	1.1	1.0	0.9	-
3	1	1	WIESON	ARY196-0383-034-H0	PCB Antenna	I-PEX	-	-	-	2.84
	2	1	WIESON	ARY196-0383-035-H0	PCB Antenna	I-PEX	2.8	3.82	4.16	-
	3	2	WIESON	ARY196-0383-036-H0	PCB Antenna	I-PEX	2.66	3.78	4.23	-
4	1	1	WIESON	ARY196-0383-039-H0	PCB Antenna	I-PEX	-	-	-	2.75
	2	1	WIESON	ARY196-0383-037-H0	PCB Antenna	I-PEX	2.14	2.18	2.26	-
	3	2	WIESON	ARY196-0383-038-H0	PCB Antenna	I-PEX	2.54	3.38	3.75	-
5	1	1	WIESON	ARY196-0383-042-H0	PCB Antenna	I-PEX	-	-	-	1.82
	2	1	WIESON	ARY196-0383-040-H0	PCB Antenna	I-PEX	1.97	1.9	2.46	-
	3	2	WIESON	ARY196-0383-041-H0	PCB Antenna	I-PEX	1.15	2.85	3.5	-
6	1	1	INPAQ	WA-P-LA-01-106	PCB Antenna	I-PEX	-	-	-	2.98
	2	1	INPAQ	WA-P-LE-03-039	PCB Antenna	I-PEX	2.74	3.42	3.67	-
	3	2	INPAQ	WA-P-LE-02-353	PCB Antenna	I-PEX	4.78	5.45	4.64	-

7	1	1	INPAQ	WA-P-LA-01-107	PCB Antenna	I-PEX	-	-	-	3.4
	2	1	INPAQ	WA-P-LE-02-378	PCB Antenna	I-PEX	3.36	2.39	2.62	-
	3	2	INPAQ	WA-P-LE-03-041	PCB Antenna	I-PEX	2.53	5.87	4.69	-
8	1	1	INPAQ	WA-P-LA-01-108	PCB Antenna	I-PEX	-	-	-	3.04
	2	1	INPAQ	WA-P-LE-02-380	PCB Antenna	I-PEX	5.46	5.75	7.1	-
	3	2	INPAQ	WA-P-LE-03-042	PCB Antenna	I-PEX	5.41	6.09	6.67	-

Note1: The above information was declared by manufacturer.

Note2: The EUT has eight sets of antennas and there are three antennas for each set.

For EUT 1~2:

Set 1~2 are the same type antenna.

Only the highest gain Set 1 antenna was selected to test and record in original report.

For EUT 3:

Set 3~8 are the same type antenna.

Only the highest gain Set 8 antenna for WLAN and Set 7 antenna for Bluetooth was selected to test and record in this report.

Note3: Directional gain information

Type	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left(\sum_{k=1}^{N_{ANT}} g_{j,k} \right)^2}{N_{ANT}} \right]$
BF	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left(\sum_{k=1}^{N_{ANT}} g_{j,k} \right)^2}{N_{ANT}} \right]$	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left(\sum_{k=1}^{N_{ANT}} g_{j,k} \right)^2}{N_{ANT}} \right]$

Ex.

Directional Gain (NSS1) formula :

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left(\sum_{k=1}^{N_{ANT}} g_{j,k} \right)^2}{N_{ANT}} \right]$$

$$NSS1(g1,1) = 10^{G1/20} ; NSS1(g1,2) = 10^{G2/20} ; NSS1(g1,3) = 10^{G3/20} ; NSS1(g1,4) = 10^{G4/20}$$

$$g_{j,k} = (NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2$$

$$DG = 10 \log[(NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2 / N_{ANT}] \Rightarrow 10$$

$$\log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / N_{ANT}]$$

Where ;

For Set 1~2:

$$2.4G \ G1= 2.2 \text{ dBi}; G2= 1.7 \text{ dBi}; DG= 4.96\text{dBi}$$

$$5G \ G1= 2.7 \text{ dBi}; G2= 1.6 \text{ dBi}; DG= 5.18\text{dBi}$$

$$6G \ G1= 2.8 \text{ dBi}; G2= 1.7 \text{ dBi}; DG= 5.28\text{dBi}$$

For Set 3~8:

$$2.4G \ G1= 5.46 \text{ dBi}; G2= 5.41 \text{ dBi}; DG = 8.45 \text{ dBi}$$

$$5G \ G1 = 5.75 \text{ dBi}; G2 = 6.09 \text{ dBi}; DG = 8.93 \text{ dBi}$$



For 2.4GHz function:

For IEEE 802.11b/g/n/VHT/ax (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11a/n/ac/ax (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

For 6GHz function:

For IEEE 802.11ax (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

For Bluetooth function (1TX/1RX):

Only Port 1 can be used as transmitting/receiving antenna.

1.3 Table for EUT Information

The EUTs are identical to each other in all aspects except for the following table:

EUT	Equipment Name	Model Name	GPIO Source	The Material of the Shielded Case	Set Ant.
1	HEOS 7.0 Platform Module	WN9722OAX22-DM (AIO57.0)	Main	Tinplate	1~2
2				Stainless steel	1~2
3	HEOS 7.0 Platform Module Type DH	WN9722HAX22-DM (AIO57.0-DH)	Second	Stainless steel	3~8

Note1: From the above, EUT 1 and EUT 3 was selected as representative model for the test and its data was recorded in this report.

Note2: The above information was declared by manufacturer.

1.4 Source Table

Item \ Source	Main	Second
GPIO	-	Disconnect one of its GPIO6 pins and route GPIO3 to the pin out instead, with corresponding changes made to the layout.

Note: The above information was declared by manufacturer.



1.5 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA320110

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Adding the EUT 2 (Please refer to section 1.3 for detailed information)	After evaluating, it does not affect the test.
2. Adding the EUT 3 (Equipment Name: HEOS 7.0 Platform Module Type DH / Model Name: WN9722HAX22-DM (AIO57.0-DH)) (Please refer to section 1.3 for detailed information)	MPE
3. Adding the Set 3~8 antenna for EUT 3 use (Please refer to section 1.2 and section 1.3 for detailed information)	

Note: Other test results are based on original test report.

1.6 Accessories

N/A

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
 - ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- ♦ 47 CFR Part 1.1307
 - ♦ 47 CFR Part 1.1310

1.8 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065 FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISCED.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= P_{th}.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	



2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For EUT 1:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option
2.4G;D1D	2.20	19.50	21.70	0.50	22.20	20	0.03302	1.00000	B
5.2G;D1D	2.70	17.68	20.38	0.50	20.88	20	0.02436	1.00000	B
5.3G;D1D	2.70	17.62	20.32	0.50	20.82	20	0.02403	1.00000	B
5.6G;D1D	2.70	18.67	21.37	0.50	21.87	20	0.03060	1.00000	B
5.8G;D1D	2.70	18.69	21.39	0.50	21.89	20	0.03074	1.00000	B
6.2G;D1D	2.80	11.41	14.21	0.50	14.71	20	0.00588	1.00000	C
6.4G;D1D	2.80	10.97	13.77	0.50	14.27	20	0.00532	1.00000	C
6.7G;D1D	2.80	11.32	14.12	0.50	14.62	20	0.00576	1.00000	C
7.0G;D1D	2.80	11.39	14.19	0.50	14.69	20	0.00586	1.00000	C
2.4G;BT-BR	2.10	9.41	11.51	0.50	12.01	20	0.00316	1.00000	B
2.4G;BT-LE	2.10	18.94	21.04	0.50	21.54	20	0.02836	1.00000	B

For EUT 3:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option
2.4G;D1D	5.46	19.17	24.63	0.5	25.13	20	0.06493	1.0000	B
5.2G;D1D	6.09	17.68	23.77	0.5	24.27	20	0.05326	1.0000	B
5.3G;D1D	6.09	17.62	23.71	0.5	24.21	20	0.05253	1.0000	B
5.6G;D1D	6.09	18.67	24.76	0.5	25.26	20	0.06690	1.0000	B
5.8G;D1D	6.09	18.69	24.78	0.5	25.28	20	0.06721	1.0000	B
6.2G;D1D	7.10	-	14.02	0.5	14.52	20	0.02248	1.0000	C
6.4G;D1D	7.10	-	13.66	0.5	14.16	20	0.02069	1.0000	C
6.7G;D1D	7.10	-	13.83	0.5	14.33	20	0.02152	1.0000	C
7.0G;D1D	7.10	-	13.89	0.5	14.39	20	0.02182	1.0000	C
2.4G;BT-BR	3.4	9.41	12.81	0.5	13.31	20	0.00427	1.0000	B
2.4G;BT-LE	3.4	18.94	22.34	0.5	22.84	20	0.03832	1.0000	B

**Simultaneous Transmission Analysis Mode: EUT 1-WLAN 2.4GHz+Bluetooth**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
2.4G;D1D	2.20	19.50	21.70	0.50	22.20	20	0.03302	1.00000	B	37.006	0.0331
2.4G;BT-LE	2.10	18.94	21.04	0.50	21.54	20	0.02836	1.00000	B	37.006	0.0284
Sum TL Ratio_B	0.0615										
Ratio Limit	1										

Simultaneous Transmission Analysis Mode: EUT 1-WLAN 5GHz+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.8G;D1D	2.70	18.69	21.39	0.50	21.89	20	0.03074	1.00000	B	37.006	0.0308
2.4G;BT-LE	2.10	18.94	21.04	0.50	21.54	20	0.02836	1.00000	B	37.006	0.0284
Sum TL Ratio_B	0.0592										
Ratio Limit	1										

Simultaneous Transmission Analysis Mode: EUT 1-WLAN 6GHz+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
6.2G;D1D	2.80	11.41	14.21	0.50	14.71	20	0.00588	1.00000	C	31.002	0.0235
2.4G;BT-LE	2.10	18.94	21.04	0.50	21.54	20	0.02836	1.00000	B	37.006	0.0284
Sum Ratio	0.0519										
Ratio Limit	1										

Simultaneous Transmission Analysis Mode: EUT 3-WLAN 2.4GHz+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
2.4G;D1D	5.46	19.17	24.63	0.5	25.13	20	0.06493	1.0000	B	37.01	0.0649
2.4G;BT-LE	3.4	18.94	22.34	0.5	22.84	20	0.03832	1.0000	B	37.01	0.0383
Sum TL Ratio_B	0.1032										
Ratio Limit	1										

Simultaneous Transmission Analysis Mode: EUT 3-WLAN 5GHz+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.8G;D1D	6.09	18.69	24.78	0.5	25.28	20	0.06721	1.0000	B	37.01	0.0672
2.4G;BT-LE	3.4	18.94	22.34	0.5	22.84	20	0.03832	1.0000	B	37.01	0.0383
Sum TL Ratio_B	0.1055										
Ratio Limit	1										

**Simultaneous Transmission Analysis Mode: EUT 3-WLAN 6GHz+Bluetooth**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
6.2G;D1D	7.1	-	14.02	0.5	14.52	20	0.02248	1.0000	C	31.00	0.0225
2.4G;BT-LE	3.4	18.94	22.34	0.5	22.84	20	0.03832	1.0000	B	37.01	0.0383
Sum Ratio	0.0608										
Ratio Limit	1										