



FCC RADIO TEST REPORT

Applicant's company	Arcadyan Technology Corporation
Applicant Address	4F, No.9, Park Avenue II, Science-based Industrial Park Hsinchu 300, Taiwan
FCC ID	RAXWA8001AAC
Manufacturer's company	Arcadyan Technology Corporation
Manufacturer Address	4F, No.9, Park Avenue II, Science-based Industrial Park Hsinchu 300, Taiwan

Product Name	Wireless Joey Access Point
Brand Name	EchoStar
Model No.	Wireless Joey Access Point
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250MHz
Received Date	Dec. 10, 2013
Final Test Date	Jan. 01, 2014
Submission Type	Original Equipment

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac (5150 ~ 5250MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart E, KDB 789033 D01 v01r03, KDB 662911 D01 v02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Product Information	6
3.6. Table for Test Modes.....	7
3.7. Table for Testing Locations.....	8
3.8. Table for Supporting Units	9
3.9. Table for Parameters of Test Software Setting	10
3.10. EUT Operation during Test	10
3.11. Duty Cycle.....	11
3.12. Test Configurations	13
4. TEST RESULT	16
4.1. AC Power Line Conducted Emissions Measurement.....	16
4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	20
4.3. Maximum Conducted Output Power Measurement.....	28
4.4. Power Spectral Density Measurement	31
4.5. Peak Excursion Measurement.....	37
4.6. Radiated Emissions Measurement	42
4.7. Band Edge Emissions Measurement	57
4.8. Frequency Stability Measurement	62
4.9. Antenna Requirements	64
5. LIST OF MEASURING EQUIPMENTS	65
6. MEASUREMENT UNCERTAINTY.....	67
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A12
APPENDIX B. TEST PHOTOS.....	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE	C1 ~ C3



History of This Test Report



Report No.: FR3D1013AB

Certificate No.: CB10301028

1. CERTIFICATE OF COMPLIANCE

Product Name : Wireless Joey Access Point
Brand Name : EchoStar
Model No. : Wireless Joey Access Point
Applicant : Arcadyan Technology Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 10, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads "Sam Chen".

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	7.64 dB
4.2	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	0.11dB
4.4	15.407(a)	Power Spectral Density	Complies	0.05 dB
4.5	15.407(a)	Peak Excursion	Complies	3.10 dB
4.6	15.407(b)	Radiated Emissions	Complies	3.04 dB
4.7	15.407(b)	Band Edge Emissions	Complies	1.03 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	5150 ~ 5250MHz
Channel Number	4 for 20MHz bandwidth ; 2 for 40MHz bandwidth 1 for 80MHz bandwidth
Channel Band Width (99%)	802.11ac MCS0, NSS1 (20MHz): 17.92 MHz ; 802.11ac MCS0, NSS1 (40MHz): 36.48 MHz ; 802.11ac MCS0, NSS1 (80MHz): 76.16 MHz
Maximum Conducted Output Power	802.11ac MCS0, NSS1 (20MHz): 16.42 dBm ; 802.11ac MCS0, NSS1 (40MHz): 16.34 dBm ; 802.11ac MCS0, NSS1 (80MHz): 16.33 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5150 ~ 5250MHz
Channel Number	4
Channel Band Width (99%)	16.64 MHz
Maximum Conducted Output Power	16.49 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna and Band width

Antenna	Three (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

Note : The product has beamforming function for 802.11n/ac mode only.

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	3	MCS 0-23
802.11n (HT40)	3	MCS 0-23
802.11ac (VHT20)	3	MCS 0-9, NSS1-3
802.11ac (VHT40)	3	MCS 0-9, NSS1-3
802.11ac (VHT80)	3	MCS 0-9, NSS1-3

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).

Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:

11a: IEEE 802.11a, HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories


Power	Brand	Model No.	Rating
Adapter	DELTA	ADP-18DW BA	Input: 100-120Vac, 0.5A, 60Hz Output: 12Vdc, 1.46A
Other			
RJ-45 Cable*1: Non-shielded, 3m			

3.3. Table for Filed Antenna

Ant.	Brand	Model No.	Antenna Type	Connector	Gain (dBi)
1	Airgain	N5x20B	PCB Antenna	I-PEX	1.7
2	Airgain	N5x20B	PCB Antenna	I-PEX	1.7
3	Airgain	N5x20B	PCB Antenna	I-PEX	1.7

Note: The EUT has three antennas. (3TX/3RX)

Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

For 80MHz bandwidth systems, use Channel 42.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-

3.5. Table for Product Information

Items	Description	
Communication Mode	<input checked="" type="checkbox"/> IP Based (Load Based)	<input type="checkbox"/> Frame Based
Beamforming Function	<input checked="" type="checkbox"/> With beamforming	<input type="checkbox"/> Without beamforming
Note: The product has beamforming function for 802.11n/ac mode only.		

3.6. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Antenna
AC Power Conducted Emission	Normal Link		-	-	-
Max. Conducted Output Power	11ac 20MHz	Band 1	MCS0, NSS1	36/40/48	1+2+3
	11ac 40MHz	Band 1	MCS0, NSS1	38/46	1+2+3
	11ac 80MHz	Band 1	MCS0, NSS1	42	1+2+3
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3
Power Spectral Density	11ac 20MHz	Band 1	MCS0, NSS1	36/40/48	1+2+3
	11ac 40MHz	Band 1	MCS0, NSS1	38/46	1+2+3
	11ac 80MHz	Band 1	MCS0, NSS1	42	1+2+3
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement	11ac 20MHz	Band 1	MCS0, NSS1	36/40/48	1+2+3
	11ac 40MHz	Band 1	MCS0, NSS1	38/46	1+2+3
	11ac 80MHz	Band 1	MCS0, NSS1	42	1+2+3
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3
Peak Excursion	11ac 20MHz	Band 1	MCS0, NSS1	48	1+2+3
	11ac 40MHz	Band 1	MCS0, NSS1	38	1+2+3
	11ac 80MHz	Band 1	MCS0, NSS1	42	1+2+3
	11a/BPSK	Band 1	6Mbps	36	1+2+3
Radiated Emission Below 1GHz	Normal Link		-	-	-
Radiated Emission Above 1GHz	11ac 20MHz	Band 1	MCS0, NSS1	36/40/48	1+2+3
	11ac 40MHz	Band 1	MCS0, NSS1	38/46	1+2+3
	11ac 80MHz	Band 1	MCS0, NSS1	42	1+2+3
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3
Band Edge Emission	11ac 20MHz	Band 1	MCS0, NSS1	36/40/48	1+2+3
	11ac 40MHz	Band 1	MCS0, NSS1	38/46	1+2+3
	11ac 80MHz	Band 1	MCS0, NSS1	42	1+2+3
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3
Frequency Stability	Un-modulation		-	40	N/A

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. AP function

Mode 2. Client function

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emissions Below 1GHz test:

Mode 1. AP function

Mode 2. Client function

Mode 1 is the worst case, so it was selected to record in this test report.

3.7. Table for Testing Locations

Test Site Location					
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.8. Table for Supporting Units

For AC Power Line Conducted Emissions test:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC
Wireless Joey Access Point	EchoStar	Wireless Joey Access Point	RAXWA8001AAC
Notebook	DELL	E6430	DoC
Mouse	Logitech	M-U0026	DoC
Earphone	SHYARO CHI	MIC-04	N/A

For Radiated Emissions Below 1GHz test:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC
Wireless Joey Access Point	EchoStar	Wireless Joey Access Point	RAXWA8001AAC
Notebook	DELL	D420	DoC
Mouse	Logitech	M-U0026	DoC
Earphone	E-BOOKI	E-EPC040	N/A

For Others test:

For IEEE 802.11a: Non-beamforming mode

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D420	DoC

For IEEE 802.11ac: Beamforming mode

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D420	DoC
Notebook	DELL	D420	DoC
WiFi USB Adapter	NETGEAR	A6200	PY312200200

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11ac MCS0, NSS1 20MHz

Test Software Version	Manual Tool Version:2.0.0.7		
Frequency	5180 MHz	5200 MHz	5240 MHz
MCS0, NSS1 20MHz	45	45	46

Power Parameters of IEEE 802.11ac MCS0, NSS1 40MHz

Test Software Version	Manual Tool Version:2.0.0.7	
Frequency	5190 MHz	5230 MHz
MCS0, NSS1 40MHz	44	44

Power Parameters of IEEE 802.11ac MCS0, NSS1 80MHz

Test Software Version	Manual Tool Version:2.0.0.7		
Frequency	5210 MHz		
MCS0, NSS1 80MHz	46		

Power Parameters of IEEE 802.11a

Test Software Version	Manual Tool Version:2.0.0.7		
Frequency	5180 MHz	5200 MHz	5240 MHz
IEEE 802.11a	45	45	45

3.10. EUT Operation during Test

For IEEE 802.11a: Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For IEEE 802.11ac: Beamforming mode

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:


During the test, the following programs under WIN 7 were executed.

The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe" to link with the remote workstation to receive and transmit packet by WiFi USB Adapter and transmit duty cycle no less 98%


3.11.Duty Cycle

IEEE 802.11ac MCS0, NSS1 20MHz




Date: 1.JAN.2014 01:20:21


IEEE 802.11ac MCS0, NSS1 40MHz



Date: 1.JAN.2014 01:21:31

IEEE 802.11ac MCS0, NSS1 80MHz



Date: 1.JAN.2014 01:22:54

IEEE 802.11a


Date: 1.JAN.2014 01:19:20

3.12. Test Configurations


3.12.1. AC Power Line Conduction Emissions and Radiation Emissions Below 1GHz Test Configuration



Item	Connection	Shield	Length
1	Power Cable	No	1.4m
2	RJ-45 Cable	No	3m
3	Audio Cable	No	1.1m
4	USB Cable	No	1.8m


3.12.2. Radiation Emissions above 1GHz Test Configuration

For IEEE 802.11a: Non-beamforming mode



Item	Connection	Shield	Length
1	Power Cable	No	1.4m
2	RJ-45 Cable	No	10m

For IEEE 802.11ac: Beamforming mode



Item	Connection	Shield	Length
1	Power Cable	No	1.4m
2	RJ-45 Cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in $50\ \Omega$. LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	53%
Test Engineer	Ryo Fan	Phase	Line
Configuration	Normal Link	Test Mode	Mode 1



Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Limit	Line	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 @	0.15000	58.36	-7.64	66.00	58.03	0.15	0.18 LINE QP
2 @	0.15000	47.76	-8.24	56.00	47.43	0.15	0.18 LINE AVERAGE
3	0.19654	52.73	-11.03	63.76	52.38	0.15	0.20 LINE QP
4	0.19654	42.76	-11.00	53.76	42.41	0.15	0.20 LINE AVERAGE
5	0.24422	43.36	-18.59	61.95	43.01	0.15	0.20 LINE QP
6	0.24422	32.62	-19.33	51.95	32.27	0.15	0.20 LINE AVERAGE
7	0.34830	41.85	-17.15	59.00	41.50	0.15	0.20 LINE QP
8	0.34830	38.95	-10.05	49.00	38.60	0.15	0.20 LINE AVERAGE
9	0.43511	31.42	-25.73	57.15	31.07	0.15	0.20 LINE QP
10	0.43511	15.57	-31.58	47.15	15.22	0.15	0.20 LINE AVERAGE
11	2.608	17.37	-28.63	46.00	16.91	0.22	0.24 LINE AVERAGE
12	2.608	30.73	-25.27	56.00	30.27	0.22	0.24 LINE QP
13	4.952	17.54	-28.46	46.00	16.93	0.29	0.32 LINE AVERAGE
14	4.952	27.29	-28.71	56.00	26.68	0.29	0.32 LINE QP

Temperature	24°C	Humidity	53%
Test Engineer	Ryo Fan	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 1



Freq	Over		Limit	Read	LISN	Cable		Remark
	MHz	dBuV				dB	dB	
1	0.15000	56.84	-9.16	66.00	56.59	0.07	0.18	NEUTRAL
2	0.15000	44.93	-11.07	56.00	44.68	0.07	0.18	NEUTRAL
3	0.16070	43.51	-21.91	65.43	43.26	0.07	0.18	NEUTRAL
4	0.16070	23.53	-31.89	55.43	23.28	0.07	0.18	NEUTRAL
5	0.20075	49.03	-14.55	63.58	48.76	0.07	0.20	NEUTRAL
6	0.20075	38.38	-15.20	53.58	38.11	0.07	0.20	NEUTRAL
7	0.21392	36.11	-26.94	63.05	35.84	0.07	0.20	NEUTRAL
8	0.21392	13.44	-39.61	53.05	13.17	0.07	0.20	NEUTRAL
9	0.24814	41.77	-20.05	61.82	41.50	0.07	0.20	NEUTRAL
10	0.24814	31.18	-20.64	51.82	30.91	0.07	0.20	NEUTRAL
11	0.30348	30.60	-29.55	60.15	30.33	0.07	0.20	NEUTRAL
12	0.30348	18.18	-31.97	50.15	17.91	0.07	0.20	NEUTRAL
13	3.491	28.20	-27.80	56.00	27.80	0.12	0.28	NEUTRAL
14	3.491	19.91	-26.09	46.00	19.51	0.12	0.28	NEUTRAL
15	13.915	24.25	-35.75	60.00	23.51	0.34	0.40	NEUTRAL
16	13.915	16.78	-33.22	50.00	16.04	0.34	0.40	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times$ RBW
Detector	Peak
Trace	Max Hold

4.2.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.2.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.6.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11ac

Configuration IEEE 802.11ac MCS0, NSS1 20MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	20.48	17.92
40	5200 MHz	20.32	17.92
48	5240 MHz	20.16	17.92

Configuration IEEE 802.11ac MCS0, NSS1 40MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	38.72	36.48
46	5230 MHz	39.04	36.48

Configuration IEEE 802.11ac MCS0, NSS1 80MHz / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
42	5210 MHz	81.28	76.16

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11a

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	19.36	16.64
40	5200 MHz	19.36	16.64
48	5240 MHz	19.52	16.64

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0, NSS1 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5180 MHz




Date: 1.JAN.2014 15:49:48

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0, NSS1 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5200 MHz




Date: 1.JAN.2014 15:49:12

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0, NSS1 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5240 MHz




Date: 1.JAN.2014 15:48:40

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0, NSS1 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5190 MHz




Date: 1.JAN.2014 15:50:51

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0, NSS1 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5230 MHz




Date: 1.JAN.2014 15:51:29

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0, NSS1 80MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5210 MHz




Date: 1.JAN.2014 15:52:21

**26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a /
Ant. 1 + Ant. 2 + Ant. 3 / 5180 MHz**




Date: 1.JAN.2014 15:44:59

**26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a /
Ant. 1 + Ant. 2 + Ant. 3 / 5200 MHz**



Date: 1.JAN.2014 15:46:28

**26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a /
Ant. 1 + Ant. 2 + Ant. 3 / 5240 MHz**



Date: 1.JAN.2014 15:47:42

4.3. Maximum Conducted Output Power Measurement

4.3.1. Limit

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW (17dBm) or 4 dBm + 10log B, where B is the 26 dB emissions bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB 789033 D01 v01r03 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E, section (E) Maximum conducted output power =>(3) Method PM (Measurement using an RF average power meter) Multiple antenna systems was performed in accordance with KDB 662911 D01 v02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11ac
Test Date	Jan. 01, 2014		

Configuration IEEE 802.11ac MCS0, NSS1 20MHz

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
36	5180 MHz	11.51	11.21	11.29	16.11	16.53	Complies
40	5200 MHz	11.61	11.32	11.25	16.17	16.53	Complies
48	5240 MHz	11.75	11.55	11.63	16.42	16.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/Nss)$ = 6.47 dBi > 6 dBi, so limit = 17 - (6.47 - 6) = 16.53 dBm.

Configuration IEEE 802.11ac MCS0, NSS1 40MHz

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
38	5190 MHz	11.78	11.48	11.45	16.34	16.53	Complies
46	5230 MHz	11.56	11.28	11.46	16.21	16.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/Nss)$ = 6.47 dBi > 6 dBi, so limit = 17 - (6.47 - 6) = 16.53 dBm.

Configuration IEEE 802.11ac MCS0, NSS1 80MHz

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
42	5210 MHz	11.61	11.26	11.78	16.33	16.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/Nss)$ = 6.47 dBi > 6 dBi, so limit = 17 - (6.47 - 6) = 16.53 dBm.

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11a
Test Date	Jan. 01, 2014		

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
36	5180 MHz	11.92	11.52	11.71	16.49	17.00	Complies
40	5200 MHz	11.82	11.60	11.62	16.45	17.00	Complies
48	5240 MHz	12.06	11.32	11.55	16.43	17.00	Complies

4.4. Power Spectral Density Measurement

4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15~5.25 GHz	4

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB 789033 D01 v01r03 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E, section (C) Maximum conducted output power => (d) Method SA-2 (trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).
3. Multiple antenna systems was performed in accordance KDB 662911 D01 v02 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11ac
Test Date	Jan. 01, 2014		

Configuration IEEE 802.11ac MCS0, NSS1 20MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	2.57	3.53	Complies
40	5200 MHz	2.80	3.53	Complies
48	5240 MHz	2.94	3.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{SS}) = 6.47 \text{ dBi} > 6 \text{ dBi}$, so limit = $4 - (6.47 - 6) = 3.53 \text{ dBm/MHz}$.

Configuration IEEE 802.11ac MCS0, NSS1 40MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	-0.19	3.53	Complies
46	5230 MHz	-0.27	3.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{SS}) = 6.47 \text{ dBi} > 6 \text{ dBi}$, so limit = $4 - (6.47 - 6) = 3.53 \text{ dBm/MHz}$.

Configuration IEEE 802.11ac MCS0, NSS1 80MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210 MHz	-3.25	3.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{SS}) = 6.47 \text{ dBi} > 6 \text{ dBi}$, so limit = $4 - (6.47 - 6) = 3.53 \text{ dBm/MHz}$.

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11a
Test Date	Jan. 01, 2014		

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	3.42	3.53	Complies
40	5200 MHz	3.48	3.53	Complies
48	5240 MHz	3.43	3.53	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{SS}) = 6.47\text{dBi} > 6\text{dBi}$, so limit = $4 - (6.47 - 6) = 3.53\text{dBm/MHz}$.


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


Power Density Plot on Configuration IEEE 802.11ac MCS0, NSS1 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5240 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0, NSS1 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5190 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0, NSS1 80MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5210 MHz



Power Density Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 / 5200 MHz



4.5. Peak Excursion Measurement

4.5.1. Limit

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1MHz (Peak Trace) / 1MHz (Average Trace)
VBW	\geq 3MHz (Peak Trace) / \geq 3MHz (Average Trace)
Detector	Peak (Peak Trace) / RMS (Average Trace)
Trace	Trace: Max hold (Peak Trace) / Trace Average Sweep Count 100 (Average Trace)
Sweep Time	AUTO

4.5.3. Test Procedures

1. Trace A, Set RBW = 1MHz, VBW = 3MHz, Span >26dB bandwidth, Max. hold.
2. Delta Mark trace A Maximum frequency and trace B same frequency.
3. Repeat the above procedure until measurements for all frequencies were complete.
4. Testing each modulation mode on a single channel in single operating band at single output port.
All signal types need test (DSSS, OFDM). All modulation types need test (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM). All bandwidth modes need test.

4.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.4.4.

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Peak Excursion

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11ac

Configuration IEEE 802.11ac 20MHz / Ant. 1 + Ant. 2 + Ant. 3

Modulation	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
BPSK (MCS0)	5240 MHz	8.21	13	Complies
QPSK (MCS1)	5240 MHz	9.40	13	Complies
16QAM (MCS3)	5240 MHz	9.49	13	Complies
64QAM (MCS5)	5240 MHz	9.29	13	Complies
256QAM (MCS8)	5240 MHz	9.90	13	Complies

Configuration IEEE 802.11ac 40MHz / Ant. 1 + Ant. 2 + Ant. 3

Modulation	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
BPSK (MCS0)	5190 MHz	8.64	13	Complies
QPSK (MCS1)	5190 MHz	8.21	13	Complies
16QAM (MCS3)	5190 MHz	9.89	13	Complies
64QAM (MCS5)	5190 MHz	9.37	13	Complies
256QAM (MCS8)	5190 MHz	9.44	13	Complies

Configuration IEEE 802.11ac 80MHz / Ant. 1 + Ant. 2 + Ant. 3

Modulation	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
BPSK (MCS0)	5210 MHz	8.71	13	Complies
QPSK (MCS1)	5210 MHz	9.29	13	Complies
16QAM (MCS3)	5210 MHz	9.33	13	Complies
64QAM (MCS5)	5210 MHz	9.68	13	Complies
256QAM (MCS8)	5210 MHz	9.63	13	Complies

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Configurations	IEEE 802.11a


Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3

Modulation	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
BPSK (6Mbps)	5180 MHz	8.27	13	Complies
QPSK (12Mbps)	5180 MHz	9.16	13	Complies
16QAM (24Mbps)	5180 MHz	8.39	13	Complies
64QAM (48Mbps)	5180 MHz	8.82	13	Complies

Note: All the test values were listed in the report.


For plots, only the modulation with worse result was shown.

Peak Excursion Plot on Configuration IEEE 802.11ac 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 256QAM (MCS8) / 5240 MHz




Date: 1.JAN.2014 16:50:17

Peak Excursion Plot on Configuration IEEE 802.11ac 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 16QAM (MCS3) / 5190 MHz




Date: 1.JAN.2014 16:53:15

Peak Excursion Plot on Configuration IEEE 802.11ac 80MHz / Ant. 1 + Ant. 2 + Ant. 3 / 64QAM (MCS5) / 5210 MHz



Date: 1.JAN.2014 16:57:13

Peak Excursion Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 / QPSK (12Mbps) / 5180 MHz



Date: 1.JAN.2014 16:43:25

4.6. Radiated Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	1MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For IEEE 802.11a: Non-beamforming mode

The EUT was programmed to be in continuously transmitting mode.

For IEEE 802.11ac: Beamforming mode

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	Normal Link
Test Date	Dec. 30, 2013	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


4.6.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	Normal Link
Test Mode	Mode 1		

Horizontal



Freq	Level	Limit	Over	Read	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
					Line	Limit	Level			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	43.58	31.45	40.00	-8.55	47.65	0.72	10.88	27.80	Peak	400 0 HORIZONTAL
2	151.25	31.75	43.50	-11.75	45.81	1.41	11.87	27.34	Peak	400 0 HORIZONTAL
3	375.32	30.34	46.00	-15.66	40.17	2.20	15.40	27.43	Peak	400 0 HORIZONTAL
4	662.44	32.84	46.00	-13.16	38.89	3.02	18.97	28.04	Peak	400 0 HORIZONTAL
5	749.74	33.38	46.00	-12.62	38.55	3.20	19.43	27.80	Peak	400 0 HORIZONTAL
6	994.18	34.76	54.00	-19.24	36.86	3.68	21.25	27.03	Peak	400 0 HORIZONTAL

Vertical


Freq	Level	Limit	Over	Read	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase	
					Line	Limit	Level				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	37.76	24.83	40.00	-15.17	37.65	0.68	14.30	27.80	QP	101	300 VERTICAL
2	54.25	36.96	40.00	-3.04	56.06	0.85	7.83	27.78	QP	100	267 VERTICAL
3	59.10	36.43	40.00	-3.57	56.34	0.90	6.95	27.76	Peak	400	0 VERTICAL
4	64.92	36.95	40.00	-3.05	57.05	0.94	6.70	27.74	Peak	182	133 VERTICAL
5	138.64	34.83	43.50	-8.67	48.48	1.42	12.34	27.41	Peak	400	0 VERTICAL
6	662.44	31.91	46.00	-14.09	37.96	3.02	18.97	28.04	Peak	400	0 VERTICAL
7	749.74	32.55	46.00	-13.45	37.72	3.20	19.43	27.80	Peak	400	0 VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~40GHz)

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 20MHz CH 36 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 23, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB						
1	15539.42	57.44	74.00	-16.56	44.14	10.77	38.12	35.59	Peak	100	259	HORIZONTAL	
2	15542.56	44.42	54.00	-9.58	31.12	10.77	38.12	35.59	Average	100	259	HORIZONTAL	

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB						
1	15543.86	44.44	54.00	-9.56	31.13	10.78	38.12	35.59	Average	100	140	VERTICAL	
2	15544.50	57.76	74.00	-16.24	44.45	10.78	38.12	35.59	Peak	100	140	VERTICAL	

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 20MHz CH 40 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 24, 2013		

Horizontal

Freq	Level	Limit		Over Line	Read Limit	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB						
1	15590.56	42.74	54.00	-11.26	31.22	7.87	34.83	38.48	Average			181	100	HORIZONTAL
2	15590.96	53.57	74.00	-20.43	42.05	7.87	34.83	38.48	Peak			181	100	HORIZONTAL

Vertical

Freq	Level	Limit		Over Line	Read Limit	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB						
1	15594.16	42.58	54.00	-11.42	31.06	7.87	34.83	38.48	Average			219	100	VERTICAL
2	15597.20	55.30	74.00	-18.70	43.77	7.88	34.83	38.48	Peak			219	100	VERTICAL

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 20MHz CH 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 24, 2013		

Horizontal

Freq	Level	Limit		Over Line	Read Limit	Cable		Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m				
1	15719.62	42.09	54.00	-11.91	30.65	7.92	34.94	38.46	Average	213	100	HORIZONTAL	
2	15720.04	55.00	74.00	-19.00	43.56	7.92	34.94	38.46	Peak	213	100	HORIZONTAL	

Vertical

Freq	Level	Limit		Over Line	Read Limit	Cable		Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m				
1	15719.28	54.38	74.00	-19.62	42.94	7.92	34.94	38.46	Peak	166	100	VERTICAL	
2	15719.40	42.08	54.00	-11.92	30.64	7.92	34.94	38.46	Average	166	100	VERTICAL	

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 40MHz CH 38 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 24, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm	
1	15570.10	56.00	74.00	-18.00	44.46	7.86	34.81	38.49	Peak	185	100 HORIZONTAL
2	15573.72	42.37	54.00	-11.63	30.85	7.86	34.83	38.49	Average	185	100 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm	
1	15571.02	42.13	54.00	-11.87	30.59	7.86	34.81	38.49	Average	123	100 VERTICAL
2	15573.64	55.46	74.00	-18.54	43.94	7.86	34.83	38.49	Peak	123	100 VERTICAL

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 40MHz CH 46 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 24, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm	
1	15687.76	54.89	74.00	-19.11	43.45	7.90	34.92	38.46	Peak	197	100 HORIZONTAL
2	15690.80	42.20	54.00	-11.80	30.76	7.90	34.92	38.46	Average	197	100 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm	
1	15691.42	42.29	54.00	-11.71	30.85	7.90	34.92	38.46	Average	5	100 VERTICAL
2	15692.76	54.50	74.00	-19.50	43.06	7.90	34.92	38.46	Peak	5	100 VERTICAL

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 80MHz CH 42 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 24, 2013		

Horizontal

Freq	Level	Limit		Over Line	Read Level	Cable Preamp Antenna			T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		
1	2318.72	37.88	74.00	-36.12	41.72	2.87	34.69	27.98	Peak	336	100 HORIZONTAL
2	2318.72	32.13	54.00	-21.87	35.97	2.87	34.69	27.98	Average	336	100 HORIZONTAL
3	15626.48	56.01	74.00	-17.99	44.53	7.88	34.88	38.48	Peak	294	100 HORIZONTAL
4	15628.36	42.90	54.00	-11.10	31.42	7.88	34.88	38.48	Average	294	100 HORIZONTAL

Vertical

Freq	Level	Limit		Over Line	Read Level	Cable Preamp Antenna			T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		
1	2318.68	48.16	74.00	-25.84	52.00	2.87	34.69	27.98	Peak	270	121 VERTICAL
2	2318.80	46.70	54.00	-7.30	50.54	2.87	34.69	27.98	Average	270	121 VERTICAL
3	15621.92	42.74	54.00	-11.26	31.24	7.88	34.86	38.48	Average	233	100 VERTICAL
4	15622.16	56.82	74.00	-17.18	45.32	7.88	34.86	38.48	Peak	233	100 VERTICAL

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11a CH 36 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dB			dBuV	dB			cm	deg		
1	15539.85	58.82	74.00	-15.18	44.18	10.37	38.78	34.51	100	276	HORIZONTAL	Peak	
2	15540.43	45.85	54.00	-8.15	31.22	10.37	38.78	34.52	100	276	HORIZONTAL	Average	

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dB			dBuV	dB			cm	deg		
1	15539.94	58.84	74.00	-15.16	44.20	10.37	38.78	34.51	106	153	VERTICAL	Peak	
2	15540.25	46.18	54.00	-7.82	31.55	10.37	38.78	34.52	106	153	VERTICAL	Average	

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11a CH 40 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15600.00	58.20	74.00	-15.80	43.66	10.36	38.77	34.59	100	270	HORIZONTAL	Peak	
2	15600.25	44.98	54.00	-9.02	30.44	10.36	38.77	34.59	100	270	HORIZONTAL	Average	

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15599.96	45.81	54.00	-8.19	31.27	10.36	38.77	34.59	108	202	VERTICAL	Average	
2	15600.26	58.05	74.00	-15.95	43.51	10.36	38.77	34.59	108	202	VERTICAL	Peak	

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11a CH 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable Loss		Antenna Factor		Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dBuV/m			dB	dBuV	dB	dB/m					
1	15719.91	58.30	74.00	-15.70	43.96	10.36	38.72	34.74	105	105	244	HORIZONTAL	Peak	
2	15720.13	45.98	54.00	-8.02	31.64	10.36	38.72	34.74	105	105	244	HORIZONTAL	Average	

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable Loss		Antenna Factor		Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dBuV/m			dB	dBuV	dB	dB/m					
1	15719.82	58.59	74.00	-15.41	44.25	10.36	38.72	34.74	100	100	136	VERTICAL	Peak	
2	15720.19	46.04	54.00	-7.96	31.70	10.36	38.72	34.74	100	100	136	VERTICAL	Average	

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.7. Band Edge Emissions Measurement

4.7.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	1MHz / 3MHz for Peak

4.7.3. Test Procedures

The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around bandedges.

4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

For IEEE 802.11a: Non-beamforming mode

The EUT was programmed to be in continuously transmitting mode.

For IEEE 802.11ac: Beamforming mode

The EUT was programmed to be in beamforming transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 20MHz CH 36, 40, 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 23, 2013		

Channel 36

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	5098.40	52.80	54.00	-1.20	12.79	6.10	33.91	0.00	Average	110	88	VERTICAL		
2	5098.40	64.84	74.00	-9.16	24.83	6.10	33.91	0.00	Peak	110	88	VERTICAL		
3	5178.40	107.59			67.36	6.15	34.08	0.00	Average	110	88	VERTICAL		
4	5180.40	119.83			79.60	6.15	34.08	0.00	Peak	110	88	VERTICAL		

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	5118.00	63.77	74.00	-10.23	23.72	6.11	33.94	0.00	Peak	100	190	VERTICAL		
2	5118.80	52.97	54.00	-1.03	12.92	6.11	33.94	0.00	Average	100	190	VERTICAL		
3	5197.60	106.20			65.93	6.16	34.11	0.00	Average	100	190	VERTICAL		
4	5198.40	117.14			76.87	6.16	34.11	0.00	Peak	100	190	VERTICAL		

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	5150.00	49.67	54.00	-4.33	9.53	6.13	34.01	0.00	Average	105	78	VERTICAL		
2	5150.00	59.22	74.00	-14.78	19.08	6.13	34.01	0.00	Peak	105	78	VERTICAL		
3	5240.80	109.23			68.87	6.18	34.18	0.00	Average	105	78	VERTICAL		
4	5242.40	120.15			79.77	6.20	34.18	0.00	Peak	105	78	VERTICAL		
5	5398.00	64.22	74.00	-9.78	23.44	6.29	34.49	0.00	Peak	105	78	VERTICAL		
6	5398.80	52.87	54.00	-1.13	12.09	6.29	34.49	0.00	Average	105	78	VERTICAL		

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 40MHz CH 38, 46 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 23, 2013		

Channel 38

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m					
MHz		dBuV/m	dBuV/m									cm	deg
1	5148.40	67.87	74.00	-6.13	27.73	6.13	34.01	0.00	Peak		109	143	VERTICAL
2	5149.20	52.81	54.00	-1.19	12.67	6.13	34.01	0.00	Average		109	143	VERTICAL
3	5192.00	112.32			72.08	6.16	34.08	0.00	Peak		109	143	VERTICAL
4	5193.60	101.53			61.29	6.16	34.08	0.00	Average		109	143	VERTICAL

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m					
MHz		dBuV/m	dBuV/m									cm	deg
1	5142.00	63.63	74.00	-10.37	23.52	6.13	33.98	0.00	Peak		105	68	VERTICAL
2	5145.60	52.78	54.00	-1.22	12.64	6.13	34.01	0.00	Average		105	68	VERTICAL
3	5233.20	106.97			66.61	6.18	34.18	0.00	Average		105	68	VERTICAL
4	5234.80	118.27			77.91	6.18	34.18	0.00	Peak		105	68	VERTICAL

Item 3, 4 are the fundamental frequency at 5230 MHz.

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11ac MCS0, NSS1 80MHz CH 42 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 23, 2013		

Channel 42

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB						
		MHz	dBuV/m	dBuV/m		dB	dBuV	dB	dB/m	dB		cm	deg	
1	5142.00	67.22	74.00	-6.78	27.11	6.13	33.98	0.00	Peak			109	143	VERTICAL
2	5143.00	52.86	54.00	-1.14	12.75	6.13	33.98	0.00	Average			109	143	VERTICAL
3	5212.00	97.10			56.78	6.17	34.15	0.00	Average			109	143	VERTICAL
4	5213.00	108.59			68.27	6.17	34.15	0.00	Peak			109	143	VERTICAL

Item 3, 4 are the fundamental frequency at 5210 MHz.

Temperature	21°C	Humidity	53%
Test Engineer	YC Chen	Configurations	IEEE 802.11a CH 36, 40, 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Dec. 27, 2013		

Channel 36

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
			Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB				
1	5099.00	52.82	54.00	-1.18	13.88	5.96	32.98	0.00	109	139	VERTICAL	Average
2	5099.00	63.34	74.00	-10.66	24.40	5.96	32.98	0.00	109	139	VERTICAL	Peak
3	5178.80	118.24			79.19	6.01	33.04	0.00	109	139	VERTICAL	Peak
4	5179.20	107.96			68.91	6.01	33.04	0.00	109	139	VERTICAL	Average

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
			Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB				
1	5119.00	52.95	54.00	-1.05	13.99	5.97	32.99	0.00	105	141	VERTICAL	Average
2	5119.00	63.48	74.00	-10.52	24.52	5.97	32.99	0.00	105	141	VERTICAL	Peak
3	5199.20	107.45			68.38	6.02	33.05	0.00	105	141	VERTICAL	Average
4	5199.20	117.06			77.99	6.02	33.05	0.00	105	141	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
			Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB				
1	5072.80	58.23	74.00	-15.77	19.32	5.95	32.96	0.00	113	77	VERTICAL	Peak
2	5082.80	45.28	54.00	-8.72	6.36	5.95	32.97	0.00	113	77	VERTICAL	Average
3	5243.20	111.39			72.25	6.05	33.09	0.00	113	77	VERTICAL	Average
4	5243.20	121.38			82.24	6.05	33.09	0.00	113	77	VERTICAL	Peak
5	5398.40	64.41	74.00	-9.59	24.72	6.14	33.55	0.00	113	77	VERTICAL	Peak
6	5403.20	52.94	54.00	-1.06	13.20	6.14	33.60	0.00	113	77	VERTICAL	Average

Item 3, 4 are the fundamental frequency at 5240 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.8. Frequency Stability Measurement

4.8.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.8.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.8.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c-f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-5^{\circ}\text{C} \sim 45^{\circ}\text{C}$.

4.8.4. Test Setup Layout



4.8.5. Test Deviation

There is no deviation with the original standard.

4.8.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.8.7. Test Result of Frequency Stability

Temperature	25°C	Humidity	63%
Test Engineer	Satoshi Yang	Test Date	Jan. 01, 2014

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5200 MHz
126.50	5199.9775
110.00	5199.9799
93.50	5199.9766
Max. Deviation (MHz)	0.023400
Max. Deviation (ppm)	4.50

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5200 MHz
-5	5199.9745
0	5199.9748
10	5199.9760
20	5199.9799
30	5199.9763
40	5199.9754
45	5199.9751
Max. Deviation (MHz)	0.025500
Max. Deviation (ppm)	4.90

4.9. Antenna Requirements

4.9.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.9.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9 kHz ~ 2.75 GHz	Apr. 12, 2013	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
Artifical Mains Network	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 04, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-507	15GHz ~ 40GHz	Jan. 14, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02121	1GHz~26.5GHz	Aug. 30, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	Aglient	N9010A	MY52220557	9kHz~44GHz	Nov. 29, 2013	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCI	101382	9kHz ~ 3GHz	Sep. 05, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

** Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch				
Receiver VSWR 1=	-0.080	dB	U-shaped	0.060
AMN/LISN VSWR 2=				
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.173	dB	K=1	0.086
Cable loss	±0.174	dB	K=2	0.087
Antenna gain	±0.169	dB	K=2	0.084
Site imperfection	±0.433	dB	Triangular	0.214
Pre-amplifier gain	±0.366	dB	K=2	0.183
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.191	dB	K=1	0.095
Cable loss	±0.169	dB	K=2	0.084
Antenna gain	±0.191	dB	K=2	0.096
Site imperfection	±0.582	dB	Triangular	0.291
Pre-amplifier gain	±0.304	dB	K=2	0.152
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.186	dB	K=1	0.093
Cable loss	±0.167	dB	K=2	0.083
Antenna gain	±0.190	dB	K=2	0.095
Site imperfection	±0.488	dB	Triangular	0.244
Pre-amplifier gain	±0.269	dB	K=2	0.134
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	± 0.038	dB	K=2	0.019
Attenuator	± 0.047	dB	K=2	0.024
Power Meter specification	± 0.300	dB	Triangular	0.150
Power Sensor specification	± 0.300	dB	Rectangular	0.150
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				1.726