



Wistron NeWeb Corp.

ANTENNA DATASHEET

Customer Name: **Yamaha**

Date:

OEM P/N	TBD
WNC P/N	TBD
Description	Antenna for YSB2022
Version	Temporary Version

Provided By Wistron NeWeb Corp	Reviewed By Wistron NeWeb Corp	Approved By Customer
Joe Chunag	Jason Hsiao	

Wistron NeWeb Corporation
20 Park Avenue II,
Hsinchu Science Park,
Hsinchu 308, Taiwan, R.O.C.
TEL: +886-3-666-7799
FAX: +886-3-666-7321
<http://www.wneweb.com>

啟基科技股份有限公司
新竹市 308 科學園區園區二路 20 號
電話：(03) 666-7799
傳真：(03) 666-7321
<http://www.wneweb.com>



Wistron NeWeb Corp.

Index

1. Product Specification

2. Antenna Performance

2.1 VSWR

2.2 Antenna Gain


2.3 Antenna Pattern

3. Outline Drawing

Revision History

Date	Version	Change Description
	Temporary	

1. Product Specification



A. Electrical Characteristics


Frequency	2400 MHz ~ 2500 MHz 5000 MHz ~ 5850 MHz
V.S.W.R. (should be measured with testing jig)	≤ 2 @ 2400 MHz ~ 2500 MHz ≤ 2 @ 5000 MHz ~ 5850 MHz
Polarization	Linear
Impedance	50 Ohm

B. Material & Mechanical Characteristics

Material	Metal
Cable Type	1.37 cable (black)
Connector Type	I-PEX

2. Antenna Performance




2.1 VSWR



2.2. Antenna Gain


	Frequency	2.4GHz	2.45GHz	2.5GHz	5GHz	5.15GHz	5.35GHz	5.55GHz	5.75GHz	5.85GHz
R0	Efficiency	61%	61%	57%	50%	55%	58%	57%	54%	54%
	Average Gain	-2.14dBi	-2.14dBi	-2.43dBi	-3.06dBi	-2.62dBi	-2.33dBi	-2.43dBi	-2.67dBi	-2.68dBi
	Peak Gain	2.9 dBi	3.1 dBi	2.8 dBi	3 dBi	3.3 dBi	3.3 dBi	3.9 dBi	4.4 dBi	4.11 dBi

2.3 Antenna Pattern




5000MHz Radiation Pattern

— 5000MHz




5150MHz Radiation Pattern

— 5150MHz



5350MHz Radiation Pattern


— 5350MHz



5550MHz

Radiation Pattern


— 5550MHz



5750MHz

Radiation Pattern

— 5750MHz



5850MHz

Radiation Pattern

— 5850MHz

