



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM180900844704  
Page: 1 of 96

# TEST REPORT

**Application No.:** SZEM1809008447CR  
**Applicant:** Navico Inc.  
**Address of Applicant:** 4500 S. 129th East Avenue, Ste. 200, Tulsa, Oklahoma, 74134 United States  
**Manufacturer:** Navico Auckland Limited  
**Address of Manufacturer:** Arrenway Drive, Rosedale, Auckland, 0632 New Zealand  
**Factory:** Shenzhen Hytera Communications Corporation Limited  
**Address of Factory:** Hytera Technology Park, Baolong Industrial City, Longgang District, Shenzhen, China

**Equipment Under Test (EUT):**

**EUT Name:** Marine VHF Radio  
**Model No.:** V60, RS40 \*

\* Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

**Trade mark:** B&G, SIMRAD  
**FCC ID:** RAYVHFRS40  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2018-09-20  
**Date of Test:** 2018-09-26 to 2018-10-19  
**Date of Issue:** 2018-10-29

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2018-10-29		Original

<b>Authorized for issue by:</b>			
		 Edison Li /Project Engineer	
		 Eric Fu /Reviewer	

## 2 Test Summary

<b>Radio Spectrum Technical Requirement</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Customer Declaration

<b>Radio Spectrum Matter Part</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

**Remark:**

Model No.: V60, RS40

Only the model V60 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, with only differences are the trade name and model no. for trading purpose.

### 3 Contents

	Page
1 COVER PAGE .....	1
2 TEST SUMMARY .....	3
3 CONTENTS .....	4
4 GENERAL INFORMATION .....	6
4.1 DETAILS OF E.U.T .....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	6
4.3 MEASUREMENT UNCERTAINTY .....	6
4.4 TEST LOCATION .....	7
4.5 TEST FACILITY .....	7
4.6 DEVIATION FROM STANDARDS .....	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
5 EQUIPMENT LIST .....	8
6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....	10
6.1 ANTENNA REQUIREMENT .....	10
6.1.1 Test Requirement: .....	10
6.1.2 Conclusion .....	10
7 RADIO SPECTRUM MATTER TEST RESULTS .....	11
7.1 MINIMUM 6DB BANDWIDTH .....	11
7.1.1 E.U.T. Operation .....	11
7.1.2 Test Setup Diagram .....	11
7.1.3 Measurement Procedure and Data .....	11
7.2 CONDUCTED PEAK OUTPUT POWER .....	12
7.2.1 E.U.T. Operation .....	12
7.2.2 Test Setup Diagram .....	12
7.2.3 Measurement Procedure and Data .....	12
7.3 POWER SPECTRUM DENSITY .....	13
7.3.1 E.U.T. Operation .....	13
7.3.2 Test Setup Diagram .....	13
7.3.3 Measurement Procedure and Data .....	13
7.4 CONDUCTED BAND EDGES MEASUREMENT .....	14
7.4.1 E.U.T. Operation .....	14
7.4.2 Test Setup Diagram .....	14
7.4.3 Measurement Procedure and Data .....	14
7.5 CONDUCTED SPURIOUS EMISSIONS .....	15
7.5.1 E.U.T. Operation .....	15
7.5.2 Test Setup Diagram .....	15
7.5.3 Measurement Procedure and Data .....	15
7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	16
7.6.1 E.U.T. Operation .....	16
7.6.2 Test Setup Diagram .....	16
7.6.3 Measurement Procedure and Data .....	17
7.7 RADIATED SPURIOUS EMISSIONS .....	42
7.7.1 E.U.T. Operation .....	43
7.7.2 Test Setup Diagram .....	43

7.7.3	Measurement Procedure and Data.....	44
<b>8</b>	<b>PHOTOGRAPHS.....</b>	<b>65</b>
8.1	TEST SETUP.....	65
8.2	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	65
<b>9</b>	<b>APPENDIX.....</b>	<b>66</b>
9.1	APPENDIX 15.247 .....	66-96

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	12 VDC battery system
Cable:	DC cable: longer than 300cm unshielded
Sample Type:	Mobile device
Transmitter Frequency Range:	2412MHz-2462MHz
Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) 802.11n(HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Frequency Spacing:	5MHz
Channel Numbers:	11 Channels
WiFi Antenna Type:	Integral
WiFi Antenna Gain:	1.5dBi

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
DC power	ZHAOXIN	RXN-305D	REF. No. SEA2700
Coaxial Attenuator	Provided by client	TS4	HYT168793

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	RF Radiated power	$\pm 4.5\text{dB}$ (below 1GHz) $\pm 4.8\text{dB}$ (above 1GHz)
8	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz) $\pm 4.8\text{dB}$ (Above 1GHz)
9	Temperature test	$\pm 1\text{ }^{\circ}\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$

#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053      Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

## 5 Equipment List

<b>RF Conducted</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-29	2018-09-28
				2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

<b>Radiated Emissions which fall in the restricted bands</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2018-07-12	2019-07-11
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2018-09-25	2019-09-24
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2017-09-29	2018-09-28
				2018-09-27	2019-09-26
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

<b>Radiated Spurious Emissions</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM180900844704  
Page: 9 of 96

Coaxial Cable	SGS	N/A	SEM026-01	2018-07-12	2019-07-11
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2018-09-25	2019-09-24
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2017-09-29	2018-09-28
				2018-09-27	2019-09-26
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

<b>RE in Chamber</b>					
<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal. Date</b>	<b>Cal. Due date</b>
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-08-05	2020-08-04
MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2018-09-25	2019-09-24
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017-06-27	2020-06-26
Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2018-04-02	2019-04-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2018-07-12	2019-07-11

<b>General used equipment</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
				2018-09-27	2019-09-26
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
				2018-09-27	2019-09-26
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
				2018-09-27	2019-09-26
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

## **6 Radio Spectrum Technical Requirement**

### **6.1 Antenna Requirement**

#### **6.1.1 Test Requirement:**

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

#### **6.1.2 Conclusion**

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.5dBi.

Antenna location: Refer to Internal photos.

## 7 Radio Spectrum Matter Test Results

### 7.1 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz


#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58.5 % RH Atmospheric Pressure: 1010 mbar

Test mode: b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

#### 7.1.2 Test Setup Diagram



#### 7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58.5 % RH Atmospheric Pressure: 1010 mbar

Test mode: b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247


### 7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
Test Method: ANSI C63.10 (2013) Section 11.10.2  
Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission

#### 7.3.1 E.U.T. Operation

Operating Environment:  
Temperature: 24.4 °C      Humidity: 58.5 % RH      Atmospheric Pressure: 1010 mbar  
Test mode: b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.4 Conducted Band Edges Measurement

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.13.3.2
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C      Humidity: 58.5 % RH      Atmospheric Pressure: 1010 mbar

Test mode: b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.5 Conducted Spurious Emissions


Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.11  
Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C      Humidity: 58.5 % RH      Atmospheric Pressure: 1010 mbar  
Test mode: b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 &amp; 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 70.7 % RH Atmospheric Pressure: 1010 mbar

Test mode: b:TX mode \_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

### 7.6.2 Test Setup Diagram




### **7.6.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
: 2.4G Wifi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2384.649	5.47	28.51	41.87	56.91	49.02	74.00	-24.98	peak
2	2390.000	5.47	28.52	41.87	51.59	43.71	74.00	-30.29	peak
3 *	2412.000	5.50	28.56	41.88	88.67	80.85	74.00	6.85	peak


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
: 2.4G Wifi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB	
1	2387.549	5.47	28.51	41.87	43.44	35.55	54.00	-18.45	Average
2	2390.000	5.47	28.52	41.87	41.09	33.21	54.00	-20.79	Average
3 *	2412.000	5.50	28.56	41.88	86.04	78.22	54.00	24.22	Average


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
: 2.4G Wifi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.736	5.47	28.51	41.87	74.06	66.17	74.00	-7.83	peak
2	2390.000	5.47	28.52	41.87	73.27	65.39	74.00	-8.61	peak
3 *	2412.000	5.50	28.56	41.88	99.79	91.97	74.00	17.97	peak


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
: 2.4G Wifi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.549	5.47	28.51	41.87	55.74	47.85	54.00	-6.15	Average
2	2390.000	5.47	28.52	41.87	53.35	45.47	54.00	-8.53	Average
3 *	2412.000	5.50	28.56	41.88	97.07	89.25	54.00	35.25	Average


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
: 2.4G Wifi 11b

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level		Limit Line	Over Limit	Remark
				dB	dB/m			
MHz								
1 *	2462.000	5.57	28.64	41.90	91.84	84.15	74.00	10.15 peak
2	2483.500	5.60	28.67	41.91	48.20	40.56	74.00	-33.44 peak
3	2487.556	5.60	28.68	41.91	49.69	42.06	74.00	-31.94 peak


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
: 2.4G Wifi 11b

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level		Limit Line	Over Limit	Remark
				dB	dB/m			
MHz								
1 *	2462.000	5.57	28.64	41.90	89.31	81.62	54.00	27.62 Average
2	2483.500	5.60	28.67	41.91	38.35	30.71	54.00	-23.29 Average
3	2496.971	5.62	28.70	41.92	40.70	33.10	54.00	-20.90 Average


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
: 2.4G Wifi 11b

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	99.91	92.22	74.00	18.22 peak
2 2483.500	5.60	28.67	41.91	50.67	43.03	74.00	-30.97 peak
3 2486.702	5.60	28.68	41.91	54.74	47.11	74.00	-26.89 peak


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
: 2.4G Wifi 11b

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level		Limit Line	Over Limit	Remark
				dB	dB/m			
MHz								
1 *	2462.000	5.57	28.64	41.90	97.31	89.62	54.00	35.62 Average
2	2483.500	5.60	28.67	41.91	41.71	34.07	54.00	-19.93 Average
3	2496.971	5.62	28.70	41.92	44.13	36.53	54.00	-17.47 Average


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	5.47	28.52	41.87	53.31	45.43	74.00	-28.57	peak
2	2390.000	5.47	28.52	41.87	49.93	42.05	74.00	-31.95	peak
3 *	2412.000	5.50	28.56	41.88	91.50	83.68	74.00	9.68	peak


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11g

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line dBuV/m	Over Limit dBuV/m	Over Limit dB	Remark
		MHz	dB	dB/m		dB	dBuV	dBuV/m			
1	2389.847	5.47	28.52	41.87	41.87	40.00	32.12	54.00	-21.88	Average	
2	2390.000	5.47	28.52	41.87	41.87	39.97	32.09	54.00	-21.91	Average	
3 *	2412.000	5.50	28.56	41.88	41.88	83.98	76.16	54.00	22.16	Average	


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	MHz	Loss	Factor	Level	Level	Line	
1	2389.605	5.47	28.52	41.87	59.58	51.70	74.00 -22.30 Peak
2	2390.000	5.47	28.52	41.87	56.63	48.75	74.00 -25.25 Peak
3 *	2412.000	5.50	28.56	41.88	100.66	92.84	74.00 18.84 Peak


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	46.02	38.14	54.00	-15.86	Average
2	2390.000	5.47	28.52	41.87	46.02	38.14	54.00	-15.86	Average
3 *	2412.000	5.50	28.56	41.88	92.61	84.79	54.00	30.79	Average


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	93.21	85.52	74.00	11.52 peak
2 2483.500	5.60	28.67	41.91	54.47	46.83	74.00	-27.17 peak
3 2485.245	5.60	28.68	41.91	56.76	49.13	74.00	-24.87 peak


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark		
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit	
1 *	2462.000	5.57	28.64	41.90	85.76	78.07	54.00	24.07	Average
2	2483.500	5.60	28.67	41.91	41.10	33.46	54.00	-20.54	Average
3	2496.921	5.62	28.70	41.92	42.24	34.64	54.00	-19.36	Average


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	101.19	93.50	74.00	19.50 Peak
2 2483.500	5.60	28.67	41.91	59.34	51.70	74.00	-22.30 Peak
3 2483.890	5.60	28.67	41.91	62.70	55.06	74.00	-18.94 Peak


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	93.66	85.97	54.00	31.97 Average
2 2483.500	5.60	28.67	41.91	46.53	38.89	54.00	-15.11 Average
3 2496.971	5.62	28.70	41.92	47.47	39.87	54.00	-14.13 Average


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11n 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB	
1	2386.823	5.47	28.51	41.87	52.98	45.09	74.00	-28.91	peak
2	2390.000	5.47	28.52	41.87	50.05	42.17	74.00	-31.83	peak
3 *	2412.000	5.50	28.56	41.88	91.15	83.33	74.00	9.33	peak


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11n 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	40.39	32.51	54.00	-21.49	Average
2	2390.000	5.47	28.52	41.87	40.39	32.51	54.00	-21.49	Average
3 *	2412.000	5.50	28.56	41.88	83.85	76.03	54.00	22.03	Average


Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11n 20

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line dBuV/m	Over Limit dBuV/m	Over Limit dB	Remark
		MHz	dB	dB/m		dB	dBuV	dBuV/m			
1	2387.791	5.47	28.51	41.87	60.50	52.61	74.00	-21.39	Peak		
2	2390.000	5.47	28.52	41.87	60.13	52.25	74.00	-21.75	Peak		
3 *	2412.000	5.50	28.56	41.88	100.24	92.42	74.00	18.42	Peak		


Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 Band edge  
Note : 2.4G Wifi 11n 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	46.48	38.60	54.00	-15.40	Average
2	2390.000	5.47	28.52	41.87	46.48	38.60	54.00	-15.40	Average
3 *	2412.000	5.50	28.56	41.88	92.54	84.72	54.00	30.72	Average


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11n 20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	93.03	85.34	74.00	11.34 peak
2 2483.500	5.60	28.67	41.91	51.89	44.25	74.00	-29.75 peak
3 2485.145	5.60	28.68	41.91	55.36	47.73	74.00	-26.27 peak


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11n 20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	85.26	77.57	54.00	23.57 Average
2 2483.500	5.60	28.67	41.91	41.72	34.08	54.00	-19.92 Average
3 2496.871	5.62	28.69	41.92	42.24	34.63	54.00	-19.37 Average


Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11n 20

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level		Limit Line	Over Limit	Remark
				dB	dB/m			
MHz								
1 *	2462.000	5.57	28.64	41.90	101.77	94.08	74.00	20.08 Peak
2	2483.500	5.60	28.67	41.91	62.08	54.44	74.00	-19.56 Peak
3	2483.840	5.60	28.67	41.91	63.50	55.86	74.00	-18.14 Peak

Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 Band edge  
Note : 2.4G Wifi 11n 20

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level		Limit Line	Over Limit	Remark
				dB	dB/m			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dBuV/m	dB
1 * 2462.000	5.57	28.64	41.90	93.31	85.62	54.00	31.62	Average
2 2483.500	5.60	28.67	41.91	46.86	39.22	54.00	-14.78	Average
3 2496.921	5.62	28.70	41.92	47.45	39.85	54.00	-14.15	Average

## **7.7 Radiated Spurious Emissions**

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C      Humidity: 56 % RH      Atmospheric Pressure: 1010 mbar

Test mode: b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). Only the data of worst case is recorded in the report.

### 7.7.2 Test Setup Diagram



### **7.7.3 Measurement Procedure and Data**


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

**Radiated emission below 1GHz**

Mode:b; Polarization:Horizontal;




Condition: 3m HORIZONTAL

Job No. : 08447CR

Test mode: b

Freq	Cable	Ant	Preamp	Read	Limit	Over	dB	
	MHz	Loss	Factor	Factor	Level	Level		
1	30.96	0.60	21.95	27.45	23.11	18.21	40.00	-21.79
2	90.22	1.10	13.12	27.36	30.28	17.14	43.50	-26.36
3	104.54	1.21	13.78	27.32	29.46	17.13	43.50	-26.37
4	207.85	1.45	16.78	26.88	32.85	24.20	43.50	-19.30
5	480.53	2.53	24.21	27.53	27.99	27.20	46.00	-18.80
6 pp	830.40	3.33	28.91	27.45	30.39	35.18	46.00	-10.82

Mode:b; Polarization:Vertical



Condition: 3m VERTICAL


Job No. : 08447CR

Test mode: b

Freq	Cable	Ant	Preamp	Read	Limit	Over	Over	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	22.50	27.45	23.53	19.18	40.00	-20.82
2	90.22	1.10	13.12	27.36	27.41	14.27	43.50	-29.23
3	117.36	1.25	13.21	27.25	29.06	16.27	43.50	-27.23
4	207.85	1.45	16.78	26.88	35.19	26.54	43.50	-16.96
5	489.03	2.56	24.38	27.56	27.71	27.09	46.00	-18.91
6 pp	830.40	3.33	28.91	27.45	27.63	32.42	46.00	-13.58

**Transmitter emission above 1GHz**


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 TX RSE  
Note : 2.4G WIFI 11B

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit		Over Limit	Remark
					dB	dBuV	dBuV/m	dBuV/m
1 1542.733	5.42	26.00	41.43	49.02	39.01	74.00	-34.99	peak
2 4456.315	7.51	33.53	42.41	46.43	45.06	74.00	-28.94	peak
3 4824.000	7.91	34.00	42.47	46.76	46.20	74.00	-27.80	peak
4 6249.464	11.06	35.35	41.41	46.45	51.45	74.00	-22.55	peak
5 7236.000	10.07	36.09	40.69	44.69	50.16	74.00	-23.84	peak
6 9648.000	10.77	37.69	37.68	39.19	49.97	74.00	-24.03	peak


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 TX RSE  
Note : 2.4G WIFI 11B

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1542.733	5.42	26.00	41.43	47.72	37.71	74.00	-36.29 peak
2 4456.315	7.51	33.53	42.41	46.57	45.20	74.00	-28.80 peak
3 4824.000	7.91	34.00	42.47	47.55	46.99	74.00	-27.01 peak
4 6470.026	11.48	35.57	41.24	45.32	51.13	74.00	-22.87 peak
5 7236.000	10.07	36.09	40.69	43.70	49.17	74.00	-24.83 peak
6 9648.000	10.77	37.69	37.68	39.88	50.66	74.00	-23.34 peak


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:middle



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2437 TX RSE  
Note : 2.4G WIFI 11B

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark		
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit	
1	1677.621	5.25	26.58	41.52	46.36	36.67	74.00	-37.33	peak
2	4417.841	7.47	33.46	42.40	47.31	45.84	74.00	-28.16	peak
3	4874.000	7.96	34.05	42.48	47.14	46.67	74.00	-27.33	peak
4	6470.026	11.48	35.57	41.24	45.52	51.33	74.00	-22.67	peak
5	7311.000	10.05	36.15	40.64	43.62	49.18	74.00	-24.82	peak
6	9748.000	10.82	37.75	37.54	37.71	48.74	74.00	-25.26	peak


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:middle



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2437 TX RSE  
Note : 2.4G WIFI 11B

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1542.733	5.42	26.00	41.43	46.95	36.94	74.00	-37.06 peak
2 4443.453	7.50	33.50	42.41	46.47	45.06	74.00	-28.94 peak
3 4874.000	7.96	34.05	42.48	47.03	46.56	74.00	-27.44 peak
4 6679.040	11.02	35.71	41.08	45.40	51.05	74.00	-22.95 peak
5 7311.000	10.05	36.15	40.64	43.28	48.84	74.00	-25.16 peak
6 9748.000	10.82	37.75	37.54	38.25	49.28	74.00	-24.72 peak


Mode:b; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 TX RSE  
Note : 2.4G WIFI 11B

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	MHz	Loss	Factor	Factor	Level	Level	
1	1542.733	5.42	26.00	41.43	48.42	38.41	74.00 -35.59 peak
2	4242.641	7.27	33.15	42.37	46.85	44.90	74.00 -29.10 peak
3	4924.000	8.01	34.11	42.49	47.60	47.23	74.00 -26.77 peak
4	6698.373	10.97	35.72	41.07	45.06	50.68	74.00 -23.32 peak
5	7386.000	10.03	36.21	40.59	42.75	48.40	74.00 -25.60 peak
6	9848.000	10.87	37.81	37.41	39.70	50.97	74.00 -23.03 peak


Mode:b; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 TX RSE  
Note : 2.4G WIFI 11B

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line dBuV/m	Over Limit dBuV/m	Over Limit dB	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1533.841	5.44	25.96	41.43	46.65	36.62	74.00	-37.38	peak	
2	4316.859	7.36	33.28	42.38	46.75	45.01	74.00	-28.99	peak	
3	4924.000	8.01	34.11	42.49	47.30	46.93	74.00	-27.07	peak	
4	6358.789	11.27	35.46	41.32	45.65	51.06	74.00	-22.94	peak	
5	7386.000	10.03	36.21	40.59	42.59	48.24	74.00	-25.76	peak	
6	9848.000	10.87	37.81	37.41	39.36	50.63	74.00	-23.37	peak	


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 TX RSE  
Note : 2.4G WIFI 11G

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	46.89	36.88	74.00	-37.12	peak	
2	4430.628	7.48	33.48	42.41	46.83	45.38	74.00	-28.62	peak	
3	4824.000	7.91	34.00	42.47	48.49	47.93	74.00	-26.07	peak	
4	6470.026	11.48	35.57	41.24	44.92	50.73	74.00	-23.27	peak	
5	7236.000	10.07	36.09	40.69	42.91	48.38	74.00	-25.62	peak	
6	9648.000	10.77	37.69	37.68	38.96	49.74	74.00	-24.26	peak	


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 TX RSE  
Note : 2.4G WIFI 11G

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark		
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit	
1	1538.281	5.43	25.98	41.43	47.47	37.45	74.00	-36.55	peak
2	4354.454	7.40	33.35	42.39	46.65	45.01	74.00	-28.99	peak
3	4824.000	7.91	34.00	42.47	47.03	46.47	74.00	-27.53	peak
4	6526.373	11.46	35.62	41.20	44.62	50.50	74.00	-23.50	peak
5	7236.000	10.07	36.09	40.69	43.72	49.19	74.00	-24.81	peak
6	9648.000	10.77	37.69	37.68	39.08	49.86	74.00	-24.14	peak


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:middle



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2437 TX RSE  
Note : 2.4G WIFI 11G

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line dBuV/m	Over Limit dBuV/m	Over Limit dB	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	45.68	35.67	74.00	-38.33	peak	
2	4469.214	7.53	33.55	42.41	47.06	45.73	74.00	-28.27	peak	
3	4874.000	7.96	34.05	42.48	47.55	47.08	74.00	-26.92	peak	
4	6545.263	11.41	35.63	41.18	45.35	51.21	74.00	-22.79	peak	
5	7311.000	10.05	36.15	40.64	44.39	49.95	74.00	-24.05	peak	
6	9748.000	10.82	37.75	37.54	38.71	49.74	74.00	-24.26	peak	


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:middle



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2437 TX RSE  
Note : 2.4G WIFI 11G

Freq	Cable Loss		Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	48.96	38.95	74.00	-35.05	peak
2	4405.090	7.46	33.44	42.40	46.47	44.97	74.00	-29.03	peak
3	4874.000	7.96	34.05	42.48	47.06	46.59	74.00	-27.41	peak
4	6451.353	11.45	35.55	41.25	45.72	51.47	74.00	-22.53	peak
5	7311.000	10.05	36.15	40.64	43.66	49.22	74.00	-24.78	peak
6	9748.000	10.82	37.75	37.54	39.41	50.44	74.00	-23.56	peak


Mode:b; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 TX RSE  
Note : 2.4G WIFI 11G

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark		
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit	
1	1529.414	5.44	25.94	41.43	48.17	38.12	74.00	-35.88	peak
2	4242.641	7.27	33.15	42.37	47.43	45.48	74.00	-28.52	peak
3	4924.000	8.01	34.11	42.49	46.53	46.16	74.00	-27.84	peak
4	6377.195	11.31	35.48	41.31	45.69	51.17	74.00	-22.83	peak
5	7386.000	10.03	36.21	40.59	42.70	48.35	74.00	-25.65	peak
6	9848.000	10.87	37.81	37.41	38.76	50.03	74.00	-23.97	peak


Mode:b; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 TX RSE  
Note : 2.4G WIFI 11G

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark		
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit	
1	1542.733	5.42	26.00	41.43	48.71	38.70	74.00	-35.30	peak
2	3867.831	6.85	32.45	42.30	49.20	46.20	74.00	-27.80	peak
3	4924.000	8.01	34.11	42.49	46.66	46.29	74.00	-27.71	peak
4	6934.778	10.31	35.86	40.90	45.64	50.91	74.00	-23.09	peak
5	7386.000	10.03	36.21	40.59	42.91	48.56	74.00	-25.44	peak
6	9848.000	10.87	37.81	37.41	39.35	50.62	74.00	-23.38	peak


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2412 TX RSE  
Note : 2.4G WIFI 11N 20

Freq	Cable Loss		Ant Factor		Preamp Factor		Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m				dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	47.69	37.68	74.00	74.00	-36.32	peak	
2	4379.699	7.43	33.39	42.40	46.57	44.99	74.00	74.00	-29.01	peak	
3	4824.000	7.91	34.00	42.47	47.30	46.74	74.00	74.00	-27.26	peak	
4	6621.375	11.19	35.67	41.13	45.16	50.89	74.00	74.00	-23.11	peak	
5	7236.000	10.07	36.09	40.69	43.58	49.05	74.00	74.00	-24.95	peak	
6	9648.000	10.77	37.69	37.68	39.74	50.52	74.00	74.00	-23.48	peak	


Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2412 TX RSE  
Note : 2.4G WIFI 11N 20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level	Level	Line	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1542.733	5.42	26.00	41.43	48.05	38.04	74.00	-35.96 peak
2 4443.453	7.50	33.50	42.41	46.11	44.70	74.00	-29.30 peak
3 4824.000	7.91	34.00	42.47	47.55	46.99	74.00	-27.01 peak
4 6507.536	11.52	35.60	41.21	45.41	51.32	74.00	-22.68 peak
5 7236.000	10.07	36.09	40.69	45.06	50.53	74.00	-23.47 peak
6 9648.000	10.77	37.69	37.68	39.79	50.57	74.00	-23.43 peak


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:middle



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2437 TX RSE  
Note : 2.4G WIFI 11N 20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level	Level	Line		
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1542.733	5.42	26.00	41.43	46.02	36.01	74.00	-37.99 peak
2	4469.214	7.53	33.55	42.41	46.26	44.93	74.00	-29.07 peak
3	4874.000	7.96	34.05	42.48	47.15	46.68	74.00	-27.32 peak
4	6340.436	11.24	35.44	41.34	45.62	50.96	74.00	-23.04 peak
5	7311.000	10.05	36.15	40.64	43.89	49.45	74.00	-24.55 peak
6	9748.000	10.82	37.75	37.54	38.42	49.45	74.00	-24.55 peak


Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:middle



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2437 TX RSE  
Note : 2.4G WIFI 11N 20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	MHz	Loss	Factor	Factor	Level	Level	
1	1511.833	5.46	25.85	41.41	45.77	35.67	74.00 -38.33 peak
2	3703.723	6.68	32.12	42.27	48.26	44.79	74.00 -29.21 peak
3	4874.000	7.96	34.05	42.48	46.74	46.27	74.00 -27.73 peak
4	6698.373	10.97	35.72	41.07	45.77	51.39	74.00 -22.61 peak
5	7311.000	10.05	36.15	40.64	43.53	49.09	74.00 -24.91 peak
6	9748.000	10.82	37.75	37.54	38.63	49.66	74.00 -24.34 peak


Mode:b; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 08447CR/08450CR  
Mode : 2462 TX RSE  
Note : 2.4G WIFI 11N 20

Freq	Cable Loss		Ant Factor		Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1542.733	5.42	26.00	41.43	47.68	37.67	74.00	-36.33	peak	
2	4482.150	7.54	33.57	42.41	46.24	44.94	74.00	-29.06	peak	
3	4924.000	8.01	34.11	42.49	47.58	47.21	74.00	-26.79	peak	
4	6621.375	11.19	35.67	41.13	44.87	50.60	74.00	-23.40	peak	
5	7386.000	10.03	36.21	40.59	42.98	48.63	74.00	-25.37	peak	
6	9848.000	10.87	37.81	37.41	38.76	50.03	74.00	-23.97	peak	

Mode:b; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 08447CR/08450CR  
Mode : 2462 TX RSE  
Note : 2.4G WIFI 11N 20

Freq	Cable Loss		Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	47.53	37.52	74.00	-36.48	peak
2	4469.214	7.53	33.55	42.41	46.42	45.09	74.00	-28.91	peak
3	4924.000	8.01	34.11	42.49	46.58	46.21	74.00	-27.79	peak
4	6488.754	11.52	35.59	41.22	44.57	50.46	74.00	-23.54	peak
5	7386.000	10.03	36.21	40.59	42.32	47.97	74.00	-26.03	peak
6	9848.000	10.87	37.81	37.41	38.79	50.06	74.00	-23.94	peak

## 8 Photographs

### 8.1 Test Setup

Please refer to setup photos.

### 8.2 EUT Constructional Details (EUT Photos)


Please Refer to external and internal photos for details.


## **9 Appendix**


### **9.1 Appendix 15.247**


#### **1.6dB Bandwidth**


Test mode:	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
11B	2412	Ant1	8.130	>=0.5	PASS
11B	2437	Ant1	8.130	>=0.5	PASS
11B	2462	Ant1	8.130	>=0.5	PASS
11G	2412	Ant1	16.410	>=0.5	PASS
11G	2437	Ant1	16.410	>=0.5	PASS
11G	2462	Ant1	16.410	>=0.5	PASS
11N20SISO	2412	Ant1	17.370	>=0.5	PASS
11N20SISO	2437	Ant1	17.370	>=0.5	PASS
11N20SISO	2462	Ant1	17.340	>=0.5	PASS













**2. Maximum peak conducted output power**


Test mode:	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
11B	2412	Ant1	13.5	<30	PASS
11B	2437	Ant1	12.32	<30	PASS
11B	2462	Ant1	11.39	<30	PASS
11G	2412	Ant1	17.98	<30	PASS
11G	2437	Ant1	16.64	<30	PASS
11G	2462	Ant1	15.26	<30	PASS
11N20SISO	2412	Ant1	18	<30	PASS
11N20SISO	2437	Ant1	16.45	<30	PASS
11N20SISO	2462	Ant1	15.74	<30	PASS


**3. Maximum Peak power spectral density**


Test mode:	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	Ant1	-13.05	<8.00	PASS
11B	2437	Ant1	-13.62	<8.00	PASS
11B	2462	Ant1	-14.59	<8.00	PASS
11G	2412	Ant1	-15.72	<8.00	PASS
11G	2437	Ant1	-17.14	<8.00	PASS
11G	2462	Ant1	-18.51	<8.00	PASS
11N20SISO	2412	Ant1	-15.29	<8.00	PASS
11N20SISO	2437	Ant1	-16.41	<8.00	PASS
11N20SISO	2462	Ant1	-17.42	<8.00	PASS














**4. Band-edge for RF Conducted Emissions**

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
11B	2412	Ant1	1.540	-50.641	<-18.46	PASS
11B	2462	Ant1	-0.550	-48.423	<-20.55	PASS
11G	2412	Ant1	-2.120	-37.669	<-22.12	PASS
11G	2462	Ant1	-4.600	-39.139	<-24.6	PASS
11N20SISO	2412	Ant1	-2.140	-36.364	<-22.14	PASS
11N20SISO	2462	Ant1	-3.800	-34.992	<-23.8	PASS











**5.RF Conducted Spurious Emissions**


Test mode:	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
11B	2412	30	10000	1000	3000	1.65	-25.130	<-18.35	PASS
11B	2412	10000	25000	1000	3000	1.65	-55.210	<-18.35	PASS
11B	2437	30	10000	1000	3000	0.51	-25.870	<-19.49	PASS
11B	2437	10000	25000	1000	3000	0.51	-55.460	<-19.49	PASS
11B	2462	30	10000	1000	3000	-0.6	-26.590	<-20.6	PASS
11B	2462	10000	25000	1000	3000	-0.6	-55.250	<-20.6	PASS
11G	2412	30	10000	1000	3000	-1.93	-27.490	<-21.93	PASS
11G	2412	10000	25000	1000	3000	-1.93	-55.310	<-21.93	PASS
11G	2437	30	10000	1000	3000	-3.33	-27.640	<-23.33	PASS
11G	2437	10000	25000	1000	3000	-3.33	-55.030	<-23.33	PASS
11G	2462	30	10000	1000	3000	-5.26	-30.850	<-25.26	PASS
11G	2462	10000	25000	1000	3000	-5.26	-54.770	<-25.26	PASS
11N20SISO	2412	30	10000	1000	3000	-1.41	-29.270	<-21.41	PASS
11N20SISO	2412	10000	25000	1000	3000	-1.41	-55.410	<-21.41	PASS
11N20SISO	2437	30	10000	1000	3000	-3.14	-28.100	<-23.14	PASS
11N20SISO	2437	10000	25000	1000	3000	-3.14	-55.400	<-23.14	PASS
11N20SISO	2462	30	10000	1000	3000	-4.16	-30.250	<-24.16	PASS
11N20SISO	2462	10000	25000	1000	3000	-4.16	-55.690	<-24.16	PASS



RF Conducted Spurious Emissions\_11B\_2412\_Ant1


































## RF Conducted Spurious Emissions\_11N20SISO\_2437\_Ant1









- End of the Report -