

**TALITOR (FAR EAST) COMPANY LIMITED
6F.-6,NO.646,Sec.5,Chongsin Rd., Sanchong
Dist.,New Taipei City 241,Taiwan**

FCC Modular Approval Request

Number:**CF305**

Version: **V04**

Date: 07-08-2012

To the FCC or FCC TCB handling this application

Hereby we,

Company name (grantee) TALITOR (FAR EAST) COMPANY LIMITED
Addresss 6F.-6,NO.646,Sec.5,Chongsin Rd., Sanchong Dist.
City / ZIP / State / Country New Taipei City 241,Taiwan

request **modular approval** for the certification of our equipment within this application, identified by:

FCC ID: RBA-EZSEE

The table below contains the justification for modular approval of this equipment:

Requirement per 15.212 and KDB 996369 D01 Module Certification Guide v01r03	Explanation from grantee (do not write yes / no, but explain why it complies / how it is achieved)
1. The modular transmitter must have its own RF shielding.	<u>Module has its own shielding</u>
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	<u>Module is buffered</u>
3. The modular transmitter must have its own power supply regulation.	<u>Module has its own power stabilization internally</u>
4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable)..	<u>Module uses external swivel antenna</u>
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed.	<u>Module was teste stand alone on a bear test board</u>
6. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	<u>User manual contains instructions to label the host device containing this module as follows: Contains FCC ID: RBA-EZSEE</u>
7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	<u>Specific installation instructions are provided in the user manual for this module</u>
8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, U-NII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.	<u>Module certified to 15.249 and with the swivel antenna filed, it remains under the emission limit of this rule part.</u>

Attestation (by grantee)

City and Country:	Date:	Name: (this must be a person)	Function:	Signature: (or official company stamp)
<u>Enschede, The Neterlands</u>	<u>2012-11-09</u>	<u>M. Koop (authorized)</u>	<u>Manager</u>	