

FCC PART 15B
ICES-003, ISSUE 6, JANUARY 2016

TEST REPORT

For

Shenzhen Jingwah Information Technology Co., Ltd.

4F, Bldg 4, Jinghua Square, No.1 Huafa North Road, Futian District, Shenzhen, China

FCC ID: RBD-S5003L
Tested Model: S5003L
Multiple Model: A5000-PB

Report Type: Original Report	Product Type: Smart Phone
Report Number:	RGMA181226002-00A
Report Date:	2019-01-18
Reviewed By:	Jerry Zhang EMC Manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

General Information	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
System Test Configuration	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	6
TEST EQUIPMENT LIST	7
ENVIRONMENTAL CONDITIONS	7
Summary of Test Results	8
Conducted emissions	9
EUT SETUP	9
EMI TEST RECEIVER SETUP	9
TEST PROCEDURE	9
TEST DATA	11
Radiated emissions	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST DATA	15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Smart Phone
EUT Model:		S5003L
Multiple Model:		A5000-PB
Rated Input Voltage:		DC3.7V from Battery or DC5V from adapter
Adapter Information	Model:	TPA-95A050100UU
	Input:	AC 100-240V, 50/60Hz, 0.15A
	Output:	DC5V, 1000mA
The Highest Operating Frequency:		5825MHz
External Dimension:		146mm(L)* 73mm(W)*11mm(H)
Serial Number:		181226002
EUT Received Date:		2019.01.03

Note: The series product model A5000-PB is electrically identical with model S5003L, we selected S5003L for fully testing, the differences details was explained in the declaration letter.

Objective

This report is prepared on behalf of **Shenzhen Jingwah Information Technology Co., Ltd.** in accordance with FCC Part 15B Part 2, subpart J, and Part 15, Subpart A and B of the Federal Communications Commission's rules, and ICES-003, Issue 6, January 2016 Information Technology Equipment (Including Digital Apparatus) — Limits and Methods of Measurement.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B, and ICES-003, Issue 6, January 2016.

Related Submittal(s)/Grant(s)

FCC Part 22H, 24E,27 PCE submissions with FCC ID: RBD-S5003L.
FCC Part 15C DTS submissions with FCC ID: RBD-S5003L.
FCC Part 15C DSS submissions with FCC ID: RBD-S5003L.
FCC Part 15E NII submissions with FCC ID: RBD-S5003L.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in downloading mode.

Equipment Modifications

No modification was made to the EUT.

EUT Exercise Software

The software "Winthrax.exe" was used during test.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	1CVM0C1
SAST	modem	AEM-2100	90200213
DELL	Keyboard	SK-8115	CN-0J4628-71616-52H-0RT6
HP	Printer	C3941A	JPTV013237

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Serial Cable	yes	No	1.2	Serial Port of Laptop	Modem
Parallel Cable	yes	No	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	yes	yes	1.8	USB Port of Laptop	Keyboard
USB Cable	No	No	1.0	USB Port of Laptop	EUT
Earphone Cable	No	No	1.0	EUT	Earphone

Block Diagram of Test Setup



Test Equipment List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emissions					
R&S	EMI Test Receiver	ESCS 30	830245/006	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10
R&S	L.I.S.N	ESH2-Z5	892107/021	2018-09-19	2019-09-19
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
Radiated emissions Below 1GHz					
R&S	EMI Test Receiver	ESCI	100224	2018-12-10	2019-12-10
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2018-05-06	2019-05-06
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiated emissions Above 1GHz					
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-01-04	2020-01-04
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2018-06-27	2019-06-27
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2018-09-05	2019-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2018-06-27	2019-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Environmental Conditions


Test Item:	Conducted emissions	Radiated emissions Below 1GHz	Radiated emissions Above 1GHz
Test Date:	2019-01-08	2019-01-10	2019-01-10
Tester:	Lily Xie	Neil Liao	Kami Zhou
Temperature:	23.1°C	25.1°C	25.1°C
Relative Humidity:	48%	53%	48~53%
ATM Pressure:	100.2kPa	101.1kPa	101.1kPa

SUMMARY OF TEST RESULTS

Rule and Clause	Description of Test	Test Result
FCC §15.107 ICES-003 Clause 6.1	Conducted emissions	Compliance
FCC §15.109 ICES-003 Clause 6.2	Radiated emissions	Compliance

CONDUCTED EMISSIONS

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B and Innovation, Science and Economic Development Canada ICES-003 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to the Main LISN with 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the PC was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN


The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Please refer to following table and plots:

Model Number: S5003L
 Port: L
 Test Mode: Downloading
 Power Source: AC120V/60Hz




Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.150000	48.6	9.000	L1	11.2	17.4	66.0
0.156097	45.1	9.000	L1	11.1	20.6	65.7
0.190505	57.4	9.000	L1	10.7	6.6	64.0
0.193566	58.2	9.000	L1	10.7	5.7	63.9
0.209621	55.7	9.000	L1	10.6	7.5	63.2
0.212988	52.0	9.000	L1	10.5	11.1	63.1

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.190505	32.1	9.000	L1	10.7	21.9	54.0
0.193566	44.2	9.000	L1	10.7	9.7	53.9
0.207957	39.1	9.000	L1	10.6	14.2	53.3
0.212988	28.0	9.000	L1	10.5	25.1	53.1
0.257874	24.7	9.000	L1	10.3	26.8	51.5
4.193667	27.2	9.000	L1	9.8	18.8	46.0

Model Number: S5003L
Port: N
Test Mode: Downloading
Power Source: AC120V/60Hz



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.187494	55.1	9.000	N	10.7	9.0	64.1
0.190505	59.3	9.000	N	10.7	4.7	64.0
0.193566	60.3	9.000	N	10.7	3.6	63.9
0.209621	57.6	9.000	N	10.5	5.6	63.2
0.214692	50.4	9.000	N	10.5	12.6	63.0
0.255827	49.1	9.000	N	10.3	12.5	61.6


Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.187494	29.9	9.000	N	10.7	24.2	54.1
0.193566	41.4	9.000	N	10.7	12.5	53.9
0.198249	39.2	9.000	N	10.6	14.5	53.7
0.211298	30.4	9.000	N	10.5	22.8	53.2
0.262017	32.2	9.000	N	10.3	19.2	51.4
4.399032	29.6	9.000	N	9.8	16.4	46.0


RADIATED EMISSIONS

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, 1GHz-26.5GHz were performed at the 3 m distance and 26.5-40 GHz was performed at 1 m distance, using the setup accordance with the ANSI C63.4-2014. The specification used was with the FCC Part 15 B and Innovation, Science and Economic Development Canada ICES-003 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 30 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	Reduced video bandwidth	/	AVG

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

During the radiated emissions, the adapter of laptop was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

According to C63.4, the above 1G test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 1 m

Distance extrapolation factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1m]})$ dB = 9.54 dB

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Meter Reading+ Corrected

Note:

Corrected = Antenna Factor + Cable Loss - Amplifier Gain

or

Corrected = Antenna Factor + Cable Loss + Insertion loss of attenuator - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Limit} - \text{Result}$$

Test Data

Please refer to following table and plots:

Condition: FCC Part 15B Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
30.9700	27.00	peak	0.95	27.95	40.00	12.05
42.6100	34.80	peak	-7.61	27.19	40.00	12.81
234.6700	40.69	peak	-6.26	34.43	46.00	11.57
395.6900	36.67	peak	-2.07	34.60	46.00	11.40
637.2200	32.06	peak	2.20	34.26	46.00	11.74
704.1500	30.05	peak	3.13	33.18	46.00	12.82

Condition: FCC Part 15B Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Vertical
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
30.9700	27.28	peak	0.95	28.23	40.00	11.77
123.1200	32.47	peak	-4.54	27.93	43.50	15.57
235.6400	39.94	peak	-6.18	33.76	46.00	12.24
366.5900	35.66	peak	-2.79	32.87	46.00	13.13
394.7200	35.21	peak	-2.08	33.13	46.00	12.87
607.1500	35.56	peak	1.12	36.68	46.00	9.32

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1595.000	52.75	peak	-8.74	44.01	74.00	29.99
1595.000	40.55	AVG	-8.74	31.81	54.00	22.19
2305.000	51.21	peak	-6.77	44.44	74.00	29.56
2305.000	39.17	AVG	-6.77	32.40	54.00	21.60
5700.000	46.97	peak	0.51	47.48	74.00	26.52
5700.000	34.73	AVG	0.51	35.24	54.00	18.76

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Vertical
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1500.000	55.87	peak	-9.12	46.75	74.00	27.25
1500.000	43.23	AVG	-9.12	34.11	54.00	19.89
2402.500	55.61	peak	-6.51	49.10	74.00	24.90
2402.500	43.19	AVG	-6.51	36.68	54.00	17.32
6000.000	46.28	peak	0.80	47.08	74.00	26.92
6000.000	34.11	AVG	0.80	34.91	54.00	19.09

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
17934.000	44.46	peak	16.68	61.14	74.00	12.86
17934.000	30.10	AVG	16.68	46.78	54.00	7.22

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Vertical
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
18000.000	42.78	peak	17.15	59.93	74.00	14.07
18000.000	30.13	AVG	17.15	47.28	54.00	6.72

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
26482.966	40.36	peak	21.76	62.12	74.00	11.88
26482.966	25.21	AVG	21.76	46.97	54.00	7.03

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Vertical
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
26431.864	40.40	peak	21.54	61.94	74.00	12.06
26431.864	24.16	AVG	21.54	45.70	54.00	8.30

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading


Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 1m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
29901.804	40.67	peak	25.56	66.23	74.00	7.77
29901.804	19.21	AVG	25.56	44.77	54.00	9.23

Condition: FCC Part 15 Class B
EUT: Smart Phone
Model: S5003L
Test Mode: Downloading

Polarization: Vertical
Power: AC 120V/60Hz
Distance: 1m



Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
29901.804	40.17	peak	25.56	65.73	74.00	8.27
29901.804	20.41	AVG	25.56	45.97	54.00	8.03

*****END OF REPORT*****