





Profile: 2390782R	Page No.: 296
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:35
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5240MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	48.251	51.530	-25.749	74.000	-3.279	PK
2	*	15720.000	52.173	50.653	-21.827	74.000	1.520	PK




Profile: 2390782R	Page No.: 297
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:35
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5260MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10520.000	47.813	51.052	-26.187	74.000	-3.239	PK
2	*	15780.000	51.396	50.138	-22.604	74.000	1.257	PK




Profile: 2390782R	Page No.: 298
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5260MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10520.000	46.396	49.635	-27.604	74.000	-3.239	PK
2	*	15780.000	51.312	50.054	-22.688	74.000	1.257	PK




Profile: 2390782R	Page No.: 299
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5300MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10600.000	48.517	51.219	-25.483	74.000	-2.702	PK
2	*	15900.000	51.186	49.119	-22.814	74.000	2.067	PK

Profile: 2390782R	Page No.: 300
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5300MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10600.000	48.680	51.382	-25.320	74.000	-2.702	PK
2	*	15900.000	51.283	49.216	-22.717	74.000	2.067	PK


Profile: 2390782R	Page No.: 301
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5320MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10640.000	48.206	51.570	-25.794	74.000	-3.364	PK
2	*	15960.000	52.300	51.167	-21.700	74.000	1.133	PK




Profile: 2390782R	Page No.: 302
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5320MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10640.000	47.700	51.064	-26.300	74.000	-3.364	PK
2	*	15960.000	51.027	49.894	-22.973	74.000	1.133	PK

Profile: 2390782R	Page No.: 303
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5500MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11000.000	47.597	49.485	-26.403	74.000	-1.888	PK
2	*	16500.000	52.116	47.183	-21.884	74.000	4.933	PK

Profile: 2390782R	Page No.: 304
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5500MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11000.000	47.306	49.194	-26.694	74.000	-1.888	PK
2	*	16500.000	51.852	46.919	-22.148	74.000	4.933	PK

Profile: 2390782R	Page No.: 305
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5580MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11160.000	48.277	49.462	-25.723	74.000	-1.185	PK
2	*	16740.000	52.201	48.143	-21.799	74.000	4.058	PK

Profile: 2390782R	Page No.: 306
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5580MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11160.000	48.504	49.689	-25.496	74.000	-1.185	PK
2	*	16740.000	52.486	48.428	-21.514	74.000	4.058	PK


Profile: 2390782R	Page No.: 307
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5700MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11400.000	47.847	48.889	-26.153	74.000	-1.042	PK
2	*	17100.000	54.228	49.441	-19.772	74.000	4.787	PK




Profile: 2390782R	Page No.: 308
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5700MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11400.000	48.637	49.679	-25.363	74.000	-1.042	PK
2	*	17100.000	52.730	47.943	-21.270	74.000	4.787	PK




Profile: 2390782R	Page No.: 309
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:36
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5745MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	48.276	48.800	-25.724	74.000	-0.524	PK
2	*	17235.000	53.753	48.316	-20.247	74.000	5.437	PK

Profile: 2390782R	Page No.: 310
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5745MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	49.264	49.788	-24.736	74.000	-0.524	PK
2	*	17235.000	53.375	47.938	-20.625	74.000	5.437	PK

Profile: 2390782R	Page No.: 311
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5785MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	47.192	48.381	-26.808	74.000	-1.189	PK
2	*	17355.000	52.310	47.848	-21.690	74.000	4.461	PK


Profile: 2390782R	Page No.: 312
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5785MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	47.893	49.082	-26.107	74.000	-1.189	PK
2	*	17355.000	51.696	47.234	-22.304	74.000	4.461	PK




Profile: 2390782R	Page No.: 313
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5825MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	46.972	48.648	-27.028	74.000	-1.676	PK
2	*	17475.000	53.079	48.885	-20.921	74.000	4.195	PK

Profile: 2390782R	Page No.: 314
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 8 : Transmit at 5825MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	46.715	48.391	-27.285	74.000	-1.676	PK
2	*	17475.000	52.700	48.506	-21.300	74.000	4.195	PK


Profile: 2390782R	Page No.: 315
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5190MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	47.825	51.030	-26.175	74.000	-3.205	PK
2	*	15570.000	49.582	49.288	-24.418	74.000	0.294	PK




Profile: 2390782R	Page No.: 316
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5190MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	48.028	51.233	-25.972	74.000	-3.205	PK
2	*	15570.000	49.647	49.353	-24.353	74.000	0.294	PK




Profile: 2390782R	Page No.: 317
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5230MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	48.040	51.380	-25.960	74.000	-3.341	PK
2	*	15690.000	50.258	49.982	-23.742	74.000	0.276	PK




Profile: 2390782R	Page No.: 318
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5230MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	47.924	51.264	-26.076	74.000	-3.341	PK
2	*	15690.000	51.137	50.861	-22.863	74.000	0.276	PK




Profile: 2390782R	Page No.: 319
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5270MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10540.000	47.756	50.966	-26.244	74.000	-3.210	PK
2	*	15810.000	51.243	50.177	-22.757	74.000	1.066	PK


Profile: 2390782R	Page No.: 320
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5270MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10540.000	47.773	50.983	-26.227	74.000	-3.210	PK
2	*	15810.000	50.208	49.142	-23.792	74.000	1.066	PK




Profile: 2390782R	Page No.: 321
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5310MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10620.000	47.536	50.752	-26.464	74.000	-3.217	PK
2	*	15930.000	50.741	49.550	-23.259	74.000	1.191	PK


Profile: 2390782R	Page No.: 322
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:37
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5310MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10620.000	47.253	50.469	-26.747	74.000	-3.217	PK
2	*	15930.000	50.175	48.984	-23.825	74.000	1.191	PK




Profile: 2390782R	Page No.: 323
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5510MHz by 802.11ax(40MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11020.000	46.920	49.022	-27.080	74.000	-2.102	PK
2	*	16530.000	51.862	47.584	-22.138	74.000	4.278	PK

Profile: 2390782R	Page No.: 324
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5510MHz by 802.11ax(40MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11020.000	47.514	49.616	-26.486	74.000	-2.102	PK
2	*	16530.000	51.754	47.476	-22.246	74.000	4.278	PK

Profile: 2390782R	Page No.: 325
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5590MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11180.000	47.126	49.359	-26.874	74.000	-2.234	PK
2	*	16770.000	53.165	48.160	-20.835	74.000	5.005	PK


Profile: 2390782R	Page No.: 326
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5590MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11180.000	46.898	49.131	-27.102	74.000	-2.234	PK
2	*	16770.000	53.361	48.356	-20.639	74.000	5.005	PK




Profile: 2390782R	Page No.: 327
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5670MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11340.000	47.253	48.624	-26.747	74.000	-1.371	PK
2	*	17010.000	51.917	47.752	-22.083	74.000	4.165	PK




Profile: 2390782R	Page No.: 328
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5670MHz by 802.11ax(40MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11340.000	46.908	48.279	-27.092	74.000	-1.371	PK
2	*	17010.000	51.082	46.917	-22.918	74.000	4.165	PK

Profile: 2390782R	Page No.: 329
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5755MHz by 802.11ax(40MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	47.747	49.025	-26.253	74.000	-1.278	PK
2	*	17265.000	51.332	47.919	-22.668	74.000	3.412	PK

Profile: 2390782R	Page No.: 330
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5755MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	47.425	48.703	-26.575	74.000	-1.278	PK
2	*	17265.000	51.635	48.222	-22.365	74.000	3.412	PK


Profile: 2390782R	Page No.: 331
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5795MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	48.161	48.060	-25.839	74.000	0.101	PK
2	*	17385.000	51.600	48.268	-22.400	74.000	3.332	PK




Profile: 2390782R	Page No.: 332
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 9 : Transmit at 5795MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	48.325	48.224	-25.675	74.000	0.101	PK
2	*	17385.000	51.231	47.899	-22.769	74.000	3.332	PK


Profile: 2390782R	Page No.: 333
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5210MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10420.000	48.032	51.028	-25.968	74.000	-2.996	PK
2	*	15630.000	50.925	49.693	-23.075	74.000	1.232	PK




Profile: 2390782R	Page No.: 334
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5210MHz by 802.11ax(80MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10420.000	47.752	50.748	-26.248	74.000	-2.996	PK
2	*	15630.000	51.652	50.420	-22.348	74.000	1.232	PK

Profile: 2390782R	Page No.: 335
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:38
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5290MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10580.000	49.038	52.054	-24.962	74.000	-3.015	PK
2	*	15870.000	51.363	49.508	-22.637	74.000	1.855	PK


Profile: 2390782R	Page No.: 336
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5290MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10580.000	48.899	51.915	-25.101	74.000	-3.015	PK
2	*	15870.000	52.419	50.564	-21.581	74.000	1.855	PK




Profile: 2390782R	Page No.: 337
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5530MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11060.000	46.534	48.679	-27.466	74.000	-2.145	PK
2	*	16590.000	52.226	48.038	-21.774	74.000	4.189	PK




Profile: 2390782R	Page No.: 338
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5530MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11060.000	45.710	47.855	-28.290	74.000	-2.145	PK
2	*	16590.000	51.651	47.463	-22.349	74.000	4.189	PK


Profile: 2390782R	Page No.: 339
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5775MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11550.000	46.769	48.329	-27.231	74.000	-1.560	PK
2	*	17265.000	51.424	48.011	-22.576	74.000	3.412	PK




Profile: 2390782R	Page No.: 340
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 10 : Transmit at 5775MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11550.000	46.525	48.085	-27.475	74.000	-1.560	PK
2	*	17325.000	51.300	47.750	-22.700	74.000	3.549	PK


Profile: 2390782R	Page No.: 345
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 11 : Transmit at 5250MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10500.000	47.393	50.437	-26.607	74.000	-3.044	PK
2	*	15750.000	52.402	50.846	-21.598	74.000	1.557	PK




Profile: 2390782R	Page No.: 346
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 11 : Transmit at 5250MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10500.000	48.692	51.736	-25.308	74.000	-3.044	PK
2	*	15750.000	51.748	50.192	-22.252	74.000	1.557	PK




Profile: 2390782R	Page No.: 347
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 11 : Transmit at 5570MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11140.000	47.771	49.033	-26.229	74.000	-1.262	PK
2	*	16710.000	53.376	48.589	-20.624	74.000	4.787	PK

Profile: 2390782R	Page No.: 348
Engineer: Yuliu	
Site: AC5	Time: 2024/06/25 - 19:39
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 11 : Transmit at 5570MHz by 802.11ax(160MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11140.000	47.700	48.962	-26.300	74.000	-1.262	PK
2	*	16710.000	53.186	48.399	-20.814	74.000	4.787	PK



U-NII 5 / 6 / 7 / 8


Profile: 2390782R	Page No.: 89
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:49
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 5955MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11910.000	47.438	47.288	-26.562	74.000	0.149	PK
2	*	17865.000	52.242	46.574	-21.758	74.000	5.667	PK




Profile: 2390782R	Page No.: 90
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:49
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 5955MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11910.000	47.486	47.336	-26.514	74.000	0.149	PK
2	*	17865.000	52.707	47.039	-21.293	74.000	5.667	PK

Profile: 2390782R	Page No.: 91
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6175MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12350.000	48.935	48.583	-25.065	74.000	0.352	PK

Profile: 2390782R	Page No.: 92
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6175MHz by 802.11ax(20MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12350.000	49.240	48.888	-24.760	74.000	0.352	PK

Profile: 2390782R	Page No.: 93
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6415MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12830.000	50.062	48.678	-23.938	74.000	1.384	PK


Profile: 2390782R	Page No.: 94
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6415MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12830.000	50.080	48.696	-23.920	74.000	1.384	PK




Profile: 2390782R	Page No.: 95
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6435MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12870.000	50.116	49.913	-23.884	74.000	0.203	PK




Profile: 2390782R	Page No.: 96
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6435MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12870.000	49.194	48.991	-24.806	74.000	0.203	PK


Profile: 2390782R	Page No.: 97
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6475MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12950.000	50.201	49.378	-23.799	74.000	0.822	PK




Profile: 2390782R	Page No.: 98
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6475MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12950.000	50.143	49.320	-23.857	74.000	0.822	PK




Profile: 2390782R	Page No.: 99
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:50
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6515MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13030.000	50.995	49.272	-23.005	74.000	1.723	PK




Profile: 2390782R	Page No.: 100
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6515MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13030.000	51.089	49.366	-22.911	74.000	1.723	PK




Profile: 2390782R	Page No.: 101
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6535MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13070.000	49.252	49.236	-24.748	74.000	0.016	PK


Profile: 2390782R	Page No.: 102
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6535MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13070.000	48.601	48.585	-25.399	74.000	0.016	PK




Profile: 2390782R	Page No.: 103
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6695MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13390.000	49.860	48.915	-24.140	74.000	0.945	PK




Profile: 2390782R	Page No.: 104
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6695MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13390.000	49.650	48.705	-24.350	74.000	0.945	PK




Profile: 2390782R	Page No.: 105
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6855MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13710.000	51.250	49.037	-22.750	74.000	2.212	PK




Profile: 2390782R	Page No.: 106
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6855MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13710.000	52.386	50.173	-21.614	74.000	2.212	PK




Profile: 2390782R	Page No.: 107
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6875MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13750.000	53.038	48.352	-20.962	74.000	4.686	PK




Profile: 2390782R	Page No.: 108
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6875MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13750.000	53.172	48.486	-20.828	74.000	4.686	PK




Profile: 2390782R	Page No.: 109
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6895MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13790.000	51.546	49.540	-22.454	74.000	2.006	PK




Profile: 2390782R	Page No.: 110
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6895MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13790.000	51.061	49.055	-22.939	74.000	2.006	PK




Profile: 2390782R	Page No.: 111
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6995MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13990.000	52.595	50.405	-21.405	74.000	2.191	PK




Profile: 2390782R	Page No.: 112
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 6995MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13990.000	50.729	48.539	-23.271	74.000	2.191	PK




Profile: 2390782R	Page No.: 113
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:51
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 7115MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	14230.000	50.822	49.520	-23.178	74.000	1.303	PK




Profile: 2390782R	Page No.: 114
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 7115MHz by 802.11ax(20MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	14230.000	51.262	49.960	-22.738	74.000	1.303	PK




Profile: 2390782R	Page No.: 115
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 5965MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11930.000	47.776	46.981	-26.224	74.000	0.795	PK
2	*	17895.000	49.481	46.402	-24.519	74.000	3.078	PK


Profile: 2390782R	Page No.: 116
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 5965MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11930.000	49.889	49.094	-24.111	74.000	0.795	PK
2	*	17895.000	51.225	48.146	-22.775	74.000	3.078	PK




Profile: 2390782R	Page No.: 117
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6165MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12330.000	50.084	49.342	-23.916	74.000	0.742	PK


Profile: 2390782R	Page No.: 118
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6165MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12330.000	49.657	48.915	-24.343	74.000	0.742	PK




Profile: 2390782R	Page No.: 119
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6405MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12810.000	50.052	49.133	-23.948	74.000	0.918	PK


Profile: 2390782R	Page No.: 120
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6405MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12810.000	49.743	48.824	-24.257	74.000	0.918	PK




Profile: 2390782R	Page No.: 121
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6445MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12890.000	48.943	48.148	-25.057	74.000	0.794	PK




Profile: 2390782R	Page No.: 122
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6445MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12890.000	49.850	49.055	-24.150	74.000	0.794	PK


Profile: 2390782R	Page No.: 123
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6485MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12970.000	50.871	49.709	-23.129	74.000	1.162	PK




Profile: 2390782R	Page No.: 124
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6485MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12970.000	50.379	49.217	-23.621	74.000	1.162	PK




Profile: 2390782R	Page No.: 125
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6525MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13050.000	48.840	47.973	-25.160	74.000	0.867	PK




Profile: 2390782R	Page No.: 126
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6525MHz by 802.11ax(40MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13050.000	49.907	49.040	-24.093	74.000	0.867	PK

Profile: 2390782R	Page No.: 127
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6565MHz by 802.11ax(40MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13130.000	50.588	49.433	-23.412	74.000	1.154	PK

Profile: 2390782R	Page No.: 128
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:52
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6565MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13130.000	50.417	49.262	-23.583	74.000	1.154	PK


Profile: 2390782R	Page No.: 129
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6685MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13370.000	51.005	48.783	-22.995	74.000	2.222	PK




Profile: 2390782R	Page No.: 130
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6685MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13370.000	51.927	49.705	-22.073	74.000	2.222	PK


Profile: 2390782R	Page No.: 131
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6845MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13690.000	50.283	48.731	-23.717	74.000	1.553	PK




Profile: 2390782R	Page No.: 132
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6845MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13690.000	49.788	48.236	-24.212	74.000	1.553	PK




Profile: 2390782R	Page No.: 133
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6885MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13770.000	51.930	49.364	-22.070	74.000	2.566	PK


Profile: 2390782R	Page No.: 134
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6885MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13770.000	51.194	48.628	-22.806	74.000	2.566	PK




Profile: 2390782R	Page No.: 135
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6925MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13850.000	51.618	50.316	-22.382	74.000	1.302	PK




Profile: 2390782R	Page No.: 136
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6925MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13850.000	51.128	49.826	-22.872	74.000	1.302	PK




Profile: 2390782R	Page No.: 137
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6965MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13930.000	50.650	49.558	-23.350	74.000	1.092	PK




Profile: 2390782R	Page No.: 138
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 6965MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13930.000	50.215	49.123	-23.785	74.000	1.092	PK




Profile: 2390782R	Page No.: 139
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 7085MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	14170.000	50.113	49.699	-23.887	74.000	0.414	PK




Profile: 2390782R	Page No.: 140
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 2 : Transmit at 7085MHz by 802.11ax(40MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	14170.000	49.099	48.685	-24.901	74.000	0.414	PK




Profile: 2390782R	Page No.: 141
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 5985MHz by 802.11ax(80MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11970.000	49.279	48.490	-24.721	74.000	0.788	PK
2	*	17955.000	53.562	48.101	-20.438	74.000	5.462	PK

Profile: 2390782R	Page No.: 142
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:53
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 5985MHz by 802.11ax(80MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11970.000	50.135	49.346	-23.865	74.000	0.788	PK
2	*	17955.000	52.739	47.278	-21.261	74.000	5.462	PK

Profile: 2390782R	Page No.: 143
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6145MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12290.000	50.623	49.606	-23.377	74.000	1.017	PK


Profile: 2390782R	Page No.: 144
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6145MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12290.000	49.618	48.601	-24.382	74.000	1.017	PK




Profile: 2390782R	Page No.: 145
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6385MHz by 802.11ax(80MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12770.000	47.917	49.139	-26.083	74.000	-1.221	PK

Profile: 2390782R	Page No.: 146
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6385MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12770.000	48.073	49.295	-25.927	74.000	-1.221	PK


Profile: 2390782R	Page No.: 147
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6465MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12930.000	51.131	49.073	-22.869	74.000	2.058	PK




Profile: 2390782R	Page No.: 148
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6465MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12930.000	50.397	48.339	-23.603	74.000	2.058	PK




Profile: 2390782R	Page No.: 149
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6545MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13090.000	52.102	50.358	-21.898	74.000	1.744	PK




Profile: 2390782R	Page No.: 150
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6545MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13090.000	52.705	50.961	-21.295	74.000	1.744	PK




Profile: 2390782R	Page No.: 151
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6625MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13250.000	50.748	49.576	-23.252	74.000	1.173	PK




Profile: 2390782R	Page No.: 152
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6625MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13250.000	51.386	50.214	-22.614	74.000	1.173	PK




Profile: 2390782R	Page No.: 153
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6705MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13410.000	49.513	49.099	-24.487	74.000	0.414	PK




Profile: 2390782R	Page No.: 154
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6705MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13410.000	49.855	49.441	-24.145	74.000	0.414	PK




Profile: 2390782R	Page No.: 155
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6785MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13570.000	50.624	50.041	-23.376	74.000	0.582	PK




Profile: 2390782R	Page No.: 156
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:54
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6785MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13570.000	49.996	49.413	-24.004	74.000	0.582	PK




Profile: 2390782R	Page No.: 157
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6865MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13730.000	51.646	48.513	-22.354	74.000	3.133	PK




Profile: 2390782R	Page No.: 158
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6865MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13730.000	51.878	48.745	-22.122	74.000	3.133	PK


Profile: 2390782R	Page No.: 159
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6945MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13890.000	49.501	48.431	-24.499	74.000	1.069	PK




Profile: 2390782R	Page No.: 160
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 6945MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13890.000	50.580	49.510	-23.420	74.000	1.069	PK




Profile: 2390782R	Page No.: 161
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 7025MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	14050.000	52.220	48.595	-21.780	74.000	3.626	PK




Profile: 2390782R	Page No.: 162
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 3 : Transmit at 7025MHz by 802.11ax(80MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	14050.000	52.734	49.109	-21.266	74.000	3.626	PK




Profile: 2390782R	Page No.: 163
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6025MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12050.000	49.698	49.340	-24.302	74.000	0.358	PK


Profile: 2390782R	Page No.: 164
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6025MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12050.000	48.200	47.842	-25.800	74.000	0.358	PK




Profile: 2390782R	Page No.: 165
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6185MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12370.000	50.958	49.456	-23.042	74.000	1.503	PK


Profile: 2390782R	Page No.: 166
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6185MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12370.000	50.437	48.935	-23.563	74.000	1.503	PK




Profile: 2390782R	Page No.: 167
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6345MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12690.000	49.073	48.749	-24.927	74.000	0.324	PK


Profile: 2390782R	Page No.: 168
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6345MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	12690.000	49.803	49.479	-24.197	74.000	0.324	PK




Profile: 2390782R	Page No.: 169
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:55
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6505MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13010.000	50.330	49.329	-23.670	74.000	1.001	PK




Profile: 2390782R	Page No.: 170
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6505MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13010.000	51.893	50.892	-22.107	74.000	1.001	PK




Profile: 2390782R	Page No.: 171
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6665MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13330.000	50.187	49.565	-23.813	74.000	0.622	PK




Profile: 2390782R	Page No.: 172
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6665MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13330.000	50.309	49.687	-23.691	74.000	0.622	PK




Profile: 2390782R	Page No.: 173
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6825MHz by 802.11ax(160MHz) with Ant1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13650.000	51.479	49.042	-22.521	74.000	2.437	PK

Profile: 2390782R	Page No.: 174
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6825MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13650.000	51.357	48.920	-22.643	74.000	2.437	PK


Profile: 2390782R	Page No.: 175
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6985MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13970.000	49.957	48.727	-24.043	74.000	1.229	PK




Profile: 2390782R	Page No.: 176
Engineer: Yuliu	
Site: AC5	Time: 2024/06/30 - 19:56
Limit: FCC_Part15.209_RE	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 4 : Transmit at 6985MHz by 802.11ax(160MHz) with Ant1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	13970.000	50.783	49.553	-23.217	74.000	1.229	PK


The worst case of Radiated Emission below 1GHz:

Profile: 2390782R	Page No.: 29
Engineer: Yuliu	
Site: AC2	Time: 2024/06/29 - 23:25
Limit: FCC_Part 15.209_RE	Margin: 0
Probe: CBL6112B_2933(30-1000MHz)	Polarity: Horizontal
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 5180MHz by 802.11a with Ant1	



N o	Mar k	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		42.974	23.189	4.173	-16.811	40.000	19.017	QP
2		89.170	27.966	12.175	-15.534	43.500	15.791	QP
3		145.066	22.157	4.360	-21.343	43.500	17.797	QP
4		275.410	24.921	4.488	-21.079	46.000	20.433	QP
5		338.581	26.750	4.930	-19.250	46.000	21.820	QP
6	*	595.631	32.499	5.494	-13.501	46.000	27.005	QP

Profile: 2390782R	Page No.: 30
Engineer: Yuliu	
Site: AC2	Time: 2024/06/29 - 23:25
Limit: FCC_Part 15.209_RE	Margin: 0
Probe: CBL6112B_2933(30-1000MHz)	Polarity: Vertical
EUT: Mobile Computer	Power: Battery Powered
Note: Mode 1 : Transmit at 5180MHz by 802.11a with Ant1	



N o	Mar k	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		44.065	23.169	4.810	-16.831	40.000	18.359	QP
2		90.746	27.731	11.648	-15.769	43.500	16.083	QP
3		131.244	23.624	5.116	-19.876	43.500	18.509	QP
4		238.550	23.711	5.214	-22.289	46.000	18.497	QP
5		404.299	28.125	4.290	-17.875	46.000	23.835	QP
6	*	653.831	33.079	5.492	-12.921	46.000	27.587	QP

Note:

1. " * ", means this data is the worst emission level.
2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).
3. The test frequency range, 9kHz~30MHz, worst case are at least 20dB below the limits, therefore no data appear in the report.
4. The test frequency range, 18GHz~40GHz test result on peak is lower than average limit, all is the noise base, therefore no data appear in the report.
5. If the test result on peak is lower than average limit, then average measurement needn't be performed.
6. We have evaluated SISO, MIMO mode, shown in the report is the worst data.

Appendix C: Contention Based Protocol

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent Freq. (MHz)	Result (dBm)	Detection Rate (%)	Limit[dBm]	Verdict
UNII5	6135	20	6135	-62.34	100	-62	PASS
				Result: Stop Transmission			
				-65.23	<90	-62	PASS
				Result: Minimal Operation			
				-69.33	0	-62	PASS
				Result: Normal Operation			
	6185	160	6110	-62.25	100	-62	PASS
				Result: Stop Transmission			
				-67.23	<90	-62	PASS
				Result: Minimal Operation			
				-69.11	0	-62	PASS
				Result: Normal Operation			
			6185	-62.19	100	-62	PASS
				Result: Stop Transmission			
				-69.11	<90	-62	PASS
				Result: Minimal Operation			
				-71.19	0	-62	PASS
				Result: Normal Operation			
			6260	-62.32	100	-62	PASS
				Result: Stop Transmission			
				-68.11	<90	-62	PASS
				Result: Minimal Operation			
				-73.14	0	-62	PASS
				Result: Normal Operation			

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent Freq. (MHz)	Result (dBm)	Detection Rate (%)	Limit[dBm]	Verdict
UNII6	6455	20	6455	-65.11	100	-62	PASS
					Result: Stop Transmission		
				-69.21	<90	-62	PASS
					Result: Minimal Operation		
				-73.54	0	-62	PASS
					Result: Normal Operation		
	6505	160	6430	-66.23	100	-62	PASS
					Result: Stop Transmission		
				-69.15	<90	-62	PASS
					Result: Minimal Operation		
				-73.21	0	-62	PASS
					Result: Normal Operation		
			6505	-64.16	100	-62	PASS
					Result: Stop Transmission		
				-70.23	<90	-62	PASS
					Result: Minimal Operation		
			6580	-74.11	0	-62	PASS
					Result: Normal Operation		
				-63.11	100	-62	PASS
					Result: Stop Transmission		
				-69.23	<90	-62	PASS
					Result: Minimal Operation		
				-72.25	0	-62	PASS
					Result: Normal Operation		

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent Freq. (MHz)	Result (dBm)	Detection Rate (%)	Limit[dBm]	Verdict
UNII7	6695	20	6695	-64.23	100	-62	PASS
					Result: Stop Transmission		
				-69.98	<90	-62	PASS
					Result: Minimal Operation		
				-74.23	0	-62	PASS
					Result: Normal Operation		
	6825	160	6750	-65.17	100	-62	PASS
					Result: Stop Transmission		
				-70.11	<90	-62	PASS
					Result: Minimal Operation		
				-74.19	0	-62	PASS
					Result: Normal Operation		
			6825	-66.35	100	-62	PASS
					Result: Stop Transmission		
				-69.15	<90	-62	PASS
					Result: Minimal Operation		
				-73.83	0	-62	PASS
					Result: Normal Operation		
			6900	-65.31	100	-62	PASS
					Result: Stop Transmission		
				-68.93	<90	-62	PASS
					Result: Minimal Operation		
				-73.73	0	-62	PASS
					Result: Normal Operation		

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent Freq. (MHz)	Result (dBm)	Detection Rate (%)	Limit[dBm]	Verdict
UNII8	7015	20	7015	-64.23	100	-62	PASS
					Result: Stop Transmission		
				-69.98	<90	-62	PASS
					Result: Minimal Operation		
				-74.23	0	-62	PASS
					Result: Normal Operation		
	6985	160	6910	-68.23	100	-62	PASS
					Result: Stop Transmission		
				-74.56	<90	-62	PASS
					Result: Minimal Operation		
				-79.41	0	-62	PASS
					Result: Normal Operation		
			6985	-69.23	100	-62	PASS
					Result: Stop Transmission		
				-74.46	<90	-62	PASS
					Result: Minimal Operation		
			7060	-81.82	0	-62	PASS
					Result: Normal Operation		
				-71.33	100	-62	PASS
					Result: Stop Transmission		
				-76.55	<90	-62	PASS
					Result: Minimal Operation		
				-83.23	0	-62	PASS
					Result: Normal Operation		

The worst case Test Graphs

