

# MPE TEST REPORT

## OET65, IEEE C95.1

**CATEGORY** : Mobile End Product  
**PRODUCT NAME** : Wireless PCI adapter  
**FCC ID.** : RC6AWI-926W  
**FILING TYPE** : Certification  
**BRAND NAME** : Amigo, PTI  
**MODEL NAME** : 1. AWI-926W  
2. Wireless PCI Adapter  
3. PTI-620G

**APPLICANT** : **Amigo Technology Co., Ltd.**  
No.6, Lane35, Jihu Rd., Neihsu, Taipei, Taiwan 114, R.O.C.

**MANUFACTURER** : **FAIR WAY ELECTRONICS FACTORY**  
Huang Chong No.3 Ind Area, Zhong Tang Town, Dong Guan  
City, Guang Dong, P.R. China

**ISSUED BY** : **SPORTON INTERNATIONAL INC.**  
6F, No. 106, Hsin Tai Wu Rd., Sec. 1, His Chih, Taipei Hsien,  
Taiwan, R.O.C.

### Statements:

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

Certificate or Test Report could not be used by the applicant to claim the product endorsement by CNLA, NVLAP or any agency of U.S. government.

The test equipment used to perform the test are calibrated and traceable to NML/ROC or NIST/USA.



Lab Code: 200079-0

**SPORTON International Inc.**

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

## 1. Introduction

Radio power energy is available everywhere in our daily environment. More and more application involves radio energy, which makes RF hazard becomes more and more important to human health. International organization such as IEEE or FCC spent a lot of effort to investigate the risk of placing human body in RF energy environment and try to define a rule to limit the RF emission of the radio device for protection of human health. SAR and MPE was defined as 2 major evaluation methods for RF hazard. SAR is mainly used for RF device which could be very close to the human body, and MPE is for device not going to be carried with the human body. In short, portable device has to follow the rule of SAR and mobile one MPE.

This test report is for the evaluation of MPE on Mobile device which the separation distance between the antenna and the human body, under normal use condition, is longer than 20cm.

## 2. MPE ( Maximum Permissible Exposure )

### 2.1 Limits

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6                                                                |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6                                                                |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6                                                                |
| 300-1500              |                                   |                                   | F/300                                    | 6                                                                |
| 1500-100,000          |                                   |                                   | 5                                        | 6                                                                |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S ( minutes ) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30                                                                 |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30                                                                 |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30                                                                 |
| 300-1500              |                                   |                                   | F/1500                                  | 30                                                                 |
| 1500-100,000          |                                   |                                   | 1.0                                     | 30                                                                 |

F = frequency in MHz

## 2.2 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (mW/cm}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=20cm, as well as the gain of the used antenna, the RF power density can be obtained.

## 2.3 Calculated Result

· Modulation Type: CCK

| Channel No. | Antenna Gain (dBi) | Antenna Gain (numeric) | Peak Output Power (dBm) | Peak Output Power ( mW ) | Power Density (S) (mW/cm <sup>2</sup> ) | Limit of Power Density (S) (mW/cm <sup>2</sup> ) |
|-------------|--------------------|------------------------|-------------------------|--------------------------|-----------------------------------------|--------------------------------------------------|
| Channel 01  | 2.5                | 1.78                   | 17.620                  | 57.8096                  | 0.0205                                  | 1                                                |
| Channel 10  | 2.5                | 1.78                   | 18.500                  | 70.7946                  | 0.0251                                  | 1                                                |
| Channel 13  | 2.5                | 1.78                   | 18.500                  | 70.7946                  | 0.0251                                  | 1                                                |

From the calculated result shown in above table, the power density is lower than limit at location 20cm far away.

· Modulation Type: OFDM

| Channel No. | Antenna Gain (dBi) | Antenna Gain (numeric) | Peak Output Power (dBm) | Peak Output Power ( mW ) | Power Density (S) (mW/cm <sup>2</sup> ) | Limit of Power Density (S) (mW/cm <sup>2</sup> ) |
|-------------|--------------------|------------------------|-------------------------|--------------------------|-----------------------------------------|--------------------------------------------------|
| Channel 01  | 2.5                | 1.78                   | 15.120                  | 32.5087                  | 0.0115                                  | 1                                                |
| Channel 10  | 2.5                | 1.78                   | 15.400                  | 34.6737                  | 0.0123                                  | 1                                                |
| Channel 13  | 2.5                | 1.78                   | 15.270                  | 35.6512                  | 0.0117                                  | 1                                                |

From the calculated result shown in above table, the power density is lower than limit at location 20cm far away.