

§1.1307(b)(1) & §2.1091 - RF EXPOSURE

According to §15.247(b)(4) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2412 – 2462 MHz:

Maximum peak output power at antenna input terminal: 21.4 (dBm)

Maximum peak output power at antenna input terminal: 138 (mW)

Predication distance: 20 (cm)

Predication frequency: 2400 (MHz)

Antenna Gain (typical): 4 (dBi)

antenna gain: 2.51 (numeric)

Power density at predication frequency at 20 cm: 0.069 (mW/cm²)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

5180 – 5240 MHz:

Maximum peak output power at antenna input terminal: 14.6 (dBm)

Maximum peak output power at antenna input terminal: 28.8 (mW)

Prediction distance: 20 (cm)

Predication frequency: 5200 (MHz)

Antenna Gain (typical): 5 (dBi)

antenna gain: 3.16 (numeric)

Power density at predication frequency at 20 cm: 0.018 (mW/cm²)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

5260 – 5320 MHz:

Maximum peak output power at antenna input terminal: 14.6 (dBm)

Maximum peak output power at antenna input terminal: 28.8 (mW)

Prediction distance: 20 (cm)

Predication frequency: 5300 (MHz)

Antenna Gain (typical): 5 (dBi)

antenna gain: 3.16 (numeric)

Power density at predication frequency at 20 cm: 0.018 (mW/cm²)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

5745 – 5825 MHz:

Maximum peak output power at antenna input terminal: 23.7 (dBm)

Maximum peak output power at antenna input terminal: 235.5 (mW)

Prediction distance: 20 (cm)

Predication frequency: 5800 (MHz)

Antenna Gain (typical): 4.5 (dBi)

antenna gain: 2.82 (numeric)

Power density at predication frequency at 20 cm: 0.132 (mW/cm²)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

Test Result

The EUT is a mobile device. The power density levels at 20 cm for each band are 0.069 mW/cm, 0.018 mW/cm, 0.018 mW/cm, 0.132 mW/cm for each band , which are all below the uncontrolled limit of 1.0mW/cm².