

FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10:2013
TEST REPORT

For

HD Action camera

Model: DVS8Q9

Data Applies To: DVSD03

Issued for

DXG Technology Corp.

15FL.,NO.4,SEC.3,MING-CHUAN EAST ROAD,TAIPEI,TAIWAN,R.O.C.

Issued by

Compliance Certification Services Inc.

Hsinchu Lab.

**No.989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)**

TEL: +886-3-5921698

FAX: +886-3-5921108

<http://www.ccsrf.com>

E-Mail: service@ccsrf.com

Issued Date: January 21, 2016



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	01/21/2016	Initial Issue	All Page 61	Vera Hsu

TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION.....	4
2. EUT DESCRIPTION.....	5
3. DESCRIPTION OF TEST MODES.....	6
4. TEST METHODOLOGY	6
5. FACILITIES AND ACCREDITATION.....	7
5.1 FACILITIES	7
5.2 ACCREDITATIONS.....	7
5.3 MEASUREMENT UNCERTAINTY	8
6. SETUP OF EQUIPMENT UNDER TEST	9
7. FCC PART 15.247 REQUIREMENTS.....	10
7.1 6dB BANDWIDTH	10
7.2 MAXIMUM PEAK OUTPUT POWER	16
7.3 AVERAGE POWER.....	18
7.4 POWER SPECTRAL DENSITY.....	20
7.5 CONDUCTED SPURIOUS EMISSION	26
7.6 RADIATED EMISSION.....	33
7.7 CONDUCTED EMISSION	53
8. APPENDIX SETUP PHOTOS	58


1. TEST REPORT CERTIFICATION

Applicant : DXG Technology Corp.
Address : 15FL.,NO.4,SEC.3,MING-CHUAN EAST
ROAD,TAIPEI,TAIWAN,R.O.C.
Equipment Under Test : HD Action camera
Model : DVS8Q9
Data Applies To : DVSD03
Tested Date : November 12 ~ December 24, 2015

APPLICABLE STANDARD	
Standard	Test Result
FCC Part 15 Subpart C AND ANSI C63.10:2013	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Jacky Chen
Section Manager

Reviewed by:



S. B. Lu
Sr. Engineer

2. EUT DESCRIPTION

Product Name	HD Action camera
Model Number	DVS8Q9
Data Applies To	DVSD03
Identify Number	T151112D10
Received Date	November 12, 2015
Frequency Range	2412MHz ~ 2462MHz
Transmit Power	IEEE 802.11b Mode: 20.20 dBm (0.1047 W) IEEE 802.11g Mode: 22.84 dBm (0.1923 W)
Channel Spacing	5MHz
Channel Number	11 Channels
Transmit Data Rate	IEEE 802.11b Mode: up to 11 Mbps IEEE 802.11g Mode: up to 54 Mbps
Type of Modulation	IEEE 802.11b Mode: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g Mode: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type	FPCB Antenna, Antenna Gain : 2.95dBi
Power Rating	3.7Vdc, 1130mAh, 4.18Wh (For Battery) 5Vdc (For Charging)
Test Voltage	120Vac, 60Hz
I/O Port	EUT: Micro HDMI Port x 1, Mini HDMI Port x 1, Micro USB Port x 1 Micro SD Card Port x 1 Panel: Mini HDMI Connector x 1
Signal Cable	Shielded HDMI cable, 1m x 1 (Detachable), with two ferrite core

The difference of the series model

Model Number	Difference
DVS8Q9	8M pixels
DVSD03	16M pixels

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. For more details, please refer to the User's manual of the EUT.
3. This submittal(s) (test report) is intended for FCC ID: RD2RWD03001 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.
4. The model DVS8Q9 was considered the main model for testing.

3. DESCRIPTION OF TEST MODES

The EUT is a 802.11b/g transceiver in HD Action camera.

IEEE 802.11b/g Mode: 1TX / 1RX

Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test mode
1	TX mode

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test mode		
Emission	Radiated Emission	Mode 1
	Conducted Emission	Mode 1

Remark: Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

Conducted / Radiated Emission Test (Above 1 GHz)

IEEE 802.11b/g Mode:

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b Mode: 1Mbps data rate (worst case) was chosen for full testing.

IEEE 802.11g Mode: 6Mbps data rate (worst case) was chosen for full testing.

Remark: The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10:2013 and FCC CFR 47, 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATION

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
No.989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.10:2013 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	INDUSTRY CANADA
Japan	VCCI
Taiwan	BSMI
USA	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

Remark: FCC Designation Number TW1027.

5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

No.	Product	Manufacturer	Model No.	Serial No.
1	Notebook PC	HP	ProBook 4421s	CNF03242PJ

No.	Signal Cable Description
1	Shielded USB cable, 1.5m × 2

SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

EUT OPERATING CONDITION

1. EUT & peripherals setup diagram is shown in appendix setup photos.
2. TX mode:
 - ⇒ **TX Data Rate:** 1Mbps Bandwidth 20 (IEEE 802.11b Mode)
6Mbps Bandwidth 20 (IEEE 802.11g Mode)
 - ⇒ **Power control**
 - IEEE 802.11b Mode Channel Low (2412MHz) Power set 30
 - IEEE 802.11b Mode Channel Mid (2437MHz) Power set 14
 - IEEE 802.11b Mode Channel High (2462MHz) Power set 30
 - IEEE 802.11g Mode Channel Low (2412MHz) Power set 30
 - IEEE 802.11g Mode Channel Mid (2437MHz) Power set 30
 - IEEE 802.11g Mode Channel High (2462MHz) Power set 12
3. All of the functions are under run.
4. Start test.

7. FCC PART 15.247 REQUIREMENTS

7.1 6dB BANDWIDTH

LIMITS


§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE



1. The transmitter output was connected to a spectrum analyzer.
2. Set RBW = 100 kHz.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


TEST RESULTS**IEEE 802.11b Mode**



Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Result
Low	2412	10.05	500	PASS
Middle	2437	10.06	500	PASS
High	2462	10.05	500	PASS


IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Result
Low	2412	16.30	500	PASS
Middle	2437	16.29	500	PASS
High	2462	15.90	500	PASS

6dB BANDWIDTH**CH Low (IEEE 802.11b Mode)****CH Middle (IEEE 802.11b Mode)**

CH High (IEEE 802.11b Mode)

CH Low (IEEE 802.11g Mode)**CH Middle (IEEE 802.11g Mode)**

CH High (IEEE 802.11g Mode)

7.2 MAXIMUM PEAK OUTPUT POWER

LIMITS

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following:

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§ KDB 662911: For power measurements on IEEE 802.11 devices

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;


Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/08/2016
Power Sensor	Anritsu	MA2411B	1126148	12/08/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the peak power detection.

TEST RESULTS**IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Maximum Peak Output Power				Result	
		Measured Value		Limit			
		(dBm)	(W)	(dBm)	(W)		
Low	2412	20.20	0.1047	30.00	1.0000	PASS	
Middle	2437	19.47	0.0885	30.00	1.0000	PASS	
High	2462	19.15	0.0822	30.00	1.0000	PASS	

Remark:

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	Maximum Peak Output Power				Result	
		Measured Value		Limit			
		(dBm)	(W)	(dBm)	(W)		
Low	2412	22.84	0.1923	30.00	1.0000	PASS	
Middle	2437	22.80	0.1905	30.00	1.0000	PASS	
High	2462	20.60	0.1148	30.00	1.0000	PASS	

Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

7.3 AVERAGE POWER

LIMITS


None: For reporting purposes only.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/08/2016
Power Sensor	Anritsu	MA2411B	1126148	12/08/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the average power detection.

TEST RESULTS**IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	18.48
Middle	2437	17.84
High	2462	17.64

Remark:

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11g Mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	17.65
Middle	2437	17.37
High	2462	15.31

Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

7.4 POWER SPECTRAL DENSITY

LIMITS

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set analyzer center frequency to DTS channel center frequency.
3. Set the span to 1.5 times the DTS channel bandwidth.
4. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{RBW}$.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS**IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)		Result
		Measured Value	Limit	
Low	2412	-2.47	8	PASS
Middle	2437	-2.34	8	PASS
High	2462	-3.04	8	PASS

Remark:



1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11g Mode


Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)		Result
		Measured Value	Limit	
Low	2412	-3.85	8	PASS
Middle	2437	-1.79	8	PASS
High	2462	-5.51	8	PASS



Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.


POWER SPECTRAL DENSITY**CH Low (IEEE 802.11b Mode)****CH Middle (IEEE 802.11b Mode)**

CH High (IEEE 802.11b Mode)



CH Low (IEEE 802.11g Mode)**CH Middle (IEEE 802.11g Mode)**

CH High (IEEE 802.11g Mode)



7.5 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


TEST RESULTS



OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT



CH Low (2.38GHz ~ 2.5GHz / IEEE 802.11b Mode)







CH Low (30MHz ~ 26.5GHz / IEEE 802.11b Mode)





CH Middle (2.38GHz ~ 2.5GHz / IEEE 802.11b Mode)**CH Middle (30MHz ~ 26.5GHz / IEEE 802.11b Mode)**

CH High (2.38GHz ~ 2.5GHz / IEEE 802.11b Mode)**CH High (30MHz ~ 26.5GHz / IEEE 802.11b Mode)**

CH Low (2.38GHz ~ 2.5GHz / IEEE 802.11g Mode)**CH Low (30MHz ~ 26.5GHz / IEEE 802.11g Mode)**

CH Middle (2.38GHz ~ 2.5GHz / IEEE 802.11g Mode)**CH Middle (30MHz ~ 26.5GHz / IEEE 802.11g Mode)**

CH High (2.38GHz ~ 2.5GHz / IEEE 802.11g Mode)**CH High (30MHz ~ 26.5GHz / IEEE 802.11g Mode)**

7.6 RADIATED EMISSION

LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Remark:

1. ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
2. ² Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

Remark: **Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST EQUIPMENT

Radiated Emission / 966Chamber_C


Name of Equipment	Manufacture	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY45280064	03/26/2016
EMI Test Receiver	Rohde & Schwarz	ESCI	101387	10/06/2016
Bi-log Antenna	TESEQ	CBL6112D	35404	08/04/2016
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-778	08/09/2016
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078732	07/14/2016
Horn Antenna	COM-POWER	AH-840	03077	12/08/2016
Pre-Amplifier	EMCI	EMC001625	980243	04/12/2016
Pre-Amplifier	COM-POWER	PAM-118A	551043	04/12/2016

Remark: Each piece of equipment is scheduled for calibration once a year.


TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.


9kHz ~ 30MHz



30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 and 1.5 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Remark :

1. *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.*
2. *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.*
3. *The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.*

TEST RESULTS

Below 1 GHz (9kHz ~ 30MHz)

No emission found between lowest internal used/generated frequency to 30MHz.

Below 1 GHz (30MHz ~ 1GHz)

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/23
Test mode	Mode 1	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
207.51	57.82	-20.30	37.52	43.50	-5.98	259	100	Peak
224.97	61.93	-19.68	42.25	46.00	-3.75	283	100	Peak
252.13	58.25	-17.24	41.01	46.00	-4.99	274	100	Peak
297.72	58.37	-16.34	42.03	46.00	-3.97	235	100	Peak
450.98	52.74	-12.65	40.09	46.00	-5.91	229	200	Peak
480.08	52.70	-12.21	40.49	46.00	-5.51	46	200	Peak
892.33	45.28	-7.56	37.72	46.00	-8.28	151	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
81.41	53.06	-23.36	29.70	40.00	-10.30	143	100	Peak
225.94	55.85	-19.59	36.26	46.00	-9.74	196	200	Peak
297.72	53.55	-16.34	37.21	46.00	-8.79	174	200	Peak
431.58	52.21	-12.95	39.26	46.00	-6.74	143	100	Peak
480.08	51.43	-12.21	39.22	46.00	-6.78	145	100	Peak
527.61	49.59	-11.40	38.19	46.00	-7.81	120	100	Peak

Remark:

1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)
3. Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
4. Margin (dB) = Remark result (dBuV/m) - Quasi-peak limit (dBuV/m).

Above 1 GHz

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/21
Test mode	IEEE 802.11b Mode / TX / CH Low	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
2016.00	48.76	3.48	52.24	74.00	-21.76	255	100	Peak
2118.00	41.18	3.70	44.88	74.00	-29.12	150	100	Peak
2640.00	41.01	4.79	45.80	74.00	-28.20	169	100	Peak
4035.00	49.04	-2.21	46.83	74.00	-27.17	142	100	Peak
4830.00	51.73	-0.22	51.51	74.00	-22.49	129	100	Peak
7230.00	45.44	2.70	48.14	74.00	-25.86	118	100	Peak
11415.00	43.44	7.12	50.56	74.00	-23.44	134	200	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
2016.00	41.41	3.48	44.89	74.00	-29.11	236	100	Peak
2128.00	41.37	3.72	45.09	74.00	-28.91	166	200	Peak
2660.00	42.35	4.83	47.18	74.00	-26.82	30	100	Peak
4035.00	48.91	-2.21	46.70	74.00	-27.30	79	200	Peak
4500.00	49.15	-1.39	47.76	74.00	-26.24	99	100	Peak
4830.00	52.82	-0.22	52.60	74.00	-21.40	96	200	Peak
7425.00	44.77	2.79	47.56	74.00	-26.44	69	100	Peak
11325.00	43.57	7.04	50.61	74.00	-23.39	194	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/21
Test mode	IEEE 802.11b Mode / TX / CH Middle	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2016.00	47.46	3.48	50.94	74.00	-23.06	236	100	Peak
2308.00	41.21	4.11	45.32	74.00	-28.68	229	100	Peak
2484.00	40.30	4.49	44.79	74.00	-29.21	152	100	Peak
4875.00	51.49	-0.06	51.43	54.00	-2.57	144	200	Average
4875.00	54.23	-0.06	54.17	74.00	-19.83	144	200	Peak
7305.00	47.83	2.73	50.56	74.00	-23.44	133	100	Peak
11310.00	43.45	7.03	50.48	74.00	-23.52	138	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2016.00	43.30	3.48	46.78	74.00	-27.22	274	100	Peak
2356.00	40.98	4.21	45.19	74.00	-28.81	238	200	Peak
2672.00	41.72	4.85	46.57	74.00	-27.43	30	100	Peak
4875.00	52.56	-0.06	52.50	54.00	-1.50	95	200	Average
4875.00	54.69	-0.06	54.63	74.00	-19.37	95	200	Peak
7305.00	45.85	2.73	48.58	74.00	-25.42	238	100	Peak
11325.00	43.77	7.04	50.81	74.00	-23.19	340	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor

Margin = Result - Limit

Remark Peak = Result(PK) - Limit(PK)

Remark AVG = Result(AV) - Limit(AV)

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/21
Test mode	IEEE 802.11b Mode / TX / CH High	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2016.00	48.52	3.48	52.00	74.00	-22.00	243	100	Peak
2372.00	40.21	4.25	44.46	74.00	-29.54	241	100	Peak
2518.00	40.60	4.55	45.15	74.00	-28.85	239	100	Peak
4920.00	53.52	0.10	53.62	54.00	-0.38	141	100	Average
4920.00	56.00	0.10	56.10	74.00	-17.90	141	100	Peak
7380.00	49.04	2.76	51.80	74.00	-22.20	119	100	Peak
10740.00	43.15	6.31	49.46	74.00	-24.54	183	200	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2016.00	41.54	3.48	45.02	74.00	-28.98	240	200	Peak
2320.00	40.40	4.13	44.53	74.00	-29.47	90	100	Peak
2666.00	42.24	4.84	47.08	74.00	-26.92	29	100	Peak
4920.00	53.40	0.10	53.50	54.00	-0.50	105	200	Average
4920.00	54.73	0.10	54.83	74.00	-19.17	105	200	Peak
7380.00	46.51	2.76	49.27	74.00	-24.73	72	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit

Remark Peak = Result(PK) - Limit(PK)

Remark AVG = Result(AV) - Limit(AV)

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/21
Test mode	IEEE 802.11g Mode / TX / CH Low	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1680.00	45.61	0.48	46.09	74.00	-27.91	253	100	Peak
2016.00	47.44	3.48	50.92	74.00	-23.08	238	100	Peak
2570.00	41.31	4.66	45.97	74.00	-28.03	42	100	Peak
4830.00	48.55	-0.22	48.33	74.00	-25.67	135	100	Peak
7230.00	42.50	2.70	45.20	54.00	-8.80	43	100	Average
7230.00	51.94	2.70	54.64	74.00	-19.36	43	100	Peak
11295.00	44.27	7.02	51.29	74.00	-22.71	201	200	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2016.00	42.79	3.48	46.27	74.00	-27.73	222	200	Peak
2260.00	40.96	4.01	44.97	74.00	-29.03	312	200	Peak
2662.00	42.62	4.83	47.45	74.00	-26.55	39	100	Peak
4815.00	50.83	-0.27	50.56	74.00	-23.44	100	200	Peak
7230.00	45.60	2.70	48.30	54.00	-5.70	80	100	Average
7230.00	53.50	2.70	56.20	74.00	-17.80	80	100	Peak
10650.00	43.53	6.15	49.68	74.00	-24.32	222	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor

Margin = Result - Limit

Remark Peak = Result(PK) - Limit(PK)

Remark AVG = Result(AV) - Limit(AV)

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/21
Test mode	IEEE 802.11g Mode / TX / CH Middle	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2016.00	48.12	3.48	51.60	74.00	-22.40	245	200	Peak
2342.00	40.52	4.18	44.70	74.00	-29.30	221	100	Peak
2488.00	40.14	4.49	44.63	74.00	-29.37	75	200	Peak
4875.00	52.37	-0.06	52.31	74.00	-21.69	132	200	Peak
7320.00	42.58	2.74	45.32	54.00	-8.68	247	100	Average
7320.00	54.17	2.74	56.91	74.00	-17.09	247	100	Peak
9735.00	44.78	4.51	49.29	74.00	-24.71	79	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2016.00	42.01	3.48	45.49	74.00	-28.51	236	100	Peak
2336.00	40.88	4.17	45.05	74.00	-28.95	305	200	Peak
2490.00	40.57	4.50	45.07	74.00	-28.93	79	100	Peak
4875.00	44.99	-0.06	44.93	54.00	-9.07	99	200	Average
4875.00	53.92	-0.06	53.86	74.00	-20.14	99	200	Peak
7320.00	42.30	2.74	45.04	54.00	-8.96	86	100	Average
7320.00	51.55	2.74	54.29	74.00	-19.71	86	100	Peak
9750.00	46.30	4.53	50.83	74.00	-23.17	111	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	HD Action camera	Test By	Rex Chiu
Test Model	DVS8Q9	Test Date	2015/12/21
Test mode	IEEE 802.11g Mode / TX / CH High	Temp. & Humidity	25°C, 50%

966Chamber_C at 3Meter / Horizontal



Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2016.00	49.01	3.48	52.49	74.00	-21.51	251	100	Peak
2358.00	40.42	4.22	44.64	74.00	-29.36	42	100	Peak
2516.00	41.42	4.55	45.97	74.00	-28.03	232	100	Peak
4920.00	50.54	0.10	50.64	74.00	-23.36	140	200	Peak
7395.00	42.50	2.77	45.27	54.00	-8.73	66	100	Average
7395.00	51.52	2.77	54.29	74.00	-19.71	66	100	Peak
10725.00	43.09	6.28	49.37	74.00	-24.63	253	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2016.00	45.03	3.48	48.51	74.00	-25.49	273	100	Peak
2268.00	40.43	4.02	44.45	74.00	-29.55	106	100	Peak
2666.00	41.99	4.84	46.83	74.00	-27.17	45	100	Peak
4920.00	52.27	0.10	52.37	74.00	-21.63	107	200	Peak
7395.00	46.30	2.77	49.07	74.00	-24.93	212	100	Peak
11325.00	43.47	7.04	50.51	74.00	-23.49	108	100	Peak


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)


Restricted Band Edges**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**

Detector mode: Peak**Polarity: Vertical****CH Low (IEEE 802.11b Mode)**

Data: 6


**Detector mode: Average****Polarity: Vertical****CH Low (IEEE 802.11b Mode)**

Data: 5




Detector mode: Peak**Polarity: Horizontal****CH High (IEEE 802.11b Mode)**

Data: 18


**Detector mode: Average****Polarity: Horizontal****CH High (IEEE 802.11b Mode)**

Data: 17



Detector mode: Peak**Polarity: Vertical****CH High (IEEE 802.11b Mode)**

Data: 20




Trace:

Freq. MHz	Reading dB _{UV}	C.F. dB/m	Result dB _{UV} /m	Limit dB _{UV} /m	Margin dB	Azimuth deg	Height cm	Remark
2483.50	51.62	4.48	56.10	74.00	-17.90			Peak

Detector mode: Average**Polarity: Vertical****CH High (IEEE 802.11b Mode)**

Data: 19




Trace:

Freq. MHz	Reading dB _{UV}	C.F. dB/m	Result dB _{UV} /m	Limit dB _{UV} /m	Margin dB	Azimuth deg	Height cm	Remark
2483.50	38.65	4.48	43.13	54.00	-10.87			Average
2484.00	38.70	4.49	43.19	54.00	-10.81			Average

Detector mode: Peak**Polarity: Horizontal****CH Low (IEEE 802.11g Mode)**

Data: 9




Trace:

Freq. MHz	Reading dB _{UV}	C.F. dB/m	Result dB _{UV} /m	Limit dB _{UV} /m	Margin dB	Azimuth deg	Height cm	Remark
2390.00	54.63	4.28	58.91	74.00	-15.09			Peak

Detector mode: Average**Polarity: Horizontal****CH Low (IEEE 802.11g Mode)**

Data: 10




Trace:


Freq. MHz	Reading dB _{UV}	C.F. dB/m	Result dB _{UV} /m	Limit dB _{UV} /m	Margin dB	Azimuth deg	Height cm	Remark
2390.00	44.83	4.28	49.11	54.00	-4.89			Average

Detector mode: Peak**Polarity: Vertical****CH Low (IEEE 802.11g Mode)**

Data: 12


**Detector mode: Average****Polarity: Vertical****CH Low (IEEE 802.11g Mode)**

Data: 11




Detector mode: Peak**Polarity: Horizontal****CH High (IEEE 802.11g Mode)**

Data: 14


**Detector mode: Average****Polarity: Horizontal****CH High (IEEE 802.11g Mode)**

Data: 13




Detector mode: Peak**Polarity: Vertical****CH High (IEEE 802.11g Mode)**

Data: 16

**Detector mode: Average****Polarity: Vertical****CH High (IEEE 802.11g Mode)**

Data: 15



7.7 CONDUCTED EMISSION

LIMITS



§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	Schwarzbeck	NSLK 8127	8127465	08/05/2016
L.I.S.N	Schwarzbeck	NSLK 8127	8127473	03/09/2016
EMI Test Receiver	Rohde & Schwarz	ESHS 30	838550/003	10/31/2016
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100111	06/28/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP

TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.10:2013.

The test procedure is performed in a 4m x 3m x 2.4m (LxWxH) shielded room.


The EUT along with its peripherals were placed on a 1.0m (W) x 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.

The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

TEST RESULTS

Product Name	HD Action camera	Test By	Jason Chia
Test Model	DVS8Q9	Test Date	2015/12/27
Test mode	Mode 1	Temp. & Humidity	26°C, 60%


LINE**Remark:**

1. Correction Factor = Insertion loss + Cable loss
2. Result level = Reading Value + Correction factor
3. Margin value = Result level – Limit value

Product Name	HD Action camera	Test By	Jason Chia
Test Model	DVS8Q9	Test Date	2015/12/27
Test mode	Mode 1	Temp. & Humidity	26°C, 60%

NEUTRAL

Data: 2



Trace:

Freq. MHz	Reading		C.F. dB	Result		Limit		Margin	
	Q.P. dBuV	AV. dBuV		Q.P. dBuV	AV. dBuV	Q.P. dBuV	AV. dBuV	Q.P. dB	AV. dB
<hr/>									
0.152	37.64	20.65	9.98	47.62	30.63	65.91	55.91	-18.29	-25.28
0.159	36.18	19.19	9.98	46.16	29.17	65.52	55.52	-19.36	-26.35
0.197	31.15	15.26	10.00	41.15	25.26	63.76	53.76	-22.61	-28.50
3.436	15.47	1.16	10.13	25.60	11.29	56.00	46.00	-30.40	-34.71
3.759	14.80	2.41	10.14	24.94	12.55	56.00	46.00	-31.06	-33.45
10.508	19.52	11.08	10.35	29.87	21.43	60.00	50.00	-30.13	-28.57

Remark:

1. Correction Factor = Insertion loss + Cable loss
2. Result level = Reading Value + Correction factor
3. Margin value = Result level – Limit value