

FCC Report (Bluetooth)

Product Name : Bluetooth Headset
Trade mark : QCY
Model No. : In2027
FCC ID : RDR-IN2027
Report Number : BLA-EMC-202009-A18-01
Date of sample receipt : 2020/9/2
Date of Test : 2020/9/2 - 2020/9/15
Date of Issue : 2020/9/18
Test standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
Test result : PASS

Prepared for:

Dongguan Hele Electronics Co.,Ltd
Dalingya Industrial Zone, Daojiao Town, Dongguan City, Guangdong, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.
IOT Test Centre of BlueAsia
No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China
TEL: +86-755-28682673
FAX: +86-755-28682673

Compile by: <i>Bason</i>	Review by: <i>Benson-wei</i>
Approved by: <i>Emen-li</i>	Date: 2020/9/18



2 Version

Version No.	Date	Description
00	2020/9/18	<i>Original</i>

BlueAsia

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 TEST FACILITY	7
5.4 TEST LOCATION	7
5.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
5.6 DESCRIPTION OF SUPPORT UNITS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	14
7.4 20dB EMISSION BANDWIDTH	15
7.5 CARRIER FREQUENCIES SEPARATION	16
7.6 HOPPING CHANNEL NUMBER	17
7.7 DWELL TIME	18
7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	19
7.9 BAND EDGE	20
7.9.1 <i>Conducted Emission Method</i>	20
7.9.2 <i>Radiated Emission Method</i>	21
7.10 SPURIOUS EMISSION	26
7.10.1 <i>Conducted Emission Method</i>	26
7.10.2 <i>Radiated Emission Method</i>	27
8 TEST SETUP PHOTO	38
9 EUT CONSTRUCTIONAL DETAILS	40
10 APPENDIX	51

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according ANSI C63.10:2013

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Bluetooth Headset
Model No.:	In2027
Test Model No.:	In2027
Serial No.:	N/A
Sample(s) Status	Engineer sample
Hardware:	V1.0
Software:	V1.0
Operation Frequency:	2402MHz-2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	Internal Antenna
Antenna gain:	1.6dBi
Power supply:	DC 3.7V
Remark: The Antenna Gain is supplied by the customer. BlueAsia is not responsible for this data	

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping or non hopping mode, non hopping mode is worse case for RE.)
<p><i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i></p> <p><i>Full battery is used during all test except ac conducted emission, DH1, DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned only worse case is reported.</i></p>	

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:
• FCC — Designation No.: CN1252
BlueAsia of Technical Services(Shenzhen) Co., Ltd has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Designation CN1252.
• ISED — CAB identifier No.: CN0028
BlueAsia of Technical Services(Shenzhen) Co., Ltd has been registered by Certification and Engineering Bureau of ISED for radio equipment testing with CAB identifier CN0028

5.4 Test Location

All tests were performed at:
<p><i>All tests were performed at:</i></p> <p><i>BlueAsia of Technical Services(Shenzhen) Co., Ltd.</i></p> <p><i>IOT Test Centre of BlueAsia</i></p> <p><i>No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China</i></p> <p><i>Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673</i></p> <p><i>Tests were sub-contracted:</i></p> <p><i>Radiation test is conducted by Global United Technology Services Co., Ltd.</i></p> <p><i>No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102</i></p> <p><i>FCC —Registration No.: 381383</i></p> <p><i>Job No.: GTS202009000065</i></p>

5.5 Other Information Requested by the Customer

None.

5.6 Description of Support Units

Manufacturer	Description	Model	Serial Number
UGREEN	Adapter	CD112	20358
Lenovo	Notebook computer	E470C	PF-10FB5C

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021


Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	EMI Test Receiver	Rohde & Schwarz	ESPI3	101082	06-10-2020	06-09-2021
2	LISN	CHASE	MN2050D	1447	06-10-2020	06-09-2021
3	LISN	Rohde & Schwarz	ENV216	3560.6550.15	06-10-2020	06-09-2021
4	EMI Test Software	EZ	EZ	N/A	N/A	N/A
5	Temperature Humidity Chamber	Mingle	TH101B	N/A	07-19-2019	07-18-2020
					07-19-2020	07-18-2021
6	Coaxial Cable	BlueAsia	BLA-XC-05	N/A	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Spectrum Analyzer	Agilent	N9030A	MY50510123	05-24-2020	05-23-2021
2	Spectrum analyzer	Rohde & Schwarz	FSP40	100817	05-24-2020	05-23-2021
3	MXA Signal Analyzer	Agilent	N9020A	MY49100060	12-18-2019	12-17-2020
4	Vector Signal Generator	Agilent	N5182A	MY49060650	12-18-2019	12-17-2020
5	Vector Signal Generator	Agilent	E4438C	MY45092582	05-24-2020	05-23-2021
6	Signal Generator	Agilent	E8257D	MY44320250	05-24-2020	05-23-2021
7	Power Sensor	D.A.R.E	RPR3006W	17I00015SNO27	05-24-2020	05-23-2021
8	Power Sensor	D.A.R.E	RPR3006W	17I00015SNO28	05-24-2020	05-23-2021
9	DC Power Supply	LODESTAR	LP305DE	N/A	07-19-2019	07-18-2020
					07-19-2020	07-18-2021
10	Temperature Humidity Chamber	Mingle	TH101B	N/A	07-19-2019	07-18-2020
					07-19-2020	07-18-2021

7 Test results and Measurement Data


7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna: <i>The antenna is PCB antenna, the best case gain of the antenna is 1.6dBi</i>	



A photograph of a device showing a yellow PCB antenna. A red box highlights the antenna, and a red arrow points to it with the label "BT ANT".


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	* Decreases with the logarithm of the frequency.																
Test setup:	 <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.2 for details																
Test results:	Pass																

Measurement data:

Line:

EUT:	Bluetooth Headset	Probe:	L1
Model:	In2027	Power Source:	AC120V/60Hz
Mode:	BT mode	Test by:	Eason
Temp./Hum.(%H): 23°C/49%RH			


Site Phase: **L1** Temperature: 26

Limit: EN301489 Class B Conduction(QP) Power: Humidity: 60 %

EUT: Bluetooth Headset

M/N: In2027

Mode: working mode


Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.1620	24.55	9.89	34.44	65.36	-30.92	QP	
2		0.1620	17.34	9.89	27.23	55.36	-28.13	AVG	
3		0.3300	20.73	9.79	30.52	59.45	-28.93	QP	
4		0.3300	15.19	9.79	24.98	49.45	-24.47	AVG	
5		0.5780	22.33	9.74	32.07	56.00	-23.93	QP	
6		0.5780	16.72	9.74	26.46	46.00	-19.54	AVG	
7		2.2659	24.75	9.81	34.56	56.00	-21.44	QP	
8		2.2659	14.53	9.81	24.34	46.00	-21.66	AVG	
9 *		8.1220	30.67	9.88	40.55	60.00	-19.45	QP	
10		8.1220	19.03	9.88	28.91	50.00	-21.09	AVG	
11		14.2060	21.90	9.96	31.86	60.00	-28.14	QP	
12		14.2060	12.27	9.96	22.23	50.00	-27.77	AVG	

Neutral:

EUT:	Bluetooth Headset	Probe:	N
Model:	In2027	Power Source:	AC120V/60Hz
Mode:	BT mode	Test by:	Eason
Temp./Hum.(%H): 23°C/49%RH			

Conducted Emission Measurement



Site: Phase: **N** Temperature: 26
Limit: EN301489 Class B Conduction(QP) Power: Humidity: 60 %

EUT: Bluetooth Headset

M/N: In2027

Mode: working mode


Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over	Comment	
							Detector	
1	0.1700	25.58	9.87	35.45	64.96	-29.51	QP	
2	0.1700	17.65	9.87	27.52	54.96	-27.44	AVG	
3	0.5660	23.74	9.73	33.47	56.00	-22.53	QP	
4 *	0.5660	18.56	9.73	28.29	46.00	-17.71	AVG	
5	1.3220	19.34	9.83	29.17	56.00	-26.83	QP	
6	1.3220	13.89	9.83	23.72	46.00	-22.28	AVG	
7	2.2860	19.30	9.86	29.16	56.00	-26.84	QP	
8	2.2860	10.56	9.86	20.42	46.00	-25.58	AVG	
9	7.9540	26.76	9.87	36.63	60.00	-23.37	QP	
10	7.9540	15.10	9.87	24.97	50.00	-25.03	AVG	
11	14.2020	17.16	10.00	27.16	60.00	-32.84	QP	
12	14.2020	6.97	10.00	16.97	50.00	-33.03	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level +Correct Factor
4. Correct Factor = LISN Factor + Cable Loss


7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	21dBm(for GFSK),21dBm(for EDR)
Test setup:	<p style="text-align: center;">Spectrum Analyzer</p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Reference to the AppendixC: Maximum conducted output power


7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	<p style="text-align: center;">Spectrum Analyzer</p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Reference to the AppendixA: 20dB Emission Bandwidth


7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	GFSK & Pi/4QPSK & 8-DPSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 <p>The diagram illustrates the test setup for carrier frequency separation. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The E.U.T is placed on a Non-Conducted Table. The table is positioned above a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Reference to the AppendixD: Carrier frequency separation


7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	<p style="text-align: center;">Spectrum Analyzer</p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data:

Reference to the AppendixF: Number of hopping channels

7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	<p style="text-align: center;">Spectrum Analyzer</p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Reference to the AppendixE: Time of occupancy

7.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) requirement:
--------------------------	--


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:




Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

7.9 Band Edge


7.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Reference to the AppendixG:Band edge measurements


7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205								
Test Method:	ANSI C63.10:2013								
Test Frequency Range:	All restriction band have been tested, and 2310MHz to 2390MHz, 2483.5MHz to 2500MHz band is the worse case								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
		Peak	1MHz	10Hz	Average Value				
Limit:	Frequency	Limit (dBuV/m @3m)		Remark					
	Above 1GHz	54.00		Average Value					
		74.00		Peak Value					
Test setup:									
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 								
Test Instruments:	Refer to section 6.0 for details								
Test mode:	Refer to section 5.2 for details								
Test results:	Pass								

Remark:

1. During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the 8-DPSK modulation which it is worse case.

Test channel:	Lowest
Peak value:	



Condition : FCC PART 15 (PK) 3m HORIZONTAL


Job No. : GTS202009000028

Test Mode : TX 2402MHz

Test Engineer: Hans

Remark :

Freq	Read	Antenna	Preamp	Cable	Limit	Over	Remark
	Level	Factor	Factor	Loss	Level	Line	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2310.000	36.19	27.14	30.43	2.81	35.71	54.00	-18.29 Average
2 2310.000	43.19	27.14	30.43	2.81	42.71	74.00	-31.29 Peak
3 2390.000	36.22	27.37	30.24	2.91	36.26	54.00	-17.74 Average
4 2390.000	43.22	27.37	30.24	2.91	43.26	74.00	-30.74 Peak
5 2400.000	36.19	27.41	30.26	2.91	36.25	54.00	-17.75 Average
6 2400.000	43.19	27.41	30.26	2.91	43.25	74.00	-30.75 Peak



Condition : FCC PART 15 (PK) 3m VERTICAL

Job No. : GTS202009000028

Test Mode : TX 2402MHz

Test Engineer: Hans


Remark :

	Read	Antenna	Preamp	Cable	Limit	Over	
Freq	Level	Factor	Factor	Loss	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2310.000	37.69	27.14	30.43	2.81	37.21	54.00	-16.79 Average
2 2310.000	43.69	27.14	30.43	2.81	43.21	74.00	-30.79 Peak
3 2390.000	36.54	27.37	30.24	2.91	36.58	54.00	-17.42 Average
4 2390.000	43.54	27.37	30.24	2.91	43.58	74.00	-30.42 Peak
5 2400.000	36.46	27.41	30.26	2.91	36.52	54.00	-17.48 Average
6 2400.000	43.46	27.41	30.26	2.91	43.52	74.00	-30.48 Peak

Test channel:

Highest

Peak value:



Condition : FCC PART 15 (PK) 3m HORIZONTAL


Job No. : GTS202009000028

Test Mode : TX 2480MHz

Test Engineer: Hans

Remark :

Freq	Read	Antenna	Preamplifier	Cable	Limit	Over	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	36.47	27.66	30.12	2.99	37.00	54.00	-17.00 Average
2	2483.500	43.47	27.66	30.12	2.99	44.00	74.00	-30.00 Peak
3	2500.000	36.59	27.70	30.13	3.01	37.17	54.00	-16.83 Average
4	2500.000	43.59	27.70	30.13	3.01	44.17	74.00	-29.83 Peak



Condition : FCC PART 15 (PK) 3m VERTICAL

Job No. : GTS202009000028

Test Mode : TX 2480MHz

Test Engineer: Hans

Remark :


	Read	Antenna	Preamp	Cable	Limit	Over		
Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m		dB	dBuV/m	dBuV/m	dB	
1 2483.500	36.80	27.66	30.12	2.99	37.33	54.00	-16.67	Average
2 2483.500	43.80	27.66	30.12	2.99	44.33	74.00	-29.67	Peak
3 2500.000	37.72	27.70	30.13	3.01	38.30	54.00	-15.70	Average
4 2500.000	44.72	27.70	30.13	3.01	45.30	74.00	-28.70	Peak

Remark:

1. Final Level = Receiver Read level + Correct factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Correct factor = Antenna Factor + Cable Loss - Preamplifier Factor

7.10 Spurious Emission

7.10.1 Conducted Emission Method




Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	<p style="text-align: center;">Spectrum Analyzer</p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Reference to the AppendixH:Conducted SpuriousEmission

7.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance 3m	
	0.009MHz-0.490MHz	2400/F(KHz)	QP		
	0.490MHz-1.705MHz	24000/F(KHz)	QP		
	1.705MHz-30MHz	30	QP		
	30MHz-88MHz	100	QP		
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				

Test setup:	<p>Below 30MHz</p>  <p>Below 1GHz</p>  <p>Above 1GHz</p> 
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters

	<p>and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Remark:


1. During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the 8-DPSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.
3. no emission found above 18G, so only show plots below 18G

■ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

EUT:	Bluetooth Headset	Polarization:	Horizontal
Model:	In2027	Power Source:	AC120V/60Hz
Mode:	BT mode	Test by:	Eason
Temp./Hum.(%H):	23°C/49%RH		
Note:			



Condition : FCC PART15 CLASS B 3m HORIZONTAL

Job.No : GTS202009000028


Test Mode : TX 2402MHz

Test Engineer: Hans

Remark :

	Read	Antenna	Preamp	Cable	Limit	Over		
Freq	Level	Factor	Factor	Cable	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.317	37.23	11.21	35.02	0.55	13.97	40.00	-26.03 QP
2	40.988	38.64	12.21	35.72	0.67	15.80	40.00	-24.20 QP
3	49.187	36.63	12.29	36.14	0.76	13.54	40.00	-26.46 QP
4	96.436	34.57	11.72	36.69	1.16	10.76	43.50	-32.74 QP
5	278.067	33.65	13.02	37.40	2.26	11.53	46.00	-34.47 QP
6	588.905	34.25	19.23	37.54	3.68	19.62	46.00	-26.38 QP

EUT:	Bluetooth Headset	Polarization:	Vertical
Model:	In2027	Power Source:	AC120V/60Hz
Mode:	BT mode	Test by:	Eason
Temp./Hum.(%H):	23°C/49%RH		
Note:			



Condition : FCC PART15 CLASS B 3m VERTICAL

Job. No : GTS202009000028

Test Mode : TX 2402MHz


Test Engineer: Hans

Remark :

Freq	Read		Antenna	Preamp	Cable	Limit	Over	Line	Over
	Level	Factor	Factor	Loss	Level				
MHz	dBuV	dB/m		dB	dB	dBuV/m	dBuV/m	dB	dB
1 35.375	39.35	11.39	35.38	0.61	15.97	40.00	-24.03	QP	
2 42.154	38.23	12.22	35.79	0.69	15.35	40.00	-24.65	QP	
3 96.099	39.36	11.65	36.69	1.16	15.48	43.50	-28.02	QP	
4 167.824	40.36	8.46	37.18	1.67	13.31	43.50	-30.19	QP	
5 216.024	36.26	11.02	37.35	1.93	11.86	46.00	-34.14	QP	
6 618.537	34.20	19.52	37.56	3.80	19.96	46.00	-26.04	QP	

■ Above 1GHz

Test channel:	Lowest
---------------	--------

Peak value:


Condition : FCC PART 15 (PK) 3m VERTICAL


Job No. : GTS202009000028

Test Mode : TX 2402MHz

Test Engineer: Hans

Remark :

Freq MHz	Read	Antenna	Preamp	Cable	Limit Line	Over Limit	Remark	
	Freq	Level dBuV	Factor	Factor				
MHz	dBuV	dB/m		dB	dB	dBuV/m	dBuV/m	dB
1 4804.000	25.87	31.35	37.73	4.61	24.10	54.00	-29.90	Average
2 4804.000	32.87	31.35	37.73	4.61	31.10	74.00	-42.90	Peak
3 7206.000	22.21	35.89	35.63	6.48	28.95	54.00	-25.05	Average
4 7206.000	29.21	35.89	35.63	6.48	35.95	74.00	-38.05	Peak
5 9608.000	22.37	37.74	34.94	7.97	33.14	54.00	-20.86	Average
6 9608.000	29.37	37.74	34.94	7.97	40.14	74.00	-33.86	Peak



Condition : FCC PART 15 (PK) 3m HORIZONTAL

Job No. : GTS202009000028

Test Mode : TX 2402MHz

Test Engineer: Hans

Remark :


Freq	Read	Antenna	Preamp	Cable	Limit	Over	Remark
	MHz	dBuV	Factor	Factor	Loss	Level	
1	4804.000	25.68	31.35	37.73	4.61	23.91	54.00 -30.09 Average
2	4804.000	32.68	31.35	37.73	4.61	30.91	74.00 -43.09 Peak
3	7206.000	23.09	35.89	35.63	6.48	29.83	54.00 -24.17 Average
4	7206.000	30.09	35.89	35.63	6.48	36.83	74.00 -37.17 Peak
5	9608.000	21.90	37.74	34.94	7.97	32.67	54.00 -21.33 Average
6	9608.000	28.90	37.74	34.94	7.97	39.67	74.00 -34.33 Peak

Remark:

1. Final Level = Receiver Read level + Correct factor
2. Correct factor = Antenna Factor + Cable Loss - Preamplifier Factor
3. **, means this data is the too weak instrument of signal is unable to test.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Middle
---------------	--------

Peak value:



Condition : FCC PART 15 (PK) 3m HORIZONTAL


Job No. : GTS202009000028

Test Mode : TX 2441MHz

Test Engineer: Hans

Remark :

Freq	Read	Antenna	Preamp	Cable	Limit	Over	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	4884.000	27.75	31.49	37.76	4.69	26.17	54.00	-27.83 Average
2	4884.000	34.75	31.49	37.76	4.69	33.17	74.00	-40.83 Peak
3	7323.000	22.86	36.18	35.60	6.63	30.07	54.00	-23.93 Average
4	7323.000	29.86	36.18	35.60	6.63	37.07	74.00	-36.93 Peak
5	9764.000	22.26	38.08	35.03	8.03	33.34	54.00	-20.66 Average
6	9764.000	29.26	38.08	35.03	8.03	40.34	74.00	-33.66 Peak



Condition : FCC PART 15 (PK) 3m VERTICAL

Job No. : GTS202009000028

Test Mode : TX 2441MHz

Test Engineer: Hans

Remark :

Freq	Read	Antenna	Preamp	Cable	Limit	Over	Remark
	Level	Factor	Factor	Loss	Level	Line	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	4884.000	25.36	31.49	37.76	4.69	23.78	54.00 -30.22 Average
2	4884.000	32.36	31.49	37.76	4.69	30.78	74.00 -43.22 Peak
3	7323.000	22.10	36.18	35.60	6.63	29.31	54.00 -24.69 Average
4	7323.000	29.10	36.18	35.60	6.63	36.31	74.00 -37.69 Peak
5	9764.000	22.06	38.08	35.03	8.03	33.14	54.00 -20.86 Average
6	9764.000	29.06	38.08	35.03	8.03	40.14	74.00 -33.86 Peak


Remark:

1. Final Level = Receiver Read level + Correct factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. **, means this data is the too weak instrument of signal is unable to test.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:

Highest

Peak value:



Condition : FCC PART 15 (PK) 3m VERTICAL


Job No. : GTS202009000028

Test Mode : TX 2480MHz

Test Engineer: Hans

Remark :

Freq	Read	Antenna	Preamp	Cable	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	
1	4960.000	24.48	31.63	37.78	4.79	23.12	54.00 -30.88 Average
2	4960.000	32.48	31.63	37.78	4.79	31.12	74.00 -42.88 Peak
3	7440.000	23.45	36.46	35.56	6.77	31.12	54.00 -22.88 Average
4	7440.000	30.45	36.46	35.56	6.77	38.12	74.00 -35.88 Peak
5	9920.000	22.90	38.42	35.14	8.09	34.27	54.00 -19.73 Average
6	9920.000	29.90	38.42	35.14	8.09	41.27	74.00 -32.73 Peak



Condition : FCC PART 15 (PK) 3m HORIZONTAL

Job No. : GTS202009000028

Test Mode : TX 2480MHz

Test Engineer: Hans

Remark :



	Read	Antenna	Preamp	Cable	Limit	Over	
Freq	Level	Factor	Factor	Loss	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	4960.000	26.94	31.63	37.78	4.79	25.58	54.00 -28.42 Average
2	4960.000	33.94	31.63	37.78	4.79	32.58	74.00 -41.42 Peak
3	7440.000	29.58	36.46	35.56	6.77	37.25	54.00 -16.75 Average
4	7440.000	22.58	36.46	35.56	6.77	30.25	74.00 -43.75 Peak
5	9920.000	21.85	38.42	35.14	8.09	33.22	54.00 -20.78 Average
6	9920.000	28.85	38.42	35.14	8.09	40.22	74.00 -33.78 Peak

Remark:

1. Final Level = Receiver Read level + Correct factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. **, means this data is the too weak instrument of signal is unable to test.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Radiated Emission



Conducted Emission

