



## **FCC Report (Bluetooth)**

**Applicant:** Dongguan Hele Electronics Co., Ltd.

**Address of Applicant:** Dalingya Industrial Zone, Daojiao Town, Dongguan City, Guangdong 523181, China

**Manufacturer:** Dongguan Hele Electronics Co., Ltd.

**Address of Manufacturer:** Dalingya Industrial Zone, Daojiao Town, Dongguan City, Guangdong 523181, China

### **Equipment Under Test (EUT)**

**Product Name:** Bluetooth headset

**Model No.:** QCY-L1

**FCC ID:** RDR-QCYL1

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** April 03, 2018

**Date of Test:** April 04-20, 2018

**Date of report issued:** April 23, 2018

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo

**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

Version No.	Date	Description
00	April 23, 2018	Original

Prepared By:

*Bill. Yuan*

Date:

April 23, 2018

Project Engineer

Check By:

*Andy Wu*

Date:

April 23, 2018

Reviewer

### 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
5 GENERAL INFORMATION .....	5
5.1 GENERAL DESCRIPTION OF EUT .....	5
5.2 TEST MODE .....	7
5.3 DESCRIPTION OF SUPPORT UNITS .....	7
5.4 ADDITIONAL INSTRUCTIONS .....	7
5.5 TEST FACILITY .....	7
5.6 TEST LOCATION .....	7
6 TEST INSTRUMENTS LIST .....	8
7 TEST RESULTS AND MEASUREMENT DATA .....	9
7.1 ANTENNA REQUIREMENT .....	9
7.2 CONDUCTED EMISSIONS .....	10
7.3 CONDUCTED OUTPUT POWER .....	13
7.4 CHANNEL BANDWIDTH .....	15
7.5 POWER SPECTRAL DENSITY .....	17
7.6 BAND EDGES .....	19
7.6.1 Conducted Emission Method .....	19
7.6.2 Radiated Emission Method .....	20
7.7 SPURIOUS EMISSION .....	22
7.7.1 Conducted Emission Method .....	22
7.7.2 Radiated Emission Method .....	24
8 TEST SETUP PHOTO .....	31
9 EUT CONSTRUCTIONAL DETAILS .....	32

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013.

### Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

Product Name:	Bluetooth headset
Model No.:	QCY-L1
Serial No.:	Lx
Test sample(s) ID:	GTS201804000074-1
Sample(s) Status	Engineer sample
Hardware:	V4.1
Software:	V4.1
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	Chip antenna
Antenna Gain:	2.50 dBi(Declared by Applicant)
Power Supply:	Battery: DC 3.7V, 0.30Wh, 80mAh DC 5.0V USB charger

<b>Operation Frequency each of channel</b>							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
...	...	...	...	...	...	...	...
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

## 5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

## 5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC Approval
Apple	PC	A1278	C1MN99ERDTY3	DOC

## 5.4 Additional Instructions

EUT Software Settings:

Mode	Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.		
Test Software Name	BlueTest3 V2.5.8		
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH1	2402	TX level : default
	CH20	2440	
	CH40	2480	

## 5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

## 5.6 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

## 6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 28 2017	June 27 2018
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 28 2017	June 27 2018
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 28 2017	June 27 2018
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2017	June 27 2018
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 28 2017	June 27 2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	June 28 2017	June 27 2018
10	Coaxial Cable	GTS	N/A	GTS211	June 28 2017	June 27 2018
11	Coaxial cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
12	Coaxial Cable	GTS	N/A	GTS212	June 28 2017	June 27 2018
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 28 2017	June 27 2018
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 28 2017	June 27 2018
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2017	June 27 2018
16	Band filter	Amindeon	82346	GTS219	June 28 2017	June 27 2018
17	Power Meter	Anritsu	ML2495A	GTS540	June 28 2017	June 27 2018
18	Power Sensor	Anritsu	MA2411B	GTS541	June 28 2017	June 27 2018
19	Loop Antenna	ZHINAN	ZN30900A	GTS534	June 28 2017	June 27 2018

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 28 2017	June 27 2018
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 28 2017	June 27 2018
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 28 2017	June 27 2018
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June 28 2017	June 27 2018


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 28 2017	June 27 2018

## 7 Test results and Measurement Data

### 7.1 Antenna requirement


<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
<b>15.203 requirement:</b>	
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>15.247(c) (1)(i) requirement:</b>	
(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
<b>E.U.T Antenna:</b>	
<i>The antenna is chip antenna, the best case gain of the antenna is 2.50dBi</i>	
	

## 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<small>* Decreases with the logarithm of the frequency.</small>																
Test setup:	 <p><i>Remark</i>  <i>E.U.T: Equipment Under Test</i>  <i>LISN: Line Impedance Stabilization Network</i>  <i>Test table height=0.8m</i></p>																
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2009 on conducted measurement.</li> </ol>																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.2 for details																
Test results:	Pass																


## Measurement data

Line:



Freq MHz	Reading level dBuV	1/ISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.237	28.30	0.40	0.11	28.81	62.22	-33.41	QP
0.237	21.40	0.40	0.11	21.91	52.22	-30.31	Average
0.317	32.22	0.39	0.10	32.71	59.80	-27.09	QP
0.317	25.21	0.39	0.10	25.70	49.80	-24.10	Average
0.402	31.18	0.35	0.11	31.64	57.81	-26.17	QP
0.402	18.19	0.35	0.11	18.65	47.81	-29.16	Average
0.529	34.56	0.31	0.11	34.98	56.00	-21.02	QP
0.529	21.20	0.31	0.11	21.62	46.00	-24.38	Average
0.634	31.05	0.28	0.12	31.45	56.00	-24.55	QP
0.634	22.27	0.28	0.12	22.67	46.00	-23.33	Average
1.129	26.73	0.20	0.15	27.08	56.00	-28.92	QP
1.129	13.10	0.20	0.15	13.45	46.00	-32.55	Average

Neutral:




Freq MHz	Reading level dBuV	1LISN/ISN factor dB	Cable loss dB	Limit level dBuV	Over limit dB	Remark
0.317	33.80	0.39	0.10	34.29	59.80	-25.51 QP
0.317	25.04	0.39	0.10	25.53	49.80	-24.27 Average
0.371	25.86	0.36	0.10	26.32	58.47	-32.15 QP
0.371	19.00	0.36	0.10	19.46	48.47	-29.01 Average
0.505	25.49	0.31	0.11	25.91	56.00	-30.09 QP
0.505	17.99	0.31	0.11	18.41	46.00	-27.59 Average
0.634	30.63	0.28	0.12	31.03	56.00	-24.97 QP
0.634	22.32	0.28	0.12	22.72	46.00	-23.28 Average
1.129	18.37	0.20	0.15	18.72	56.00	-37.28 QP
1.129	6.33	0.20	0.15	6.68	46.00	-39.32 Average
2.133	17.25	0.20	0.18	17.63	56.00	-38.37 QP
2.133	6.51	0.20	0.18	6.89	46.00	-39.11 Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*


## 7.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


### Measurement Data

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	5.38	30.00	Pass
Middle	5.67		
Highest	5.54		


**Test plot as follows:**



Lowest channel




Middle channel



Highest channel


## 7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


### Measurement Data

Test channel	Channel Bandwidth (MHz)	Limit(KHz)	Result
Lowest	0.695	>500	Pass
Middle	0.697		
Highest	0.695		


Test plot as follows:



Lowest channel




Middle channel



Highest channel


## 7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


### Measurement Data

Test channel	Power Spectral Density (dBm/3kHz)	Limit(dBm/3kHz)	Result
Lowest	-10.21	8.00	Pass
Middle	-9.41		
Highest	-10.15		


**Test plot as follows:**



Lowest channel




Middle channel




Highest channel

## 7.6 Band edges


### 7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### Test plot as follows:




Lowest channel



Highest channel

## 7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205								
Test Method:	ANSI C63.10:2013								
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak				
		RMS	1MHz	3MHz	Average				
Limit:	Frequency	Limit (dBuV/m @3m)		Value					
	Above 1GHz	54.00		Average					
		74.00		Peak					
Test setup:									
Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.</li> </ol>								
Test Instruments:	Refer to section 6.0 for details								
Test mode:	Refer to section 5.2 for details								
Test results:	Pass								

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test channel:	Lowest
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	42.05	27.59	5.38	30.18	44.84	74.00	-29.16	Horizontal
2400.00	58.72	27.58	5.39	30.18	61.51	74.00	-12.49	Horizontal
2390.00	42.52	27.59	5.38	30.18	45.31	74.00	-28.69	Vertical
2400.00	60.67	27.58	5.39	30.18	63.46	74.00	-10.54	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	32.79	27.59	5.38	30.18	35.58	54.00	-18.42	Horizontal
2400.00	43.98	27.58	5.39	30.18	46.77	54.00	-7.24	Horizontal
2390.00	32.67	27.59	5.38	30.18	35.46	54.00	-18.54	Vertical
2400.00	45.55	27.58	5.39	30.18	48.34	54.00	-5.67	Vertical

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.06	27.53	5.47	29.93	47.13	74.00	-26.88	Horizontal
2500.00	43.39	27.55	5.49	29.93	46.50	74.00	-27.51	Horizontal
2483.50	44.76	27.53	5.47	29.93	47.83	74.00	-26.17	Vertical
2500.00	44.31	27.55	5.49	29.93	47.42	74.00	-26.59	Vertical

**Average value:**


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.61	27.53	5.47	29.93	38.68	54.00	-15.33	Horizontal
2500.00	33.73	27.55	5.49	29.93	36.84	54.00	-17.17	Horizontal
2483.50	36.75	27.53	5.47	29.93	39.82	54.00	-14.18	Vertical
2500.00	33.58	27.55	5.49	29.93	36.69	54.00	-17.31	Vertical

**Remark:**

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.


## 7.7 Spurious Emission

### 7.7.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Test plot as follows:**


Lowest channel





Middle channel




Highest channel



## 7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9KHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	
	Above 1GHz	Peak	1MHz	3MHz	
		Peak	1MHz	10Hz	
Limit:	Frequency		Value	Measurement Distance	
	0.009MHz-0.490MHz		2400/F(KHz)		
	0.490MHz-1.705MHz		24000/F(KHz)		
	1.705MHz-30MHz		30		
	30MHz-88MHz		100		
	88MHz-216MHz		150		
	216MHz-960MHz		200		
	960MHz-1GHz		500		
	Above 1GHz		500		
			Average	3m	
			5000		
			Peak		
Test setup:	Below 30MHz 				
	Below 1GHz 				
	Above 1GHz 				



Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


#### Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

#### Measurement data:


##### 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

**Measurement Data****■ Below 1GHz****Horizontal:**

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
147.921	47.58	7.56	1.56	37.06	19.64	43.50	-23.86	QP
152.130	51.10	7.80	1.58	37.09	23.39	43.50	-20.11	QP
155.910	50.62	8.05	1.60	37.11	23.16	43.50	-20.34	QP
159.784	50.22	8.30	1.63	37.13	23.02	43.50	-20.48	QP
260.144	51.73	12.47	2.18	37.39	28.99	46.00	-17.01	QP
272.278	51.45	12.84	2.24	37.40	29.13	46.00	-16.87	QP

**Vertical:**



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
155.910	44.89	8.05	1.60	37.11	17.43	43.50	-26.07	QP
167.824	43.43	8.46	1.67	37.18	16.38	43.50	-27.12	QP
252.063	38.21	12.22	2.14	37.38	15.19	46.00	-30.81	QP
272.278	39.25	12.84	2.24	37.40	16.93	46.00	-29.07	QP
287.990	37.65	13.27	2.31	37.41	15.82	46.00	-30.18	QP
312.179	36.58	13.85	2.42	37.43	15.42	46.00	-30.58	QP

## ■ Above 1GHz

Test channel:	Lowest							
---------------	--------	--	--	--	--	--	--	--

### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	36.13	31.78	8.60	32.09	44.42	74.00	-29.58	Vertical
7206.00	31.05	36.15	11.65	32.00	46.85	74.00	-27.15	Vertical
9608.00	30.77	37.95	14.14	31.62	51.24	74.00	-22.76	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	40.18	31.78	8.60	32.09	48.47	74.00	-25.53	Horizontal
7206.00	32.70	36.15	11.65	32.00	48.50	74.00	-25.50	Horizontal
9608.00	30.09	37.95	14.14	31.62	50.56	74.00	-23.44	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

### Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	25.17	31.78	8.60	32.09	33.46	54.00	-20.54	Vertical
7206.00	19.87	36.15	11.65	32.00	35.67	54.00	-18.33	Vertical
9608.00	19.02	37.95	14.14	31.62	39.49	54.00	-14.51	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	29.26	31.78	8.60	32.09	37.55	54.00	-16.45	Horizontal
7206.00	21.97	36.15	11.65	32.00	37.77	54.00	-16.23	Horizontal
9608.00	18.65	37.95	14.14	31.62	39.12	54.00	-14.88	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

### Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. \*\*, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	36.56	31.85	8.67	32.12	44.96	74.00	-29.04	Vertical
7320.00	31.33	36.37	11.72	31.89	47.53	74.00	-26.47	Vertical
9760.00	31.03	38.35	14.25	31.62	52.01	74.00	-21.99	Vertical
12200.00	*					74.00		Vertical
14640.00	*					74.00		Vertical
4880.00	40.69	31.85	8.67	32.12	49.09	74.00	-24.91	Horizontal
7320.00	33.02	36.37	11.72	31.89	49.22	74.00	-24.78	Horizontal
9760.00	30.38	38.35	14.25	31.62	51.36	74.00	-22.64	Horizontal
12200.00	*					74.00		Horizontal
14640.00	*					74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	25.52	31.85	8.67	32.12	33.92	54.00	-20.08	Vertical
7320.00	20.11	36.37	11.72	31.89	36.31	54.00	-17.69	Vertical
9760.00	19.23	38.35	14.25	31.62	40.21	54.00	-13.79	Vertical
12200.00	*					54.00		Vertical
14640.00	*					54.00		Vertical
4880.00	29.67	31.85	8.67	32.12	38.07	54.00	-15.93	Horizontal
7320.00	22.24	36.37	11.72	31.89	38.44	54.00	-15.56	Horizontal
9760.00	18.90	38.35	14.25	31.62	39.88	54.00	-14.12	Horizontal
12200.00	*					54.00		Horizontal
14640.00	*					54.00		Horizontal

**Remark:**

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*\*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest							
---------------	---------	--	--	--	--	--	--	--

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.58	31.93	8.73	32.16	45.08	74.00	-28.92	Vertical
7440.00	31.35	36.59	11.79	31.78	47.95	74.00	-26.05	Vertical
9920.00	31.04	38.81	14.38	31.88	52.35	74.00	-21.65	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	40.72	31.93	8.73	32.16	49.22	74.00	-24.78	Horizontal
7440.00	33.04	36.59	11.79	31.78	49.64	74.00	-24.36	Horizontal
9920.00	30.39	38.81	14.38	31.88	51.70	74.00	-22.30	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.59	31.93	8.73	32.16	34.09	54.00	-19.91	Vertical
7440.00	20.16	36.59	11.79	31.78	36.76	54.00	-17.24	Vertical
9920.00	19.28	38.81	14.38	31.88	40.59	54.00	-13.41	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	29.75	31.93	8.73	32.16	38.25	54.00	-15.75	Horizontal
7440.00	22.29	36.59	11.79	31.78	38.89	54.00	-15.11	Horizontal
9920.00	18.95	38.81	14.38	31.88	40.26	54.00	-13.74	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

**Remark:**

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*\*”, means this data is the too weak instrument of signal is unable to test.

## 8 Test Setup Photo

Radiated Emission



## Conducted Emission



## 9 EUT Constructional Details

Reference to the test report No. GTS201804000074F01

-----End-----