Meru Networks, Inc FCC ID: RE7-AP1010

# 4 FCC §15.247(i) & §2.1091 - RF Exposure

## 4.1 Applicable Standard

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)	
Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*(100)	30	
1.34-30	824/f	2.19/f	$*(180/f^2)$	30	
30-300	27.5	0.073	0.2	30	
300-1500	/	/	f/1500	30	
1500-100,000	/	/	1.0	30	

f = frequency in MHz

#### 4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

#### 4.3 MPE Results

#### For 2.4 GHz Band

Maximum peak output power at antenna input terminal (dBm):			
Maximum peak output power at antenna input terminal (mW):			
Prediction distance (cm):	<u>20</u>		
Prediction frequency (MHz):	<u>2412</u>		
Maximum Antenna Gain, typical (dBi):	<u>3</u>		
Maximum Antenna Gain (numeric):	<u>2.0</u>		
Power density of prediction frequency at 20.0 cm (mW/cm <sup>2</sup> ):	<u>0.176</u>		
MPE limit for uncontrolled exposure at prediction frequency (mW/cm <sup>2</sup> ):			

<sup>\* =</sup> Plane-wave equivalent power density

Meru Networks, Inc FCC ID: RE7-AP1010

### For 5.8 GHz Band

Maximum peak output power at antenna input terminal (dBm):25.04Maximum peak output power at antenna input terminal (mW):319.15Prediction distance (cm):20Prediction frequency (MHz):5825

<u>Maximum Antenna Gain, typical (dBi):</u> 4 <u>Maximum Antenna Gain (numeric):</u> 2.51

Power density of prediction frequency at 20.0 cm (mW/cm<sup>2</sup>): 0.159

MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>): 1.0

The device meets MPE both 2.4 GHz and 5.8 GHz bands for the uncontrolled exposure environment.