

Atlas Compliance & Engineering, Inc.

FCC Change Test Report

FCC CFR 47 Part 15.209 and 15.249 COMPLIANCE

Reference: 0335GDIcontr_subc

*Go Direct International Ltd.
15 Emerson Road
Milford, New Hampshire, 03055 USA*

Product:

PS2 RF Controller

Model:

RadioWave Joypad

Test Report Number: 0349GDIcontr_PCII
Date of Report: December 12, 2003

This report contains 28 pages and may be reproduced in full only. Partial reproduction may only be done with the written consent of Atlas Compliance & Engineering, Inc.





Table of Contents

Table of Contents	2
General Information	3
Test Equipment.....	4
Test Configuration.....	5
EUT Description / Note:.....	5
EUT Support Program.....	5
EUT Modifications for Compliance	5
EUT Support Devices.....	6
I/O Ports and Cables	6
Equipment Under Test.....	7
Equipment Block Diagram	17
Test Setup (Radiated Emissions).....	18
Test Methods for Emissions	23
Conducted Emission Testing.....	23
Temperature and Humidity.....	24
Sample Calculations	24
FCC Part 15 Subpart C 15.209 and 15.249 Limits	25
Report of Measurements Radiated Data	26
Report of Measurements 15.209 Radiated Data	27
COMPLIANCE VERIFICATION REPORT	28
Table 1 - Support Equipment Used For Test	6
Table 2 - EUT Port Termination's.....	6
Table 3 - Host Port Termination's.....	6
Table 4 - Radiated Emission Limits, General Requirements.....	25
Table 5 - Radiated Emission Limits, Operation within the bands 902 – 928 MHz, 2400 – 2483.5 MHz, 5725 – 5875 MHz, and 24.0 – 24.25 GHz.....	25
Table 6 - Radiated Emission Level.....	26
Table 7 - Radiated Emission Level Below 30 MHz	27
Table 8 - Radiated Emission Level Below 1000 MHz	27
Figure 1 - Test Setup Diagram	17



General Information


Test Report Number: 0349GDIcontr_PCII
Date Product Tested: December 8 - 10, 2003
Date of Report: December 12, 2003
Applicant: Go Direct International Ltd.
15 Emerson Road
Milford, New Hampshire, 03055 USA
Contact Person: Edward Hames
Equipment Tested: PS2 RF Controller
Trade Name: RadioWave Joypad Controller
Model: RadioWave Joypad
Purpose Of Test: To demonstrate the compliance of the PS2 RF Controller, RadioWave Joypad, with the requirements of FCC CFR 47 Part 15 Rules and Regulations to the limits of Subpart C 15.209 and 15.249 using the procedure stated in ANSI C63.4-1992.
Frequency Range Investigated: 8 MHz to 10,000 MHz
FCC ID: REJGDC
Test Site Locations: Field Strength Measurement Facility:
Atlas Compliance & Engineering, Inc.
726 Hidden Valley Road
Royal Oaks, California 95076
Test Personnel: Mario E. Baraona Sr.
EMC Engineer



Test Equipment

The following list contains the test equipment that was utilized in making the measurements in this report.

Description _ Model	Serial	Manufacturer	Calibrated	Calibration Due
BiLog Antenna _ CBL6141	4034	Chase/Schaffner	7/6/03	7/6/04
Horn Antenna _ 3115	9003-3340	EMCO	1/23/03	1/23/04
Active Loop Antenna _ 6502	9108-2669	EMCO	12/13/02	12/13/03
Pre amp 9 kHz – 2 GHz _ CPA9231A	3323	Schaffner	5/24/03	5/24/04
Pre amp 1 – 26.5 GHz _ 8449B	3008A00910	HP	5/24/03	5/24/04
EMI Test Receiver 9 kHz - 2500 MHz _ ESPC	DE15934	Rohde & Schwarz	6/11/03	6/11/04
EMI Test Receiver 9 kHz - 2500 MHz _ ESPC	DE14459	Rohde & Schwarz	12/2/03	12/2/04
EMI Receiver 100 Hz – 22 GHz _ 8566B	2542A13058 (IF) 2637A03426 (RF)	HP	5/24/03	5/24/04
LISN _ 3825/2	9007-1683	EMCO	9/11/03	9/11/04
LISN _ 4825/2	9808-1088	EMCO	9/11/03	9/11/04



Test Configuration

Customer: Go Direct International Ltd.
Test Date: December 8 - 10, 2003
Specification: FCC CRF 47 Part 15.249 Limits,
ANSI C63.4-1992 Methods

EUT Description / Note:

The EUT, RadioWave Joypad, a PS2 RF Controller, was powered up with new batteries and in a continuous transmitting mode which is selectable throughout its operating range. The EUT is battery powered therefore no conducted emissions testing was performed. EUT frequencies of operation are 903.813, 906.972, 910.132, 913.292, 916.452, 919.66, 922.789, and 925.931 MHz

EUT Support Program

The EUT was constantly at 919.66 MHz. The other frequencies between 903.82 MHz and 925.95 MHz were tested to find maximum emissions, 919.634 MHz was where the maximum emission level was observed. Band edge measurements were taken with the EUT operating throughout 903.83 MHz and 925.95 MHz with FSK modulation.

EUT Modifications for Compliance

There were no modifications performed on the EUT. The test results state the emission levels of the EUT in the condition as it was received on December 8, 2003.



EUT Support Devices

Table 1 - Support Equipment Used For Test

Model:	Description:	S/N	FCC ID#
SCPH_39001	Sony, PlayStation 2 NTSC	U9242211	DoC
14AF-41	Toshiba Color TV	15611401 A	DoC


I/O Ports and Cables

Table 2 - EUT Port Termination's

I/O Port	Cable Type	Length	Connector	Termination
Battery	N/A	N/A	N/A	New Batteries (4-AA)

Table 3 - Host Port Termination's

I/O Port	Cable Type	Length	Connector	Termination
AV	Triple Coax, Ferrite Bead	8 FT	RCA (3x)	Monitor
Power	Non-Shielded	7 FT	IEC	Power Mains



Equipment Under Test


The photographs below show the condition of the EUT for test.




Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223





Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223




Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223





Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223



Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223





Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223



Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223



Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223



Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223







Equipment Block Diagram

Following is the block diagram of the test setup. Refer to TEST CONFIGURATION pages for port connections and information.


Figure 1 - Test Setup Diagram






Test Setup (Radiated Emissions)

The photographs below show worst case setup for radiated emission testing of the Joypad. In the X axis.



Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223



In the Y axis.




Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223



In the Z axis.






The photographs below show worst case setup for radiated emission testing at 3 Meters and 10 Meters with a loop antenna.



Atlas Compliance & Engineering, Inc.
1792 Little Orchard St.
San Jose, CA 95125
Phone 408.971.9743
Fax 831.761.3223





Test Methods for Emissions

The test procedure stated in ANSI C63.4-1992 was used to collect the test data. The radiated emission data of the EUT was taken with the Rohde & Schwarz EMI Test Receiver or HP 8566B. Incorporating the application of correction factors programmed into the Test Receiver and verified for distance, antenna, cable loss, and amplifier gain, the data was reduced as shown in the Sample Calculations. These correction factors are available upon request. The corrected data was then compared to the emission limits to determine compliance.


During radiated emission testing, the EUT was placed on a nonconductive rotating table 0.8 meter above the conductive grid. The nonconductive table dimensions were 1 meter deep by 1.5 meters wide at 0.8 meter high. The EUT is centered on the tabletop and the measurement antenna was placed 3 meters from the EUT as noted in the test data. The EUT, being a hand-held device, was tested in 3 orthogonal axes to determine which attitude produced the highest emission.

For radiated emissions testing, scans in the frequency range of 8 MHz to 10000 MHz were made. Each frequency between 9 kHz and 150 kHz was measured at a bandwidth of 200 Hz, between 150 kHz and 30 MHz was measured at a bandwidth of 10 kHz, between 30 MHz and 1000 MHz was measured at a bandwidth of 120 kHz and between 1000 MHz and above was measured at a bandwidth of 1 MHz. Measurements were made employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz, and above 1GHz which employed an average detector. All readings within 10 dB of the limits were recorded, and those emissions were then measured using the appropriate detector and bandwidth for a 2-second measurement time.

Measurements were made at a distance of 3 meters.

Conducted Emission Testing

The EUT is a battery powered device therefore no conducted emission testing was performed.



Temperature and Humidity


The ambient temperature of the actual EUT was within the range of 10° to 40° C (50° to 104° F) unless the particular equipment requirements specify testing over a different temperature range. The humidity levels were within the range of 10% to 90% relative humidity unless the EUT operating requirements call for a different level.

Sample Calculations

An example of how the EMI Test Receiver reading is converted using correction factors is given for the emissions recorded in Table 6. These correction factors are programmed into the EMI Test Receiver and verified. For radiated emissions in dB μ V/m, the EMI Test Receiver reading in dB μ V is corrected by using the following formula:

Meter Reading (dB μ V/m)
- Pre amp Gain (dB)
+ Cable Loss (dB)
+ Antenna Factor (dB)
= Corrected Reading (dB μ V/m)

This reading is then compared to the applicable specification limits and the difference will determine compliance. For conducted emissions, no correction factors are needed when a 50 μ H LISN is used.



FCC Part 15 Subpart C 15.209 and 15.249 Limits

Table 4 - Radiated Emission Limits, General Requirements

Frequency MHz	Field Strength μV/m	Measurement Distance Meters
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

NOTE:


1. The lower limit shall apply at the transition frequencies.
2. The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission.
3. The emission limits shown are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

*Table 5 - Radiated Emission Limits,
 Operation within the bands 902 – 928 MHz, 2400 – 2483.5 MHz,
 5725 – 5875 MHz, and 24.0 – 24.25 GHz.*

Frequency MHz	Field Strength of fundamental millivolts/meter	Field Strength of harmonics microvolts/meter
902 – 928	50	500
2400 – 2483.5	50	500
5725 – 5875	50	500
24000 – 24250	250	2500

NOTE:

1. Field strength limits are specified at a distance of 3 meters..
2. As shown in 15.35(b), for frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report of Measurements Radiated Data

The following table reports the results of the radiated measurements for the PS2 RF Controller, RadioWave Joypad.

Table 6 - Radiated Emission Level

15.249 Limit dB μ V/m	Fundamental Frequency MHz	Level dB μ V/m	Detector	Azimuth, Height	Orthogonal Plane	Antenna	Polarity	Margin dB
94 @ 3 meters	919.66	73.71	QP	45, 3.2M	X	BiLog	H	-20.79
		73.10	QP	335, 1M	Y	BiLog	V	-20.90
15.249 Limit dB μ V/m	Harmonic Frequency MHz	Level dB μ V	Detector	Azimuth, Height		Antenna	Polarity	Margin dB
54 @ 3 meters	1839.30	30	AV	260, 1.5M	X	Horn	H	-23.94
		29	AV	335, 1.1M	Y	Horn	V	-2294
54 @ 3 meters	2758.92	31	AV	20, 1.8M	X	Horn	H	-19.44
		27	AV	100, 1.1M	Y	Horn	V	-23.44
54 @ 3 meters	3678.66	26	AV	80, 2.2M	X	Horn	H	-20.44
		25	AV	100, 1M	Y	Horn	V	-21.60
54 @ 3 meters	4598.34	24	AV	10, 1.3M	X	Horn	H	-21.62
		26	AV	180, 1.4M	Y	Horn	V	-19.62
54 @ 3 meters	5517.90	24	AV	10, 1.3M	X	Horn	H	-18.50
		23	AV	0,1M	Y	Horn	V	-19.50
54 @ 3 meters	6437.64	25	AV	10, 1.3M	X	Horn	H	-17.21
		24	AV	0, 1M	Y	Horn	V	-18.21
54 @ 3 meters	7357.34	23	AV	10, 1.3M	X	Horn	H	-17.20
		25	AV	0,1M	Y	Horn	V	-15.20
54 @ 3 meters	8276.96	24	AV	10, 1.3M	X	Horn	H	-15.54
		25	AV	0,1M	Y	Horn	V	-14.54
54 @ 3 meters	9196.60	24	AV	10, 1.3M	X	Horn	H	-14.05
		25	AV	0, 1M	Y	Horn	V	-13.05
46 @ 3 meters	Bandedge 902	18.22	QP	0, 1.2M	X	BiLog	H	-28.28
46 @ 3 meters	Bandedge 928	18.41	QP	280, 1.2M	Y	BiLog	H	-27.39

Test Method: ANSI C63.4-1992
 Spec Limit: FCC 15.249
 No other emissions were observed.

Note: PK = Peak
 H = Horizontal
 V = Vertical

COMMENTS: System continuously running. Ambient temperature 68°F and relative humidity of 35%. Test distance of 3 meters. Quasi-peak and average detectors were not used since the peak readings were under the limits (unless otherwise noted). No emissions observed after the forth harmonic, measurements taken are baseline measurements after the forth harmonic. Band edge measurements were taken with FSK modulation, which are also at baseline.



Report of Measurements 15.209 Radiated Data

A Scan was performed throughout the Frequency range. There were no other observable emissions.

Table 7 - Radiated Emission Level Below 30 MHz

15.209 Limit dB μ V/M	Unwanted Frequency MHz	Level dB μ V	Detector	Test Distance in Meters	Margin dB	Antenna
49.5 @ 10 meters	8.005	9.90	QP	10	-39.60	Loop
49.5 @ 10 meters	16.00	8.89	QP	10	-40.61	Loop
49.5 @ 10 meters	14.765	9.47	QP	10	-40.03	Loop
49.5 @ 10 meters	29.465	10.52	QP	10	-38.98	Loop

Exploratory radiated emissions measurements were performed from 8 MHz to 30 MHz at 10 Meter and 3 Meter distances. The loop antenna was placed at 1 Meter height and was rotated about its vertical axis. The EUT was also rotated 360 degrees in front of the antenna.

Limit was extrapolated at 40 db/decade for measurement at 10 Meters. Emissions were at the noise floor. No other emissions were observed .


Table 8 - Radiated Emission Level Below 1000 MHz

Frequency MHz	QP Level dB μ V	QP Limit dB μ V	Margin dB	Azimuth, Height	Antenna, Polarization
432.0	28.44	47.00	-18.56	135, 2.4M	Bilog, V
897.85	24.33	47.00	-22.67	135, 1.1M	Bilog, V
432.0	26.86	47.00	-20.14	45, 3M	Bilog, H
895.8	28.94	47.00	-18.06	60, 1.2M	Bilog, H

<u>Start Freq.</u> 30MHz	<u>Stop Freq.</u> 1000MHz	<u>Step</u> 25kHz	<u>IF BW</u> 120kHz	<u>Detector</u> PK	<u>Scan-Time</u> 10msec	<u>Atten.</u> 0dB
-----------------------------	------------------------------	----------------------	------------------------	-----------------------	----------------------------	----------------------

Test Method: ANSI C63.4-1992
Spec Limit: FCC 15.209

Note: AV = Average
QP = Quasi Peak



COMPLIANCE VERIFICATION REPORT

TEST CERTIFICATE

APPLICANT: Go Direct International Ltd.
15 Emerson Road
Milford, New Hampshire, 03055 USA

Trade Name: PS2 RF Controller

Model: RadioWave Joypad

I HEREBY CERTIFY THAT:

The measurements shown in this report were made in accordance with the procedures indicated and that the energy emitted by this equipment, as received, was found to be within the FCC CFR 47 Part 15 Subpart C section 15.209 and 15.249 for Radiated emissions. Additionally, it should be noted that the results in this report apply only to the items tested, as identified herein.

I FURTHER CERTIFY THAT:

On the basis of the measurements taken at the test site, the equipment tested is capable of operation in compliance with the requirements set forth in FCC CFR 47 Part 15.209 and 15.249 Rules and Regulations.

On this Date: December 12, 2003

Mario E. Baraona Sr.

Mario E. Baraona Sr.
Atlas Compliance & Engineering, Inc.

Printed Name

Signature

Go Direct International Ltd. Representative