



MAX LIGHT

MEASUREMENT REPORT

Maximum Permissible Exposure

EUT : Wireless LAN PCI Card

Applicant : Xinetron Co., Ltd.
4F, No. 171, Sec. 2, Tatung Road, Hsichih,
Taipei Hsien, R.O.C.

Manufacturer : Xinetron Co., Ltd.
4F, No. 171, Sec. 2, Tatung Road, Hsichih,
Taipei Hsien, R.O.C.

Model No : WI011RE/GWI22B/WLP11B

FCC ID : REUWI011RE

Basis of Calculations:

$$E^2/3770 = S, \text{ mW/cm}^2$$

$$E, \text{ V/m} = (P_{\text{watts}} \cdot G_{\text{gain}} \cdot 30)^{.5} / d, \text{ meters}$$

$$d = ((P_{\text{watts}} \cdot G \cdot 30) / 3770 \cdot S)^{.5} \quad P_{\text{watts}} \cdot G_{\text{gain}} = 10^{(P_{\text{dBm}} - 30 + G_{\text{dBi}}) / 10}$$

Test Result:

Max RF Power (dBm)	TX Antenna Gain (dBi)	MPE Safe Distance(cm)
13.79	3.75	2.1

NOTE: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.