

FCC TEST REPORT
for
SZ Reach Tech Co., Ltd.

Portable wireless recorder

Model No.: yc300, yCxxx, yF300, yFxxx, yDxxx, yCat, yFoot, yLive, yZxxx, yMxxx ("x" Stands for the characters of 0~9, A~Z, a~z, space or symbols +, -)

Prepared for : SZ Reach Tech Co., Ltd.
Address : 6/F, Block B, Kingdee Software Park, # 2, Keji 12t, Shenzhen, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772


Report Number : R0217030104W
Date of Test : Mar. 28~Apr. 13, 2017
Date of Report : Apr. 14, 2017

TABLE OF CONTENT

1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
1.2. Auxiliary Equipment Used during Test.....	6
1.3. Description of Test Facility.....	6
1.4. Measurement Uncertainty.....	6
2. TEST METHODOLOGY.....	7
2.1. Summary of Test Results.....	7
2.2. Description of Test Modes.....	7
2.3. Description Of Test Setup.....	8
3. CONDUCTED EMISSION TEST.....	9
3.1. Block Diagram of Test Setup.....	9
3.2. Power Line Conducted Emission Measurement Limits (15.207).....	9
3.3. Configuration of EUT on Measurement.....	9
3.4. Operating Condition of EUT.....	9
3.5. Test Procedure.....	10
3.6. Test equipment.....	10
3.7. Power Line Conducted Emission Measurement Results.....	10
4. BANDWIDTH.....	15
4.1. Test Limit.....	15
4.2. Test Setup.....	15
4.3. Test Procedure.....	15
4.4. Test Equipment.....	16
4.5. Test Results.....	16
5. MAXIMUM CONDUCTED OUTPUT POWER TEST.....	24
5.1. Test Limit.....	24
5.2. Test Setup.....	25
5.3. Test Procedure.....	25
5.4. Test Equipment.....	25
5.5. Test Results.....	26
6. PEAK POWER SPECTRAL DENSITY TEST.....	33
6.1. Test Limit.....	33
6.2. Test Setup.....	34
6.3. Test Procedure.....	34
6.4. Test Equipment.....	35
6.5. Test Results.....	35
7. RADIATED EMISSION TEST.....	43
7.1. Test Limit.....	43
7.2. Test Setup.....	44
7.3. Test Procedure.....	45
7.4. Test Equipment.....	45
7.5. Test Results.....	45

8. BAND EDGE TEST.....	50
8.1. Test Limit.....	50
8.2. Test Setup.....	50
8.3. Test Procedure.....	50
8.4. Test Equipment.....	51
8.5. Test Results.....	51
9. ANTENNA APPLICATION.....	56
9.1. Antenna requirement.....	56
9.2. Result.....	56
10. PHOTOGRAPH.....	57
10.1. Photo of Conducted Emission Measurement.....	57
10.2. Photo of Radiation Emission Test.....	57
APPENDIX I (EXTERNAL PHOTOS).....	59
APPENDIX II(INTERNAL PHOTOS).....	63

TEST REPORT

Applicant : SZ Reach Tech Co., Ltd.
Manufacturer : SZ Reach Tech Co., Ltd.
EUT : Portable wireless recorder
Model No. : yc300, yCxxx, yF300, yFxxx, yDxxx, yCat, yFoot, yLive, yZxxx, yMxxx("x" Stands for the characters of 0~9, A~Z, a~z, space or symbols +, -)
Trade Mark : 
Rating : Input DC 12V, 5A (Via Adapter Input 100-240V, 1.6A max, 50/60Hz, Output DC 12V, 5A)

Measurement Procedure Used:
FCC Part15 Subpart E 2016, Paragraph 15.407

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart E requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.


Date of Test :

Mar. 28~Apr. 13, 2017



Prepared By :

(Tested Engineer / Winkey Wang)



Reviewer :

(Project Manager / Tangcy. T)



Approved & Authorized Signer :

(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Portable wireless recorder

Model Number : yc300, yCxxx, yF300, yFxxx, yDxxx, yCat, yFoot, yLive, yZxxx, yMxxx("x" Stands for the characters of 0~9, A~Z, a~z, space or symbols +, -)
(Note: All samples are the same except the model number and colour, so we prepare "yc300" for test only.)

Test Power Supply : AC 120V, 60Hz for adapter / AC 240V, 60Hz for adapter

Frequency : 5180-5240MHz
(5180MHz, 5200MHz, 5220MHz, 5240MHz)

Modulation : OFDM

Antenna Type : Rod Antenna

Antenna Gain: : 0 dBi

Applicant : SZ Reach Tech Co., Ltd.
Address : 6/F, Block B, Kingdee Software Park, # 2, Keji 12t, Shenzhen, China

Manufacturer : SZ Reach Tech Co., Ltd.
Address : 6/F, Block B, Kingdee Software Park, # 2, Keji 12t, Shenzhen, China

Date of receipt : Mar. 24, 2017

Date of Test : Mar. 28~Apr. 13, 2017

1.2. Auxiliary Equipment Used during Test

Adapter : Model No.: ST-A0060AAL-A1250
Input: 100-240V~50/60Hz 1.6A MAX , Class I
Output: DC 12V, 5A

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 06, 2016.

IC-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, Jun. 13, 2016.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.1 dB (Horizontal)
Ur = 4.3 dB (Vertical)

Conduction Uncertainty : Uc = 3.4dB

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC Part 15, Subpart E (15.407).

2.1. Summary of Test Results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result
FCC Part 15, Paragraph 15.207 & 15.407	Conducted Emission	PASS
FCC Part 15, Paragraph 15.407(b)(1)(4)(5)(7)	Undesirable Emission Restricted Band	PASS
FCC Part 15, Paragraph 15.407(a)(1)	26dB Bandwidth	PASS
FCC Part 15, Paragraph 15.407(a)(1)(2)(3)	Maximum Conducted Output Power	PASS
FCC Part 15, Paragraph 15.407(a)(1)(2)(3)	Peak Power Spectral Density	PASS
FCC Part 15, Paragraph 15.203	Antenna Requirement	PASS

2.2. Description of Test Modes


The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.


Mode	Test channel	TX Configuration				Simultaneously (4TX)
		ANT_1	ANT_2	ANT_3	ANT_4	
TX (Transmitting)	5180MHz	☒	☒	☒	☒	☒
	5200MHz	☒	☒	☒	☒	☒
	5240MHz	☒	☒	☒	☒	☒

2.3. Description Of Test Setup

CE




RE



3. Conducted Emission Test

3.1. Block Diagram of Test Setup

3.1.1. Block diagram of connection between the EUT and simulators



3.2. Power Line Conducted Emission Measurement Limits (15.207)

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4. Operating Condition of EUT

- 3.4.1. Setup the EUT and simulator as shown as Section 3.1.
- 3.4.2. Turn on the power of all equipment.
- 3.4.3. Let the EUT work in test mode(TX Mode) and measure it.

3.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 3.6.

3.6. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Two-Line V-network	Rohde & Schwarz	ENV216	100055	Jul. 19, 2016	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jun. 17, 2016	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Jun. 17, 2016	1 Year

3.7. Power Line Conducted Emission Measurement Results


PASS.

The frequency range from 150KHz to 30 MHz is investigated.

The EUT was tested on (TX Mode) Mode is attached in the following pages.


CONDUCTED EMISSION TEST DATA

Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 120V/60Hz (Worst Case)
 Comment: Live Line
 Tem.:25°C Hum.:50%



CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 120V/60Hz (Worst Case)
 Comment: Neutral Line
 Tem.:25°C Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1700	35.97	19.90	55.87	64.96	-9.09	QP	
2	0.1700	27.03	19.90	46.93	54.96	-8.03	AVG	
3	0.2207	22.47	19.89	42.36	52.79	-10.43	AVG	
4	0.2540	29.46	19.89	49.35	61.62	-12.27	QP	
5	0.3830	14.61	19.93	34.54	48.21	-13.67	AVG	
6	0.4100	22.40	19.94	42.34	57.65	-15.31	QP	
7	2.1220	13.97	20.14	34.11	56.00	-21.89	QP	
8	2.1220	5.87	20.14	26.01	46.00	-19.99	AVG	
9	8.4860	8.66	20.30	28.96	60.00	-31.04	QP	
10	8.4860	3.37	20.30	23.67	50.00	-26.33	AVG	
11	25.4580	18.34	20.28	38.62	60.00	-21.38	QP	
12	25.4580	16.62	20.28	36.90	50.00	-13.10	AVG	

CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 240V/60Hz (Worst Case)
 Comment: Live Line
 Tem.:25°C Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1580	34.62	19.90	54.52	65.56	-11.04	QP	
2	0.4460	28.44	19.96	48.40	56.95	-8.55	QP	
3	0.4540	22.15	19.96	42.11	46.80	-4.69	AVG	
4	0.4980	21.06	19.98	41.04	46.03	-4.99	AVG	
5	0.5020	28.74	19.98	48.72	56.00	-7.28	QP	
6	0.8780	25.99	20.09	46.08	56.00	-9.92	QP	
7	0.8780	16.13	20.09	36.22	46.00	-9.78	AVG	
8	1.1660	24.15	20.12	44.27	56.00	-11.73	QP	
9	1.2140	16.24	20.12	36.36	46.00	-9.64	AVG	
10	1.4660	22.93	20.13	43.06	56.00	-12.94	QP	
11	1.5580	13.69	20.13	33.82	46.00	-12.18	AVG	
12	1.8780	13.03	20.14	33.17	46.00	-12.83	AVG	

CONDUCTED EMISSION TEST DATA

Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 240V/60Hz (Worst Case)
 Comment: Neutral Line
 Tem.:25°C Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1700	34.25	19.90	54.15	64.96	-10.81	QP	
2	0.4580	26.35	19.96	46.31	56.73	-10.42	QP	
3	0.4620	21.08	19.96	41.04	46.66	-5.62	AVG	
4	0.8180	15.31	20.07	35.38	46.00	-10.62	AVG	
5	1.1140	25.67	20.12	45.79	56.00	-10.21	QP	
6	1.4980	28.14	20.13	48.27	56.00	-7.73	QP	
7	1.7940	17.12	20.14	37.26	46.00	-8.74	AVG	
8	1.8740	26.99	20.14	47.13	56.00	-8.87	QP	
9	2.1460	16.44	20.14	36.58	46.00	-9.42	AVG	
10	2.2700	25.08	20.15	45.23	56.00	-10.77	QP	
11	3.1700	14.52	20.16	34.68	46.00	-11.32	AVG	
12	4.2220	12.37	20.19	32.56	46.00	-13.44	AVG	


4. Bandwidth

4.1. Test Limit

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

4.2. Test Setup



4.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

3. Set the spectrum analyzer as:

26 dB & 99% bandwidth

RBW = approximately 1% of the emission bandwidth;

Set the VBW > RBW;

Detector = Peak

Trace mode = Max hold.

Sweep = auto couple.

6 dB bandwidth

RBW = 300 kHz;

Set the video bandwidth (VBW) ≥ 3 RBW;

Detector = Peak

Trace mode = Max hold.

Sweep = auto couple.

4. Measure the maximum width of the emission that is 26dB /6dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer.
5. Repeat until all the rest channels are investigated.

4.4. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Jul. 12, 2016	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Jun. 17, 2016	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Jun. 17, 2016	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	May 06, 2016	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB9163-289	May 06, 2016	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Jun. 17, 2016	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
8.	Power Sensor	Agilent	KFSW150502	15I00041SN045	Jun. 17, 2016	1 Year
9.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Jun. 17, 2016	1 Year
10.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Jun. 17, 2016	1 Year
11.	Signal Generator	Agilent	E4421B	MY41000743	Jun. 17, 2016	1 Year
12.	DC Power supply	IV	IV-8080	YQSB0096	Jun. 17, 2016	1 Year
13.	TEMP&HUMI PROGRAMMABLE CHAMBER	Bell Group	BE-THK-150M8	SE-0137	Jun. 17, 2016	1 Year
14.	Spectrum Analysis	Rohde & Schwarz	FSV40	132.1.3008K39-100965	Jun. 17, 2016	1 Year
15.	Pre-amplifier	Agilent	8449B	3008A00252	Jun. 17, 2016	1 Year
16.	Horn Antenna	SCHWARZBECK	BBHA9170	9170-068	Jun. 17, 2016	1 Year

4.5. Test Results


Pass.


Please refer to the following data.


Bandwidth:


Channel	Frequency (MHz)	26dB Bandwidth (MHz)				99% Bandwidth (MHz)			
		ANT_1	ANT_2	ANT_3	ANT_4	ANT_1	ANT_2	ANT_3	ANT_4
Low	5180	22.07	22.01	21.97	22.12	17.89	17.85	17.87	17.89
Mid	5200	22.16	22.16	22.17	22.07	17.87	17.87	17.88	17.88
High	5240	22.04	22.07	22.08	22.00	17.88	17.87	17.88	17.86


***Note: Only recorded the plots of the worst case in this report.














5. Maximum Conducted Output Power Test

5.1. Test Limit

1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.


(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum

power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2. Test Setup



5.3. Test Procedure

1. Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
2. Set RBW = 1 MHz.
3. Set VBW \geq 3 MHz.
4. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
5. Sweep time = auto.
6. Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
7. If transmit duty cycle $< 98\%$, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
8. Trace average at least 100 traces in power averaging (rms) mode.
9. Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

5.4. Test Equipment

Same as clause 4.4.

5.5. Test Results

Pass.


Please refer to the following data.


Test Mode: TX Mode


Channel	Frequency (MHz)	Maximum transmit power (dBm)					Limit (dBm)	Result
		ANT_1	ANT_2	ANT_3	ANT_4	Total		
Low	5180	9.66	9.44	10.10	9.56	15.72	23.98	Pass
Mid	5200	12.12	11.42	10.96	10.99	17.42	23.98	Pass
High	5240	12.07	10.89	11.95	11.61	17.67	23.98	Pass


***Note: Directional Gain=0dB_i+10*log(4)=6.02dB_i>6dB_i, so the limit shall be reduced to
24-(6.02-6)=23.98dBm


***Note: Only recorded the plots of the worst case in this report.














6. Peak Power Spectral Density Test

6.1. Test Limit

1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum

power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

6.2. Test Setup



6.3. Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz).

1. The EUT is directly connected to the spectrum analyzer;
2. Set RBW $\geq 1/T$;
3. Set VBW ≥ 3 RBW.;
3. Set the span to encompass the entire emissions bandwidth (EBW) of the signal;
5. Detector=RMS;
6. Sweep time= auto couple;
7. Trace mode=max. hold;

6.4. Test Equipment

Same as clause 4.4.

6.5. Test Results

Pass.


Please refer to the following data.

Test Mode: TX Mode


Channel	Frequency (MHz)	Final Power Spectral Density (dBm)					Power Spectral Density Limit (dBm/MHz)	Result
		ANT_1	ANT_2	ANT_3	ANT_4	Total		
Low	5180	3.064	3.041	3.108	2.969	9.07	10.98	Pass
Mid	5200	3.286	3.178	3.167	3.192	9.23	10.98	Pass
High	5240	3.367	3.281	3.161	3.017	9.23	10.98	Pass

***Note: Directional Gain=0dBi+10*log(4)=6.02dBi>6dBi, so the limit shall be reduced to
11-(6.02-6)=10.98 dBm/MHz


***Note: Only recorded the plots of the worst case in this report.





Test Mode: Low Channel---5180, ANT_1




Test Mode: Middle Channel---5200, ANT 1









Test Mode: Low Channel---5180, ANT_3



Test Mode: Middle Channel---5200, ANT_3





7. Radiated Emission Test

7.1. Test Limit

7.1.1. Test Limits (< 30 MHZ)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

7.1.2. Test Limits (\geq 30 MHZ)

FIELD STRENGTH of Fundamental: @3M	FIELD STRENGTH of Harmonics	S15.209 30 - 88 MHz	40 dBuV/m
902-928 MHZ		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
94 dB μ V/m @3m	54 dB μ V/m @3m	ABOVE 960 MHz	54dBuV/m


7.1.3. Restriction Band of Operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8


All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

7.2. Test Setup


7.2.1. 9k to 30MHz emissions:



7.2.2. 30M to 1G emissions:



7.2.3. 1G to 40G emissions:



7.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turntable shall be rotated 360 degrees to determine the position of max. emission level. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

Measurements are made on 9KHz to 30MHz and 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz.

The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

The test results are listed in Section 8.5.

7.4. Test Equipment


Same as clause 4.4.

7.5. Test Results

Please refer the following pages. Only the worst case (x orientation).


The test results of 9kHz-30MHz and above 18000MHz are attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Job No.:	0217030104W	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	AC 120V/60Hz
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX Mode	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.1347	37.88	-10.42	27.46	40.00	-12.54	QP	300	130	
2	56.7917	40.99	-15.09	25.90	40.00	-14.10	QP	300	240	
3	82.3588	45.93	-21.20	24.73	40.00	-15.27	QP	300	360	
4	93.4402	48.83	-21.60	27.23	43.50	-16.27	QP	300	180	
5	111.7380	47.97	-20.74	27.23	43.50	-16.27	QP	300	100	
6	400.4319	44.08	-12.86	31.22	46.00	-14.78	QP	300	220	

Job No.:	0217030104W	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	AC 120V/60Hz
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX Mode	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.4157	45.72	-10.53	35.19	40.00	-4.81	QP	300	58	
2	59.0251	43.29	-15.31	27.98	40.00	-12.02	QP	300	95	
3	70.0903	50.80	-19.64	31.16	40.00	-8.84	QP	300	100	
4	93.4402	43.83	-16.60	27.23	43.50	-16.27	QP	300	69	
5	200.6881	45.44	-15.85	29.59	43.50	-13.91	QP	300	120	
6	400.4319	51.65	-11.86	39.79	46.00	-6.21	QP	300	250	

Test Results (Above 1000MHz)

Test mode:	TX Mode (4TX)	Test channel:	Low CH
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
10360.00	39.57	31.98	17.08	33.91	54.72	74.00	-19.28	Vertical
15540.00	34.53	32.65	20.03	34.85	52.36	74.00	-21.64	Vertical
10360.00	38.11	31.98	17.08	33.91	53.26	74.00	-20.74	Horizontal
15540.00	38.00	32.65	20.03	34.85	55.83	74.00	-18.17	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
10360.00	29.15	31.98	17.08	33.91	44.30	54.00	-9.70	Vertical
15540.00	28.23	32.65	20.03	34.85	46.06	54.00	-7.94	Vertical
10360.00	30.37	31.98	17.08	33.91	45.52	54.00	-8.48	Horizontal
15540.00	28.57	32.65	20.03	34.85	46.40	54.00	-7.60	Horizontal

Test mode:	TX Mode (4TX)	Test channel:	Mid CH
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
10400.00	41.44	32.44	17.18	33.91	57.15	74.00	-16.85	Vertical
15600.00	37.04	32.78	20.12	34.86	55.08	74.00	-18.92	Vertical
10400.00	40.70	32.44	17.18	33.91	56.41	74.00	-17.59	Horizontal
15600.00	37.82	32.78	20.12	34.86	55.86	74.00	-18.14	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
10400.00	30.06	32.44	17.18	33.91	45.77	54.00	-8.23	Vertical
15600.00	26.42	32.78	20.12	34.86	44.46	54.00	-9.54	Vertical
10400.00	30.01	32.44	17.18	33.91	45.72	54.00	-8.28	Horizontal
15600.00	27.93	32.78	20.12	34.86	45.97	54.00	-8.03	Horizontal

Test mode:	TX Mode (4TX)	Test channel:	High CH
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
10480.00	40.50	32.59	18.02	33.92	57.19	74.00	-16.81	Vertical
15720.00	36.67	32.87	20.15	34.88	54.81	74.00	-19.19	Vertical
10480.00	40.84	32.59	18.02	33.92	57.53	74.00	-16.47	Horizontal
15720.00	40.88	32.87	20.15	34.88	59.02	74.00	-14.98	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
10480.00	31.05	32.59	18.02	33.92	47.74	54.00	-6.26	Vertical
15720.00	31.28	32.87	20.15	34.88	49.42	54.00	-4.58	Vertical
10480.00	28.72	32.59	18.02	33.92	45.41	54.00	-8.59	Horizontal
15720.00	29.54	32.87	20.15	34.88	47.68	54.00	-6.32	Horizontal

Note:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

8. BAND EDGE TEST

8.1. Test Limit

For transmitter operating in the 5.15-5.25GHz band: all emissions outside of the 5.15-5.35GHz outside of the 5.15-5.35GHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5.25-5.35GHz band: all emissions outside of the 5.15-5.35GHz band shall not exceed an EIRP of -27dBm/MHz. Devices operating in the 5.25-5.35GHz band that generate emissions in the 5.15-5.25GHz band must meet all applicable technical requirements for operation in the 5.15-5.25GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27dBm/MHz in the 5.15-5.25GHz band.

For transmitters operating in the 5.45-5.725GHz band: all emissions outside of the 5.47-5.725GHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5.725-5.825GHz band: all emissions within the frequency range from the band edge to 10MHz above or below the band edge shall not exceed an EIRP of -17dBm/MHz; for frequencies 10MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27dBm/MHz.

8.2. Test Setup

Same as clause 7.2.

8.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.
For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turntable shall be rotated 360 degrees to determine the position of max. emission level. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

Measurements are made on 9KHz to 30MHz and 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All readings are above 1GHz, peak & average values with a resolution bandwidth of 1MHz.

The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 9.5.

8.4. Test Equipment

Same as clause 4.4.

8.5. Test Results

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	EIRP (dBm)	Limit (dBm)	Polarization
TX Mode (4TX)								
5150.00	41.96	28.65	13.58	31.04	53.15	-42.05	-27.00	Vertical
5350.00	45.58	29.16	14.68	31.96	57.46	-37.74	-27.00	Vertical
5150.00	45.25	28.65	13.58	31.04	56.44	-38.76	-27.00	Horizontal
5350.00	45.31	29.16	14.68	31.96	57.19	-38.01	-27.00	Horizontal

Remark: 1. According to KDB 789033 D02 section H) d) (iii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows: $EIRP[\text{dBm}] = E[\text{dB}\mu\text{V}/\text{m}] - 95.2$


For conducted test:

***Note: Only recorded the plots of the worst case in this report.


TX Mode (ANT_1): Band Edge, Left Side




TX Mode (ANT_1): Band Edge, Right Side




TX Mode (ANT_2): Band Edge, Left Side




TX Mode (ANT_2): Band Edge, Right Side




TX Mode (ANT_3): Band Edge, Left Side




TX Mode (ANT_3): Band Edge, Right Side



TX Mode (ANT_4): Band Edge, Left Side



TX Mode (ANT_4): Band Edge, Right Side



Note: EIRP BAND EDGE=Reading Level+antenna gain

9. ANTENNA APPLICATION


9.1. Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.407.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2. Result

The EUT's antenna used a rod antenna which is permanently attached, The antenna's gain is 1.0dBi and meets the requirement.





10. PHOTOGRAPH

10.1. Photo of Conducted Emission Measurement



10.2. Photo of Radiation Emission Test





APPENDIX I (EXTERNAL PHOTOS)







APPENDIX II(INTERNAL PHOTOS)

