

FCC Test Report

Product Name	CMG-SBO-H
Model No	CMG-SBOF9C
FCC ID.	RGE-CMG-SBOF9C1

Applicant	Comigo Ltd.
Address	15 HaPardes St., Yarkona 45915 Israel

Date of Receipt	Jan. 21, 2015
Issue Date	Mar. 12, 2015
Report No.	1510452R-RFUSP26V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report

Issue Date: Mar. 12, 2015

Report No.: 1510452R-RFUSP26V00



Product Name	CMG-SBO-H
Applicant	Comigo Ltd.
Address	15 HaPardes St., Yarkona 45915 Israel
Manufacturer	GIGA-BYTE TECHNOLOGY CO., LTD
Model No.	CMG-SBOF9C
FCC ID.	RGE-CMG-SBOF9C1
EUT Rated Voltage	AC 100-240V, 50-60Hz
EUT Test Voltage	AC 120V/60Hz
Trade Name	COMIGO
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2014 ANSI C63.4: 2014, ANSI C63.10: 2013 KDB 558074 D01 DTS Meas Guidance v03r02
Test Result	Complied

Documented By

:

(Senior Adm. Specialist / Joanne Lin)

Tested By

:

(Engineer / Benjamin Pan)

Approved By

:

(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. EUT Description.....	5
1.2. Operational Description	7
1.3. Tested System Details.....	8
1.4. Configuration of Tested System	8
1.5. EUT Exercise Software	8
1.6. Test Facility	10
2. Conducted Emission.....	11
2.1. Test Equipment.....	11
2.2. Test Setup	11
2.3. Limits	12
2.4. Test Procedure	12
2.5. Uncertainty	12
2.6. Test Result of Conducted Emission.....	13
3. Peak Power Output	15
3.1. Test Equipment.....	15
3.2. Test Setup	15
3.3. Limits	15
3.4. Test Procedure	15
3.5. Uncertainty	15
3.6. Test Result of Peak Power Output.....	16
4. Radiated Emission.....	18
4.1. Test Equipment.....	19
4.2. Test Setup	20
4.3. Limits	21
4.4. Test Procedure	22
4.5. Uncertainty	22
4.6. Test Result of Radiated Emission.....	23
5. RF antenna conducted test.....	34
5.1. Test Equipment.....	35
5.2. Test Setup	35
5.3. Limits	35
5.4. Test Procedure	35
5.5. Uncertainty	35
5.6. Test Result of RF antenna conducted test.....	36
6. Band Edge	39
6.1. Test Equipment.....	39
6.2. Test Setup	40
6.3. Limits	40
6.4. Test Procedure	41
6.5. Uncertainty	41
6.6. Test Result of Band Edge	41

7.	Occupied Bandwidth	54
7.1.	Test Equipment.....	54
7.2.	Test Setup	54
7.3.	Limits	54
7.4.	Test Procedure	54
7.5.	Uncertainty	54
7.6.	Test Result of Occupied Bandwidth	55
8.	Power Density	61
8.1.	Test Equipment.....	61
8.2.	Test Setup	61
8.3.	Limits	61
8.4.	Test Procedure	61
8.5.	Uncertainty	61
8.6.	Test Result of Power Density	62
9.	EMI Reduction Method During Compliance Testing	67
Attachment 1: EUT Test Photographs		
Attachment 2: EUT Detailed Photographs		

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	CMG-SBO-H
Trade Name	COMIGO
Model No.	CMG-SBOF9C
FCC ID.	RGE-CMG-SBOF9C1
Frequency Range	802.11b/g/n-20BW: 2412-2462MHz
Number of Channels	802.11b/g/n-20MHz: 11
Data Speed	802.11b: 1-11Mbps, 802.11g: 6-54Mbps, 802.11n: up to 150Mbps
Type of Modulation	802.11b:DSSS (DBPSK, DQPSK, CCK) 802.11g/n:OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	PIFA Antenna
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto
Power Adapter	MFR: Asian Power Devices Inc., M/N: WB-18D12R Input: AC 100-240V~50-60Hz, 0.5A Max. Output: 12V $\overline{=}$ 1.5A Cable Out: Non-Shielded, 1.5m, with one ferrite core bonded.

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	ACON	APP6P-701321	PIFA	-0.12dBi for 2.4 GHz

Note: The antenna of EUT is conform to FCC 15.203.

802.11b/g/n-20MHz Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 01:	2412 MHz	Channel 02:	2417 MHz	Channel 03:	2422 MHz	Channel 04:	2427 MHz
Channel 05:	2432 MHz	Channel 06:	2437 MHz	Channel 07:	2442 MHz	Channel 08:	2447 MHz
Channel 09:	2452 MHz	Channel 10:	2457 MHz	Channel 11:	2462 MHz		

Note:

1. The EUT is a CMG-SBO-H with a built-in 2.4GHz WLAN transceiver.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps 、802.11g is 6Mbps 、802.11n(20M-BW) is 7.2Mbps)
4. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g/n transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.
5. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test Mode:	Mode 1: Transmit (802.11b 1Mbps)
	Mode 2: Transmit (802.11g 6Mbps)
	Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Monitor	DELL	U2410	CN-0J257M-728-011-04NL	Non-Shielded, 1.8m
2 Keyboard	Logitech	Y-U0009	LZ027HU	N/A
3 USB Mouse	Logitech	M-U0003	LZ024HR	N/A
4 Cambridge SoundWorks	Creative	S80130	AM01303200000941	Non-Shielded, 1.9m

Signal Cable Type	Signal cable Description
A HDMI Cable	Shielded, 2m, with two ferrite cores bonded.
B Keyboard Cable	Shielded, 1.8m
C Mouse Cable	Shielded, 1.8m
D Fiber Cable	Non-Shielded, 1.8m
E RJ45 Cable	Shielded, 2m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4
- (2) Execute software “Ampak RFestTool V5.2” on the EUT.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Press “OK” to start the continuous Transmit.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from

QuieTek Corporation's Web Site: <http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site:

<http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195

Site Name: Quietek Corporation
Site Address: No.5-22, Ruishukeng,
Linkou Dist. New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Conducted Emission


2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2015	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2015	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar., 2015	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2015	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBμV) Limit		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

Product : CMG-SBO-H
 Test Item : Conducted Emission Test
 Power Line : Line 1
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV	Margin dB	Limit dBμV
Line 1					
Quasi-Peak					
0.248	9.663	28.310	37.973	-25.227	63.200
0.591	9.682	17.820	27.502	-28.498	56.000
1.045	9.706	28.550	38.256	-17.744	56.000
4.029	9.831	14.870	24.701	-31.299	56.000
8.982	9.942	24.440	34.382	-25.618	60.000
11.943	9.978	25.530	35.508	-24.492	60.000
Average					
0.248	9.663	24.280	33.943	-19.257	53.200
0.591	9.682	7.290	16.972	-29.028	46.000
1.045	9.706	5.760	15.466	-30.534	46.000
4.029	9.831	9.240	19.071	-26.929	46.000
8.982	9.942	18.500	28.442	-21.558	50.000
11.943	9.978	23.200	33.178	-16.822	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : CMG-SBO-H
 Test Item : Conducted Emission Test
 Power Line : Line 2
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV	dB	dBμV
Line 2					
Quasi-Peak					
0.162	9.667	26.530	36.197	-29.460	65.657
0.248	9.663	28.390	38.053	-25.147	63.200
0.591	9.682	18.180	27.862	-28.138	56.000
1.041	9.706	29.120	38.826	-17.174	56.000
4.209	9.835	16.130	25.965	-30.035	56.000
8.947	9.971	24.780	34.751	-25.249	60.000
Average					
0.162	9.667	20.320	29.987	-25.670	55.657
0.248	9.663	27.930	37.593	-15.607	53.200
0.591	9.682	2.040	11.722	-34.278	46.000
1.041	9.706	4.130	13.836	-32.164	46.000
4.209	9.835	11.200	21.035	-24.965	46.000
8.947	9.971	19.030	29.001	-20.999	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

3. Peak Power Output


3.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Power Meter	Anritsu	ML2495A/6K00003357	May, 2014
X	Power Sensor	Anritsu	MA2411B/0738448	Jun., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

3.2. Test Setup



3.3. Limits

The maximum peak power shall be less 1 Watt.

3.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 D01 DTS Meas Guidance v03r02 section 9.1.2 PKPM1 Peak power meter method.

3.5. Uncertainty

± 1.27 dB

3.6. Test Result of Peak Power Output

Product : CMG-SBO-H
 Test Item : Peak Power Output Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit	Result
		1	2	5.5	11	1		
		Measurement Level (dBm)						
01	2412	11.31	-	-	-	14.48	<30dBm	Pass
06	2437	11.19	10.94	10.75	10.59	14.54	<30dBm	Pass
11	2462	11.15	-	-	-	14.37	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : CMG-SBO-H
Test Item : Peak Power Output Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		6	9	12	18	24	36	48	54	6		
		Measurement Level (dBm)										
01	2412	14.26	-	-	-	-	-	-	-	23.56	<30dBm	Pass
06	2437	14.17	14.14	14.04	13.92	13.79	13.66	13.54	13.42	23.75	<30dBm	Pass
11	2462	14.12	-	-	-	-	-	-	-	24.43	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product : CMG-SBO-H
 Test Item : Peak Power Output Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		7.2	14.4	21.7	28.9	43.3	57.8	65	72.2	7.2		
		Measurement Level (dBm)										
01	2412	13.64	-	-	-	-	-	-	-	22.98	<30dBm	Pass
06	2437	13.47	13.33	13.2	12.96	12.87	12.72	12.67	12.62	22.95	<30dBm	Pass
11	2462	13.38	-	-	-	-	-	-	-	22.92	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

4. Radiated Emission

4.1. Test Equipment

The following test equipments are used during the radiated emission test:


Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep., 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun., 2014
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun., 2014
	X	Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun., 2014
	X	Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun., 2014

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct, 2014
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar, 2014
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan., 2015
	X	Horn Antenna	TRC	AH-0801/95051	Aug., 2014
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan., 2015
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul., 2014
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul., 2014


- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
 2. The test instruments marked with "X" are used to measure the final test results.

4.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dBμV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2014 and tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2014 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The frequency range from 9kHz to 10th harmonics is checked.

4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

4.6. Test Result of Radiated Emission

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
Horizontal					
Peak Detector:					
4824.000	3.261	40.670	43.931	-30.069	74.000
7236.000	10.650	43.680	54.330	-19.670	74.000
9648.000	13.337	37.600	50.936	-23.064	74.000
Average Detector:					
7236.000	10.650	37.160	47.810	-6.190	54.000
Vertical					
Peak Detector:					
4824.000	6.421	41.360	47.781	-26.219	74.000
7236.000	11.495	45.680	57.175	-16.825	74.000
9648.000	13.807	37.170	50.976	-23.024	74.000
Average Detector:					
7236.000	11.495	39.750	51.245	-2.755	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
Peak Detector:					
4874.000	3.038	40.820	43.857	-30.143	74.000
7311.000	11.795	43.890	55.684	-18.316	74.000
9748.000	12.635	37.080	49.715	-24.285	74.000
Average Detector:					
7311.000	11.795	36.790	48.584	-5.416	54.000
Vertical					
Peak Detector:					
4874.000	5.812	40.210	46.021	-27.979	74.000
7311.000	12.630	43.660	56.289	-17.711	74.000
9748.000	13.126	36.850	49.976	-24.024	74.000
Average Detector:					
7311.000	12.630	36.510	49.139	-4.861	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
Peak Detector:					
4924.000	2.858	41.770	44.627	-29.373	74.000
7386.000	12.127	42.860	54.988	-19.012	74.000
9848.000	12.852	37.450	50.303	-23.697	74.000
Average Detector:					
7386.000	12.127	35.540	47.668	-6.332	54.000
Vertical					
Peak Detector:					
4924.000	5.521	41.060	46.580	-27.420	74.000
7386.000	13.254	44.020	57.274	-16.726	74.000
9848.000	13.367	36.860	50.227	-23.773	74.000
Average Detector:					
7386.000	13.254	37.360	50.614	-3.386	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
Horizontal					
Peak Detector:					
4824.000	3.261	40.350	43.611	-30.389	74.000
7236.000	10.650	53.480	64.130	-9.870	74.000
9648.000	13.337	37.420	50.756	-23.244	74.000
Average Detector:					
7236.000	10.650	37.080	47.730	-6.270	54.000
Vertical					
Peak Detector:					
4824.000	6.421	40.010	46.431	-27.569	74.000
7236.000	11.495	55.530	67.025	-6.975	74.000
9648.000	13.807	36.870	50.676	-23.324	74.000
Average Detector:					
7236.000	11.495	38.870	50.365	-3.635	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB μ V	dB μ V/m	dB	dB μ V/m
Horizontal					
Peak Detector:					
4874.000	3.038	39.680	42.717	-31.283	74.000
7311.000	11.795	52.290	64.084	-9.916	74.000
9748.000	12.635	37.000	49.635	-24.365	74.000
Average Detector:					
7311.000	11.795	35.630	47.424	-6.576	54.000
Peak Detector:					
4874.000	5.812	40.770	46.581	-27.419	74.000
7311.000	12.630	55.030	67.659	-6.341	74.000
9748.000	13.126	36.910	50.036	-23.964	74.000
Average Detector:					
7311.000	12.630	38.490	51.119	-2.881	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB μ V	dB μ V/m	dB	dB μ V/m
Horizontal					
Peak Detector:					
4924.000	2.858	40.800	43.657	-30.343	74.000
7386.000	12.127	50.290	62.418	-11.582	74.000
9848.000	12.852	37.330	50.183	-23.817	74.000
Average Detector:					
7386.000	12.127	34.320	46.448	-7.552	54.000
Vertical					
Peak Detector:					
4924.000	5.521	41.490	47.010	-26.990	74.000
7386.000	13.254	52.890	66.144	-7.856	74.000
9848.000	13.367	37.380	50.747	-23.253	74.000
Average Detector:					
7386.000	13.254	36.860	50.114	-3.886	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)(2412MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB μ V	dB μ V/m	dB	dB μ V/m
Horizontal					
Peak Detector:					
4824.000	3.261	39.690	42.951	-31.049	74.000
7236.000	10.650	51.450	62.100	-11.900	74.000
9648.000	13.337	37.140	50.476	-23.524	74.000
Average Detector:					
7236.000	10.650	35.340	45.990	-8.010	54.000
Vertical					
Peak Detector:					
4824.000	6.421	40.460	46.881	-27.119	74.000
7236.000	11.495	53.810	65.305	-8.695	74.000
9648.000	13.807	37.080	50.886	-23.114	74.000
Average Detector:					
7236.000	11.495	37.760	49.255	-4.745	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
Peak Detector:					
4874.000	3.038	40.180	43.217	-30.783	74.000
7311.000	11.795	49.620	61.414	-12.586	74.000
9748.000	12.635	37.300	49.935	-24.065	74.000
Average Detector:					
7311.000	11.795	33.620	45.414	-8.586	54.000
Vertical					
Peak Detector:					
4874.000	5.812	40.800	46.611	-27.389	74.000
7311.000	12.630	53.650	66.279	-7.721	74.000
9748.000	13.126	37.050	50.176	-23.824	74.000
Average Detector:					
7311.000	12.630	37.510	50.139	-3.861	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Peak Detector:					
4924.000	2.858	40.010	42.867	-31.133	74.000
7386.000	12.127	49.010	61.138	-12.862	74.000
9848.000	12.852	37.210	50.063	-23.937	74.000
Average Detector:					
7386.000	12.127	33.620	45.748	-8.252	54.000
Vertical					
Peak Detector:					
4924.000	5.521	40.720	46.240	-27.760	74.000
7386.000	13.254	50.780	64.034	-9.966	74.000
9848.000	13.367	37.690	51.057	-22.943	74.000
Average Detector:					
7386.000	13.254	35.780	49.034	-4.966	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss –Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : CMG-SBO-H
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)(2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
53.280	-11.697	46.736	35.039	-4.961	40.000
189.080	-10.027	41.280	31.253	-12.247	43.500
404.420	0.889	30.407	31.296	-14.704	46.000
594.540	3.555	27.722	31.277	-14.723	46.000
743.920	3.898	30.325	34.223	-11.777	46.000
984.480	8.098	24.297	32.395	-21.605	54.000
Vertical					
53.280	-11.767	44.566	32.799	-7.201	40.000
189.080	-5.617	39.068	33.451	-10.049	43.500
458.740	-2.562	31.890	29.328	-16.672	46.000
596.480	0.907	27.763	28.670	-17.330	46.000
747.800	1.665	31.333	32.998	-13.002	46.000
943.740	3.383	23.905	27.288	-18.712	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : CMG-SBO-H
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)(2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
53.280	-11.697	46.185	34.488	-5.512	40.000
189.080	-10.027	41.667	31.640	-11.860	43.500
322.940	-4.536	34.817	30.282	-15.718	46.000
540.220	3.499	26.854	30.353	-15.647	46.000
747.800	3.915	31.138	35.053	-10.947	46.000
947.620	6.971	24.681	31.652	-14.348	46.000
Vertical					
107.600	-4.027	32.316	28.289	-15.211	43.500
189.080	-5.617	38.069	32.452	-11.048	43.500
458.740	-2.562	29.400	26.838	-19.162	46.000
606.180	2.246	25.972	28.218	-17.782	46.000
747.800	1.665	30.348	32.013	-13.987	46.000
945.680	3.300	24.751	28.051	-17.949	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : CMG-SBO-H
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)(2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBμV	dBμV/m	dB	dBμV/m
Horizontal					
134.760	-7.473	38.211	30.738	-12.762	43.500
268.620	-5.522	36.135	30.613	-15.387	46.000
404.420	0.889	31.113	32.002	-13.998	46.000
540.220	3.499	27.418	30.917	-15.083	46.000
745.860	3.906	34.594	38.500	-7.500	46.000
928.220	7.230	23.774	31.004	-14.996	46.000
Vertical					
107.600	-4.027	32.247	28.220	-15.280	43.500
189.080	-5.617	38.637	33.020	-10.480	43.500
377.260	0.647	30.450	31.097	-14.903	46.000
606.180	2.246	25.302	27.548	-18.452	46.000
792.420	2.681	27.504	30.185	-15.815	46.000
968.960	3.936	24.382	28.318	-25.682	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

5. RF antenna conducted test


5.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2014
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2014
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

5.2. Test Setup

RF antenna Conducted Measurement:



5.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.4. Test Procedure

The EUT was tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.

5.5. Uncertainty


The measurement uncertainty

Conducted is defined as $\pm 1.27\text{dB}$


5.6. Test Result of RF antenna conducted test

Product : CMG-SBO-H
 Test Item : RF antenna conducted test
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product : CMG-SBO-H
 Test Item : RF Antenna Conducted Spurious
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product : CMG-SBO-H
 Test Item : RF Antenna Conducted Spurious
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)


Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



6. Band Edge

6.1. Test Equipment

RF Conducted Measurement

The following test equipments are used during the band edge tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2014
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2014
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.

RF Radiated Measurement:


The following test equipments are used during the band edge tests:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct., 2014
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar., 2015
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan., 2015
	X	Horn Antenna	TRC	AH-0801/95051	Aug., 2014
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan., 2015
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul., 2014
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul., 2014


- Note:
1. All instruments are calibrated every one year.
 2. The test instruments marked by "X" are used to measure the final test results.

6.2. Test Setup

RF Conducted Measurement



RF Radiated Measurement:



6.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

6.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2014 and tested according to DTS test procedure of Jan. 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2014 on radiated measurement.

6.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

6.6. Test Result of Band Edge

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2390.000	31.509	26.832	58.341	74.00	54.00	Pass
01 (Peak)	2400.000	31.561	32.248	63.809	--	--	--
01 (Peak)	2412.800	31.645	73.693	105.337	--	--	--
01 (Average)	2390.000	31.509	15.040	46.549	74.00	54.00	Pass
01 (Average)	2400.000	31.561	23.274	54.835	--	--	--
01 (Average)	2412.600	31.642	69.814	101.457	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

RF RadRF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2390.000	30.915	26.296	57.211	74.00	54.00	Pass
01 (Peak)	2400.000	30.912	32.023	62.935	--	--	--
01 (Peak)	2412.800	30.955	73.211	104.166	--	--	--
01 (Average)	2390.000	30.915	15.512	46.427	74.00	54.00	Pass
01 (Average)	2400.000	30.912	23.612	54.524	--	--	--
01 (Average)	2411.200	30.944	69.470	100.414	--	--	--

Figure Channel 01: VERTICAL (Peak)





Figure Channel 01: VERTICAL (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2462.700	32.025	75.738	107.763	--	--	--
11 (Peak)	2483.500	32.182	26.803	58.985	74.00	54.00	Pass
11 (Peak)	2489.100	32.224	27.592	59.816	74.00	54.00	Pass
11 (Average)	2461.100	32.013	72.085	104.098	--	--	--
11 (Average)	2483.500	32.182	14.615	46.797	74.00	54.00	Pass
11 (Average)	2488.700	32.222	17.626	49.847	74.00	54.00	Pass

Figure Channel 11: Horizontal (Peak)





Figure Channel 11: Horizontal (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)

RF RadRF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2462.700	31.295	76.027	107.322	--	--	--
11 (Peak)	2483.500	31.435	26.369	57.804	74.00	54.00	Pass
11 (Peak)	2488.100	31.466	28.731	60.197	74.00	54.00	Pass
11 (Average)	2461.100	31.285	72.319	103.603	--	--	--
11 (Average)	2483.500	31.435	15.102	46.537	74.00	54.00	Pass
11 (Average)	2488.700	31.471	18.510	49.980	74.00	54.00	Pass

Figure Channel 11: VERTICAL (Peak)





Figure Channel 11: VERTICAL (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2390.000	31.509	34.634	66.143	74.00	54.00	Pass
01 (Peak)	2400.000	31.561	42.997	74.558	--	--	--
01 (Peak)	2411.800	31.636	75.234	106.871	--	--	--
01 (Average)	2390.000	31.509	18.732	50.241	74.00	54.00	Pass
01 (Average)	2400.000	31.561	23.388	54.949	--	--	--
01 (Average)	2413.000	31.646	62.260	93.906	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

RF RadRF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2390.000	30.915	34.521	65.436	74.00	54.00	Pass
01 (Peak)	2400.000	30.912	43.370	74.282	--	--	--
01 (Peak)	2411.600	30.946	75.622	106.569	--	--	--
01 (Average)	2390.000	30.915	19.724	50.639	74.00	54.00	Pass
01 (Average)	2400.000	30.912	24.110	55.022	--	--	--
01 (Average)	2413.000	30.956	62.298	93.254	--	--	--

Figure Channel 01: VERTICAL (Peak)





Figure Channel 01: VERTICAL (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2461.700	32.017	77.854	109.871	--	--	--
11 (Peak)	2483.500	32.182	35.489	67.671	74.00	54.00	Pass
11 (Average)	2462.700	32.025	64.278	96.303	--	--	--
11 (Average)	2483.500	32.182	19.569	51.751	74.00	54.00	Pass

Figure Channel 11: Horizontal (Peak)





Figure Channel 11: Horizontal (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2461.700	31.288	78.636	109.924	--	--	--
11 (Peak)	2483.500	31.435	36.767	68.202	74.00	54.00	Pass
11 (Average)	2460.700	31.281	65.152	96.433	--	--	--
11 (Average)	2483.500	31.435	20.584	52.019	74.00	54.00	Pass

Figure Channel 11: VERTICAL (Peak)





Figure Channel 11: VERTICAL (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. " * ", means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)

RF RadRF Radiated Measurement (HORIZONTAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2389.400	31.507	34.249	65.756	74.00	54.00	Pass
01 (Peak)	2390.000	31.509	32.643	64.152	74.00	54.00	Pass
01 (Peak)	2400.000	31.561	40.958	72.519	--	--	--
01 (Peak)	2412.200	31.640	73.424	105.064	--	--	--
01 (Average)	2390.000	31.509	18.953	50.462	74.00	54.00	Pass
01 (Average)	2400.000	31.561	23.413	54.974	--	--	--
01 (Average)	2413.000	31.646	61.563	93.209	--	--	--

Figure Channel 01:

HORIZONTAL (Peak)





Figure Channel 01:

HORIZONTAL (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)

RF RadRF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2389.600	30.917	36.451	67.368	74.00	54.00	Pass
01 (Peak)	2390.000	30.915	34.933	65.848	74.00	54.00	Pass
01 (Peak)	2400.000	30.912	42.414	73.326	--	--	--
01 (Peak)	2412.000	30.950	73.742	104.691	--	--	--
01 (Average)	2390.000	30.915	19.512	50.427	74.00	54.00	Pass
01 (Average)	2400.000	30.912	23.805	54.717	--	--	--
01 (Average)	2412.800	30.955	61.671	92.626	--	--	--

Figure Channel 01:

VERTICAL (Peak)





Figure Channel 01:

VERTICAL (Average)



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2462.314	32.022	75.096	107.118	--	--	--
11 (Peak)	2483.500	32.182	32.273	64.455	74.00	54.00	Pass
11 (Average)	2461.118	32.013	63.654	95.667	--	--	--
11 (Average)	2483.500	32.182	18.939	51.121	74.00	54.00	Pass

Figure Channel 11:

Horizontal (Peak)





Figure Channel 11:

Horizontal (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : CMG-SBO-H
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)

RF Radiated Measurement (VERTICAL):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2461.500	31.287	75.960	107.247	--	--	--
11 (Peak)	2483.500	31.435	33.462	64.897	74.00	54.00	Pass
11 (Peak)	2485.500	31.449	34.714	66.163	74.00	54.00	Pass
11 (Average)	2460.900	31.283	64.384	95.667	--	--	--
11 (Average)	2483.500	31.435	19.758	51.193	74.00	54.00	Pass

Figure Channel 11: VERTICAL (Peak)





Figure Channel 11: VERTICAL (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

7. Occupied Bandwidth


7.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2014
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2014
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

7.2. Test Setup



7.3. Limits

The minimum bandwidth shall be at least 500 kHz.

7.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2014; tested according to DTS test procedure of Jan KDB558074 for compliance to FCC 47CFR 15.247 requirements.

7.5. Uncertainty

$\pm 150\text{Hz}$

7.6. Test Result of Occupied Bandwidth

Product : CMG-SBO-H
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412	8150	>500	Pass
6	2437	8150	>500	Pass
11	2462	8150	>500	Pass

Figure Channel 1:




Figure Channel 6:





Figure Channel 11:



Product : CMG-SBO-H
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412	15200	>500	Pass
6	2437	15200	>500	Pass
11	2462	15200	>500	Pass

Figure Channel 1:




Figure Channel 6:





Figure Channel 11:



Product : CMG-SBO-H
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412	16150	>500	Pass
6	2437	15400	>500	Pass
11	2462	15200	>500	Pass

Figure Channel 1:




Figure Channel 6:





Figure Channel 11:



8. Power Density


8.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2014
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2014
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.

8.2. Test Setup



8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

8.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2013; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using KDB 558074 section 10.2 PKPSD (peak PSD) method.

8.5. Uncertainty

± 1.27 dB

8.6. Test Result of Power Density

Product : CMG-SBO-H
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412	3.580	< 8dBm	Pass
6	2437	3.860	< 8dBm	Pass
11	2462	3.320	< 8dBm	Pass

Figure Channel 1:




Figure Channel 6:





Figure Channel 11:



Product : CMG-SBO-H
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412	3.520	< 8dBm	Pass
6	2437	3.360	< 8dBm	Pass
11	2462	2.910	< 8dBm	Pass

Figure Channel 1:




Figure Channel 6:





Figure Channel 11:



Product : CMG-SBO-H
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412	2.990	< 8dBm	Pass
6	2437	2.600	< 8dBm	Pass
11	2462	2.640	< 8dBm	Pass

Figure Channel 1:




Figure Channel 6:





Figure Channel 11:



9. EMI Reduction Method During Compliance Testing

No modification was made during testing.

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs