



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No. :** CQASZ20200200098E-02  
**Applicant:** Stillwater Designs & Audio ,Inc  
**Address of Applicant:** 3100 N Husband Street, Stillwater OK 74075 United States of America  
**Equipment Under Test (EUT):**  
**EUT Name:** Marine Audio  
**Model No.:** KMC2, KMC3  
**Test Model No.:** KMC2  
**Brand Name:** KICKER  
**FCC ID:** RGR-46KMC2  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-03-02  
**Date of Test:** 2020-03-02 to 2020-03-26  
**Date of Issue:** 2020-03-26  
**Test Result :** PASS\*

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

Tom Chen.

(Tom Chen)

**Reviewed By:**

Aaron Ma

(Aaron Ma)

**Approved By:**

Jack Ai

( Jack Ai)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200200098E-02	Rev.01	Initial report	2020-03-26

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits .....	5
4.1.3 EUT RF Exposure.....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Stillwater Designs & Audio ,Inc
Address of Applicant:	3100 N Husband Street, Stillwater OK 74075 United States of America
Manufacturer:	Eastern Partner Limited
Address of Manufacturer:	1002, 10/F, 189 Des Voeux Road, Central Hong Kong

#### 3.2 General Description of EUT

Product Name:	Marine Audio
Model No.:	KMC2, KMC3
Test Model No.:	KMC2
Trade Mark:	KICKER
Hardware Version:	20200104 REV:06
Software Version:	20200106U2
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	FCCAssist 2.4 (manufacturer declare )
Antenna Type:	PCB antenna
Antenna Gain:	-0.58dBi
Power Supply:	DC12V

Model No.: KMC2, KMC3

Only the model KMC2 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

#### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	-4.930	-5.5±1	-4.5	0.355
Middle(2441MHz)	-5.310	-6.0±1	-5.0	0.316
Highest(2480MHz)	-4.600	-5.5±1	-4.5	0.355
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	-4.290	-5.0±1	-4.0	0.398
Middle(2441MHz)	-4.630	-5.5±1	-4.5	0.355
Highest(2480MHz)	-4.050	-5.0±1	-4.0	0.398

#### Worst case: π/4DQPSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-4.290	-5.0±1	-4.0	0.398	0.123	3.0
Middle (2441MHz)	-4.630	-5.5±1	-4.5	0.355	0.111	
Highest (2480MHz)	-4.050	-5.0±1	-4.0	0.398	0.125	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200200098E-01