


## RF Exposure Evaluation Report

**Report Reference No.**.....: **MTEB24120264-H**

**FCC ID.**.....: **RGR-KMC4**

Compiled by

( position+printed name+signature) ..: File administrators Alisa Luo




Supervised by

( position+printed name+signature) ..: Test Engineer Sunny Deng



Approved by

( position+printed name+signature) ..: Manager Yvette Zhou



Date of issue.....: **Dec.20,2024**

**Representative Laboratory Name.** : **Shenzhen Most Technology Service Co., Ltd.**

Address.....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**.....: **Stillwater Designs and Audio Inc.**

Address.....: 3100 N Husband St. Stillwater OK 74075 USA

**Test specification/ Standard**.....: **47 CFR Part 1.1307;47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**.....: Weather Resistant Gauge -Style Media Center with Bluetooth

Trade Mark.....: KICKER

Model/Type reference.....: KMC4

Listed Models .....: N/A

Modulation Type.....: GFSK, π/4DQPSK, 8DPSK

Operation Frequency.....: 2402MHz to 2480MHz

Hardware Version.....: 1120-KMC402-MB06

Software Version.....: KMC4-X3-KIC-V1.45

Rating.....: DC 12V by DC Source

Result.....: **PASS**

## TEST REPORT

Equipment under Test : Weather Resistant Gauge -Style Media Center with Bluetooth

Model /Type : KMC4

Listed Models : N/A

Remark 1 : N/A

Applicant : **Stillwater Designs and Audio Inc.**

Address : 3100 N Husband St. Stillwater OK 74075 USA

Manufacturer : **Eastern Partner Limited**

Address : Room 1413, ICC Tower ,Fuhau San Road,Futian CBD,Shenzhen 518048,China

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## 1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2024.12.20	Initial Issue	Alisa Luo

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 2.1.3 EUT RF Exposure

BT classic

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-3.927	-3.927±1	-2.927
Middle(2441MHz)	-3.591	-3.591±1	-2.591
Highest(2480MHz)	-3.531	-3.531±1	-2.531

π /4DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-3.036	-3.036±1	-2.036
Middle(2441MHz)	-2.723	-2.723±1	-1.723
Highest(2480MHz)	-2.666	-2.666±1	-1.666

8DPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-2.604	-2.604±1	-1.604
Middle(2441MHz)	-2.273	-2.273±1	-1.273
Highest(2480MHz)	-2.236	-2.236±1	-1.236

Worst case: 8DPSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Highest(2480MHz)	-1.236	0.75	0	0.00015	1.0	Pass

Note: 1) Refer to report MTEB24080209-R for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (0.75 \cdot 1) / (4 \cdot 3.1416 \cdot 202) = 0.00015$

Note: 3 )EUT's Bluetooth module is more than 20cm away from the human body.

.....THE END OF REPORT.....