

DE 2000-03

This device complies with Part 15 of FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

WITTENBORG		CFT600	/P2110R		030302	xxxxx
VOLT		240	V~	HZ/CPS.	50/60	
TOTAL		5,7	kW	KÜHLUNG, REFRIGERATION REFROIDISSEMENT		W
HEIZUNG . HEATING CHAUFFAGE		5,61	kW	COMPRESSOR COMPRESSEUR		A
		30	A	KESSELINHALT, BOILER CAP. CAPACITE DE BUILOIRE	10	L.
		ATM	bar			
			Bar	N&W Global Technology		
Min. dyn. line pres. 0,8bar, Max. st. line pres. 10 bar						
	IPX1		LISTED 28G0	FCC ID RH4-RFID-IDENT600		

Scotchcal, 3698, ED, aluminum-colored
 Sign: silver
 Writing: black
 Supplier:
UL approved company !
 according UL and CSA regulation

.	.	.	.	.	Modell:	
.	c	Comment listed 28G0 addet	14.11.06	Diestel	Gewicht:	kg Blatt
.	b	Adjustment discription	09.11.06	Diestel	Volumen:	ml 1 von
.	a	Adjustment series	24.10.05	Diestel	DIN 6 T1 Projektions- methode 1	1
ÄNDRG.-NR.	INDEX	BESCHREIBUNG DER ÄNDERUNG	DATUM	NAME	GEPR.	A4
ERSATZ F.	.	 N&W Global Technology	MAßSTAB		WERKSTOFF	
ERSETZT D.	.					
TOLERANZEN						
	DATUM	NAME	BENENNUNG		ARTIKEL- NR.	ROHTEIL
GEZ.	07.07.05	Diestel	Type plate, printed CFT600 / P2110R		FERTIGTEIL	36034400
GEPR.	.	.				
GEPR.	.	.			ZEICH- NUNGS- NR.	35279200c