



TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1211-1096MPE01R1

Page 1 of 5

MPE REPORT

Product Name HSPA+ Module

Manufacture AnyDATA Shanghai Co., Ltd

Model DTL718-W

FCC ID RHZDTL718-W

Test date 2012-12-21

Approved by

Director

Revised by

Manager

Performed by

Engineer

Test By

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

Contact: Yang Weizhong

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: <http://www.ta-shanghai.com>

E-mail: yangweizhong@ta-shanghai.com

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1211-1096MPE01R1

Page 2 of 5

Maximum Permissible Exposure

Type of EUT: HSPA+ Module

FCC ID: RHZDTL718-W

Manufacturer: AnyDATA Shanghai Co., Ltd

Model: DTL718-W

Maximum conducted output power (measured) and antenna Gain:

Band	Maximum Average Conducted Output Power (dBm)	Antenna Gain (dBi)
UMTS Band II	23.35	4.5
UMTS Band V	23.32	4.5

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1211-1096MPE01R1

Page 3 of 5

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500MHz is f/1500, 1500~100,000MHz is f/1500. So

Band	The maximum permissible exposure
WCDMA Band II	1 mW/cm²
WCDMA Band V	0.56 mW/cm²

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1211-1096MPE01R1

Page 4 of 5

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.



TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1211-1096MPE01R1

Page 5 of 5

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided.

This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm^2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to

an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

UMTS Band II: $PG = 23.35\text{dBm} + (4.5\text{dBi}) = 27.85\text{dBm} = 609.54 \text{ mW} = 0.610 \text{ W}$

UMTS Band V $PG = 23.32\text{dBm} + (4.5\text{dBi}) = 27.82\text{dBm} = 605.34 \text{ mW} = 0.605 \text{ W}$

$R = 20 \text{ cm}$

$\pi = 3.1416$

Solving for S , the power density at 20 cm is

Band	Test Result (mW/cm^2)	Limit Value (mW/cm^2)
UMTS Band II	0.1214	1 mW/cm^2
UMTS Band V	0.1204	0.56 mW/cm^2

Note: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of 47 CFR Part 15.247 (b) (5)