

# FCC TEST REPORT

## (PART 90)

|            |                                                    |
|------------|----------------------------------------------------|
| Applicant: | Telit Communications S.p.A                         |
| Address:   | Via Stazione di Prosecco, 5/B Sgonico, 34010 Italy |


|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Manufacturer or Supplier | Telit Communications S.p.A                                                                           |
| Address                  | Via Stazione di Prosecco, 5/B Sgonico, 34010 Italy                                                   |
| Product                  | LTE Cat 1 bis module                                                                                 |
| Brand Name               | Telit Cinterion or  |
| Model Name               | LE310P1-SN                                                                                           |
| FCC ID                   | RI7LE310P1SN                                                                                         |
| Date of tests            | Apr. 16, 2025~ Jun. 27, 2025                                                                         |

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 90, Subpart R, S**  
☒ **ANSI/TIA/EIA-603- D**  
☒ **FCC Part 2**

☒ **ANSI/TIA/EIA-603-E**  
☒ **ANSI C63.26-2015**

**CONCLUSION:** The submitted sample was found to COMPLY with the test requirement

|                                                                                     |                                                                                      |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Prepared by Hanwen Xu<br>Engineer / Mobile Department                               | Approved by Peibo Sun<br>Manager / Mobile Department                                 |
|  |  |
| Date: Jun. 27, 2025                                                                 | Date: Jun. 27, 2025                                                                  |

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## Table of Contents

|          |                                                                                 |           |
|----------|---------------------------------------------------------------------------------|-----------|
| <b>1</b> | <b>SUMMARY OF TEST RESULTS .....</b>                                            | <b>5</b>  |
| 1.1      | MEASUREMENT UNCERTAINTY .....                                                   | 6         |
| 1.2      | TEST SITE AND INSTRUMENTS .....                                                 | 7         |
| <b>2</b> | <b>GENERAL INFORMATION .....</b>                                                | <b>9</b>  |
| 2.1      | GENERAL DESCRIPTION OF EUT .....                                                | 9         |
| 2.2      | CONFIGURATION OF SYSTEM UNDER TEST .....                                        | 10        |
| 2.3      | DESCRIPTION OF SUPPORT UNITS .....                                              | 11        |
| 2.4      | DESCRIPTION OF TEST MODES .....                                                 | 12        |
| 2.5      | GENERAL DESCRIPTION OF APPLIED STANDARDS .....                                  | 14        |
| <b>3</b> | <b>TEST TYPES AND RESULTS .....</b>                                             | <b>15</b> |
| 3.1      | OUTPUT POWER MEASUREMENT .....                                                  | 15        |
| 3.1.1    | LIMITS OF OUTPUT POWER MEASUREMENT .....                                        | 15        |
| 3.1.2    | TEST PROCEDURES .....                                                           | 15        |
| 3.1.3    | TEST SETUP .....                                                                | 16        |
| 3.1.4    | TEST RESULTS .....                                                              | 17        |
| 3.2      | FREQUENCY STABILITY MEASUREMENT .....                                           | 19        |
| 3.2.1    | LIMITS OF FREQUENCY STABILITY MEASUREMENT .....                                 | 19        |
| 3.2.2    | TEST PROCEDURE .....                                                            | 19        |
| 3.2.3    | TEST SETUP .....                                                                | 19        |
| 3.2.4    | TEST RESULTS .....                                                              | 20        |
| 3.3      | OCCUPIED BANDWIDTH MEASUREMENT .....                                            | 21        |
| 3.3.1    | LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT .....                                  | 21        |
| 3.3.2    | TEST SETUP .....                                                                | 21        |
| 3.3.3    | TEST PROCEDURES .....                                                           | 21        |
| 3.3.4    | TEST RESULTS .....                                                              | 21        |
| 3.4      | EMISSION MASK MEASUREMENT .....                                                 | 22        |
| 3.4.1    | LIMITS OF EMISSION MASK MEASUREMENT .....                                       | 22        |
| 3.4.2    | TEST SETUP .....                                                                | 22        |
| 3.4.3    | TEST PROCEDURES .....                                                           | 23        |
| 3.4.4    | TEST RESULTS .....                                                              | 23        |
| 3.5      | CONDUCTED SPURIOUS EMISSIONS .....                                              | 24        |
| 3.5.1    | LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT .....                        | 24        |
| 3.5.2    | TEST PROCEDURE .....                                                            | 24        |
| 3.5.3    | TEST SETUP .....                                                                | 24        |
| 3.5.4    | TEST RESULTS .....                                                              | 25        |
| 3.6      | RADIATED EMISSION MEASUREMENT .....                                             | 26        |
| 3.6.1    | LIMITS OF RADIATED EMISSION MEASUREMENT .....                                   | 26        |
| 3.6.2    | TEST PROCEDURES .....                                                           | 26        |
| 3.6.3    | DEVIATION FROM TEST STANDARD .....                                              | 26        |
| 3.6.4    | TEST SETUP .....                                                                | 27        |
| 3.6.5    | TEST RESULTS .....                                                              | 29        |
| 3.7      | PEAK TO AVERAGE RATIO .....                                                     | 39        |
| 3.7.1    | LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT .....                               | 39        |
| 3.7.2    | TEST SETUP .....                                                                | 39        |
| 3.7.3    | TEST PROCEDURES .....                                                           | 39        |
| 3.7.4    | TEST RESULTS .....                                                              | 39        |
| <b>4</b> | <b>INFORMATION ON THE TESTING LABORATORIES .....</b>                            | <b>40</b> |
| <b>5</b> | <b>MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 41</b> |           |
| <b>6</b> | <b>APPENDIX .....</b>                                                           | <b>42</b> |



## Test Report No.: PBJ-NQN2504110217RF05

|                                             |    |
|---------------------------------------------|----|
| FCC-LTE-BAND14 .....                        | 42 |
| PEAK-TO-AVERAGE RATIO(CCDF) .....           | 42 |
| TEST RESULT .....                           | 42 |
| TEST GRAPHS .....                           | 42 |
| 26DB BANDWIDTH AND OCCUPIED BANDWIDTH ..... | 47 |
| TEST RESULT .....                           | 47 |
| TEST GRAPHS .....                           | 47 |
| BAND EDGE .....                             | 48 |
| TEST RESULT .....                           | 48 |
| TEST GRAPHS .....                           | 49 |
| CONDUCTED SPURIOUS EMISSION .....           | 53 |
| TEST RESULT .....                           | 53 |
| TEST GRAPHS .....                           | 53 |
| FREQUENCY STABILITY .....                   | 55 |
| TEST RESULT .....                           | 55 |



Test Report No.: PBJ-NQN2504110217RF05

## RELEASE CONTROL RECORD

| ISSUE NO.             | REASON FOR CHANGE | DATE ISSUED   |
|-----------------------|-------------------|---------------|
| PBJ-NQN2504110217RF05 | Original release  | Jun. 27, 2025 |



## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 90 & Part 2 |                              |        |
|----------------------------------------|------------------------------|--------|
| STANDARD SECTION                       | TEST TYPE AND LIMIT          | RESULT |
| §2.1046<br>§90.635(b)                  | Conducted Output Power       | PASS   |
| §2.1055<br>§90.213                     | Frequency Stability          | PASS   |
| §2.1049<br>§90.209                     | Occupied Bandwidth           | PASS   |
| §2.1051<br>§90.691                     | Emission Masks               | PASS   |
| §2.1051<br>§90.691                     | Conducted Spurious Emissions | PASS   |
| §2.1053<br>§90.691                     | Radiated Spurious Emissions  | PASS   |

### \*Test Lab Information Reference

#### Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

#### Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

**Accredited Test Lab Cert 6613.01**

**The FCC Site Registration No. is 434559; The Designation No. is CN1325.**




## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT         | FREQUENCY     | UNCERTAINTY |
|---------------------|---------------|-------------|
| Conducted emissions | 9kHz~30MHz    | 2.66dB      |
| Radiated emissions  | 9KHz ~ 30MHz  | 2.68dB      |
|                     | 30MHz ~ 1GHz  | 3.26dB      |
|                     | 1GHz ~ 18GHz  | 4.48dB      |
|                     | 18GHz ~ 40GHz | 4.12dB      |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



The verdicts in this test report are given according the above diagram:

| Case | Measured Value  | Uncertainty Range | Verdict |
|------|-----------------|-------------------|---------|
| 1    | below pass mark | below pass mark   | Passed  |
| 2    | below pass mark | within pass mark  | Passed  |
| 3    | above pass mark | within pass mark  | Failed  |
| 4    | above pass mark | above pass mark   | Failed  |

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



## 1.2 TEST SITE AND INSTRUMENTS

| Equipment                          | Manufacturer                 | Model No.   | Serial No.            | Last Cal. | Next Cal. |
|------------------------------------|------------------------------|-------------|-----------------------|-----------|-----------|
| Pre-Amplifier                      | R&S                          | SCU18F1     | 100815                | Aug.30,23 | Aug.29,25 |
| Pre-Amplifier                      | R&S                          | SCU08F1     | 101028                | Jan.22,24 | Jan.21,26 |
| Vector Signal Generator            | R&S                          | SMBV100B    | 102176                | Mar.29,24 | Mar.28,26 |
| Signal Generator                   | R&S                          | SMB100A     | 182185                | Mar.29,24 | Mar.28,26 |
| 3m Fully-anechoic Chamber          | TDK                          | 9m*6m*6m    | HRSW-SZ-EMC-01Chamber | Nov.25,22 | Nov.24,25 |
| 3m Semi-anechoic Chamber           | TDK                          | 9m*6m*6m    | HRSW-SZ-EMC-02Chamber | Nov.25,22 | Nov.24,25 |
| EMI TEST Receiver                  | R&S                          | ESR26       | 101734                | Mar.28,24 | Mar.27,26 |
| EMI TEST Receiver                  | R&S                          | ESW44       | 101973                | Mar.28,24 | Mar.27,26 |
| Bilog Antenna                      | SCHWARZBECK                  | VULB 9163   | 1264                  | Jul.04,25 | Jul.03,27 |
| Horn Antenna                       | ETS-LINDGREN                 | 3117        | 227836                | Aug.22,23 | Aug.21,25 |
| Horn Antenna (18GHz-40GHz)         | Steatite Q-par Antennas      | QMS 00880   | 23486                 | Jul.15,24 | Jul.14,26 |
| Horn Antenna                       | Steatite Q-par Antennas      | QMS 00208   | 23485                 | Mar.22,25 | Mar.21,27 |
| Loop Antenna                       | SCHWARZ                      | HFH2-Z2/Z2E | 100976                | Feb.22,25 | Feb.21,27 |
| WIDEBANDRADIO COMMUNICATION TESTER | R&S                          | CMW500      | 169399                | Jun.19,24 | Jun.18,26 |
| Radio Communication Tester         | Rohde&Schwarz                | CMX500      | 101446                | Mar.21,25 | Mar.20,27 |
| Test Software                      | EMC32                        | EMC32       | N/A                   | N/A       | N/A       |
| 6DB attenuator                     | Tonscend Technology Co., Ltd | N/A         | 23062787              | N/A       | N/A       |
| Test Software                      | ELEKTRA                      | ELEKTRA4.32 | N/A                   | N/A       | N/A       |
| Open Switch and Control Unit       | R&S                          | OSP220      | 101964                | N/A       | N/A       |
| DC Source                          | HYELEC                       | HY3010B     | 551016                | Aug.31,23 | Aug.30,25 |
| Hygrothermograph                   | DELI                         | 20210528    | SZ014                 | Mar.18,25 | Mar.17,27 |
| PC                                 | LENOVO                       | E14         | HRSW0024              | N/A       | N/A       |



|                      |        |                  |                |           |           |
|----------------------|--------|------------------|----------------|-----------|-----------|
| TMC-AMI18843A(CABLE) | R&S    | HF290-NMNM-7.00M | N/A            | N/A       | N/A       |
| TMC-AMI18843A(CABLE) | R&S    | HF290-NMNM-4.00M | N/A            | N/A       | N/A       |
| CABLE                | R&S    | W13.02           | N/A            | Apr.27,24 | Apr.26,25 |
| CABLE                | R&S    | W13.02           | N/A            | Apr.26,25 | Apr.25,26 |
| CABLE                | R&S    | W12.14           | N/A            | Apr.27,24 | Apr.26,25 |
| CABLE                | R&S    | W12.14           | N/A            | Apr.26,25 | Apr.25,26 |
| CABLE                | R&S    | J12J103539-00-1  | SEP-03-20-069  | Apr.27,24 | Apr.26,25 |
| CABLE                | R&S    | J12J103539-00-1  | SEP-03-20-069  | Apr.26,25 | Apr.25,26 |
| CABLE                | R&S    | J12J103539-00-1  | SEP-03-20-070  | Apr.27,24 | Apr.26,25 |
| CABLE                | R&S    | J12J103539-00-1  | SEP-03-20-070  | Apr.26,25 | Apr.25,26 |
| Temperature Chamber  | votsch | VT4002           | 58566078100050 | May.30,24 | May.29,26 |

**NOTE:**

1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                       |                                                                                                      |                                 |
|-----------------------|------------------------------------------------------------------------------------------------------|---------------------------------|
| PRODUCT               | LTE Cat 1 bis module                                                                                 |                                 |
| BRAND NAME            | Telit Cinterion or  |                                 |
| MODEL NAME            | LE310P1-SN                                                                                           |                                 |
| NOMINAL VOLTAGE       | 3.8V dc                                                                                              |                                 |
| MODULATION TECHNOLOGY | LTE                                                                                                  | QPSK, 16QAM                     |
| FREQUENCY RANGE       | LTE Band 14<br>Channel Bandwidth: 5MHz                                                               | 790.5MHz ~ 795.5MHz             |
|                       | LTE Band 14<br>Channel Bandwidth: 10MHz                                                              | 793MHz                          |
| EMISSION DESIGNATOR   | LTE Band 14<br>Channel Bandwidth: 5MHz                                                               | QPSK: 4M57G7D<br>16QAM: 4M57W7D |
|                       | LTE Band 14<br>Channel Bandwidth: 10MHz                                                              | QPSK: 9M10G7D<br>16QAM: 4M94W7D |
| MAX. EIRP POWER       | LTE Band 14<br>Channel Bandwidth: 5MHz                                                               | 198.61mW                        |
|                       | LTE Band 14<br>Channel Bandwidth: 10MHz                                                              | 204.17mW                        |
| ANTENNA GAIN          | 2dBi                                                                                                 |                                 |
| ANTENNA TYPE          | Main Ant:Fixed External Antenna                                                                      |                                 |
| HW VERSION            | 0.0                                                                                                  |                                 |
| SW VERSION            | M0E.200001                                                                                           |                                 |
| I/O PORTS             | Refer to user's manual                                                                               |                                 |
| DATA CABLE            | N/A                                                                                                  |                                 |
| EXTREME TEMPERATURE   | -10°C ~ 55°C                                                                                         |                                 |
| EXTREME VOLTAGE       | 3.4Vdc ~ 4.2Vdc                                                                                      |                                 |

#### NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receivers.





| MODULATION MODE | TX FUNCTION |
|-----------------|-------------|
| LTE             | 1TX/1RX     |

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



## 2.2 CONFIGURATION OF SYSTEM UNDER TEST

### FOR RADIATION EMISSION TEST





## 2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT   | BRAND    | MODEL NO. | SERIAL NO. | FCC ID |
|-----|-----------|----------|-----------|------------|--------|
| 1   | DC source | LONG WEI | PS-6403D  | 010934269  | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | DC Line: Unshielded, Detachable 1.0m                |

## 2.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP/EIRP and radiated emission was found when positioned on Y-plane for LTE. Following channel(s) was (were) selected for the final test as listed below:

| EUT CONFIGURE MODE | DESCRIPTION                             |
|--------------------|-----------------------------------------|
| A                  | EUT + Adapter + USB Cable with LTE link |
| B                  | EUT + DC Supply with LTE link           |

### LTE BAND 14 MODE

| EUT CONFIGURE MODE | TEST ITEM             | AVAILABLE CHANNEL | TESTED CHANNEL      | CHANNEL BANDWIDTH | MODULATION  | MODE                                      |
|--------------------|-----------------------|-------------------|---------------------|-------------------|-------------|-------------------------------------------|
| A                  | ERP                   | 23305 to 23355    | 23305, 23330, 23355 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset                        |
|                    |                       | 23330             | 23330               | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset                        |
| B                  | FREQUENCY STABILITY   | 23330             | 23330               | 10MHz             | QPSK        | 50 RB / 0 RB Offset                       |
| A                  | OCCUPIED BANDWIDTH    | 23305 to 23355    | 23305, 23330, 23355 | 5MHz              | QPSK, 16QAM | 25 RB / 0 RB Offset                       |
|                    |                       | 23330             | 23330               | 10MHz             | QPSK, 16QAM | 50 RB / 0 RB Offset                       |
| A                  | PEAK TO AVERAGE RATIO | 23305 to 23355    | 23305, 23330, 23355 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset<br>25 RB / 0 RB Offset |
|                    |                       | 23330             | 23330               | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset<br>50 RB / 0 RB Offset |
| A                  | BAND EDGE             | 23305 to 23355    | 23305               | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset                        |
|                    |                       |                   |                     |                   |             | 25 RB / 0 RB Offset                       |
|                    |                       |                   | 23355               | 5MHz              | QPSK, 16QAM | 1 RB / 24 RB Offset                       |
|                    |                       |                   |                     |                   |             | 25 RB / 0 RB Offset                       |
|                    |                       | 23300             | 23330               | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset                        |
|                    |                       |                   |                     |                   |             | 50 RB / 0 RB Offset                       |
|                    |                       |                   |                     |                   |             | 1 RB / 49 RB Offset                       |
|                    |                       |                   |                     |                   |             | /                                         |
| A                  | CONDUCTED EMISSION    | 23305 to 23355    | 23305, 23330, 23355 | 5MHz              | QPSK        | 1 RB / 0 RB Offset                        |
|                    |                       | 23330             | 23330               | 10MHz             | QPSK        | 1 RB / 0 RB Offset                        |



|   |                   |                |                     |       |      |                    |
|---|-------------------|----------------|---------------------|-------|------|--------------------|
| A | RADIATED EMISSION | 23305 to 23355 | 23305, 23330, 23355 | 5MHz  | QPSK | 1 RB / 0 RB Offset |
|   |                   | 23330          | 23330               | 10MHz | QPSK | 1 RB / 0 RB Offset |

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

| <b>TEST CONDITION</b> |                                 |                                |                  |
|-----------------------|---------------------------------|--------------------------------|------------------|
| <b>TEST ITEM</b>      | <b>ENVIRONMENTAL CONDITIONS</b> | <b>INPUT POWER</b>             | <b>TESTED BY</b> |
| EIRP(ERP)             | 24deg. C, 60%RH                 | DC 3.8V dc By Adapter          | Hanwen Xu        |
| FREQUENCY STABILITY   | 24deg. C, 61%RH                 | DC 3.4V/ 3.8V/ 4.2V By Adapter | Hanwen Xu        |
| OCCUPIED BANDWIDTH    | 24deg. C, 61%RH                 | DC 3.8V dc By Adapter          | Hanwen Xu        |
| BAND EDGE             | 24deg. C, 61%RH                 | DC 3.8V dc By Adapter          | Hanwen Xu        |
| CONDUCTED EMISSION    | 24deg. C, 61%RH                 | DC 3.8V dc By Adapter          | Hanwen Xu        |
| RADIATED EMISSION     | 23deg. C, 70%RH                 | AC 120V/60Hz                   | Hanwen Xu        |



## **2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 90**

**ANSI/TIA/EIA-603-D**

**ANSI/TIA/EIA-603-E**

**ANSI C63.26-2015**

**NOTE:** All test items have been performed and recorded as per the above standards.



### 3 TEST TYPES AND RESULTS

#### 3.1 OUTPUT POWER MEASUREMENT

##### 3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Per FCC Part 90.635(a)(b)

The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

##### 3.1.2 TEST PROCEDURES

###### **EIRP / ERP MEASUREMENT:**

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as  $P_{\text{Meas}}$ , typically dBW or dBm);

$P_{\text{Meas}}$  = measured transmitter output power or PSD, in dBm or dBW;

$G_T$  = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna, in dB


###### **CONDUCTED POWER MEASUREMENT:**

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



### 3.1.3 TEST SETUP

#### CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).



### 3.1.4 TEST RESULTS

#### AVERAGE CONDUCTED OUTPUT POWER (dBm)

| LTE Band 14 |            |         |           |                        |                      |                        |
|-------------|------------|---------|-----------|------------------------|----------------------|------------------------|
| Band/BW     | Modulation | RB Size | RB Offset | Low<br>CH 23305        | Mid<br>CH 23330      | High<br>CH 23355       |
|             |            |         |           | Frequency<br>790.5 MHz | Frequency<br>793 MHz | Frequency<br>795.5 MHz |
| 14/ 5       | QPSK       | 1       | 0         | 23.02                  | 23.08                | 23.06                  |
|             |            | 1       | 12        | 23.03                  | 23.06                | 23.01                  |
|             |            | 1       | 24        | 23.11                  | 23.13                | 23.04                  |
|             |            | 12      | 0         | 22.05                  | 22.15                | 22.31                  |
|             |            | 12      | 6         | 22.02                  | 22.06                | 22.12                  |
|             |            | 12      | 13        | 22.10                  | 22.07                | 22.05                  |
|             |            | 25      | 0         | 22.09                  | 22.08                | 22.10                  |
|             | 16QAM      | 1       | 0         | 22.08                  | 22.28                | 22.70                  |
|             |            | 1       | 12        | 22.04                  | 22.35                | 22.75                  |
|             |            | 1       | 24        | 22.13                  | 22.25                | 22.47                  |
|             |            | 12      | 0         | 21.69                  | 22.03                | 22.25                  |
|             |            | 12      | 7         | 21.67                  | 22.09                | 22.13                  |
|             |            | 12      | 13        | 22.12                  | 22.02                | 22.01                  |
|             |            | 25      | 0         | 21.11                  | 21.15                | 21.41                  |
| Band/BW     | Modulation | RB Size | RB Offset | /                      | Mid<br>CH 23330      | /                      |
|             |            |         |           | /                      | Frequency<br>793 MHz | /                      |
| 14/ 10      | QPSK       | 1       | 0         | /                      | 23.25                | /                      |
|             |            | 1       | 24        | /                      | 23.05                | /                      |
|             |            | 1       | 49        | /                      | 23.07                | /                      |
|             |            | 25      | 0         | /                      | 22.04                | /                      |
|             |            | 25      | 12        | /                      | 22.01                | /                      |
|             |            | 25      | 25        | /                      | 22.05                | /                      |
|             |            | 50      | 0         | /                      | 22.04                | /                      |
|             | 16QAM      | 1       | 0         | /                      | 22.42                | /                      |
|             |            | 1       | 12        | /                      | 22.47                | /                      |
|             |            | 1       | 24        | /                      | 22.38                | /                      |
|             |            | 12      | 0         | /                      | 22.15                | /                      |
|             |            | 12      | 18        | /                      | 22.12                | /                      |
|             |            | 12      | 36        | /                      | 22.14                | /                      |
|             |            | 27      | 0         | /                      | 21.18                | /                      |



## ERP

## LTE BAND 14

## 5MHz QPSK

| Channel | Frequency (MHz) | Conducted Power (dBm) | G <sub>T</sub> -L <sub>C</sub> (dB) | ERP (dBm) | ERP (mW) | Limit (W) |
|---------|-----------------|-----------------------|-------------------------------------|-----------|----------|-----------|
| 23305   | 790.5           | 23.11                 | 2                                   | 22.96     | 197.70   | 3         |
| 23330   | 793             | 23.13                 | 2                                   | 22.98     | 198.61   | 3         |
| 23355   | 795.5           | 23.06                 | 2                                   | 22.91     | 195.43   | 3         |

## 5MHz 16QAM

| Channel | Frequency (MHz) | Conducted Power (dBm) | G <sub>T</sub> -L <sub>C</sub> (dB) | ERP (dBm) | ERP (mW) | Limit (W) |
|---------|-----------------|-----------------------|-------------------------------------|-----------|----------|-----------|
| 23305   | 790.5           | 22.13                 | 2                                   | 21.98     | 157.76   | 3         |
| 23330   | 793             | 22.35                 | 2                                   | 22.20     | 165.96   | 3         |
| 23355   | 795.5           | 22.75                 | 2                                   | 22.60     | 181.97   | 3         |

## 10MHz QPSK

| Channel | Frequency (MHz) | Conducted Power (dBm) | G <sub>T</sub> -L <sub>C</sub> (dB) | ERP (dBm) | ERP (mW) | Limit (W) |
|---------|-----------------|-----------------------|-------------------------------------|-----------|----------|-----------|
| 23330   | 793             | 23.25                 | 2                                   | 23.10     | 204.17   | 3         |

## 10MHz 16QAM

| Channel | Frequency (MHz) | Conducted Power (dBm) | G <sub>T</sub> -L <sub>C</sub> (dB) | ERP (dBm) | ERP (mW) | Limit (W) |
|---------|-----------------|-----------------------|-------------------------------------|-----------|----------|-----------|
| 23330   | 793             | 22.47                 | 2                                   | 22.32     | 170.61   | 3         |

**REMARKS:** ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



## 3.2 FREQUENCY STABILITY MEASUREMENT

### 3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability of mobile, portable and control transmitters operating in the wideband segment must be 1.25 parts per million or better when AFC is locked to a base station, and 5 parts per million or better when AFC is not locked

### 3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 3.2.3 TEST SETUP





### 3.2.4 TEST RESULTS

Please Refer to Appendix of this test report.

Note: VL = Low voltage(3.4V); VN/NV = Normal voltage(3.8V); VH = High voltage(4.2V);  
NT = Normal temperature (25°C)




### 3.3 OCCUPIED BANDWIDTH MEASUREMENT

#### 3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 3.3.2 TEST SETUP



#### 3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 3.3.4 TEST RESULTS

Please Refer to Appendix of this test report.




### 3.4 EMISSION MASK MEASUREMENT

#### 3.4.1 LIMITS OF EMISSION MASK MEASUREMENT

According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \log_{10}(f/6.1)$  decibels or  $50 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

#### 3.4.2 TEST SETUP





### 3.4.3 TEST PROCEDURES

- a) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
- b) Tune the analyzer to the nominal center frequency of the emission bandwidth (EBW).
- c) Set the resolution bandwidth (RBW)  $\geq 1\%$  EBW in the 1MHz band immediately outside and adjacent to the band edge.
- d) Beyond the 1MHz band from the band edge, RBW=1MHz was used.
- e) Set the video bandwidth (VBW) to  $\geq 3 \times$  RBW.
- f) Select the average power (RMS) display detector.
- g) Set the number of measurement points to  $\geq 1001$ .
- h) Use auto-coupled sweep time.
- i) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
- j) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.
- k) Record the max trace plot into the test report.

### 3.4.4 TEST RESULTS

Please Refer to Appendix of this test report.



### 3.5 CONDUCTED SPURIOUS EMISSIONS


#### 3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission equal to  $-13\text{dBm}$

#### 3.5.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.
- Measuring frequency range is from 9kHz up to a frequency including its 10<sup>th</sup> harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

#### 3.5.3 TEST SETUP





### 3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix of this test report.



### 3.6 RADIATED EMISSION MEASUREMENT

#### 3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

(1) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission equal to  $-13\text{dBm}$

(2) For operations in the 763–775 MHz and 793–805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to  $-70\text{ dBW/MHz}$  equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80\text{ dBW}$  EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

#### 3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  
 $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}.$

**NOTE:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.


#### 3.6.3 DEVIATION FROM TEST STANDARD

No deviation




### 3.6.4 TEST SETUP

#### <Below 30MHz>




#### < Frequency Range 30MHz~1GHz >





**< Frequency Range above 1GHz >**




For the actual test configuration, please refer to the attached file (Test Setup Photo).



### 3.6.5 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.






|                          |                 |                 |               |
|--------------------------|-----------------|-----------------|---------------|
| MODE                     | TX channel      | FREQUENCY RANGE | 30 MHz ~ 1GHz |
| ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH | INPUT POWER     | AC 120V 60HZ  |
| TESTED BY                | Hanwen Xu       |                 |               |


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1  | 32.600          | -71.26          | -13.00          | 58.26           | -7.58           | V            | 325.6         | 1.00               |
| 1  | 65.600          | -69.91          | -13.00          | 56.91           | -7.27           | V            | 355.1         | 2.00               |
| 1  | 105.550         | -68.42          | -13.00          | 55.42           | 4.30            | V            | 219.2         | 1.00               |
| 1  | 182.350         | -77.73          | -13.00          | 64.73           | -9.07           | V            | 351.2         | 1.00               |
| 1  | 269.350         | -77.41          | -13.00          | 64.41           | -3.32           | V            | 177.4         | 1.00               |
| 1  | 378.600         | -74.26          | -13.00          | 61.26           | -0.04           | V            | 257.4         | 1.00               |



**ABOVE 1GHz**

**Note:** For higher frequency, the emission is too low to be detected.






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 5MHz / QPSK   | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,576.500       | -53.23          | -40.00          | 13.23           | 17.14           | V            | 1             | 1.00               |
| 3  | 2,364.750       | -46.92          | -13.00          | 33.92           | 24.43           | V            | 359           | 2.00               |






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 5MHz / QPSK   | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,581.500       | -51.85          | -40.00          | 11.85           | 17.40           | H            | 287.7         | 2.00               |
| 3  | 2,372.250       | -46.80          | -13.00          | 33.80           | 24.65           | H            | 1             | 1.00               |






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 5MHz / QPSK   | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,581.500       | -52.67          | -40.00          | 12.67           | 17.25           | V            | 1             | 1.00               |
| 3  | 2,372.250       | -47.33          | -13.00          | 34.33           | 24.36           | V            | 359.1         | 1.00               |






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 5MHz / QPSK   | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,586.500       | -52.11          | -40.00          | 12.11           | 17.22           | H            | 293.6         | 2.00               |
| 3  | 2,379.750       | -47.26          | -13.00          | 34.26           | 24.40           | H            | 1             | 1.00               |






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 5MHz / QPSK   | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,586.500       | -52.84          | -40.00          | 12.84           | 17.11           | V            | 359           | 2.00               |
| 3  | 2,379.750       | -47.99          | -13.00          | 34.99           | 24.14           | V            | 1             | 1.00               |






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 10MHz / QPSK  | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,577.000       | -53.37          | -40.00          | 13.37           | 17.35           | H            | 286.4         | 2.00               |
| 3  | 2,365.500       | -46.91          | -13.00          | 33.91           | 24.74           | H            | 359           | 1.00               |






|                   |               |                          |                  |
|-------------------|---------------|--------------------------|------------------|
| CHANNEL BANDWIDTH | 10MHz / QPSK  | MODE                     | TX channel 26740 |
| FREQUENCY RANGE   | Above 1000MHz | ENVIRONMENTAL CONDITIONS | 23deg. C, 70%RH  |
| INPUT POWER       | AC 120V 60HZ  | TESTED BY                | Hanwen Xu        |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| Rg | Frequency [MHz] | PK+ Level [dBm] | PK+ Limit [dBm] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|-----------------|-----------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2  | 1,577.000       | -52.92          | -40.00          | 12.92           | 17.16           | V            | 0.9           | 2.00               |
| 3  | 2,365.500       | -46.72          | -13.00          | 33.72           | 24.42           | V            | 145.3         | 1.00               |






### 3.7 PEAK TO AVERAGE RATIO

#### 3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

#### 3.7.2 TEST SETUP



#### 3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

#### 3.7.4 TEST RESULTS

Please Refer to Appendix of this test report.



## **4 INFORMATION ON THE TESTING LABORATORIES**

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China  
Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

**Suzhou EMC/RF Lab:**

Tel: +86 (0557) 368 1008



## **5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No modifications were made to the EUT by the lab during the test.



## 6 APPENDIX


### FCC-LTE-Band14

#### PEAK-TO-AVERAGE RATIO(CCDF)

##### Test Result


| Band   | Bandwidth | Modulation | Channel | RB Configuration | Result(dB) | Limit(dB) | Verdict |
|--------|-----------|------------|---------|------------------|------------|-----------|---------|
| Band14 | 5MHz      | QPSK       | 23305   | 1RB#0            | 5.37       | 13        | PASS    |
| Band14 | 5MHz      | QPSK       | 23305   | 25RB#0           | 6.43       | 13        | PASS    |
| Band14 | 5MHz      | QPSK       | 23330   | 1RB#0            | 6.04       | 13        | PASS    |
| Band14 | 5MHz      | QPSK       | 23330   | 25RB#0           | 6.55       | 13        | PASS    |
| Band14 | 5MHz      | QPSK       | 23355   | 1RB#0            | 5.86       | 13        | PASS    |
| Band14 | 5MHz      | QPSK       | 23355   | 25RB#0           | 6.49       | 13        | PASS    |
| Band14 | 5MHz      | 16QAM      | 23305   | 1RB#0            | 6.03       | 13        | PASS    |
| Band14 | 5MHz      | 16QAM      | 23305   | 25RB#0           | 7.12       | 13        | PASS    |
| Band14 | 5MHz      | 16QAM      | 23330   | 1RB#0            | 6.89       | 13        | PASS    |
| Band14 | 5MHz      | 16QAM      | 23330   | 25RB#0           | 7.15       | 13        | PASS    |
| Band14 | 5MHz      | 16QAM      | 23355   | 1RB#0            | 7.08       | 13        | PASS    |
| Band14 | 5MHz      | 16QAM      | 23355   | 25RB#0           | 7.27       | 13        | PASS    |
| Band14 | 10MHz     | QPSK       | 23330   | 1RB#0            | 5.61       | 13        | PASS    |
| Band14 | 10MHz     | QPSK       | 23330   | 50RB#0           | 6.64       | 13        | PASS    |
| Band14 | 10MHz     | 16QAM      | 23330   | 1RB#0            | 6.34       | 13        | PASS    |
| Band14 | 10MHz     | 16QAM      | 23330   | 27RB#0           | 7.17       | 13        | PASS    |

##### Test Graphs






**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05






**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05






**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05





**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05






## 26DB BANDWIDTH AND OCCUPIED BANDWIDTH

### Test Result


| Band   | Bandwidth | Modulation | Channel | RB Configuration | Occupied Bandwidth (MHz) | 26dB Bandwidth (MHz) | Verdict |
|--------|-----------|------------|---------|------------------|--------------------------|----------------------|---------|
| Band14 | 5MHz      | QPSK       | 23305   | 25RB#0           | 4.5688                   | 5.663                | PASS    |
| Band14 | 5MHz      | QPSK       | 23330   | 25RB#0           | 4.5603                   | 5.668                | PASS    |
| Band14 | 5MHz      | QPSK       | 23355   | 25RB#0           | 4.5747                   | 5.719                | PASS    |
| Band14 | 5MHz      | 16QAM      | 23305   | 25RB#0           | 4.5571                   | 5.879                | PASS    |
| Band14 | 5MHz      | 16QAM      | 23330   | 25RB#0           | 4.5701                   | 5.757                | PASS    |
| Band14 | 5MHz      | 16QAM      | 23355   | 25RB#0           | 4.5662                   | 5.672                | PASS    |
| Band14 | 10MHz     | QPSK       | 23330   | 50RB#0           | 9.1037                   | 10.95                | PASS    |
| Band14 | 10MHz     | 16QAM      | 23330   | 27RB#0           | 4.9417                   | 6.412                | PASS    |

### Test Graphs





**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05



## BAND EDGE

### Test Result

| Band   | Bandwidth | Modulation | Channel | RB Configuration | Result(dBm) | Verdict     |
|--------|-----------|------------|---------|------------------|-------------|-------------|
| Band14 | 5MHz      | QPSK       | 23305   | 1RB#0            | -11.62      | FAIL        |
| Band14 | 5MHz      | QPSK       | 23305   | 1RB#0            | -15.21      | PASS Final1 |
| Band14 | 5MHz      | QPSK       | 23305   | 25RB#0           | -18.98      | PASS        |
| Band14 | 5MHz      | QPSK       | 23355   | 1RB#24           | -49.35      | PASS        |
| Band14 | 5MHz      | QPSK       | 23355   | 25RB#0           | -36.08      | PASS        |
| Band14 | 5MHz      | 16QAM      | 23305   | 1RB#0            | -13.15      | PASS        |
| Band14 | 5MHz      | 16QAM      | 23305   | 25RB#0           | -19.69      | PASS        |
| Band14 | 5MHz      | 16QAM      | 23355   | 1RB#24           | -47.68      | PASS        |
| Band14 | 5MHz      | 16QAM      | 23355   | 25RB#0           | -36.12      | PASS        |
| Band14 | 10MHz     | QPSK       | 23330   | 1RB#0            | -24.81      | PASS        |
| Band14 | 10MHz     | QPSK       | 23330   | 1RB#49           | -49.15      | PASS        |
| Band14 | 10MHz     | QPSK       | 23330   | 50RB#0           | -37.55      | PASS        |

Huarui 7layers High Technology  
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech  
District, Suzhou City, Anhui Province, China

Tel: +86 (0557) 368 1008


**BUREAU VERITAS** Test Report No.: **PBJ-NQN2504110217RF05**

|        |       |       |       |         |        |      |
|--------|-------|-------|-------|---------|--------|------|
| Band14 | 10MHz | 16QAM | 23330 | 1RB#0   | -26.39 | PASS |
| Band14 | 10MHz | 16QAM | 23330 | 1RB#49  | -49.37 | PASS |
| Band14 | 10MHz | 16QAM | 23330 | 27RB#0  | -22.84 | PASS |
| Band14 | 10MHz | 16QAM | 23330 | 27RB#23 | -35.74 | PASS |

**Test Graphs**




**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05






**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05





**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05






**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05  
**CONDUCTED SPURIOUS EMISSION**

### Test Result

| Band   | Bandwidth | Modulation | Channel | RB Configuration | Frequency Range | Result (dBm) | Verdict |
|--------|-----------|------------|---------|------------------|-----------------|--------------|---------|
| Band14 | 5MHz      | QPSK       | 23305   | 1RB#0            | 30~1000         | -63.55       | PASS    |
| Band14 | 5MHz      | QPSK       | 23305   | 1RB#0            | 1000~10000      | -50.00       | PASS    |
| Band14 | 5MHz      | QPSK       | 23330   | 1RB#0            | 30~1000         | -63.30       | PASS    |
| Band14 | 5MHz      | QPSK       | 23330   | 1RB#0            | 1000~10000      | -50.15       | PASS    |
| Band14 | 5MHz      | QPSK       | 23355   | 1RB#0            | 30~1000         | -62.95       | PASS    |
| Band14 | 5MHz      | QPSK       | 23355   | 1RB#0            | 1000~10000      | -44.26       | PASS    |
| Band14 | 10MHz     | QPSK       | 23330   | 1RB#0            | 30~1000         | -52.47       | PASS    |
| Band14 | 10MHz     | QPSK       | 23330   | 1RB#0            | 1000~10000      | -50.04       | PASS    |


### Test Graphs



Huarui 7layers High Technology  
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech  
District, Suzhou City, Anhui Province, China

Tel: +86 (0557) 368 1008





## FREQUENCY STABILITY

## Test Result

| Voltage |           |            |         |                  |               |                  |                |                 |          |          |             |         |
|---------|-----------|------------|---------|------------------|---------------|------------------|----------------|-----------------|----------|----------|-------------|---------|
| Band    | Bandwidth | Modulation | Channel | RB Configuration | Voltage [Vdc] | Temperature (°C) | Deviation (Hz) | Deviation (ppm) | FL (MHz) | FH (MHz) | Limit (MHz) | Verdict |
| Band 14 | 5MHz      | QPSK       | 23305   | 25RB #0          | VN            | NT               | -1200.00       | -1.518027       | 788.3864 | --       | 788-798     | PASS    |
| Band 14 | 5MHz      | QPSK       | 23305   | 25RB #0          | VL            | NT               | -1280.00       | -1.619228       | 788.3963 | --       | 788-798     | PASS    |
| Band 14 | 5MHz      | QPSK       | 23305   | 25RB #0          | VH            | NT               | -1420.00       | -1.796331       | 788.3882 | --       | 788-798     | PASS    |
| Band 14 | 5MHz      | QPSK       | 23355   | 25RB #0          | VN            | NT               | 510.00         | 0.641106        | --       | 797.5062 | 788-798     | PASS    |
| Band 14 | 5MHz      | QPSK       | 23355   | 25RB #0          | VL            | NT               | 670.00         | 0.842238        | --       | 797.4744 | 788-798     | PASS    |
| Band 14 | 5MHz      | QPSK       | 23355   | 25RB #0          | VH            | NT               | 780.00         | 0.980515        | --       | 797.4782 | 788-798     | PASS    |

| Temperature |           |            |         |                  |               |                  |                |                 |          |          |             |         |
|-------------|-----------|------------|---------|------------------|---------------|------------------|----------------|-----------------|----------|----------|-------------|---------|
| Band        | Bandwidth | Modulation | Channel | RB Configuration | Voltage [Vdc] | Temperature (°C) | Deviation (Hz) | Deviation (ppm) | FL (MHz) | FH (MHz) | Limit (MHz) | Verdict |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | -30              | -1670.00       | -2.112587       | 788.2461 | --       | 788-798     | PASS    |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | -20              | -1240.00       | -1.568627       | 788.2459 | --       | 788-798     | PASS    |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | -10              | -1250.00       | -1.581278       | 788.2439 | --       | 788-798     | PASS    |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | 0                | -1410.00       | -1.783681       | 788.2459 | --       | 788-798     | PASS    |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | 10               | -1310.00       | -1.657179       | 788.2384 | --       | 788-798     | PASS    |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | 20               | -1220.00       | -1.543327       | 788.244  | --       | 788-798     | PASS    |
| Band 14     | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | 30               | -1440.00       | -1.821632       | 788.2432 | --       | 788-798     | PASS    |
| Band        | 5MHz      | QPSK       | 23305   | 25RB #0          | NV            | 40               | -              | -               | 788.2    | --       | 788         | PASS    |



**BUREAU VERITAS** Test Report No.: PBJ-NQN2504110217RF05

|        |      |      |       |        |    |     |          |           |          |          |         |      |
|--------|------|------|-------|--------|----|-----|----------|-----------|----------|----------|---------|------|
| d14    |      |      | 5     | #0     |    |     | 1350.00  | 1.707780  | 461      |          | -798    | S    |
| Band14 | 5MHz | QPSK | 23305 | 25RB#0 | NV | 50  | -1300.00 | -1.644529 | 788.2443 | --       | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | -30 | 950.00   | 1.194217  | --       | 797.7336 | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | -20 | 810.00   | 1.018228  | --       | 797.7288 | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | -10 | 740.00   | 0.930233  | --       | 797.7279 | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | 0   | 820.00   | 1.030798  | --       | 797.726  | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | 10  | 850.00   | 1.068510  | --       | 797.7277 | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | 20  | 960.00   | 1.206788  | --       | 797.7258 | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | 30  | 810.00   | 1.018228  | --       | 797.7284 | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | 40  | 970.00   | 1.219359  | --       | 797.725  | 788-798 | PASS |
| Band14 | 5MHz | QPSK | 23355 | 25RB#0 | NV | 50  | 640.00   | 0.804525  | --       | 797.7269 | 788-798 | PASS |

---END---