



# FCC RF Exposure Test Report

Report No. : PBJ-NQN2504110217SA01  
Applicant : TELIT COMMUNICATIONS S.P.A  
Address : VIA STAZIONE DI PROSECCO, 5/B SGONICO,34010 ITALY  
Product : LTE Cat 1bis Module  
FCC ID : RI7LE310P1SN  
Brand : Telit Cinterion or   
Model No. : LE310P1-SN  
Standards : FCC Part 2 (Section 2.1091)  
KDB 447498 D01 General RF Exposure Guidance v06

Sample Received Date : Apr. 16, 2025  
Date of Testing : Apr. 16, 2025~ Jun. 27, 2025  
Test Lab : The FCC Site Registration No. is 434559; The Designation No. is CN1325.  
Issued By : Huarui 7layers High Technology (Suzhou) Co., Ltd.  
Address : Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province China

**CERTIFICATION:** The above equipment have been tested by **Huarui 7Layers High Technology (Suzhou) Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By : \_\_\_\_\_  
(Chang Gao / Engineer)

Approved By : \_\_\_\_\_  
(Peibo Sun /Manager)

This report is governed  
business/cps/about-us/  
only with our prior written  
quality or characteristic  
the results thereof base  
acceptance criteria with  
omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and you shall raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Chang Gao

ie Conditions of Testing as posted at the date of issuance of this report or  
your exclusive use. Any copying or replication of this report to or for  
our findings solely with respect to the test samples identified herein  
was taken or any similar or identical product unless specifically  
and detailed to us. Measurement uncertainty is only provided upon request  
into account, unless otherwise requested in writing. You have 60 days  
to notify us of any material error or  
issue you wish to raise. A failure to

home/about-us/our-  
our name or trademark, is permitted  
not indicative or representative of the  
all of the tests requested by you and  
conformity are based on simple  
to notify us of any material error or  
issue you wish to raise. A failure to

Peibo Sun



## **TABLE OF CONTENTS**

RELEASE CONTROL RECORD .....	3
1. DESCRIPTION OF EQUIPMENT UNDER TEST .....	4
2. MPE(MAXIMUM PERMISSIBLE EXPOSURE) ASSESSMENT .....	5
2.1 INTRODUCTION .....	5
2.2 RF RADIATION EXPOSURE LIMITS .....	5
2.3 MPE ASSESSMENT METHOD .....	6
2.4 MPE CALCULATION FOR STANDALONE OPERATIONS .....	6
3. INFORMATION ON THE TESTING LABORATORIES .....	8



## Release Control Record

Report No.	Reason for Change	Date Issued
PBJ-NQN2504110217SA01	Original release	Jun. 27, 2025
</		



## 1. Description of Equipment Under Test

<b>EUT Type*</b>	LTE Cat 1bis Module
<b>FCC ID*</b>	RI7LE310P1SN
<b>Brand Name*</b>	Telit Cinterion or 
<b>Model Name*</b>	LE310P1-SN
<b>Tx Frequency Bands (Unit: MHz)</b>	LTE Band 2 : 1850.7MHz ~ 1909.3MHz LTE Band 4 : 1710.7MHz ~ 1754.3MHz LTE Band 5 : 824.7MHz ~ 848.3MHz LTE Band 12 : 699.7MHz ~ 715.3MHz LTE Band 13: 779.5MHz ~ 784.5MHz LTE Band 14: 790.5MHz ~ 795.5MHz LTE Band 66 : 1710.7MHz ~ 1779.3MHz LTE Band 71 : 665.5MHz ~ 695.5MHz
<b>Uplink Modulations*</b>	LTE : QPSK, 16QAM
<b>Antenna Type*</b>	LTE: Fixed External Antenna
<b>HW VERSION*</b>	0.0
<b>SW VERSION*</b>	M0E.200001
<b>EUT Stage*</b>	Identical Prototype

**Note:**

1. \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.



## **2. MPE(Maximum Permissible Exposure) Assessment**

### **2.1 Introduction**

According to 47 CFR §2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitting antenna and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 cm separation requirement. The limits to be used for MPE evaluation are specified in §1.1310. All unlicensed personal communications service (PCS) devices and unlicensed NII devices shall be subject to the limits for general population/uncontrolled exposure.

### **2.2 RF Radiation Exposure Limits**

According to 47 CFR §1.1310, the criteria listed in below table shall be used to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093.

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (min)
(A) Limits for Occupational / Controlled Exposures				
0.3 – 3.0	614	1.63	100	6
3.0 – 30	1842/f	4.89/f	900/f <sup>2</sup>	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	-	-	f/300	6
1500 – 100000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposures				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/f	2.19/f	180/f <sup>2</sup>	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	-	-	f/1500	30
1500 – 100000	-	-	1.0	30

#### **Limits for maximum permissible exposure (MPE)**

#### **Notes:**

1. f = frequency in MHz
2. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided they are made aware of the potential for exposure.
3. General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



## **2.3 MPE Assessment Method**

Calculations can be made to predict RF field strength and power density levels around typical RF sources. For example, in the case of a single radiating antenna, a prediction for power density in the far-field of the antenna can be made by use of the general Equations below. This equation is generally accurate in the far-field of an antenna but will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction.

$$\text{Power Density (S)} = \frac{PG}{4\pi R^2} = \frac{\text{EIRP}}{4\pi R^2}$$

Where

S = Power Density, unit in mW/cm<sup>2</sup>

P = Power input to the antenna, unit in mW

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna, unit in cm

EIRP = Effective isotropically radiated power

## **2.4 MPE Calculation for Standalone Operations**

The manufacturer expects that the radiated component of this device will not close to the human body during normal usage and the warning statement was also stated in the user instruction. Since the transmitting antenna will be kept at least 20 cm away from the human body, the MPE level is calculated based on this condition and the result is listed in below table.



**BUREAU  
VERITAS** FCC RF Exposure Test Report

CALCULATION FOR MAXIMUM E.I.R.P

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum output power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Power Density at 20cm (mW/cm^2)	Limit (mW/cm^2)	Power Density / Limit Ratio	Result
LTE Band2	1850.7	1	25	26.00	398.107	0.079	1.000	0.079	Pass
LTE Band4	1710.7	3	25	28.00	630.957	0.126	1.000	0.126	Pass
LTE Band5	824.7	-1	25	24.00	251.189	0.050	0.550	0.091	Pass
LTE Band12	699.7	2	25	27.00	501.187	0.100	0.466	0.214	Pass
LTE Band13	779.5	2	25	27.00	501.187	0.100	0.520	0.192	Pass
LTE Band14	790.5	2	25	27.00	501.187	0.100	0.527	0.189	Pass
LTE Band66	1710.7	3	25	27.00	501.187	0.100	1.000	0.100	Pass
LTE Band71	665.5	2	25	27.00	501.187	0.100	0.444	0.225	Pass

CALCULATION MAX ANTENNA GAIN :

Band	Frequency (dBi)	Antenna Gain (dBi)	Conducted Tune-up Peak Power(dBm)	Limit EIRP (dBm)	Limit EIRP (W)	Power Density at 20cm (mW/cm^2)	limit (mW/cm^2)	Result (PASS / FAIL)
LTE Band 2	1850.7	8.00	25	33.01	2	0.397	1	Pass
LTE Band 4	1710.7	5.00	25	30.00	1	0.199	1	Pass
LTE Band 5	824.7	9.40	25	38.45	7	0.548	0.55	Pass
LTE Band 12	699.7	8.68	25	34.77	3	0.467	0.466	Pass
LTE Band 13	779.5	9.15	25	34.77	3	0.524	0.52	Pass
LTE Band 14	790.5	9.21	25	34.77	3	0.524	0.527	Pass
LTE Band 66	1710.7	5.00	25	30.00	1	0.251	1	Pass
LTE Band 71	665.5	8.46	25	34.77	3	0.446	0.444	Pass



### **3. Information on the Testing Laboratories**

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. , were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

**Suzhou EMC/RF Lab:**

Tel: +86 (0557) 368 1008

---END---