

Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist.,

Taoyuan City, 33383 TAIWAN (R.O.C.)

Declaration of the Modular Approval

Applicant / Grantee	GlobalSat WorldCom Corporation
FCC ID:	RID-LM110H1
Model:	LM110H1

The single module transmitter has been evaluated then tested meeting the requirements under Part 15C Section 2.12 as below:

Modular approval requirement	EUT Condition	Comply
(a) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	The modular transmitter must have its own RF shielding." The radio portion of this module has been shielded, please see exhibition External Photo.	V
(b) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	The modular transmitter must have buffered modulation/data inputs." The EUT has buffered data input; it is integrated in chip SX1276.	V
(c) The modular transmitter must have its own power supply regulation.	The modular transmitter must have its own power supply regulation." The part number of this regulator is SX1276.	V
(d) The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The modular transmitter must comply with the antenna requirements of section 15.203 and 15.204(C)." The EUT meets the FCC antenna requirements. The spurious emission, unique antenna connector and photo of antennas are shown in the test report.	V
(e) The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the	The modular transmitter must be tested in a stand-alone configuration" The EUT was tested in a stand-alone configuration via a USB extender. Please see section Photographs of Test Configuration in the test report, the EUT was plugged in this extender.	V

Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist.,

Taoyuan City, 33383 TAIWAN (R.O.C.)

length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)) must not be inside another device during testing.		
(f) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	The modular transmitter must be labeled with its own FCC ID number." Please see exhibition Label Sample for the FCC ID of this module. And also in the exhibition Users Manual, there are instructions give to the OEM on how to label the end product.	V
(g) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization requirements, which are based on the intended use/configurations.	The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements." The EUT is compliant with all applicable FCC rules. Detail instructions for maintaining compliance are given in the Users Manual.	V
(h) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The module is compliant with MPE requirements. MPE is addressed in the RF exposure exhibition.	V

Dated**June 22, 2018****By:****Miffy Tsao****Signature****Printed****Title:** *Specialist***On behalf of :****Bureau Veritas Consumer Products
Services (H.K.) Ltd., Taoyuan Branch****Telephone:****+886-3-3183232#1948**