



## ALIBRATION & CERTIFICATION TECH. CO., LTD.

Product Compliance Division, EMC Team  
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA  
TEL : +82 31 639 8518 FAX : +82 31 639 8525

## CERTIFICATION

**Manufacture:**  
TECHSAN I & C CO.,LTD.

546-4. Ami-Ri Bubai-Eub, Ichon-City, Kyoungki-Do  
Korea

TECHSAN I & C FRN : 009419888

Date of Issue : DECEMBER 19, 2003

Test Report No.: HCT-F03-1203

Test Site: HYUNDAI CALIBRATION & CERTIFICATION  
TECHNOLOGIES CO., LTD.  
HCT FRN : 0005-8664-21

**FCC ID :**

**RJ5PT4200U**

**MODEL / TYPE :**

**PT4200U**

<b>Rule Part(s):</b>	Part 15 & 2; ET Docket 95-19
<b>Equipment Class:</b>	FCC Class B Peripheral Device (JBP)
<b>Standard(s):</b>	FCC Class B: 1998 (CISPR 22)
<b>EUT Type:</b>	PDP MONITOR
<b>Max. Resolution(s):</b>	1280x768(@64KHz/ 60Hz)
<b>Model(s):</b>	PT4200U
<b>Port/Connector(s)</b>	RS-232C INPUT, DVI INPUT, RGB PC INPUT, PC/DVI AUDIO INPUT, COMPONENT INPUT 1/2, AV INPYUT, OPICAL(SPDIF) DIGITAL AUDIO OUT JAK, S-VIDEO INPUT, ANT. IN, AC(POWER) INPUT

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992 (Grant Notes: #19, #28).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Ki Soo Kim

Report prepared by : Ki-Soo Kim

Manager of EMC Tech. Part



HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.



## TABLE OF CONTENTS

	PAGE
<b>REPORT COVER</b>	<b>1</b>
<b>TABLE OF CONTENTS</b>	<b>2</b>
<b>1.1 SCOPE</b>	<b>3</b>
<b>2.1 INTRODUCTION (SITE DESCRIPTION)</b>	<b>4</b>
<b>3.1 PRODUCTION INFORMATION</b>	<b>5</b>
<b>4.1 DESCRIPTION OF TESTS (CONDUCTED)</b>	<b>6</b>
<b>4.3 DESCRIPTION OF TESTS (RADIATED)</b>	<b>7</b>
<b>5.1 LIST OF SUPPORT EQUIPMENT</b>	<b>8-9</b>
<b>6.1 TEST DATA (CONDUCTED)</b>	<b>10-13</b>
<b>7.1 TEST DATA (RADIATED)</b>	<b>14</b>
<b>8.1 SIMPLE CALCULATIONS</b>	<b>15</b>
<b>9.1 TEST EQUIPMENT</b>	<b>16</b>
<b>10.1 TEST SOFTWARE USED</b>	<b>17</b>
<b>11.1 CONCLUSION</b>	<b>18</b>

**ATTACHMENT A: FCC ID LABEL & LOCATION**

**ATTACHMENT B: EXTERNAL PHOTOGRAPHS**

**ATTACHMENT C: BLOCK DIAGRAM(S)**

**ATTACHMENT D: TEST SETUP PHOTOGRAPHS**

**ATTACHMENT E: USER'S MANUAL**

**ATTACHMENT F: INTERNAL PHOTOGRAPHS**

## MEASUREMENT REPORT

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

**Applicant Name:** TECHSAN I & C CO., LTD.

**Address:** 436 MOGOK-DONG, PYOUNGTAEK-SHI, KYUNGGI-DO,  
KOREA, 459-040

- FCC ID : **RJ5PT4200U**
- Equipment Class: **FCC Class B Peripheral Device (JBP)**
- EUT Type: **PDP MONITOR**
- Model(s): **PT4200U**
- Max. Resolution: **1280x768 (@64KHz/ 60Hz)**
- Power Cord: **Unshielded**
- Rule Part(s): **FCC Part 15 Subpart B**
- Test Procedure(s): **ANSI C63.4 (1992)**
- Dates of Tests: **DECEMBER 10, 2003~DECEMBER 11,2003**
- Place of Tests: **254-1,MAEKOK-RI,HOBUP-MYUN,ICHON-SI,KYOUNGKI-DO,467-701,KOREA**

## 2.1 INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSIC63.4-1992) was used in determining radiated and conducted emissions emanating from **TECHSAN I & C CO., LTD. PDP MONITOR FCC ID: RJ5PT4200U**

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, MAEKOK-RI, HOBUP-MYUN, ICHON-SI, KYOUNGKI-DO, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 23, 2003 (Confirmation Number: EA90661)

## 3.1 PRODUCT INFORMATION

### 3.2 Equipment Description

Equipment Under Test (EUT) is the **TECHSAN I & C CO.,LTD.** ( Model : **PT4200U** ) **PDP MONITOR**

FCC ID: **RJ5PT4200U**

Maximum Resolution(s): **1280 X 768 (@64KHz/ 60Hz)**

Dimensions: **40.8"(W) x 27.9"(H) x 11.8"(D)**

Power Supply: **AC 110-240V, 50/ 60Hz**

Connectivity: **Composite : Input RCA-pin × 1, Out RCA-Pin × 1, video signal : YpbPr × 2**

**S-video : Mini DIN 4-pin × 1, DTV input : RCA Pin Y Pb Pr × (480p,750p,1080i)**

**Audio input : RCA-pin Type(L/R) × 6:Full support separated audio input/output for each Video input/output**

**Speaker output : Cinch Conn Type(L/R) × 1(4cinch connectirs type)**

**Audio system : Stereo, Control Ports : RS-232**

**DVI input : DVI Cable**

Power Consumption : **380Watts**

Weight (Net):**98.81(lb)**

## 4.1 Description of Tests(Conducted)

### 4.2 Powerline Conducted RFI (150kHz- 30MHz)

The power line conducted RFI measurements were performed according to CISPR 22.

The EUT was placed on a non-conducting 1.0 by 1.5 meter table which is 0.8 meters in height and 0.40 meters away from the vertical wall of the shielded enclosure. Power to the EUT is provided through a Rohde & Schwarz 50 Ω / 50 uH Line Impedance Stabilization Network (LISN) and the support equipment through a separate Solar 50 Ω / 50 uH Line- Conducted Test Facility LISN. Sufficient time for the EUT, support equipment, and test equipment were allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME. The spectrum was scanned from 150kHz to 30 MHz. Each maximum EME was remeasured using an EMI receiver. The detector function of the receiver was set to CISPR quasi- peak and average mode with the bandwidth set to 9 kHz. Each emission was maximized consistent with the typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum Diagram emission. Excess cable lengths were bundled at the centre with 30- 40cm. in length. The worst-case configuration is noted in the test report and the photographs are attached. Each EME reported was calibrated using the Rohde & Schwarz SMX signal generator and are listed on Table 1. RFI Conducted FCC Class B

RFI CONDUCTED	FCC CLASS B Limits dB(uV/m)	CISPR 22 CLASS B Limits dB(uV/m)	
Freq. Range	FCC Class B Quasi-Peak	CISPR 22 Quasi-Peak	CISPR 22 Average
150kHz - 0.5MHz	48*	66-56**	56-46**
0.5MHz - 5MHz	48	56	46
5MHz - 30MHz	48	60	50

\*FCC Class B limits starts from 450kHz  
 \*\*Limits decreases linearly with the logarithm of frequency

**Table 1. RFI Conducted Limits**

## 4.3 Description of Tests(Radiated)

### Radiated Emissions

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The spectrum was scanned from 30 to 300 MHz using biconical antenna, 300 to 1000 MHz using log- periodic antenna, and above 1 GHz using linearly polarized horn antennas. Final measurements were made outdoors at 10-meter test range using Dipole antennas and EMI receiver. For frequencies above 1 GHz, horn antennas were used. Sufficient time for the EUT, support equipment, and test equipment were allowed in order for them to warm up to their normal operating condition. The EMI receiver detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120 kHz. The EUT, support equipment, and interconnecting cables were arranged to the configuration that produces the maximum EME emission found during preliminary scan. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Horizontal and vertical antenna polarizations were checked. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/ or support equipment, and powering the monitor the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

ITE Radiated Limits			
Frequency (MHz)	FCC Limit @ 3m. Quasi- Peak dB[ $\mu$ V/m]	FCC Limit @ 10m.* Quasi – Peak dB [ $\mu$ V/m]	CISPR Limit @ 10m. Quasi-Peak dB [ $\mu$ V/m]
<b>30-88</b>	<b>40.0</b>	<b>29.5</b>	<b>30.0</b>
<b>88-216</b>	<b>43.5</b>	<b>33.0</b>	<b>30.0</b>
<b>216-230</b>	<b>46.0</b>	<b>35.6</b>	<b>30.0</b>
<b>230-960</b>	<b>46.0</b>	<b>35.6</b>	<b>37.0</b>
<b>960-1000</b>	<b>54.0</b>	<b>43.5</b>	<b>37.0</b>
<b>&gt; 1000</b>	<b>54.0</b>	<b>43.5</b>	<b>No Specified Limit</b>
<b>* Limit extrapolated 20 dB/decade</b>			

Table 2. Radiated Class B limits @ 10-meters

## 5.1 Support Equipment Used

DEVICE TYPE	MANUFACTURER	MODEL NUMBER	FCC ID / DoC	CONNECTED TO
MONITOR (EUT)	TECHSAN I & C CO., LTD.	PT4200U	RJ5PT4200U	P.C
P.C	H.P	HP Pavilion 700	DoC	EUT
KEY BOARD	H.P	5181	DoC	P.C
MOUSE	Microsoft	Intellimouse optical USB and PS/2 compatible	DoC	P.C
PRINTER	H/P	C6410A	DoC	P.C

Cable Termination	<b>Component port 75Ω</b> <b>S-Video Port 75Ω</b> <b>Video Port 75Ω</b> <b>Audio Port 30 KΩ</b>
-------------------	--

## 5.2 Cable Description

		Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
PDP Monitor (EUT)	Power	N	N/A	1.8(P)
	Video	N/A	Y	1.6(D)
	Audio	N/A	Y	1.6(D)
	RS-232C	N/A	Y	1.7(D)
	Component	N/A	Y	1.6(D)
	Speaker	N/A	N	3.0(D)
	D-sub	N/A	Y	1.8(D)
	DVI	N/A	Y	1.8(D)
	S-video	N/A	Y	1.6(D)
	PC	N	N/A	1.8(P)
KEY BOARD		N/A	N/A	1.8(D)
MOUSE		N/A	Y	1.8(D)
PRINTER		N	Y	1.8(P),1.8(D)

The marked "(D)" means the Data Cable and "(P)" means the Power Cable.

## 5.3 Noise Suppression Parts on Cable. (I/O CABLE)

		Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
PDP Monitor (EUT)	Video	N	N/A	Y	BOTH END
	Audio	N	N/A	Y	BOTH END
	RS-232C	N	N/A	Y	BOTH END
	Component	N	N/A	Y	BOTH END
	Speaker	Y	EUT END	N	N/A
	D-sub	Y	BOTH END	Y	BOTH END
	DVI	Y	BOTH END	Y	BOTH END
	S-video	N	N/A	Y	BOTH END
	PC	N	N/A	N/A	N/A
	KEYBOARD	N	N/A	Y	PC END
MOUSE		N	N/A	Y	PC END
PRINTER		Y	BOTH END	Y	BOTH END


## 6.1 LINE-CONDUCTED TEST DATA

**HYUNDAI C-TECH.  
EMC TESTING Laboratory**

EUT: PT4200U  
 Manufacturer: TECHSAN I&C  
 Operating Condition: NORMAL  
 Test Site: SHIELD ROOM  
 Operator: JP-HONG  
 Test Specification: CISPR 22 CLASS B  
 Comment: H  
 Start of Test: 12/11/03 / 10:27:51AM

**SCAN TABLE: "CISPR 22 Voltage"**

CISPR 22 Voltage						
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			


**MEASUREMENT RESULT: "PDP\_fin\_QP"**

12/11/03 10:30AM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line dB	PE
0.195000	55.60	10.1	64	8.3	1	---
0.225000	47.20	10.1	63	15.5	1	---
0.315000	43.00	10.1	60	16.8	1	---
0.595000	44.70	10.2	56	11.3	1	---
4.355000	39.80	10.3	56	16.2	1	---
4.750000	41.60	10.3	56	14.4	1	---
10.695000	48.80	10.4	60	11.2	1	---
10.890000	48.30	10.4	60	11.7	1	---
11.090000	51.00	10.4	60	9.0	1	---

**MEASUREMENT RESULT "PDP\_fin AV"**

12/11/03 10:30AM


Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.180000	50.60	10.1	55	3.9	1	---
0.200000	44.30	10.1	54	9.4	1	---
0.225000	42.50	10.1	53	10.2	1	---
0.590000	28.00	10.2	46	18.0	1	---
4.750000	27.80	10.3	46	18.2	1	---
4.950000	25.50	10.3	46	20.5	1	---
10.695000	34.30	10.4	50	15.7	1	---
10.910000	35.00	10.4	50	15.0	1	---
11.485000	33.90	10.4	50	16.1	1	---

HYUNDAI C-TECH.  
 EMC TESTING Laboratory

EUT: PT4200U  
 Manufacturer: TECHSAN I&C  
 Operating Condition: NORMAL  
 Test Site: SHIELD ROOM  
 Operator: JP-HONG  
 Test Specification: CISPR 22 CLASS B  
 Comment: N  
 Start of Test: 12/11/03 / 10:23:23AM

**SCAN TABLE: "CISPR 22 Voltage"**

CISPR 22 Voltage						
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			


**MEASUREMENT RESULT: "PDP\_fin\_QP"**

12/11/03 10:26AM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.200000	57.00	10.1	64	6.7	1	---
0.315000	42.10	10.1	60	17.7	1	---
0.340000	38.20	10.1	59	21.0	1	---
0.595000	42.50	10.2	56	13.5	1	---
4.755000	37.80	10.3	56	18.2	1	---
4.950000	39.20	10.3	56	16.8	1	---
10.690000	49.00	10.4	60	11.0	1	---
10.890000	49.10	10.4	60	10.9	1	---
11.090000	52.30	10.4	60	7.7	1	---

**MEASUREMENT RESULT "PDP\_fin AV"**

12/11/03 10:26AM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.180000	50.30	10.1	55	4.2	1	---
0.200000	44.40	10.1	54	9.2	1	---
0.225000	41.90	10.1	53	10.8	1	---
0.590000	26.00	10.2	46	20.0	1	---
4.355000	22.70	10.3	46	23.3	1	---
4.750000	25.60	10.3	46	20.4	1	---
10.690000	34.60	10.4	50	15.4	1	---
11.090000	37.50	10.4	50	12.5	1	---
11.515000	36.10	10.4	50	13.9	1	---

## 7.1 RADIATED TEST DATA

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
36.90	18.3	16.5	1.3	V	36.1	40	-3.9
60.30	23.4	7.7	1.8	V	32.9	40	-7.1
68.00	25.1	6.4	1.8	V	33.3	40	-6.7
120.60	20.0	12.8	2.4	H	35.2	43.5	-8.3
120.60	18.0	12.8	2.4	V	33.2	43.5	-10.3
333.10	11.2	16.4	4.2	H	31.8	46	-14.2
362.00	12.8	16.6	4.4	H	33.8	46	-12.3
374.00	16.6	16.7	4.4	H	37.7	46	-8.3
408.00	14.1	17.2	4.6	H	35.9	46	-10.1
561.00	12.1	20.4	5.4	H	37.9	46	-8.1
561.00	13.8	20.4	5.4	V	39.6	46	-6.4
768.00	12.1	23.1	6.3	H	41.5	46	-4.5

Radiated Measurements at 3-meters.

### NOTES:

1. All modes( PC, Video, S-Vide, DVI, TV mode) of operation were investigated, and the worst-case emissions are reported.
2. The radiated limits are listed on Table 2 (Page 7).

\*\* AFCL = Antenna Factor (Roberts dipole) and Cable Loss .

\*\*\* Measurements using CISPR quasi-peak mode. Above 1GHz, peak detector function mode is used using a resolution bandwidth of 1MHz and a video bandwidth of 1MHz. The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.

## 8.1 Sample Calculations

$$dB \square = 20 \log_{10} (\square)$$

$$dB \square = dBm + 107$$

### 8.2 Example 1:

**@ 20.3 MHz**

Class B limit	= $250 \mu V = 47.96 \text{ dB}\mu V$
Reading	= $-67.8 \text{ dBm}$ (calibrated level)
Convert to $\text{dB}\mu V$	= $-67.8 + 107 = 39.2 \text{ dB}\mu V$
$10^{(39.2/20)}$	= $91.2 \mu V$
<b>Margin</b>	= $39.2 - 47.96 = -8.76$
	<b>= 8.8 dB below limit</b>

### 8.3 Example 2:

**@ 66.7 MHz**

Class B limit	= $100 \mu V/m = 40.0 \text{ dB}\mu V/m$
Reading	= $-76.0 \text{ dBm}$ (calibrated level)
Convert to $\text{dB}\mu V/m$	= $-76.0 + 107 = 31.0 \text{ dB}\mu V/m$
Antenna Factor + Cable Loss	= $5.8 \text{ dB}$
Total	= $36.8 \text{ dB}\mu V/m$
<b>Margin</b>	= $36.8 - 40.0 = -3.2$
	<b>= 3.2 dB below limit</b>

## 9.1 Test Equipment

<u>Type</u>	<u>Manufacture</u>	<u>Model Number</u>	<u>CAL Date</u>
EMI Test Receiver	Rohed & Schwarz	ESI40	2003.11.16
EMI Test Receiver	Rohed & Schwarz	ESVS30	2003.07.16
LISN	Rohed & Schwarz	ESH2-Z5	2003.08.21
LISN	EMCO	3825/2	2003.02.24
Amplifier	Hewlett-Packard	8447E	2003.08.23
Aborbing Clamp	Rohed & Schwarz	MDS-21	2003.04.24
Dipole Antennas	Schwarzbeck	VHAP	2003.07.24
Dipole Antennas	Schwarzbeck	UHAP	2003.07.24
Biconical Antenna	Schwarzbeck	VHA9103	2003.07.23
Log-Periodic Antenna	Schwarzbeck	UHALP9107	2003.07.23
Antenna Position Tower	HD	MA240	N/A
Turn Table	EMCO	1050	N/A
Power Analyzer	Voltech	PM 3300	2003.02.15
Reference Network Impedance	Voltech	IEC 555	N/A
AC Power Source	PACIFIC	Magnetic Module	N/A
AC Power Source	PACIFIC	360AMX	2003.11.25
Controller	HD GmbH	HD 100	N/A
SlideBar	HD GmbH	KMS 560	N/A

## 10.1 Test Software Used

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software, contained on a 3-1/2 inch disc, was inserted into drive A and is auto starting on power-up. Once loaded, the program sequentially exercises each system component in turn. The sequence used is :(1) Display test, (2) RS 232 test (3) Key board test,(4) Printer test,(5) FDD test,(6) HDD test. The complete cycle takes about 20 seconds and is repeated continuously. As the keyboard and mouse are strictly input devices, no data is transmitted to them during test. They are however, continuously scanned for data input activity. The video resolution modes setup and change program was used during the radiated and conducted emission testing.

NOTE: This is a sample of the basic program used during the test. However, during testing, a different software program may be used; whichever determines the worst-case condition. In addition, the program used also depends on the number and type of devices being tested.

Actual program used is the Display "H" Pattern , White Pattern , 100/0/75/0 Colour bars,1000 Hz Audio signal.  
All resolution modes were investigated and tested

## 11.1 Conclusion

The data collected shows that the **TECHSAN I & C CO., LTD. PDP Monitor** FCC ID: **RJ5PT4200U**. complies with §15.107 and §15.109 of the FCC Rules.