

INNO-A20

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.636 mW/g, SAR(10g): 0.345 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.10 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Left Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom, Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$, $\epsilon_r = 38.5$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.642 mW/g, SAR (10g): 0.342 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.04 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Left Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.619 mW/g, SAR (10g): 0.330 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.18 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Left Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$, $\epsilon_r = 38.5$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.890 mW/g, SAR (10g): 0.478 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.14 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ ρ $= 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.877 mW/g, SAR (10g): 0.463 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.03 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.750 mW/g, SAR (10g): 0.390 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.08 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.347 mW/g, SAR (10g): 0.215 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.12 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Left Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom, Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.403 mW/g, SAR (10g): 0.237 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.26 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Right Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20 (Body)

SAM II Phantom; Flat Section; Position: (90°, 90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(4.60, 4.60, 4.60); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.52 \text{ mho/m}$, $\epsilon_r = 51.9$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.261 mW/g, SAR(10g): 0.150 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.05 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20 (Body)

SAM II Phantom; Flat Section; Position: (90°, 90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(4.60,4.60,4.60); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.52 \text{ mho/m}$ $\epsilon_r = 51.9$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.179 mW/g, SAR (10g): 0.100 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.03 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20 (Body)

SAM II Phantom; Flat Section; Position: (90°,90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(4.60,4.60,4.60); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.52 \text{ mho/m}$ $\epsilon_r = 51.9$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.193 mW/g, SAR (10g): 0.114 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: 0.09 dB

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.1°C

Date Tested : March 25, 2005



INNO-A20

SAM II Phantom; Section; Position: ; Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(5.34,5.34,5.34); Crest factor: 8.0; Brain 1900 MHz: $\sigma = 1.43 \text{ mho/m}$ $\epsilon_r = 38.5$ $\rho = 1.00 \text{ g/cm}^3$

:

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Comment:

MODEL : INNO-A20


Company : Innostream Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005



INNO-A20 (Body)

SAM II Phantom; Section; Position: ; Frequency: 1900 MHz

Probe: ET3DV6 - SN1609; ConvF(4.60,4.60,4.60); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.52 \text{ mho/m}$ $\epsilon_r = 51.9$ $\rho = 1.00 \text{ g/cm}^3$

:

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Comment:

MODEL : INNO-A20

Company : Innostream Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.1 °C

Date Tested : March 25, 2005

