


FCC PART 15.249  
EMI MEASUREMENT AND TEST REPORT  
For  
ENJOY TECHNOLOGY CO., LIMITED  
UNIT 04&#65292;7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL Hong Kong China

**FCC ID: RJM-RFX19**

January 29, 2013

This Report Concerns: Original Report	Equipment Type: Audience response system
Test Engineer:	Anna Lv 
Test Engineer of performing the tests:	Hans Hu 
Report No.:	BST120015723Y-1ER-3
Receive EUT Date/Test Date:	January 02, 2013 / January 02, 2013- January 29, 2013
Reviewed By:	Mike Moo 
Prepared By:	Shenzhen BST Technology Co.,Ltd. 3F,Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District,Shenzhen,Guangdong,China Tel: 0755-26747751-3 Fax: 0755-26747751-3 ext.826

**Note:** The test report is specially limited to the above company and this particular sample only.  
It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd.  
This report must not be used by the client to claim product certification,approval,or  
endorsement by NVLAP, NIST or any agency of the US Government.

## TABLE OF CONTENTS

<b>1.</b>	<b>GENERAL INFORMATION .....</b>	<b>3</b>
1.1.	Report information.....	3
1.2.	Measurement Uncertainty .....	3
<b>2.</b>	<b>PRODUCT DESCRIPTION .....</b>	<b>4</b>
2.1.	EUT Description .....	4
2.2.	Block Diagram of EUT Configuration.....	6
2.3.	Support Equipment List .....	6
2.4.	Test Conditions .....	6
2.5.	Configuration of Test Setup.....	6
<b>3.</b>	<b>TEST RESULTS SUMMARY .....</b>	<b>7</b>
	Modifications .....	7
<b>4.</b>	<b>TEST EQUIPMENT USED .....</b>	<b>8</b>
<b>5.</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>9</b>
5.1.	Standard Applicable.....	9
5.2.	Antenna Connected Construction .....	9
5.3.	Result .....	9
<b>6.</b>	<b>CONDUCTED POWER LINE TEST .....</b>	<b>10</b>
6.1.	Test Equipment .....	10
6.2.	Test Procedure .....	10
6.3.	Test Setup.....	10
6.4.	Conducted Power line Emission Limits.....	10
6.5.	Conducted Power Line Test Result.....	11
<b>7.</b>	<b>RADIATED EMISSION TEST .....</b>	<b>12</b>
7.1.	Test Equipment .....	12
7.2.	Test Procedure .....	12
7.3.	Radiated Test Setup .....	12
7.4.	Radiated Emission Limit.....	14
7.5.	Radiated Emission Test Result .....	15
<b>8.</b>	<b>BAND EDGE .....</b>	<b>20</b>
8.1.	Test Equipment .....	20
8.2.	Test Procedure .....	20
8.3.	Band Edge FCC 15.249(d) Limit.....	20
8.4.	Band Edge Test Result.....	21

## 1. GENERAL INFORMATION

### 1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

#### Test Facility -

The test site used to collect the data is located on the address of  
 Global United Technology Service Co., Ltd  
 (FCC Registered Test Site Number: 600491) on  
 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District,  
 Shenzhen, China 518102  
 The Test Site is constructed and calibrated to meet the FCC requirements.

### 1.2. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

## 2. PRODUCT DESCRIPTION

### 2.1. EUT Description

Applicant : ENJOY TECHNOLOGY CO., LIMITED  
Address : UNIT 04&#65292;7/F BRIGHT WAY TOWER NO.33 MONG  
KOK RD KL Hong Kong China  
Manufacturer : GUANGZHOU QILE TECHNOLOGY CO.,LTD  
Address : 3/F and 4/F, 29-1#, Dayuan Nan Road, Baiyun District,  
Guangzhou, Guangdong Province, China  
EUT Description : Audience response system  
  
Trade Name : ENJOY® VoteWorks®  
Model Number : RFX19 VoteWorks® Engage  
Receiver frequency : 2402-2480MHz  
modulation type : GFSK(1Mbps)  
Antenna gain : 0dBi  
Power Supply : DC 3V (Powered by battery)  
Channel : 79

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

## 2.2. Block Diagram of EUT Configuration



Figure 1 EUT Setup

## 2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used (Y/N)

## 2.4. Test Conditions

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-25
Humidity (%RH)	25-75	50-63
Barometric pressure (mbar)	860-1060	950-1000

## 2.5. Configuration of Test Setup

EUT Orthogonal Axis:

X - denotes Laid on Table; Y - denotes Vertical Stand; Z - denotes Side Stand

### 3. TEST RESULTS SUMMARY

#### FCC 15 Subpart C, Paragraph 15.249

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

N/A:Not Apply

Statement: All testing was performed using the test procedures found in ANSI C63.4-2003.

#### Modifications

No modification was made.

#### 4. TEST EQUIPMENT USED

EQUIPMENT/FACILITIES	MANUFACTURER	MODEL	SERIAL NO.	DATE OF CAL.	CAL. INTERVAL
3m Semi-Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 30 2012	1 Year
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 04 2012	1 Year
BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRO NIK	VULB9163	GTS214	Feb. 25 2012	1 Year
Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRO NIK	9120D-829	GTS208	June 30 2012	1 Year
Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2012	1 Year
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Cable	Resenberger	N/A	NO.1	Apr. 6, 2012	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Apr. 6, 2012	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Apr. 6, 2012	1 Year
Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 04 2012	1 Year
Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 04 2012	1 Year
Amplifier (18-26GHz)	R&S	AFS33-1800 2 650-30-8P-4 4	GTS218	June 30 2012	1 Year
Band filter	Amindeon	82346	GTS219	Mar. 31 2012	1 Year
Active Loop Antenna	Beijing Daze	ZN30900A	GTS215	Mar. 31 2012	1 Year
Power Meter	R&S	NRVS	GTS216	Apr. 6, 2012	1 Year
Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	Sep. 08 2012	1 Year
EMI Test Receiver	R&S	ESCS30	GTS223	Jul. 04 2012	1 Year
10dB Pulse Limita	R&S	N/A	GTS224	Jul. 04 2012	1 Year
Coaxial Switch	ANRITSU CORP	MP59B	GTS225	Jul. 04 2012	1 Year
LISN	SCHWARZBECK MESS-ELEKTRO NIK	NSLK 8127	GTS226	Jul. 04 2012	1 Year
Coaxial Cable	SCHWARZBECK	N/A	NO.4	Apr. 6, 2012	1 Year
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Spectrum analyzer	agilent	E4440A	GTS251	Jul. 04 2012	N/A

## 5. ANTENNA REQUIREMENT

### 5.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 5.2. Antenna Connected Construction

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used in this product is PCB antenna. The antenna is permanently attached. Refer to the product photo.

### 5.3. Result

Compliance

## 6. CONDUCTED POWER LINE TEST

### 6.1. Test Equipment


Please refer to section 4 this report.

### 6.2. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.).This provides a 50ohm/50uh coupling impedance for the measuring equipment.The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling impedance with 50ohm termination.

Both sides of A.C. Line are check for maximum conducted interference.In order to find the maximum emission,the relative positions of equipment and all of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement .Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

### 6.3. Test Setup



For the actual test configuration,Please refer to the related items-Photos of testing

### 6.4. Conducted Power line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHZ)	Class A QP/AV	Class B QP/AV
0.15-0.5	79/66	65-56/56-46
0.5-5.0	73/60	56-46
5.0-3.0	73/60	60-50

**Note:** In the above table, the tighter limit applies at the band edges.

## **6.5. Conducted Power Line Test Result**

### **Not Apply**

This EUT is powered by battery only, therefore this Test Item is not applicable.

## 7. RADIATED EMISSION TEST

### 7.1. Test Equipment

Please refer to section 4 this report.

### 7.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz, and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.


Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit.

### 7.3. Radiated Test Setup


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



## 7.4. Radiated Emission Limit

All emission from a digital device,including any network of conductors and apparatus connected thereto,shall not exceed the level of field strength specified below :

### A. Fundamental and Harmonics Radiated Emissions 15.249(a) Limit

Fundamental Frequency (MHz)	Field as strength of Fundamental(3m)			Field as strength of Harmonics(3m)		
	mV/m	dBuV/m		uV/m	dBuV/m	
902-928	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)
2400-2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(3) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function,corresponding to 20dB above the maximum permitted average limit.

### B. Spurious Radiated Emissions.

Frequency (MHz)	Limit			
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dB $\mu$ V/m)	Measurement distance (m)	The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
0.009 - 0.490	2400/F(kHz)	/	300	
0.490 - 1.705	24000/F(kHz)	/	30	
1.705-30	30	29.5	30	
30 - 88	100	40	3	
88 - 216	150	43.5	3	
216 - 960	200	46	3	
Above 960	500	54	3	

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) In the Above Table,the tighter limit applies at the band edges.

(3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

## 7.5. Radiated Emission Test Result

Pass

Test mode: TX

### A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2402	83.2/94.1	VERT	94/114	-10.8/-19.9
2402	76.28/84.9	HORIZ	94/114	-17.72/-29.1

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2441	83.09/94.07	VERT	94/114	-10.91/-19.93
2441	77.08/84.18	HORIZ	94/114	-16.92/-29.82

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2480	82.42/93.4	VERT	94/114	-11.58/-20.6
2480	73.56/85.2	HORIZ	94/114	-20.44/-28.8

## B. General Radiated Emissions Data

Pass

Test mode: TX

**For below 9kHz-30MHz Spurious**

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	HORIZ	-	-
-	-	VERT	-	-

## Note:


1. Emissions attenuated more than 20 dB below the permissible value are not reported.

Pass

Test mode: TX


**For 30M-1000MHz Spurious**

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

**Condition:**

: RBW:120.000KHz VBW:300.000KHz

Freq MHz	Level dBuV/m	Line dBuV/m	Limit dB	Over	Remark	Pol/Phase
				Freq	Level	Line
1	30.97	31.36	40.00	-8.64	QP	HORIZONTAL
2	127.00	24.97	43.50	-18.53	QP	HORIZONTAL
3	361.74	28.01	46.00	-17.99	QP	HORIZONTAL
4	545.07	30.42	46.00	-15.58	QP	HORIZONTAL
5	676.02	32.41	46.00	-13.59	QP	HORIZONTAL
6 Max	950.53	37.93	46.00	-8.07	QP	HORIZONTAL



## Condition:

: RBW:120.000KHz VBW:300.000KHz

	Freq	Level	Line	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB			
1	30.97	31.15	40.00	-8.85	QP		VERTICAL
2	83.35	27.26	40.00	-12.74	QP		VERTICAL
3	118.27	28.40	43.50	-15.10	QP		VERTICAL
4	378.23	27.31	46.00	-18.69	QP		VERTICAL
5	591.63	30.60	46.00	-15.40	QP		VERTICAL
6 Max	942.77	37.82	46.00	-8.18	QP		VERTICAL

Pass

Test mode:TX

**For For 1000MHz-25000MHz Spurious**

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4804.0	39.1/54.16	VERT	54.0/74.0	-14.9/-19.84
7206.0	40.8/55.39		54.0/74.0	-13.2/-18.61
9608.0	41.86/59.4		54.0/74.0	-12.14/-14.6
4804.0	37.72/50.53	HORIZ	54.0/74.0	-16.28/-23.47
7206.0	39.15/52.77		54.0/74.0	-14.85/-21.23
9608.0	40.68/55.35		54.0/74.0	-13.32/-18.65

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4882.0	42.07/53.44	VERT	54.0/74.0	-11.93/-20.56
7323.0	44.11/55.68		54.0/74.0	-9.89/-18.32
9764.0	46.2/58.27		54.0/74.0	-7.8/-15.73
4882.0	39.82/56.11	HORIZ	54.0/74.0	-14.18/-17.89
7323.0	41.13/53.46		54.0/74.0	-12.87/-20.54
9764.0	43.17/54.13		54.0/74.0	-10.83/-19.87

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4960.0	42.2/50.62	VERT	54.0/74.0	-11.58/-24.08
7440.0	43.56/57.78		54.0/74.0	-10.44/-16.22
9920.0	47.53/60.47		54.0/74.0	-6.47/-13.53
4960.0	38.82/46.73	HORIZ	54.0/74.0	-15.18/-27.27
7440.0	40.22/53.59		54.0/74.0	-13.78/-20.41
9920.0	44.77/52.55		54.0/74.0	-9.23/-21.45

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.
2. Emissions attenuated more than 20 dB below the permissible value are not reported.

## 8. BAND EDGE

### 8.1. Test Equipment

Please refer to Section 4 this report.

### 8.2. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement. The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz respectively.

### 8.3. Band Edge FCC 15.249(d) Limit


Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

## 8.4. Band Edge Test Result

Pass


Test mode: TX

TX:2402MHz



Site : 3m chamber  
 Condition : FCC PART 15 (PK) VERTICAL  
 Remark : L ch


	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	38.30	27.58	3.81	30.10	39.59	74.00	-34.41 Peak
2	2390.000	29.30	27.58	3.81	30.10	30.59	54.00	-23.41 Average



Site : 3m chamber  
Condition : FCC PART 15 (PK) HORIZONTAL  
Remark : L ch


	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	37.48	27.58	3.81	30.10	38.77	74.00 -35.23 Peak
2	2390.000	27.10	27.58	3.81	30.10	28.39	54.00 -25.61 Average

TX:2480MHz



Site : 3m chamber  
 Condition : FCC PART 15 (PK) VERTICAL  
 Remark : H ch

Freq	Read		Antenna		Cable		Preamp	Limit Level	Over Line	Over Limit	Remark
	Level	Factor	Loss	Factor	dB	dB	dBuV/m				
MHz	dBuV	dB/m	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	dB	dB
1 2483.500	37.14	27.52	3.89	30.60	37.95	74.00	-36.05	74.00	-36.05	Peak	
2 2483.500	28.30	27.52	3.89	30.60	29.11	54.00	-24.89	54.00	-24.89	Average	



Site : 3m chamber  
 Condition : FCC PART 15 (PK) HORIZONTAL  
 Remark : H ch

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	35.96	27.52	3.89	30.60	36.77	74.00	-37.23 Peak
2	2483.500	28.60	27.52	3.89	30.60	29.41	54.00	-24.59 Average