



FCC TEST REPORT

According to

FCC Rules and Regulations Part 15 Subpart C

Applicant	: Jia Teng Technology Co., Ltd.
Address	: 4F, No. 417, Ruiguand Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)
Equipment	: Intelligent Mobile Extension Cloud Server
Model No.	: WP2085, WP1264
Trade Name	: Uni Talk
FCC ID	: RKCIPPBX

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Cerpass Technology Corp.**, the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



Contents

1. Report of Measurements and Examinations	6
1.1 List of Measurements and Examinations	6
2. Test Configuration of Equipment under Test.....	7
2.1 Feature of Equipment under Test.....	7
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System.....	8
2.5 General Information of Test.....	9
2.6 Measurement Uncertainty	9
3. Antenna Requirements.....	10
3.1 Standard Applicable	10
3.2 Antenna Construction and Directional Gain.....	10
4. Test of Conducted Emission.....	11
4.1 Test Limit	11
4.2 Test Procedures	11
4.3 Typical Test Setup	12
4.4 Measurement Equipment.....	12
4.5 Test Result and Data	13
4.6 Test Photographs	23
5. Test of Radiated Emission	24
5.1 Test Limit	24
5.2 Test Procedures	24
5.3 Typical Test Setup	25
5.4 Measurement Equipment.....	25
5.5 Test Result and Data (9kHz ~ 30MHz).....	26
5.6 Test Result and Data (30MHz ~ 25GHz).....	26
5.7 Test Photographs (30MHz~1000MHz).....	62
5.8 Test Photographs (1GHz~25GHz)	63
6. 6dB Bandwidth Measurement Data.....	64
6.1 Test Limit	64
6.2 Test Procedures	64
6.3 Test Setup Layout	64
6.4 Measurement Equipment.....	64
6.5 Test Result and Data	64
7. Maximum Peak and Average Output Power.....	77
7.1 Test Limit	77
7.2 Test Procedures	77
7.3 Test Setup Layout	77
7.4 Measurement Equipment.....	77
7.5 Test Result and Data	78
8. Power Spectral Density	80
8.1 Test Limit	80
8.2 Test Procedures	80



8.3	Test Setup Layout	80
8.4	Measurement Equipment.....	80
8.5	Test Result and Data.....	80
9.	Band Edges Measurement.....	93
9.1	Test Limit	93
9.2	Test Procedure	93
9.3	Test Setup Layout	93
9.4	Measurement Equipment.....	93
9.5	Test Result and Data.....	93
9.6	Restrict Band Emission Measurement Data	110
10.	Restricted Bands of Operation	112
10.1	Labeling Requirement.....	112
Appendix A. Photographs of EUT.....		A1 ~ A15



History of this test report

■ ORIGINAL.

☐ Additional attachment as following record:

Attachment No.	Issue Date	Description



CERTIFICATE OF COMPLIANCE

According to

FCC Rules and Regulations Part 15 Subpart C

Applicant : Jia Teng Technology Co., Ltd.
Address : 4F, No. 417, Ruiguand Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)
Equipment : Intelligent Mobile Extension Cloud Server
Model No. : WP2085, WP1264
FCC ID : RKCIPPBX


I HEREBY CERTIFY THAT :


The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 2009, KDB558074 & KDB662911**. The equipment was ***passed*** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2010)**.

The test was carried out on Dec. 10, 2012 at Cerpass Technology Corp.

Approved by:

Tested by:


Hill Chen
EMC/RF B.U. Assistant Manager


Ben Lu
Engineer



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	Antenna Requirement	Pass
15.207	Conducted Emission	Pass
15.209 15.247(d)	Radiated Emission	Pass
15.247(a)(2)	6dB Bandwidth	Pass
15.247(b)	Maximum Peak Output Power	Pass
15.247(d)	100kHz Bandwidth of Frequency Band Edges	Pass
15.247(e)	Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	Pass



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Model No.	WP2085	WP1264
Hardware		
Dimension	145X102X29mm	360X120X44mm
Antenna Spec.	Two detachable 7dBi antenna	
Wireless Frequency	2.400GHz~2.484GHz	
Input Voltage	AC 100-240V 50Hz/60Hz 0.3A	
Output Voltage	DC 12V 1A	
Interface	RJ-45 Port X1(WAN)、RJ-45 Port x4(LAN)、Reset/WPS Button、USB Port X1、AC X1	
Wireless		
Data Rate	802.11b/802.11g/802.11n(40MHz)	
Max. Transfer Rate	300Mbps	
Wireless Security Support	64/128 bit WEP、WPA(TKIP with IEEE 802.1x)、WPA2(AES with IEEE 802.1x)、WPAPSK/WPA2PSK	
Router Specification		
WAN Mode	Static、DHCP、PPPoE	
Internet Sharing	DHCP Server、NAT、Port Mapping	
Firewall	IP/Port filtering、Block Port Scan、Block SYN Flood	
Clock Synchronization	NTP Client	
QoS	Voice First	

2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT 20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	---	---

802.11n, HT 40 (2422MHz~2452MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
03	2422	07	2442
04	2427	08	2447
05	2432	09	2452
06	2437	---	---



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. The complete test system included Notebook, Mouse and EUT for the test.
- c. An executive program, "QA Test" under WIN XP was executed to transmit and receive data via wireless.
- d. The following test modes were performed for test:
Test Mode 1: Model No. WP2085
 - 802.11b/g/n HT20: CH01: 2412MHz, CH06: 2437MHz, CH11: 2462MHz
 - 802.11n HT40: CH03: 2422MHz, CH06: 2437MHz, CH09: 2452MHzTest Mode 2: Model No. WP1264
 - 802.11b/g/n HT20: CH01: 2412MHz, CH06: 2437MHz, CH11: 2462MHz
 - 802.11n HT40: CH03: 2422MHz, CH06: 2437MHz, CH09: 2452MHzcause "Test Mode 1" generated the worst test result, it was reported as final data.

* Power output of data rate:

802.11b		802.11g		802.11n HT20		802.11n HT40	
Data Rate (Mbps)	Power output (dBm)	Data Rate (Mbps)	Power output (dBm)	Data Rate (Mbps)	Power output (dBm)	Data Rate (Mbps)	Power output (dBm)
11	15.52	54	18.41	130/15	17.46	270/15	17.45
5.5	15.46	48	18.39	117/14	17.37	243/14	17.38
2	15.47	36	18.37	104/13	17.36	216/13	17.36
1	15.48	24	18.39	78/12	17.33	162/12	17.34
---	---	18	18.35	52/11	17.35	108/11	17.35
---	---	12	18.38	39/10	17.39	81/10	17.39
---	---	9	18.36	26/9	17.37	54/9	17.39
---	---	6	18.39	13/8	17.36	27/8	17.35
---	---	---	---	65/7	17.35	135/7	17.36
---	---	---	---	58.5/6	17.37	121.5/6	17.39
---	---	---	---	52/5	17.36	108/5	17.35
---	---	---	---	39/4	17.37	81/4	17.35
---	---	---	---	26/3	17.40	54/3	17.36
---	---	---	---	19.5/2	17.39	40.5/2	17.38
---	---	---	---	13/1	17.38	27/1	17.40
---	---	---	---	6.5/0	17.40	13.5/0	17.41

2.4 Description of Test System

Device	Manufacturer	Model No.	Description
Notebook	ASUS	A8J	Power Cable, Adapter Unshielding 1.8 m
Mouse	DELL	M-UV83	Data Cable, USB Shielding 1.85m



2.5 General Information of Test

Test Site :	Cerpass Technology Corp. 2F-11, No. 3, Yuan Qu St., (Nankang Software Park), Taipei, Taiwan 115, R.O.C.
Test Site Location (OATS2-SD) :	No.68-1, Shihbachongsi, Shihding Township, Taipei City 223, Taiwan, R.O.C.
FCC Registration Number :	TW1049, TW1061, 488071, 390316
IC Registration Number :	4934B-1, 4934D-1
VCCI Registration Number :	T-1173 for Telecommunication Test C-4139 for Conducted emission test R-3428 for Radiated emission test G-97 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30MHz Radiation: from 30MHz to 25,000MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.
Laboratory Accreditation	

2.6 Measurement Uncertainty

Measurement Item	Uncertainty
Radiated emission	$\pm 4.11\text{dB}$
Peak Output Power(conducted)	$\pm 1.38\text{dB}$
Peak Output Power(Radiated)	$\pm 1.70\text{dB}$
Power Spectral Density	$\pm 1.39\text{dB}$
Radiated emission(3m)	$\pm 4.11\text{dB}$
Radiated emission(10m)	$\pm 3.89\text{dB}$



3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

ANT R, ANT L

Antenna Type: Dipole Antenna

Antenna Gain: 7 dBi

Note: Directional gain = $G_{ANT} + 10 \log(N)$ dBi = $7 + 10 \log(2) = 6.0$ (dBi)



4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2009 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

4.3 Typical Test Setup




4.4 Measurement Equipment

Instrument	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
EMI Receiver	R&S	ESCI	100443	2012/01/12	2013/01/11
LISN	Schwarzbeck	NSLK 8127	8127-516	2012/03/08	2013/03/07
LISN	Schwarzbeck	NSLK 8127	8127-568	2012/08/22	2013/08/21



4.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: 802.11g, CH1	Temperature	: 23 °C
Test Date	: Nov. 22, 2012	Humidity	: 68 %




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1900	0.12	48.84	48.96	64.03	-15.07	QP	P
2	0.1900	0.12	38.64	38.76	54.03	-15.27	AVG	P
3	0.2140	0.12	46.61	46.73	63.04	-16.31	QP	P
4	0.2140	0.12	38.59	38.71	53.04	-14.33	AVG	P
5	0.2340	0.12	46.98	47.10	62.30	-15.20	QP	P
6	0.2340	0.12	37.85	37.97	52.30	-14.33	AVG	P
7	0.7060	0.17	33.42	33.59	56.00	-22.41	QP	P
8	0.7060	0.17	20.44	20.61	46.00	-25.39	AVG	P
9	3.9180	0.43	32.91	33.34	56.00	-22.66	QP	P
10	3.9180	0.43	22.05	22.48	46.00	-23.52	AVG	P
11	4.6860	0.46	34.79	35.25	56.00	-20.75	QP	P
12	4.6860	0.46	24.38	24.84	46.00	-21.16	AVG	P
13	5.1620	0.48	37.47	37.95	60.00	-22.05	QP	P
14	5.1620	0.48	25.68	26.16	50.00	-23.84	AVG	P

Note: Level = Reading + Factor
Margin = Level – Limit



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: 802.11g, CH1	Temperature	: 23 °C
Test Date	: Nov. 22, 2012	Humidity	: 68 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1819	0.12	50.97	51.09	64.39	-13.30	QP	P
2	0.1819	0.12	40.27	40.39	54.39	-14.00	AVG	P
3	0.2100	0.12	50.54	50.66	63.20	-12.54	QP	P
4	0.2100	0.12	41.51	41.63	53.20	-11.57	AVG	P
5	0.2300	0.12	51.00	51.12	62.45	-11.33	QP	P
6	0.2300	0.12	40.15	40.27	52.45	-12.18	AVG	P
7	0.2380	0.12	51.53	51.65	62.16	-10.51	QP	P
8	0.2380	0.12	43.58	43.70	52.16	-8.46	AVG	P
9	0.2500	0.12	47.78	47.90	61.75	-13.85	QP	P
10	0.2500	0.12	36.86	36.98	51.75	-14.77	AVG	P
11	0.5860	0.15	35.48	35.63	56.00	-20.37	QP	P
12	0.5860	0.15	18.93	19.08	46.00	-26.92	AVG	P
13	1.4340	0.24	32.40	32.64	56.00	-23.36	QP	P
14	1.4340	0.24	20.37	20.61	46.00	-25.39	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
15	3.5220	0.36	35.11	35.47	56.00	-20.53	QP	P
16	3.5220	0.36	25.93	26.29	46.00	-19.71	AVG	P
17	3.8220	0.38	38.04	38.42	56.00	-17.58	QP	P
18	3.8220	0.38	27.93	28.31	46.00	-17.69	AVG	P
19	4.4699	0.40	39.65	40.05	56.00	-15.95	QP	P
20	4.4699	0.40	30.22	30.62	46.00	-15.38	AVG	P
21	4.7660	0.42	41.05	41.47	56.00	-14.53	QP	P
22	4.7660	0.42	31.23	31.65	46.00	-14.35	AVG	P
23	4.9460	0.43	41.11	41.54	56.00	-14.46	QP	P
24	4.9460	0.43	31.36	31.79	46.00	-14.21	AVG	P
25	5.9460	0.47	41.48	41.95	60.00	-18.05	QP	P
26	5.9460	0.47	31.92	32.39	50.00	-17.61	AVG	P
27	6.1380	0.47	40.88	41.35	60.00	-18.65	QP	P
28	6.1380	0.47	31.77	32.24	50.00	-17.76	AVG	P
29	6.7860	0.50	40.76	41.26	60.00	-18.74	QP	P
30	6.7860	0.50	31.19	31.69	50.00	-18.31	AVG	P
31	7.5220	0.53	38.14	38.67	60.00	-21.33	QP	P
32	7.5220	0.53	28.50	29.03	50.00	-20.97	AVG	P

Note: Level = Reading + Factor
Margin = Level – Limit



Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: 802.11n HT20, CH1	Temperature	: 23 °C
Test Date	: Nov. 22, 2012	Humidity	: 68 %




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1819	0.12	49.07	49.19	64.39	-15.20	QP	P
2	0.1819	0.12	37.10	37.22	54.39	-17.17	AVG	P
3	0.2020	0.12	45.39	45.51	63.52	-18.01	QP	P
4	0.2020	0.12	32.79	32.91	53.52	-20.61	AVG	P
5	0.2340	0.12	48.29	48.41	62.30	-13.89	QP	P
6	0.2340	0.12	39.43	39.55	52.30	-12.75	AVG	P
7	0.2700	0.12	39.82	39.94	61.12	-21.18	QP	P
8	0.2700	0.12	30.60	30.72	51.12	-20.40	AVG	P
9	4.6740	0.46	35.47	35.93	56.00	-20.07	QP	P
10	4.6740	0.46	25.08	25.54	46.00	-20.46	AVG	P
11	6.2819	0.52	36.91	37.43	60.00	-22.57	QP	P
12	6.2819	0.52	26.50	27.02	50.00	-22.98	AVG	P
13	15.5020	0.88	31.45	32.33	60.00	-27.67	QP	P
14	15.5020	0.88	22.57	23.45	50.00	-26.55	AVG	P

Note: Level = Reading + Factor
Margin = Level – Limit



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 23 °C
Test Date	: Nov. 22, 2012	Humidity	: 68 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2100	0.12	51.29	51.41	63.20	-11.79	QP	P
2	0.2100	0.12	42.80	42.92	53.20	-10.28	AVG	P
3	0.2300	0.12	51.60	51.72	62.45	-10.73	QP	P
4	0.2300	0.12	40.89	41.01	52.45	-11.44	AVG	P
5	0.2540	0.12	46.26	46.38	61.62	-15.24	QP	P
6	0.2540	0.12	34.46	34.58	51.62	-17.04	AVG	P
7	0.7500	0.18	34.58	34.76	56.00	-21.24	QP	P
8	0.7500	0.18	22.04	22.22	46.00	-23.78	AVG	P
9	1.6700	0.26	30.31	30.57	56.00	-25.43	QP	P
10	1.6700	0.26	18.09	18.35	46.00	-27.65	AVG	P
11	3.7220	0.36	36.63	36.99	56.00	-19.01	QP	P
12	3.7220	0.36	27.14	27.50	46.00	-18.50	AVG	P
13	4.4300	0.40	40.67	41.07	56.00	-14.93	QP	P
14	4.4300	0.40	30.52	30.92	46.00	-15.08	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F
15	4.7220	0.41	40.50	40.91	56.00	-15.09	QP	P
16	4.7220	0.41	30.84	31.25	46.00	-14.75	AVG	P
17	5.4300	0.44	40.72	41.16	60.00	-18.84	QP	P
18	5.4300	0.44	31.64	32.08	50.00	-17.92	AVG	P
19	5.8460	0.46	41.58	42.04	60.00	-17.96	QP	P
20	5.8460	0.46	31.87	32.33	50.00	-17.67	AVG	P
21	6.0780	0.47	41.15	41.62	60.00	-18.38	QP	P
22	6.0780	0.47	31.66	32.13	50.00	-17.87	AVG	P
23	6.7820	0.50	41.14	41.64	60.00	-18.36	QP	P
24	6.7820	0.50	31.81	32.31	50.00	-17.69	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit



Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: 802.11n HT40, CH3	Temperature	: 23 °C
Test Date	: Nov. 22, 2012	Humidity	: 68 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	0.11	47.74	47.85	65.36	-17.51	QP	P
2	0.1620	0.11	29.96	30.07	55.36	-25.29	AVG	P
3	0.1740	0.11	47.68	47.79	64.76	-16.97	QP	P
4	0.1740	0.11	27.94	28.05	54.76	-26.71	AVG	P
5	0.2020	0.12	49.56	49.68	63.52	-13.84	QP	P
6	0.2020	0.12	36.11	36.23	53.52	-17.29	AVG	P
7	0.2180	0.12	46.71	46.83	62.89	-16.06	QP	P
8	0.2180	0.12	31.88	32.00	52.89	-20.89	AVG	P
9	0.2500	0.12	44.15	44.27	61.75	-17.48	QP	P
10	0.2500	0.12	29.39	29.51	51.75	-22.24	AVG	P
11	0.2860	0.12	39.16	39.28	60.64	-21.36	QP	P
12	0.2860	0.12	27.81	27.93	50.64	-22.71	AVG	P
13	0.6540	0.16	34.34	34.50	56.00	-21.50	QP	P
14	0.6540	0.16	19.40	19.56	46.00	-26.44	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F
15	3.5340	0.40	34.56	34.96	56.00	-21.04	QP	P
16	3.5340	0.40	23.50	23.90	46.00	-22.10	AVG	P
17	4.5340	0.46	38.43	38.89	56.00	-17.11	QP	P
18	4.5340	0.46	28.02	28.48	46.00	-17.52	AVG	P
19	4.9940	0.48	39.47	39.95	56.00	-16.05	QP	P
20	4.9940	0.48	29.14	29.62	46.00	-16.38	AVG	P
21	5.7300	0.51	40.45	40.96	60.00	-19.04	QP	P
22	5.7300	0.51	29.68	30.19	50.00	-19.81	AVG	P
23	7.0060	0.56	39.75	40.31	60.00	-19.69	QP	P
24	7.0060	0.56	29.04	29.60	50.00	-20.40	AVG	P
25	28.6860	1.29	43.22	44.51	60.00	-15.49	QP	P
26	28.6860	1.29	37.67	38.96	50.00	-11.04	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 23 °C
Test Date	: Nov. 22, 2012	Humidity	: 68 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	0.11	53.22	53.33	65.99	-12.66	QP	P
2	0.1500	0.11	35.48	35.59	55.99	-20.40	AVG	P
3	0.1580	0.11	50.81	50.92	65.56	-14.64	QP	P
4	0.1580	0.11	41.87	41.98	55.56	-13.58	AVG	P
5	0.1860	0.12	53.78	53.90	64.21	-10.31	QP	P
6	0.1860	0.12	43.13	43.25	54.21	-10.96	AVG	P
7	0.2060	0.12	55.69	55.81	63.36	-7.55	QP	P
8	0.2060	0.12	46.87	46.99	53.36	-6.37	AVG	P
9	0.2340	0.12	53.87	53.99	62.30	-8.31	QP	P
10	0.2340	0.12	46.34	46.46	52.30	-5.84	AVG	P
11	0.2500	0.12	49.74	49.86	61.75	-11.89	QP	P
12	0.2500	0.12	34.29	34.41	51.75	-17.34	AVG	P
13	0.2660	0.12	49.44	49.56	61.24	-11.68	QP	P
14	0.2660	0.12	40.14	40.26	51.24	-10.98	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
15	0.2940	0.12	42.79	42.91	60.41	-17.50	QP	P
16	0.2940	0.12	30.51	30.63	50.41	-19.78	AVG	P
17	0.9780	0.20	38.44	38.64	56.00	-17.36	QP	P
18	0.9780	0.20	25.91	26.11	46.00	-19.89	AVG	P
19	3.4060	0.36	38.96	39.32	56.00	-16.68	QP	P
20	3.4060	0.36	30.16	30.52	46.00	-15.48	AVG	P
21	4.0580	0.38	42.59	42.97	56.00	-13.03	QP	P
22	4.0580	0.38	33.68	34.06	46.00	-11.94	AVG	P
23	4.5220	0.40	44.01	44.41	56.00	-11.59	QP	P
24	4.5220	0.40	35.30	35.70	46.00	-10.30	AVG	P
25	4.8420	0.42	45.13	45.55	56.00	-10.45	QP	P
26	4.8420	0.42	35.86	36.28	46.00	-9.72	AVG	P
27	5.2740	0.44	45.07	45.51	60.00	-14.49	QP	P
28	5.2740	0.44	36.28	36.72	50.00	-13.28	AVG	P
29	5.5100	0.45	45.76	46.21	60.00	-13.79	QP	P
30	5.5100	0.45	36.39	36.84	50.00	-13.16	AVG	P
31	5.9420	0.46	45.68	46.14	60.00	-13.86	QP	P
32	5.9420	0.46	36.10	36.56	50.00	-13.44	AVG	P
33	6.4020	0.48	45.23	45.71	60.00	-14.29	QP	P
34	6.4020	0.48	36.03	36.51	50.00	-13.49	AVG	P
35	7.2860	0.51	43.15	43.66	60.00	-16.34	QP	P
36	7.2860	0.51	34.46	34.97	50.00	-15.03	AVG	P
37	12.7140	0.73	37.34	38.07	60.00	-21.93	QP	P
38	12.7140	0.73	28.62	29.35	50.00	-20.65	AVG	P
39	16.2260	0.87	42.10	42.97	60.00	-17.03	QP	P
40	16.2260	0.87	36.96	37.83	50.00	-12.17	AVG	P
41	27.1580	1.24	42.09	43.33	60.00	-16.67	QP	P
42	27.1580	1.24	35.60	36.84	50.00	-13.16	AVG	P

Note: Level = Reading + Factor

Margin = Level – Limit



5. Test of Radiated Emission

5.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


5.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.




5.3 Typical Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

5.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Bilog Antenna	Schaffner	CBL6112B	2840	2012/03/23	2013/03/22
Amplifier	Agilent	8447D	2944A10593	2012/03/21	2013/03/20
EMI Receiver	HP	8546A/ 85460A	3807A00454/ 3704A00386	2012/08/22	2013/08/21
Spectrum Analyzer	R&S	FSP40	100047	2012/03/01	2013/02/28
Horn Antenna	EMCO	3115	31589	2012/03/01	2013/02/28
Preamplifier	Agilent	8449B	3008A01954	2012/02/29	2013/02/28
Loop Antenna	EMCO	6507	40855	2012/02/29	2013/02/28




5.5 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

5.6 Test Result and Data (30MHz ~ 25GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11g, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	45.13	37.91	-1.24	36.67	40.00	-3.33	QP	100	360
2	51.45	45.24	-8.51	36.73	40.00	-3.27	QP	100	360
3	65.20	47.24	-11.84	35.40	40.00	-4.60	QP	100	360
4	85.55	44.32	-7.78	36.54	40.00	-3.46	QP	100	360
5	125.70	41.35	-5.38	35.97	43.50	-7.53	Peak	100	360
6	224.70	46.31	-6.76	39.55	46.00	-6.45	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11g, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	47.49	-4.99	42.50	46.00	-3.50	QP	100	0
2	560.40	32.12	7.05	39.17	46.00	-6.83	Peak	100	0
3	625.50	38.36	0.57	38.93	46.00	-7.07	Peak	100	0
4	749.40	37.22	5.06	42.28	46.00	-3.72	QP	100	0
5	853.00	31.60	9.53	41.13	46.00	-4.87	QP	100	0
6	942.60	31.40	11.30	42.70	46.00	-3.30	QP	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	36.88	35.79	-6.91	28.88	40.00	-11.12	Peak	100	360
2	47.88	45.36	-8.70	36.66	40.00	-3.34	QP	100	360
3	148.25	40.13	-14.69	25.44	43.50	-18.06	Peak	100	360
4	170.25	35.95	-11.29	24.66	43.50	-18.84	Peak	100	360
5	225.25	44.01	-15.00	29.01	46.00	-16.99	Peak	100	360
6	250.00	44.08	-13.52	30.56	46.00	-15.44	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	42.23	0.10	42.33	46.00	-3.67	QP	100	0
2	571.60	34.08	2.88	36.96	46.00	-9.04	Peak	100	0
3	625.50	38.21	4.23	42.44	46.00	-3.56	QP	100	0
4	749.40	39.31	2.67	41.98	46.00	-4.02	QP	100	0
5	840.40	31.00	8.52	39.52	46.00	-6.48	Peak	100	0
6	942.60	31.78	6.99	38.77	46.00	-7.23	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11b, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4624.38	47.62	5.61	53.23	74.00	-20.77	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4823.75	48.22	3.94	52.16	74.00	-21.84	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11b, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.95	46.57	6.59	53.16	74.00	-20.84	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4673.95	47.30	4.73	52.03	74.00	-21.97	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11b, CH11	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.10	46.51	7.16	53.67	74.00	-20.33	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b, CH11	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.18	47.71	5.15	52.86	74.00	-21.14	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11g, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.40	48.31	5.62	53.93	74.00	-20.07	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4623.05	48.40	3.93	52.33	74.00	-21.67	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11g, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.40	46.43	6.58	53.01	74.00	-20.99	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.28	47.34	4.72	52.06	74.00	-21.94	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11g, CH11	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4922.10	46.38	7.15	53.53	74.00	-20.47	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g, CH11	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4922.75	47.39	5.15	52.54	74.00	-21.46	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	45.13	37.31	-1.24	36.07	40.00	-3.93	QP	100	360
2	51.45	43.62	-8.51	35.11	40.00	-4.89	QP	100	360
3	63.00	46.54	-11.45	35.09	40.00	-4.91	QP	100	360
4	86.38	43.07	-7.93	35.14	40.00	-4.86	QP	100	360
5	125.70	42.12	-5.38	36.74	43.50	-6.76	Peak	100	360
6	220.30	41.31	-6.05	35.26	46.00	-10.74	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	47.93	-4.99	42.94	46.00	-3.06	QP	100	0
2	567.40	32.25	7.11	39.36	46.00	-6.64	Peak	100	0
3	594.00	34.45	3.62	38.07	46.00	-7.93	Peak	100	0
4	625.50	38.43	0.57	39.00	46.00	-7.00	Peak	100	0
5	749.40	37.82	5.06	42.88	46.00	-3.12	QP	100	0
6	942.60	31.26	11.30	42.56	46.00	-3.44	QP	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	38.80	36.26	-7.23	29.03	40.00	-10.97	Peak	100	360
2	47.88	45.02	-8.70	36.32	40.00	-3.68	QP	100	360
3	148.25	39.62	-14.69	24.93	43.50	-18.57	Peak	100	360
4	170.80	36.46	-12.06	24.40	43.50	-19.10	Peak	100	360
5	222.50	43.82	-15.35	28.47	46.00	-17.53	Peak	100	360
6	250.00	43.90	-13.52	30.38	46.00	-15.62	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	42.24	0.10	42.34	46.00	-3.66	QP	100	0
2	594.00	34.60	3.19	37.79	46.00	-8.21	Peak	100	0
3	624.80	36.63	4.29	40.92	46.00	-5.08	QP	100	0
4	749.40	38.93	2.67	41.60	46.00	-4.40	QP	100	0
5	834.80	30.12	8.91	39.03	46.00	-6.97	Peak	100	0
6	954.50	32.45	7.49	39.94	46.00	-6.06	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.10	47.55	5.61	53.16	74.00	-20.84	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT20, CH1	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4822.80	48.51	3.93	52.44	74.00	-21.56	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT20, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.70	46.69	6.60	53.29	74.00	-20.71	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT20, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4875.45	47.86	4.76	52.62	74.00	-21.38	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT20, CH11	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.80	46.67	7.16	53.83	74.00	-20.17	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47,93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT20, CH11	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.38	47.71	5.15	52.86	74.00	-21.14	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	45.95	39.10	-2.20	36.90	40.00	-3.10	QP	100	360
2	50.63	43.16	-7.58	35.58	40.00	-4.42	QP	100	360
3	63.00	47.11	-11.45	35.66	40.00	-4.34	QP	100	360
4	86.38	42.06	-7.93	34.13	40.00	-5.87	QP	100	360
5	124.88	41.62	-4.91	36.71	43.50	-6.79	Peak	100	360
6	219.75	40.17	-6.04	34.13	46.00	-11.87	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	47.93	-4.99	42.94	46.00	-3.06	QP	100	0
2	555.50	31.46	7.64	39.10	46.00	-6.90	Peak	100	0
3	625.50	38.39	0.57	38.96	46.00	-7.04	Peak	100	0
4	750.10	37.29	5.11	42.40	46.00	-3.60	QP	100	0
5	853.00	31.35	9.53	40.88	46.00	-5.12	QP	100	0
6	945.40	30.80	11.40	42.20	46.00	-3.80	QP	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read	Factor	Result	Limit	Margin	Remark	Ant	Tab
	MHz	Value						Pos	Pos
		dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	36.88	33.65	-6.91	26.74	40.00	-13.26	Peak	100	360
2	47.88	44.96	-8.70	36.26	40.00	-3.74	QP	100	360
3	148.25	38.64	-14.69	23.95	43.50	-19.55	Peak	100	360
4	170.25	34.82	-11.29	23.53	43.50	-19.97	Peak	100	360
5	226.63	44.10	-14.97	29.13	46.00	-16.87	Peak	100	360
6	250.00	44.35	-13.52	30.83	46.00	-15.17	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	42.45	0.10	42.55	46.00	-3.45	QP	100	0
2	553.40	33.64	3.62	37.26	46.00	-8.74	Peak	100	0
3	625.50	38.49	4.23	42.72	46.00	-3.28	QP	100	0
4	749.40	39.81	2.67	42.48	46.00	-3.52	QP	100	0
5	830.60	31.46	8.59	40.05	46.00	-5.95	QP	100	0
6	942.60	31.86	6.99	38.85	46.00	-7.15	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4844.25	47.53	6.01	53.54	74.00	-20.46	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT40, CH3	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4844.83	48.33	4.27	52.60	74.00	-21.40	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT40, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.03	47.29	6.59	53.88	74.00	-20.12	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT40, CH6	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.10	47.47	4.73	52.20	74.00	-21.80	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT40, CH9	Temperature	: 22 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4904.80	46.53	7.12	53.65	74.00	-20.35	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11n HT40, CH9	Temperature	: 22 °C
Memo	:	Humidity	: 65 %



Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4904.18	47.49	5.15	52.64	74.00	-21.36	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz (detector sample mode) for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured. (The worst case noise floor measurements value is 47.93 dBuV at 16.10GHz)
7. The data is worse case.



6. 6dB Bandwidth Measurement Data


6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and VBW $\geq 3 \times$ RBW.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

6.3 Test Setup Layout



6.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2012/03/01	2013/02/28

6.5 Test Result and Data

Test Date: Dec. 07, 2012

Temperature: 22°C


Atmospheric pressure: 1020 hPa

Humidity: 65%


Modulation Standard	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	
			ANT R	ANT L
802.11b (11Mbps)	01	2412	11.6	11.3
	06	2437	11.6	11.6
	11	2462	11.6	11.6
802.11g (54Mbps)	01	2412	16.4	16.5
	06	2437	16.4	16.3
	11	2462	16.3	16.4
802.11n HT20 (130Mbps)	01	2412	16.8	16.7
	06	2437	16.7	16.7
	11	2462	16.7	17.6
802.11n HT40 (270Mbps)	03	2422	36.0	36.2
	06	2437	36.0	36.0
	09	2452	35.6	35.6



Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 01




Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 06






Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 11




Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 01






Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 06




Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 06




Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 09






Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 01




Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 06






Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 11




Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 01






Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 06




Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 06



Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 09





7. Maximum Peak and Average Output Power


7.1 Test Limit

The Maximum Peak Output Power Measurement is 25.99dBm.

7.2 Test Procedures

- The transmitter output was connected to the power meter.
- The maximum peak and average output power was measured and recorded.

7.3 Test Setup Layout



7.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
SERIES POWER METER	Anritsu	ML2495A	1224005	2012/06/22	2013/06/21
POWER SENSOR	Anritsu	MA2411B	1207295	2012/07/09	2013/07/08



7.5 Test Result and Data

Test Date: Dec. 07, 2012

Temperature: 22°C

Atmospheric pressure: 1020 hPa

Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)			Peak Power Output (mW)
			ANT R	ANT L	R+L	ANT R+L
802.11b (11Mbps)	01	2412	15.68	15.32	18.51	71.02
	06	2437	16.21	15.52	18.89	77.43
	11	2462	15.57	15.10	18.35	68.42
802.11g (54Mbps)	01	2412	17.95	18.84	21.43	138.93
	06	2437	17.10	18.41	20.81	120.63
	11	2462	16.28	17.60	20.00	100.01

Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)			Peak Power Output (mW)
			ANT R	ANT L	R+L	R+L
802.11n HT20 (130Mbps)	01	2412	15.85	17.19	19.58	90.82
	06	2437	16.08	17.46	19.83	96.27
	11	2462	15.75	17.25	19.57	90.67
802.11n HT40 (270Mbps)	03	2422	12.26	13.84	16.13	41.04
	06	2437	15.84	17.45	19.73	93.96
	09	2452	15.68	17.60	19.76	94.53



Test Date: Dec. 07, 2012

Temperature: 22°C

Atmospheric pressure: 1020 hPa

Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	Average Power Output (dBm)			Average Power Output (mW)
			ANT R	ANT L	R+L	ANT R+L
802.11b (11Mbps)	01	2412	13.41	13.16	16.30	42.63
	06	2437	14.35	13.37	16.90	48.95
	11	2462	13.92	12.90	16.45	44.16
802.11g (54Mbps)	01	2412	8.68	9.47	12.10	16.23
	06	2437	8.21	8.51	11.37	13.72
	11	2462	7.93	7.90	10.93	12.37

Modulation Standard	Channel	Frequency (MHz)	Average Power Output (dBm)			Average Power Output (mW)
			ANT R	ANT L	R+L	R+L
802.11n HT20 (130Mbps)	01	2412	6.68	8.25	10.55	11.34
	06	2437	7.46	8.60	11.08	12.82
	11	2462	7.65	8.11	10.90	12.29
802.11n HT40 (270Mbps)	03	2422	3.19	4.93	7.16	5.20
	06	2437	7.31	8.74	11.09	12.86
	09	2452	7.33	8.75	11.11	12.91



8. Power Spectral Density


8.1 Test Limit

The Maximum of Power Spectral Density Measurement is 3.99dBm.

8.2 Test Procedures

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 100KHz RBW and 300KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- The power spectral density was measured and recorded.

8.3 Test Setup Layout



8.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2012/03/01	2013/02/28

8.5 Test Result and Data

Test Date: Dec. 07, 2012

Temperature: 25°C

Atmospheric pressure: 1020 hPa


Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)	
			ANT R	ANT L
802.11b (11Mbps)	01	2412	-2.67	-2.17
	06	2437	-4.14	-4.13
	11	2462	-6.60	-5.50
802.11g (54Mbps)	01	2412	-12.71	-12.00
	06	2437	-13.94	-14.04
	11	2462	-14.38	-15.11


Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)		
			ANT R	ANT L	ANT R+L
802.11n HT20 (130Mbps)	01	2412	-14.10	-14.23	-11.15
	06	2437	-14.54	-15.14	-11.82
	11	2462	-14.59	-15.94	-12.20
802.11n HT40 (270Mbps)	03	2422	-14.10	-16.57	-12.15
	06	2437	-14.72	-17.76	-12.97
	09	2452	-14.80	-17.01	-12.76



Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 01




Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 06






Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 11




Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 01






Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 06




Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 06




Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 09






Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 01




Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 06






Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 11




Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 01






Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 06




Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 06



Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 09





9. Band Edges Measurement


9.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

9.2 Test Procedure

- The transmitter output was connected to the spectrum analyzer via a low lose cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

9.3 Test Setup Layout



9.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2012/03/01	2013/02/28

9.5 Test Result and Data

Test Date: Dec. 07, 2012

Temperature: 22°C



Atmospheric pressure: 1020 hPa

Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	maximum value in frequency (MHz)		maximum value (dBm)	
			ANT R	ANT L	ANT R	ANT L
802.11b (11Mbps)	01	2412	2397.20	2398.00	-35.41	-33.99
	11	2462	2487.10	2498.50	-43.22	-45.54
802.11g (54Mbps)	01	2412	2399.60	2400.00	-40.51	-40.02
	11	2462	2484.30	2509.90	-45.48	-46.08
802.11n HT20 (130Mbps)	01	2412	2399.80	2400.00	-41.59	-40.67
	11	2462	2483.90	2502.90	-45.52	-46.01
802.11n HT40 (270Mbps)	03	2422	2394.20	2399.20	-45.22	-44.25
	09	2452	2486.90	2485.30	-42.46	-43.37





Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 01







Modulation Standard: 802.11b (11Mbps), ANT R
Channel: 11







Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 01







Modulation Standard: 802.11g (54Mbps), ANT R
Channel: 11







Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 01







Modulation Standard: 802.11n HT20 (130Mbps), ANT R
Channel: 11







Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 03







Modulation Standard: 802.11n HT40 (270Mbps), ANT R
Channel: 09







Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 01







Modulation Standard: 802.11b (11Mbps), ANT L
Channel: 11







Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 01







Modulation Standard: 802.11g (54Mbps), ANT L
Channel: 11







Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 01







Modulation Standard: 802.11n HT20 (130Mbps), ANT L
Channel: 11







Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 03





Modulation Standard: 802.11n HT40 (270Mbps), ANT L
Channel: 09





9.6 Restrict Band Emission Measurement Data

Test Date: Dec. 10, 2012

Temperature: 22 °C

Atmospheric pressure: 1020 hPa

Humidity: 65 %

Modulation Standard: IEEE 802.11b (11Mbps)

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2362.84	H	49.79	1.73	51.52	Peak	74	54	-22.58	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2387.32	V	61.85	2.28	64.13	Peak	74	54	-9.87	188	1.00
2387.52	V	50.70	2.29	52.99	Ave	74	54	-1.01	188	1.00
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2494.87	H	50.49	0.13	50.62	Peak	74	54	-23.38	360	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2483.66	V	64.49	-2.36	62.13	Peak	74	54	-11.87	108	1.00
2486.99	V	51.89	-2.54	49.35	Ave	74	54	-4.65	108	1.00

Modulation Standard: IEEE 802.11g (54Mbps)

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2353.35	H	49.72	1.76	51.48	Peak	74	54	-22.52	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2389.76	V	63.47	2.25	65.72	Peak	74	54	-8.28	190	1.00
2389.82	V	49.27	2.25	51.52	Ave	74	54	-2.48	190	1.00
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2489.36	H	49.90	0.22	50.12	Peak	74	54	-23.88	360	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2483.66	V	66.46	-2.36	64.10	Peak	74	54	-9.90	115	1.00
2483.57	V	50.64	-2.35	48.29	Ave	74	54	-5.71	115	1.00



Modulation Standard: IEEE 802.11n HT20 (130Mbps)

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2362.02	H	49.72	1.73	51.45	Peak	74	54	-22.55	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2389.76	V	63.91	2.25	66.16	Peak	74	54	-7.84	258	1.00
2389.82	V	50.58	2.25	52.83	Ave	74	54	-1.17	258	1.00
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2494.60	H	50.24	0.13	50.37	Peak	74	54	-23.63	360	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2483.96	V	66.73	-2.38	64.35	Peak	74	54	-9.65	114	1.00
2483.57	V	50.13	-2.35	47.78	Ave	74	54	-6.22	114	1.00

Modulation Standard: IEEE 802.11n HT40 (270Mbps)

Channel 3						Fundamental Frequency: 2422 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2353.86	H	51.51	1.76	53.27	Peak	74	54	-20.73	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2389.76	V	62.26	2.25	64.51	Peak	74	54	-9.49	208	1.00
2389.82	V	50.59	2.25	52.84	Ave	74	54	-1.16	229	1.00
Channel 9						Fundamental Frequency: 2452 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2484.04	H	51.19	0.29	51.48	Peak	74	54	-22.52	360	1.00
---	H	---	---	---	Ave	74	54	---	---	---
2484.72	V	68.93	-2.41	66.52	Peak	74	54	-7.48	227	1.00
2484.80	V	54.85	-2.41	52.44	Ave	74	54	-1.56	227	1.00

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3 MHz (detector peak mode) for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3 MHz (detector sample mode) for Average detection at frequency above 1GHz.



10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.