



Inter**Lab**[®]

FCC Measurement/Technical Report on

Bluetooth transceivers

MKi9000 - eBox4R2

MKi9100 - eBox4R2

MKi9200 - eBox4R2

Report Reference: MDE_Parro_0907_FCCa

Test Laboratory:

7 layers AG
Borsigstrasse 11
40880 Ratingen
Germany
email: info@7Layers.de



Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the testing laboratory.

7 layers AG
Borsigstrasse 11
40880 Ratingen, Germany
Phone: +49 (0) 2102 749 0
Fax: +49 (0) 2102 749 350
www.7Layers.com

Aufsichtsratsvorsitzender •
Chairman of the Supervisory Board:
Markus Becker
Vorstand • Board:
Dr. Hermann Buitkamp
Wilfried Klassmann

Registergericht • registered in:
Düsseldorf, HRB 44096
USt-IdNr • VAT No.:
DE 203159652
TAX No. 147/5869/0385



Table of Contents

0 Summary	3
0.1 Technical Report Summary	3
0.2 Measurement Summary	4
1 Administrative Data	7
1.1 Testing Laboratory	7
1.2 Project Data	7
1.3 Applicant Data	7
1.4 Manufacturer Data	7
2 Test object Data	8
2.1 General EUT Description	8
2.2 EUT Main components	9
2.3 Ancillary Equipment	9
2.4 EUT Setups	9
2.5 Operating Modes	10
2.6 Product labelling	10
3 Test Results	11
3.1 Occupied bandwidth	11
3.2 Peak power output	14
3.3 Spurious RF conducted emissions	17
3.4 Spurious radiated emissions	20
3.5 Band edge compliance	27
3.6 Dwell time	31
3.7 Channel separation	33
3.8 Number of hopping frequencies	35
4 Test Equipment	36
5 Photo Report	42
6 Setup Drawings	48
7 Annex measurement plots	49
7.1 Occupied bandwidth	49
7.2 Peak power output	58
7.3 Band edge compliance conducted and Spurious RF conducted emissions	67
7.4 Band edge compliance radiated	85
7.5 Radiated emissions (f < 30 MHz)	88
7.6 Dwell time	90
7.7 Channel separation	91
7.8 Number of hopping frequencies	92



0 Summary

0.1 Technical Report Summary

Type of Authorization

Certification for an Intentional Radiator (Frequency Hopping Spread Spectrum).

Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 (10-1-08 Edition) and 15 (10-1-08 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

Note:

The tests were selected and performed with reference to the FCC Public Notice DA 00-705, released March 30, 2000.

Instead of applying ANSI C63.4-1992 which is referenced in the FCC Public Note, the newer ANSI C63.4-2003 is applied.

Summary Test Results:

The EUT complied with all performed tests as listed in chapter 0.2 Measurement Summary.



0.2 Measurement Summary

FCC Part 15, Subpart C		§ 15.207	
Conducted emissions (AC power line)			
OP-Mode	Setup	Port	2003
		AC Port (power line)	Final Result
			N/A
FCC Part 15, Subpart C		§ 15.247 (a) (1)	
Occupied bandwidth			
The measurement was performed according to FCC § 15.31		10-1-08	
OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_d01	Temp ant.connector	passed
op-mode 2	Setup_d01	Temp ant.connector	passed
op-mode 3	Setup_d01	Temp ant.connector	passed
op-mode 6	Setup_d01	Temp ant.connector	passed
op-mode 7	Setup_d01	Temp ant.connector	passed
op-mode 8	Setup_d01	Temp ant.connector	passed
op-mode 10	Setup_d01	Temp ant.connector	passed
op-mode 11	Setup_d01	Temp ant.connector	passed
op-mode 12	Setup_d01	Temp ant.connector	passed
FCC Part 15, Subpart C		§ 15.247 (b) (1)	
Peak power output			
The measurement was performed according to FCC § 15.31		10-1-08	
OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_d01	Temp ant.connector	passed
op-mode 2	Setup_d01	Temp ant.connector	passed
op-mode 3	Setup_d01	Temp ant.connector	passed
op-mode 6	Setup_d01	Temp ant.connector	passed
op-mode 7	Setup_d01	Temp ant.connector	passed
op-mode 8	Setup_d01	Temp ant.connector	passed
op-mode 10	Setup_d01	Temp ant.connector	passed
op-mode 11	Setup_d01	Temp ant.connector	passed
op-mode 12	Setup_d01	Temp ant.connector	passed
FCC Part 15, Subpart C		§ 15.247 (d)	
Spurious RF conducted emissions			
The measurement was performed according to FCC § 15.31		10-1-08	
OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_d01	Temp ant.connector	passed
op-mode 2	Setup_d01	Temp ant.connector	passed
op-mode 3	Setup_d01	Temp ant.connector	passed
op-mode 6	Setup_d01	Temp ant.connector	passed
op-mode 7	Setup_d01	Temp ant.connector	passed
op-mode 8	Setup_d01	Temp ant.connector	passed
op-mode 10	Setup_d01	Temp ant.connector	passed
op-mode 11	Setup_d01	Temp ant.connector	passed
op-mode 12	Setup_d01	Temp ant.connector	passed



FCC Part 15, Subpart C**§ 15.247 (d), § 15.35 (b), § 15.209**

Spurious radiated emissions

The measurement was performed according to ANSI C63.4

2003

OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_a01	Enclosure	passed
op-mode 2	Setup_a01	Enclosure	passed
op-mode 3	Setup_a01	Enclosure	passed
op-mode 1	Setup_b01	Enclosure	passed
op-mode 2	Setup_b01	Enclosure	passed
op-mode 3	Setup_b01	Enclosure	passed
op-mode 1	Setup_c01	Enclosure	passed
op-mode 2	Setup_c01	Enclosure	passed
op-mode 3	Setup_c01	Enclosure	passed
op-mode 6	Setup_c01	Enclosure	passed
op-mode 7	Setup_c01	Enclosure	passed
op-mode 8	Setup_c01	Enclosure	passed
op-mode 10	Setup_c01	Enclosure	passed
op-mode 11	Setup_c01	Enclosure	passed
op-mode 12	Setup_c01	Enclosure	passed

FCC Part 15, Subpart C**§ 15.247 (d)**

Band edge compliance

The measurement was performed according to FCC § 15.31
(10-1-08) / ANSI C63.4 (2003)

10-1-08 / 2003

OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_d01	Temp ant.connector	passed
op-mode 3	Setup_d01	Temp ant.connector	passed
op-mode 3	Setup_a01	Enclosure	passed
op-mode 6	Setup_d01	Temp ant.connector	passed
op-mode 8	Setup_d01	Temp ant.connector	passed
op-mode 8	Setup_a01	Enclosure	passed
op-mode 10	Setup_d01	Temp ant.connector	passed
op-mode 12	Setup_d01	Temp ant.connector	passed
op-mode 12	Setup_a01	Enclosure	passed

**FCC Part 15, Subpart C****§ 15.247 (a) (1) (iii)****Dwell time**

The measurement was performed according to FCC § 15.31	10-1-08
OP-Mode Setup Port Final Result op-mode 2 Setup_d01 Temp ant.connector passed	

FCC Part 15, Subpart C**§ 15.247 (a) (1)****Channel separation**

The measurement was performed according to FCC § 15.31	10-1-08
OP-Mode Setup Port Final Result op-mode 4 Setup_d01 Temp ant.connector passed	

FCC Part 15, Subpart C**§ 15.247 (a) (iii)****Number of hopping frequencies**

The measurement was performed according to FCC § 15.31	10-1-08
OP-Mode Setup Port Final Result op-mode 4 Setup_d01 Temp ant.connector passed	

N/A not applicable (the EUT is powered by DC)

The EUTs MKi9100 and MKi9200 are variants of the EUT MKi9000. The EUT MKi9200 was tested completely, for both other EUTs only some of the tests have been performed in order to demonstrate that the results of all EUTs are comparable.

For details please refer to the table above and to the complete documentation below.



7 layers AG, Borsigstr. 11
40880 Ratingen, Germany
Phone +49 (0)2102 749 0

Responsible for
Accreditation Scope:

Responsible
for Test Report:



1 Administrative Data

1.1 Testing Laboratory

Company Name: 7 Layers AG
Address: Borsigstr. 11
40880 Ratingen
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716.

The test facility is also accredited by the following accreditation organisation:
- Deutscher Akkreditierungs Rat DAR-Registration no. DAT-P-192/99-01

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka
Dipl.-Ing. Robert Machulec
Dipl.-Ing. Thomas Hoell
Dipl.-Ing. Andreas Petz

Report Template Version: 2009-07-27

1.2 Project Data

Responsible for testing and report: Dipl.-Ing. Carsten Steinröder
Date of Test(s): 2009-10-09 to 2009-10-29
Date of Report: 2009-11-20

1.3 Applicant Data

Company Name: Parrot SA
Address: 174 Quai de Jemmapes
75010 Paris
France
Contact Person: Mr. Ludovic Legeay

1.4 Manufacturer Data

Company Name: please see applicant data
Address:
Contact Person:



2 Test object Data

2.1 General EUT Description

Equipment under Test	Bluetooth transceiver
Type Designation:	MKi9000 - eBox4R2 MKi9100 - eBox4R2 MKi9200 - eBox4R2
Kind of Device: (optional)	Bluetooth Handsfree Carkit, Mobile Accessory
Voltage Type:	DC (vehicular battery)
Voltage level:	12 V
Modulation Type:	GFSK, 8DPSK, $\pi/4$ DQPSK

General product description:

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4 GHz. In the US a band of 83.5 MHz width is available. In this band, the Bluetooth technology defines 79 RF channels spaced 1 MHz (2402 - 2480 MHz). The actual RF channel is chosen from a pseudo-random hopping sequence through the 79 channels. A channel is occupied for a defined amount of time slots, with a nominal slot length of 625 μ s. The maximum time slot length on one channel is defined by the packet type and is 0.625 ms for DH1 packets, 1.875 ms for DH3 and 3.125 ms for DH5. The nominal hop rate is 1600 hops/s for DH1, 1600/3 for DH3 and 1600/5 for DH5. All frequencies are equally used. The maximum nominal average time of occupancy is 0.4 s within a period of 79*0.4 seconds.

The basic data rate of 1 Mbps uses GFSK modulation and the enhanced data rate uses PSK modulation. For the enhanced data rate of 3 Mbps 8DPSK modulation and of 2 Mbps $\pi/4$ DQPSK modulation is used.

Specific product description for the EUT:

The EUT is a handsfree car kit which uses Bluetooth technology to be connected to e.g. a mobile phone.

The EUT provides the following ports:

Ports
Enclosure
Display 1 port (for MKi 9200 only)
Display 2 port (for MKi 9100 only)
Microphone
DC Port (power line)
Audio input

The main components of the EUT are listed and described in Chapter 2.2.

2.2 EUT Main components

Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status	Date of Receipt
EUT A (Code: CX056a01)	Bluetooth transceiver	MKI9000 - eBox4R2	PI040195PV 9I000075	HW00	1.27 RC1	2009-10-09
Remark: EUT is equipped with an integral antenna (gain = 1.29 dBi).						
EUT B (Code: CX054b01)	Bluetooth transceiver	MKI9100 - eBox4R2	PI040195PV 9I000083	HW00	1.27 RC1	2009-10-09
Remark: EUT is equipped with an integral antenna (gain = 1.29 dBi).						
EUT C (Code: CX055c01)	Bluetooth transceiver	MKI9200 - eBox4R2	PI040195PV 9I000100	HW00	1.27 RC1	2009-10-09
Remark: EUT is equipped with an integral antenna (gain = 1.29 dBi).						
EUT D (Code: CX055d01)	Bluetooth transceiver	MKI9200 - eBox4R2	PI040195PV 9I000016	HW00	1.27 RC1	2009-10-09
Remark: EUT is equipped with a temporary antenna connector.						

NOTE: The short description is used to simplify the identification of the EUT in this test report.

2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
AE1	Display 1	–	–	–	–	–
AE2	Display 2	–	–	–	–	–
AE3	Microphone	–	–	–	–	–
AE4	Cable harness	–	–	–	–	–
AE5	Audio in	–	–	–	–	–

2.4 EUT Setups

This chapter describes the combination of EUTs and ancillary equipment used for testing.

Setup No.	Combination of EUTs	Description
Setup_a01	EUT A+AE3+AE4	setup for radiated measurements
Setup_b01	EUT B+AE2+AE3+AE4+AE5	setup for radiated measurements
Setup_c01	EUT C+AE1+AE3+AE4+AE5	setup for radiated measurements
Setup_d01	EUT D+AE4	setup for conducted measurements



2.5 Operating Modes

This chapter describes the operating modes of the EUTs used for testing.

Op. Mode	Description of Operating Modes	Remarks
op-mode 1	The EUT transmits on 2402 MHz	Loopback mode, basic data rate 1 Mbps
op-mode 2	The EUT transmits on 2441 MHz	Loopback mode, basic data rate 1 Mbps
op-mode 3	The EUT transmits on 2480 MHz	Loopback mode, basic data rate 1 Mbps
op-mode 4	The EUT is in Hopping mode	The EUT is hopping on 79 channels, basic data rate 1 Mbps
op-mode 6	The EUT transmits on 2402 MHz	Loopback mode, enhanced data rate 3 Mbps
op-mode 7	The EUT transmits on 2441 MHz	Loopback mode, enhanced data rate 3 Mbps
op-mode 8	The EUT transmits on 2480 MHz	Loopback mode, enhanced data rate 3 Mbps
op-mode 10	The EUT transmits on 2402 MHz	Loopback mode, enhanced data rate, 2 Mbps
op-mode 11	The EUT transmits on 2441 MHz	Loopback mode, enhanced data rate, 2 Mbps
op-mode 12	The EUT transmits on 2480 MHz	Loopback mode, enhanced data rate, 2 Mbps

2.6 Product labelling

2.6.1 FCC ID label

Please refer to the documentation of the applicant.

2.6.2 Location of the label on the EUT

Please refer to the documentation of the applicant.

3 Test Results

3.1 Occupied bandwidth

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: FCC §15.31, 10-1-08

3.1.1 Test Description

The Equipment Under Test (EUT) was setup to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.

The results recorded were measured with the modulation which produces the worst-case (widest) occupied bandwidth. The resolution bandwidth for measuring the reference level and the occupied bandwidth was 30 kHz.

The EUT was connected to the spectrum analyzer via a short coax cable.

3.1.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Implication by the test laboratory:

Since the Bluetooth technology defines a fixed channel separation of 1 MHz this design parameter defines the maximum allowed occupied bandwidth depending on the EUT's output power:

1. Under the provision that the systems operates with an output power no greater than 125 mW (21.0 dBm):
Implicit Limit: $\text{Max. } 20 \text{ dB BW} = 1.0 \text{ MHz} / 2/3 = 1.5 \text{ MHz}$
2. If the systems output power exceeds 125 mW (21.0 dBm):
Implicit Limit: $\text{Max. } 20 \text{ dB BW} = 1.0 \text{ MHz}$

Used conversion factor: Output power (dBm) = $10 \log (\text{Output power (W)} / 1\text{mW})$

The measured output power of the system is below 125 mW (21.0 dBm).

For the results, please refer to the related chapter of this report.
Therefore the limit is determined as 1.5 MHz.



3.1.3 Test Protocol

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port
op-mode 1	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
0.890	—

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 2	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
0.890	—

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
0.890	—

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 6	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.258	—

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 7	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.254	—

Remark: Please see annex for the measurement plot.



Op. Mode	Setup	Port
op-mode 8	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.254	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 10	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.262	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 11	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.266	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_d01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.262	-

Remark: Please see annex for the measurement plot.

3.1.4 Test result: Occupied bandwidth

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed
	op-mode 6	passed
	op-mode 7	passed
	op-mode 8	passed
	op-mode 10	passed
	op-mode 11	passed
	op-mode 12	passed



3.2 Peak power output

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: FCC §15.31, 10-1-08

3.2.1 Test Description

The Equipment Under Test (EUT) was set up to perform the output power measurements. The resolution bandwidth for measuring the output power was set to 3 MHz. The reference level of the spectrum analyzer was set higher than the output power of the EUT. The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

3.2.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (b) (1)

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)
==> Maximum Output Power: 30 dBm



3.2.3 Test Protocol

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port
op-mode 1	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
0.10	The EIRP including antenna gain (1.29 dBi) is 1.39 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 2	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
1.80	The EIRP including antenna gain (1.29 dBi) is 3.09dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
1.75	The EIRP including antenna gain (1.29 dBi) is 3.04 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 6	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
0.30	The EIRP including antenna gain (1.29 dBi) is 1.59 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 7	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
2.01	The EIRP including antenna gain (1.29 dBi) is 3.30 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 8	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
1.73	The EIRP including antenna gain (1.29 dBi) is 3.02 dBm

Remark: Please see annex for the measurement plot.



Op. Mode	Setup	Port
op-mode 10	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
-0.07	The EIRP including antenna gain (1.29 dBi) is 1.22 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 11	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
1.60	The EIRP including antenna gain (1.29 dBi) is 2.89 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_d01	Temp.ant.connector

Output power dBm	Remarks
1.26	The EIRP including antenna gain (1.29 dBi) is 2.55 dBm

Remark: Please see annex for the measurement plot.

3.2.4 Test result: Peak power output

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed
	op-mode 6	passed
	op-mode 7	passed
	op-mode 8	passed
	op-mode 10	passed
	op-mode 11	passed
	op-mode 12	passed



3.3 Spurious RF conducted emissions

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: FCC §15.31, 10-1-08

3.3.1 Test Description

The Equipment Under Test (EUT) was set up to perform the spurious emissions measurements.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Detector: Peak-Maxhold
- Frequency range: 30 – 25000 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Sweep Time: 330 s

The reference value for the measurement of the spurious RF conducted emissions is determined during the test "band edge compliance" (cf. chapter 3.5). This value is used to calculate the 20 dBc limit.

3.3.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (c)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.



3.3.3 Test Protocol

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port		
op-mode 1	Setup_d01	Temp ant.connector		
Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	0.37	-19.63	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 2	Setup_d01	Temp ant.connector		
Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	1.95	-18.06	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 3	Setup_d01	Temp ant.connector		
Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	1.81	-18.19	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 6	Setup_d01	Temp ant.connector		
Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	-2.45	-22.45	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 7	Setup_d01	Temp ant.connector		
Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	-0.88	-20.88	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.



Op. Mode	Setup	Port
op-mode 8	Setup_d01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	-0.89	-20.89	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 10	Setup_d01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	-2.39	-22.39	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 11	Setup_d01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	-0.80	-20.80	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_d01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	-	-0.85	-20.85	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
Please see annex for the measurement plot.

3.3.4 Test result: Spurious RF conducted emissions

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed
	op-mode 6	passed
	op-mode 7	passed
	op-mode 8	passed
	op-mode 10	passed
	op-mode 11	passed
	op-mode 12	passed

3.4 Spurious radiated emissions

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: ANSI C 63.4, 2003

3.4.1 Test Description

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003. The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The radiated emissions measurements were made in a typical installation configuration. The measurement procedure is implemented into the EMI test software ES-K1 from R&S.

1. Measurement up to 30 MHz

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003. The Equipment Under Test (EUT) was set up on a non-conductive table in the anechoic chamber.

The radiated emissions measurements were made in a typical installation configuration. The measurement procedure is implemented into the EMI test software ES-K1 from R&S. The Loop antenna HFH2-Z2 is used.

Step 1: pre-measurement

- Anechoic chamber
- Antenna distance: 10 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 - 0.15 and 0.15 – 30 MHz
- Frequency steps: 0.1 kHz and 5 kHz
- IF-Bandwidth: 0.2 kHz and 10 kHz
- Measuring time / Frequency step: 100 ms

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 – 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 200 Hz - 10 kHz
- Measuring time / Frequency step: 100 ms

2. Measurement above 30 MHz and up to 1 GHz

Step 1: Preliminary scan

Preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Detector: Peak-Maxhold
- Frequency range: 30 – 1000 MHz
- Frequency steps: 60 kHz
- IF-Bandwidth: 120 kHz

- Measuring time / Frequency step: 100 µs (BT Timing 1.25 ms)
- Turntable angle range: -180 to 180°
- Turntable step size: 90°
- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: second measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is, to find out the approximate turntable angle and antenna height for each frequency.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: -180 to 180°
- Turntable step size: 45°
- Height variation range: 1 – 4 m
- Height variation step size: 0.5 m
- Polarisation: horizontal + vertical

After this step the EMI test system has determined the following values for each frequency (of step 1):

- Frequency
- Azimuth value (of turntable)
- Antenna height

The last two values have now the following accuracy:

- Azimuth value (of turntable): 45°
- Antenna height: 0.5 m

Step 3: final measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will be slowly varied by +/- 22.5° around this value. During this action the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position the antenna height is also slowly varied by +/- 25 cm around the antenna height determined. During this action the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: -22.5° to + 22.5 ° around the determined value
- Height variation range: -0.25 m to + 0.25 m around the determined value

Step 4: final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed:

EMI receiver settings for step 4:

- Detector: Quasi-Peak (< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s



3. Measurement above 1 GHz

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:

The measurement distance was reduced to 1 m. The results were extrapolated by the extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements, inverse linear-distance squared for the power reference level measurements). Due to the fact that in this frequency range a double ridged wave guided horn antenna (up to 18 GHz) and a horn antenna (18-25 GHz) are used, the steps 2-4 are omitted. Step 1 was performed with one height of the receiving antenna only.

EMI receiver settings:

- Detector: Peak, Average
- RBW = VBW = 100 kHz

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

For the enhanced data rate packets the test is performed as worst-case-check in order to verify that emissions have a comparable level as found at basic data rate. Typically, the measurement for these packets is performed in the frequency range 1 to 8 GHz but it depends on the emissions found during the test for the basic data rate. Please refer to the results for the used frequency range.

3.4.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (μ V/m)	Measurement distance (m)	Limit(dB μ V/m @10m)
0.009 – 0.49	2400/F(kHz)	300	Limit (dB μ V/m) +30dB
0.49 – 1.705	24000/F(kHz)	30	Limit (dB μ V/m) +10dB
1.705 - 30	30	30	Limit (dB μ V/m) +10dB

Frequency in MHz	Limit (μ V/m)	Measurement distance (m)	Limit (dB μ V/m)
30 - 88	100	3	40.0
88 - 216	150	3	43.5
216 - 960	200	3	46.0
above 960	500	3	54.0

§15.35(b)

..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dB μ V/m) = 20 log (Limit (μ V/m)/1 μ V/m)

3.4.3 Test Protocol

Temperature: 25 °C
 Air Pressure: 1002 hPa
 Humidity: 31 %

3.4.3.1 Measurement up to 30 MHz

Op. Mode	Setup	Port								
op-mode 1	Setup_c01	Enclosure								
Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB	
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV	
0°	-	-	-	-	-	-	-	-	-	-
90°	-	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found therefore step 2 was not performed. The found peak at 91.2 kHz is emission from loop antenna power supply.

3.4.3.2 Measurement above 30 MHz

Op. Mode	Setup	Port								
op-mode 1	Setup_a01	Enclosure								
Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB	
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV	
Vertical + horizontal	-	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. The measurement was performed from 1 GHz up to 8 GHz.

Op. Mode	Setup	Port								
op-mode 2	Setup_a01	Enclosure								
Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB	
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV	
Vertical + horizontal	-	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. The measurement was performed from 1 GHz up to 8 GHz.

Op. Mode	Setup	Port								
op-mode 3	Setup_a01	Enclosure								
Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB	
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV	
Vertical + horizontal	-	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. The measurement was performed from 1 GHz up to 8 GHz.

Op. Mode	Setup	Port
op-mode 1	Setup_b01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. The measurement was performed from 1 GHz up to 8 GHz.

Op. Mode	Setup	Port
op-mode 2	Setup_b01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. The measurement was performed from 1 GHz up to 8 GHz.

Op. Mode	Setup	Port
op-mode 3	Setup_b01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. The measurement was performed from 1 GHz up to 8 GHz.

Op. Mode	Setup	Port
op-mode 1	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

Op. Mode	Setup	Port
op-mode 2	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

Op. Mode	Setup	Port
op-mode 3	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

Op. Mode	Setup	Port
op-mode 6	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 18 GHz because no significant spurious emissions were found outside this range this frequency in op-mode 1, 2 and 3.

Op. Mode	Setup	Port
op-mode 7	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 18 GHz because no significant spurious emissions were found outside this range this frequency in op-mode 1, 2 and 3.

Op. Mode	Setup	Port
op-mode 8	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 18 GHz because no significant spurious emissions were found outside this range this frequency in op-mode 1, 2 and 3.



Op. Mode	Setup	Port
op-mode 10	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
 The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this range this frequency in op-mode 1, 2 and 3.

Op. Mode	Setup	Port
op-mode 11	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
 The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this range this frequency in op-mode 1, 2 and 3.

Op. Mode	Setup	Port
op-mode 12	Setup_c01	Enclosure

Polarisation	Frequency MHz	Corrected value dB μ V/m			Limit dB μ V/m	Limit dB μ V/m	Limit dB μ V/m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.
 The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this range this frequency in op-mode 1, 2 and 3.

3.4.4 Test result: Spurious radiated emissions

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed
	op-mode 6	passed
	op-mode 7	passed
	op-mode 8	passed
	op-mode 10	passed
	op-mode 11	passed
	op-mode 12	passed



3.5 Band edge compliance

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: ANSI C 63.4, 2003
FCC §15.31, 10-1-08

3.5.1 Test Description

The procedure to show compliance with the band edge requirement is divided into two measurements: 1. Show compliance of the lower band edge by a conducted measurement and 2. show compliance of the higher band edge by a radiated and conducted measurement.

For the first measurement the EUT is set to transmit on the lowest channel (2402 MHz). The lower band edge is 2400 MHz.

Analyzer settings:

- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz

For the second measurement the EUT is set to transmit on the highest channel (2480 MHz). The higher band edge is 2483.5 MHz.

Analyzer settings for conducted measurement:

- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz

Analyzer settings for radiated measurement:

- Detector: Peak, Average
- RBW = VBW = 100 kHz

3.5.2 Test Requirements / Limits

FCC Part 15.247 (d)

"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

...

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the measurement of the **lower band edge** the RF power at the band edge shall be "at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power..."

For the measurement of the **higher band edge** the limit is "specified in Section 15.209(a)".

3.5.3 Test Protocol

3.5.3.1 Lower band edge

Conducted measurement

Temperature: 24 °C
 Air Pressure: 1011 hPa
 Humidity: 38 %

Op. Mode	Setup	Port		
op-mode 1	Setup_d01	Temp ant.connector		
Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Delta to limit dB
2400.00	-57.76	0.37	-19.63	38.13

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 6	Setup_d01	Temp ant.connector		
Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Delta to limit dB
2400.00	-54.18	-2.45	-22.45	31.73

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 10	Setup_d01	Temp ant.connector		
Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Delta to limit dB
2400.00	-54.78	-2.39	-22.39	32.39

Remark: Please see annex for the measurement plot.



3.5.3.2 Higher band edge

Conducted measurement

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port		
op-mode 3	Setup_d01	Temp ant.connector		
Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Delta to limit dB
2483.50	-62.98	1.81	-18.19	44.79

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 8	Setup_d01	Temp ant.connector		
Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Delta to limit dB
2483.50	-60.79	-0.89	-20.89	39.90

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port		
op-mode 12	Setup_d01	Temp ant.connector		
Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Delta to limit dB
2483.50	-63.18	-0.85	-20.85	42.33

Remark: Please see annex for the measurement plot.



Radiated measurement

Temperature: 25 °C
Air Pressure: 1002 hPa
Humidity: 31 %

Op. Mode	Setup	Port
op-mode 3	Setup_a01	Enclosure

Frequency MHz	Polarisation	Corrected value dB μ V/m		Limit Peak dB μ V/m	Limit AV dB μ V/m	Delta to Peak limit/dB	Delta to AV limit dB
		Peak	AV				
2483.50	Vertical + horizontal	48.96	37.23	74.00	54.00	25.04	16.77

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 8	Setup_a01	Enclosure

Frequency MHz	Polarisation	Corrected value dB μ V/m		Limit Peak dB μ V/m	Limit AV dB μ V/m	Delta to Peak limit/dB	Delta to AV limit dB
		Peak	AV				
2483.50	Vertical + horizontal	49.25	37.12	74.00	54.00	24.75	16.88

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_a01	Enclosure

Frequency MHz	Polarisation	Corrected value dB μ V/m		Limit Peak dB μ V/m	Limit AV dB μ V/m	Delta to Peak limit/dB	Delta to AV limit dB
		Peak	AV				
2483.50	Vertical + horizontal	48.81	37.12	74.00	54.00	25.19	16.88

Remark: Please see annex for the measurement plot.

3.5.4 Test result: Band edge compliance

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 3	passed
	op-mode 6	passed
	op-mode 8	passed
	op-mode 10	passed
	op-mode 12	passed



3.6 Dwell time

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: FCC §15.31, 10-1-08

3.6.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6 s

with:

- hop rate = $1600 * 1/s$ for DH1 packets = 1600 s^{-1}
- hop rate = $1600/3 * 1/s$ for DH3 packets = 533.33 s^{-1}
- hop rate = $1600/5 * 1/s$ for DH5 packets = 320 s^{-1}
- number of hopping channels = 79
- $31.6 \text{ s} = 0.4 \text{ seconds multiplied by the number of hopping channels} = 0.4 \text{ s} * 79$

The following shortcuts are used for the different packet types:

- Basic data rate, 1 Mbps: DH1, DH3, DH5
- Enhanced data rate, 3 Mbps: 3-DH1, 3-DH3, 3-DH5
- Enhanced data rate, 2 Mbps: 2-DH1, 2-DH3, 2-DH5

The worst case value is reported.

3.6.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6 seconds.



3.6.3 Test Protocol

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port	
op-mode 2	Setup_d01	Temp ant.connector	
Packet type	Time slot length ms	Dwell time	Dwell time ms
DH5	2.889	time slot length * 1600/5 /79 * 31.6	370

Remark: Please see annex for the measurement plots.

3.6.4 Test result: Dwell time

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 2	passed



3.7 Channel separation

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: FCC §15.31, 10-1-08

3.7.1 Test Description

The Equipment Under Test (EUT) was set up to perform the channel separation measurements. The channel separation is independent from the modulation pattern. The EUT was connected to spectrum analyzer via a short coax cable.

Analyzer settings:

- Detector: Peak-Maxhold
- Span: 3 MHz
- Centre Frequency: 2442 MHz
- Resolution Bandwidth (RBW): 30 kHz
- Video Bandwidth (VBW): 100 kHz
- Sweep Time: Coupled

3.7.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.



3.7.3 Test Protocol

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port
op-mode 4	Setup_d01	Temp ant.connector
Channel separation		Remarks
MHz		-
1.000		-

Remark: Please see annex for the measurement plot.

3.7.4 Test result: Channel separation

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 4	passed



3.8 Number of hopping frequencies

Standard FCC Part 15, 10-1-08
Subpart C

The test was performed according to: FCC §15.31, 10-1-08

3.8.1 Test Description

The Equipment Under Test (EUT) was set up to perform the number of hopping frequencies measurement. The number of hopping frequencies is independent from the modulation pattern.

The EUT was connected to spectrum analyzer via a short coax cable.

Analyzer settings:

- Detector: Peak-Maxhold
- Centre frequency: 2442 MHz
- Frequency span: 84 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Sweep Time: Coupled

3.8.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.8.3 Test Protocol

Temperature: 24 °C
Air Pressure: 1011 hPa
Humidity: 38 %

Op. Mode	Setup	Port
op-mode 4	Setup_d01	Temp ant.connector
Number of hopping channels		Remarks
79		-

Remark: Please see annex for the measurement plot.

3.8.4 Test result: Number of hopping frequencies

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 4	passed



4 Test Equipment

Test Equipment Anechoic Chamber

Lab ID:	Lab 2		
Manufacturer:	Frankonia		
Description:	Anechoic Chamber for radiated testing		
Type:	10.58x6.38x6		
	Calibration Details	Last Execution	Next Exec.
	IC renewal	2009/01/21	2011/01/20
	FCC renewal	2009/01/07	2011/01/06

Single Devices for Anechoic Chamber

Single Device Name	Type	Serial Number	Manufacturer
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6	none	Frankonia
	Calibration Details	Last Execution	Next Exec.
	FCC listing 96716 3m Part15/18	2009/01/07	2011/01/06
	ANSI C64.3 NSA	2009/01/21	2011/01/20
Controller Innco 2000	CO 2000	C02000/328/12470 406/L	Innco innovative constructions GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita

Test Equipment Auxiliary Equipment for Radiated emissions

Lab ID: Lab 2
Description: Equipment for emission measurements
Serial Number: see single devices

Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Type	Serial Number	Manufacturer	
Antenna mast	AS 620 P		HD GmbH	
Biconical dipole	VUBA 9117	9117108	Schwarzbeck	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2008/10/27	2013/10/26
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P	849785	Miteq	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4	-	Miteq	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
Broadband Amplifier 30MHz-18GHz	JS4-00101800-35-5P	896037	Miteq	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
Cable "ESI to EMI Antenna"	EcoFlex10	W18.01-2+W38.01- Kabel Kusch 2		
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
Cable "ESI to Horn Antenna"	UFB311A+UFB293C	W18.02-2+W38.02- Rosenberger Micro-Coax 2		
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
Double-ridged horn	HF 906	357357/001	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2009/04/16	2012/04/15
Double-ridged horn	HF 906	357357/002	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2009/04/28	2012/04/27
Dreheinheit	DE 325		HD GmbH	
High Pass Filter	4HC1600/12750-1.5-KK	9942011	Trilithic	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
High Pass Filter	5HC2700/12750-1.5-KK	9942012	Trilithic	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
High Pass Filter	5HC3500/12750-1.2-KK	200035008	Trilithic	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Path Calibration		2009/05/18	2009/11/17
Log.-per. Antenna	HL 562 Ultralog	830547/003	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard Calibration		2009/05/27	2012/05/26

Single Devices for Auxiliary Equipment for Radiated emissions (continued)

Single Device Name	Type	Serial Number	Manufacturer
Loop Antenna	HFH2-Z2	829324/006	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	DKD calibration		2008/10/07 2011/10/06
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH

Test Equipment Digital Signalling Devices

Lab ID: Lab 2
Description: Signalling equipment for various wireless technologies.

Single Devices for Digital Signalling Devices

Single Device Name	Type	Serial Number	Manufacturer
Bluetooth Signalling Unit CBT	1153.9000.35	100302	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/04/28 2011/04/27
Digital Radio Communication Tester	CMD 55	831050/020	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	standard calibration		2008/10/07 2010/10/06
Digital Radio Test Set	6103E	2359	Racal Instruments, Ltd.
Universal Radio Communication Tester	CMU 200	837983/052	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2008/12/01 2011/11/30
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	HW options: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B54V14, B56V14, B68 3v04, B95, PCMCIA, U65V02		2007/01/02
	SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K27 4v10, K28 4v10, K42 4v11, K43 4v11, K53 4v10, K65 4v10, K66 4v10, K68 4v10,		
	Firmware: μP1 8v40 01.12.05		

	SW: K62, K69		2008/11/03
Vector Signal Generator	SMU200A	100912	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	standard calibration		2008/10/28 2011/10/27



Test Equipment Emission measurement devices

Lab ID: Lab 2
Description: Equipment for emission measurements
Serial Number: see single devices

Single Devices for Emission measurement devices

Single Device Name	Type	Serial Number	Manufacturer
Personal Computer	Dell		Dell
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2007/12/05 2010/12/04
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2007/12/06 2009/12/05

Test Equipment InterLab Bluetooth RF Test Solution - Setup C

Lab ID:	Lab 1
Manufacturer:	7 layers, Inc.
Description:	Bluetooth BDR and EDR RF Conformance Test System
Type:	InterLab BT RF
HW/SW Status	Date of Start Date of End
Bluetooth RF Test Solution (version 2.3.4 package 1)	2009/03/25 2009/06/03
Bluetooth RF Test Solution (version 2.3.4 package 2)	2009/06/03

Single Devices for InterLab Bluetooth RF Test Solution - Setup C

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>
ADU 200 Relay Box 7	Relay Box	A04380	Ontrak Control Systems Inc.
Bluetooth Signalling Unit CBT CBT		100589	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/08/06 2010/08/05
Power Meter NRVD	857.8008.02	832025/059	<i>Last Execution</i> <i>Next Exec.</i>
	<i>Calibration Details</i>		
	Standard Calibration		2009/06/23 2010/06/22
Power Sensor NRV Z1 A	828.3018.03	832279/013	
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/06/23 2010/06/22
Power Supply	NGSM 32/10	2725	<i>Last Execution</i> <i>Next Exec.</i>
	<i>Calibration Details</i>		
	Standard Calibration		2009/04/28 2010/04/27
Rubidium Frequency Normal MFS	828.3018.03	002	Datum GmbH
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/06/23 2010/06/22
Signal Analyser FSIQ26	1119.6001.26	832695/007	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/06/24 2011/06/23
Signal Generator SMP 03	1035.5005.03	833680/003	
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/06/23 2012/06/22
ThermoHygro Datalogger Opus10 THI (8152.00) 04 (Environ)		7481	Lufft Mess- und Regeltechnik GmbH
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2009/01/23 2010/01/22
TOCT Switching Unit	Switching Unit	030106	7 layers, Inc.
Vector Signal Generator SMIQ03B B	1125.5555.03	832870/017	
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard		2007/05/24 2010/05/23



Test Equipment Multimeter 12

Lab ID: Lab 1
Description: Ex-Tech 520
Serial Number: 05157876

Single Devices for Multimeter 12

Single Device Name	Type	Serial Number	Manufacturer
Digital Multimeter 12 (Multimeter)	EX520	05157876	Extech Instruments Corp.

Test Equipment Power Supply 04

Lab ID: Lab 1
Manufacturer: Rohde & Schwarz GmbH & Co.KG
Description: NGSM 32/10
Type: Power Supply
Serial Number: 3725

Calibration Details	Last Execution	Next Exec.
Standard calibration	2009/04/28	2010/04/27

Test Equipment Shielded Room 07

Lab ID: Lab 1
Description: Shielded Room 4m x 6m

Test Equipment T/H Logger 04

Lab ID: Lab 1
Description: Lufft Opus10
Serial Number: 7481

Single Devices for T/H Logger 04

Single Device Name	Type	Serial Number	Manufacturer
ThermoHygro DataloggerOpus10 THI (8152.00) 04 (Environ)		7481	Lufft Mess- und Regeltechnik GmbH
Calibration Details			Last Execution
Standard calibration		2009/01/23	2010/01/22

Test Equipment Temperature Chamber 01

Lab ID: Lab 1
Manufacturer: see single devices
Description: Temperature Chamber KWP 120/70
Type: Weiss
Serial Number: see single devices

Single Devices for Temperature Chamber 01

Single Device Name	Type	Serial Number	Manufacturer
Temperature Chamber Weiss 01	KWP 120/70	59226012190010	Weiss Umwelttechnik GmbH
Calibration Details			Last Execution
Specific calibration		2009/03/12	2010/03/11

5 Photo Report




Photo 1: Test setup for radiated measurements (Enclosure, below 30MHz)




Photo 2: Setup_a01. Test setup for radiated measurements (Enclosure, 30MHz to 1GHz)



Photo 3: Setup_b01. Test setup for radiated measurements (Enclosure, 30MHz to 1GHz)




Photo 4: Setup_c01. Test setup for radiated measurements (Enclosure, 30MHz to 1GHz)




Photo 5: Test setup for radiated measurements (Enclosure, above 1 GHz)



Photo 6: EUT connector view




Photo 7: AE 1 Display 1




Photo 8: AE 2 Display 2



Photo 9: AE 3 Microphone





Photo 10: AE 4 cable harness



Photo 10: AE 5 audio in

6 Setup Drawings



Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

Drawing 1: Setup in the Anechoic chamber:

Measurements below 1 GHz: Semi-anechoic, conducting ground plane.
Measurements above 1 GHz: Fully-anechoic, absorbers on all surfaces


7 Annex measurement plots

7.1 Occupied bandwidth

7.1.1 Occupied bandwidth operating mode 1

Op. Mode


op-mode 1



7.1.2 Occupied bandwidth operating mode 2

Op. Mode

op-mode 2



Title: 20dB Bandwidth


Comment A: CH M: 2441 MHz; 20dB bandwidth (kHz):890.4

Date: 29.OCT.2009 10:27:33

7.1.3 Occupied bandwidth operating mode 3

Op. Mode

op-mode 3




Title: 20dB Bandwidth
 Comment A: CH T: 2480 MHz; 20dB bandwidth (kHz):890.4
 Date: 29.OCT.2009 10:40:53

7.1.4 Occupied bandwidth operating mode 6

Op. Mode


op-mode 6



7.1.5 Occupied bandwidth operating mode 7

Op. Mode


op-mode 7



7.1.6 Occupied bandwidth operating mode 8

Op. Mode


op-mode 8



7.1.7 Occupied bandwidth operating mode 10

Op. Mode


op-mode 10



7.1.8 Occupied bandwidth operating mode 11

Op. Mode


op-mode 11



7.1.9 Occupied bandwidth operating mode 12

Op. Mode

op-mode 12




7.2 Peak power output

7.2.1 Peak power output operating mode 1

Op. Mode


op-mode 1



7.2.2 Peak power output operating mode 2

Op. Mode

op-mode 2




Title: Peak outputpower Power
 Comment A: CH M: 2441 MHz
 Date: 29.OCT.2009 10:27:58

7.2.3 Peak power output operating mode 3

Op. Mode

op-mode 3




Title: Peak outputpower Power
 Comment A: CH T: 2480 MHz
 Date: 29.OCT.2009 10:41:19

7.2.4 Peak power output operating mode 6

Op. Mode


op-mode 6



7.2.5 Peak power output operating mode 7

Op. Mode


op-mode 7



7.2.6 Peak power output operating mode 8

Op. Mode

op-mode 8



Comment:


The black bar at the top of the measurement plot above was created by the test system. The following settings were used for the measurement above:

RBW: 3 MHz
 VBW: 3 MHz
 SWT: 5 ms
 RF Att: 30 dB
 Rev Lvl: 1.73 dBm

7.2.7 Peak power output operating mode 10

Op. Mode


op-mode 10



7.2.8 Peak power output operating mode 11

Op. Mode

op-mode 11



Comment:


The black bar at the top of the measurement plot above was created by the test system. The following settings were used for the measurement above:

RBW: 3 MHz
 VBW: 3 MHz
 SWT: 5 ms
 RF Att: 30 dB
 Rev Lvl: 1.60 dBm

7.2.9 Peak power output operating mode 12

Op. Mode

op-mode 12




7.3 Band edge compliance conducted and Spurious RF conducted emissions

7.3.1 Band edge compliance conducted operating mode 1

Op. Mode

op-mode 1




(determination of reference value for spurious emissions measurement)

7.3.2 Spurious RF conducted emissions operating mode 1

Op. Mode

op-mode 1




Title: spurious emissions
Comment A: CH B: 2402 MHz
Date: 14.OCT.2009 13:57:47

(spurious emissions measurement)

7.3.3 Spurious RF conducted emissions operating mode 2


Op. Mode

op-mode 2



Title: Band Edge Compliance
 Comment A: CH M: 2441 MHz
 Date: 14.OCT.2009 13:59:29

(determination of reference value for spurious emissions measurement)




Title: spurious emissions
 Comment A: CH M: 2441 MHz
 Date: 14.OCT.2009 14:11:07

(spurious emissions measurement)

7.3.4 Band edge compliance conducted operating mode 3

Op. Mode

op-mode 3




Title: Band Edge Compliance
 Comment A: CH T: 2480 MHz
 Date: 14.OCT.2009 14:13:40

(determination of reference value for spurious emissions measurement)

7.3.5 Spurious RF conducted emissions operating mode 3

Op. Mode

op-mode 3




Title: spurious emissions
 Comment A: CH T: 2480 MHz
 Date: 14.OCT.2009 14:25:17

(spurious emissions measurement)

7.3.6 Band edge compliance conducted operating mode 6

Op. Mode

op-mode 6




Title: Band Edge Compliance
 Comment A: CH B: 2402 MHz
 Date: 14.OCT.2009 15:22:04

(determination of reference value for spurious emissions measurement)

7.3.7 Spurious RF conducted emissions operating mode 6

Op. Mode

op-mode 6




Title: spurious emissions
 Comment A: CH B: 2402 MHz
 Date: 14.OCT.2009 15:33:42

(spurious emissions measurement)

7.3.8 Spurious RF conducted emissions operating mode 7


Op. Mode

op-mode 7



Title: Band Edge Compliance
 Comment A: CH M: 2441 MHz
 Date: 14.OCT.2009 15:35:56

(determination of reference value for spurious emissions measurement)




Title: spurious emissions
 Comment A: CH M: 2441 MHz
 Date: 14.OCT.2009 15:47:33

(spurious emissions measurement)

7.3.9 Band edge compliance conducted operating mode 8

Op. Mode

op-mode 8




Title: Band Edge Compliance
 Comment A: CH T: 2480 MHz
 Date: 14.OCT.2009 15:49:05

(determination of reference value for spurious emissions measurement)

7.3.10 Spurious RF conducted emissions operating mode 8

Op. Mode

op-mode 8




Title: spurious emissions
 Comment A: CH T: 2480 MHz
 Date: 14.OCT.2009 16:00:43

(spurious emissions measurement)

7.3.11 Band edge compliance conducted operating mode 10

Op. Mode

op-mode 10




Title: Band Edge Compliance
 Comment A: CH B: 2402 MHz
 Date: 14.OCT.2009 14:31:04

(determination of reference value for spurious emissions measurement)

7.3.12 Spurious RF conducted emissions operating mode 10

Op. Mode

op-mode 10




Title: spurious emissions
 Comment A: CH B: 2402 MHz
 Date: 14.OCT.2009 14:42:42

(spurious emissions measurement)

7.3.13 Band edge compliance conducted operating mode 11

Op. Mode

op-mode 11




(determination of reference value for spurious emissions measurement)

7.3.14 Spurious RF conducted emissions operating mode 11

Op. Mode

op-mode 11




Title: spurious emissions
 Comment A: CH M: 2441 MHz
 Date: 14.OCT.2009 14:58:45

(spurious emissions measurement)

7.3.15 Band edge compliance conducted operating mode 12

Op. Mode

op-mode 12




Title: Band Edge Compliance
 Comment A: CH T: 2480 MHz
 Date: 14.OCT.2009 15:01:04

(determination of reference value for spurious emissions measurement)

7.3.16 Spurious RF conducted emissions operating mode 12

Op. Mode

op-mode 12



Title: spurious emissions
 Comment A: CH T: 2480 MHz
 Date: 14.OCT.2009 15:12:42


(spurious emissions measurement)

7.4 Band edge compliance radiated

7.4.1 Band edge compliance radiated operating mode 3

Op. Mode

op-mode 3




Radiated measurement (higher band edge)

7.4.2 Band edge compliance radiated operating mode 8

Op. Mode

op-mode 8




Radiated measurement (higher band edge)

7.4.3 Band edge compliance radiated operating mode 12

Op. Mode

op-mode 12




Radiated measurement (higher band edge)


7.5 Radiated emissions (f < 30 MHz)

Op. Mode

op-mode 1




Antenna position 90°
EUT position front side




Antenna position 90°
EUT position right side

Op. Mode

op-mode 1



Antenna position 0°
EUT position front side




Antenna position 0°
EUT position right side

7.6 Dwell time

Op. Mode


op-mode 2 Time slot measurement of a DH5 packet



7.7 Channel separation

Op. Mode


op-mode 4



7.8 Number of hopping frequencies

Op. Mode

op-mode 4



Title: Number of hopping frequencies

Comment A: CH H: Hopping

Date: 14.OCT.2009 14:29:59