

## RF Exposure Evaluation declaration

Product Name	WiFi AP
Model No.	Bitlomat 200 Sector Base Station
FCC ID	RNF-BTLM200

Applicant	Bitlomat, LLC.
Address	1850 SECOND ST STE 201HIGHLAND PARK, IL 60035,USA

Date of Receipt	Jan. 18, 2013
Date of Declaration	Apr. 22, 2013
Report No.	131352R-RFUSP32V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.  
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$r$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : WiFi AP  
Test Item : RF Exposure Evaluation  
Test Site : No.3 OATS

註解 [u1]: Refer "Product"

Operation Frequency	5180~5240MHz, 5745~5850MHz
Maximum Conducted output power	29.39dBm
Antenna gain	15.91dBi

#### Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = <b>60 cm</b> (mW/cm <sup>2</sup> )
868.9604	0.720258

Power density is much lower than the limit (1 mW/cm<sup>2</sup>).