

RF EXPOSURE EVALUATION METHOD**SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Maximum measured transmitter power

802.11b

Frequency (MHz)	Max Antenna Gain (dBm)	EIRP (dBm)PK	EIRP (mW)
2412	0	11.84	15.275
2437	0	11.53	14.223
2462	0	11.69	14.757

802.11g

Frequency (MHz)	Max Antenna Gain (dBm)	EIRP (dBm) PK	EIRP (mW)
2412	0	10.73	11.83
2437	0	10.62	11.535
2462	0	10.89	12.274

802.11n

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm) PK	EIRP (mW)
2412	0	9.87	9.705
2437	0	9.89	9.75
2462	0	9.96	9.908

802.11b

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm)AV	EIRP (mW)
2412	0	9.36	8.63
2437	0	9.11	8.15
2462	0	9.08	8.091

802.11g

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm) AV	EIRP (mW)
2412	0	8.46	7.015
2437	0	8.32	6.792
2462	0	8.10	6.46

802.11n

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm) AV	EIRP (mW)
2412	0	7.98	6.28
2437	0	7.74	5.94
2462	0	8.05	6.382

Refer to 447498 25 D01 General RF Exposure Guidance v05 Appendix A, you see that for Maximum Conducted AV Output Power 8.63 mW(<10mW), so no SAR is required.

For Tune Up information

IEEE 802.11b

max possible output power (AV): 9.0 ± 0.5 dbm

you see that for Maximum Conducted Output Power 8.91 mW(9.5dBm)(<10mW), so no SAR is required.