

FCC TEST REPORT

FOR

DongGuan KingSheng Electronics&Tech Co. Ltd

DLX Wii mote and nunchuk bundle

Model No.: SL-1700+1703M

Prepared for : DongGuan KingSheng Electronics&Tech Co. Ltd
Address : Building 39, Arising Sun Industrial City, LinCun Village, TangXia
Town, DongGuan City, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1F., Xingyuan Industrial Park, Tongda Road, Bao'an Blvd., Bao'an
District, Shenzhen, Guangdong, China

Date of receipt of test sample : December 13, 2012
Number of tested samples : 1
Serial number : Prototype
Date of Test : December 13, 2012 –January 17, 2013
Date of Report : January 17, 2013

FCC TEST REPORT
FCC CFR 47 PART 15 C(15.247) / RSS-210 Issue 8/RSS-Gen Issue 3

Report Reference No. : LCS121213114TF

Date of Issue : January 17, 2013

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1F., Xingyuan Industrial Park, Tongda Road, Bao'an Blvd.,
Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure..... : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐

Applicant's Name : DongGuan KingSheng Electronics&Tech Co. Ltd

Address : Building 39, Arising Sun Industrial City, LinCun Village,
TangXia Town, DongGuan City, China

Test Specification

Standard..... : FCC CFR 47 PART 15 C(15.247) / RSS-210 Issue 8/
RSS-Gen Issue 3

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : DLX Wii mote and nunchuk bundle


Trade Mark : N/A

Model/ Type reference : SL-1700+1703M

Ratings : DC 3.0V by 2*AA Batteries

Result : **Positive**

Compiled by:



Yoyo Wang/ File administrators

Supervised by:



Vito Cao/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC -- TEST REPORT**Test Report No. : LCS121213114TF**January 17, 2013

Date of issue

Type / Model..... : SL-1700+1703M

EUT..... : **DLX Wii mote and nunchuk bundle****Applicant..... : DongGuan KingSheng Electronics&Tech Co. Ltd**Address..... : Building 39, Arising Sun Industrial City, LinCun Village,
TangXia Town, DongGuan City, China

Telephone..... : /

Fax..... : /

Manufacturer..... : DongGuan KingSheng Electronics&Tech Co. LtdAddress..... : Building 39, Arising Sun Industrial City, LinCun Village,
TangXia Town, DongGuan City, China

Telephone..... : /

Fax..... : /

Factory..... : DongGuan KingSheng Electronics&Tech Co. LtdAddress..... : Building 39, Arising Sun Industrial City, LinCun Village,
TangXia Town, DongGuan City, China

Telephone..... : /

Fax..... : /

Test Result:**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1 Description of Device (EUT).....	5
1.2 Host System Configuration List and Details	5
1.3 External I/O Cable	5
1.4 Description of Test Facility	5
1.5 Statement of The Measurement Uncertainty	6
1.6 Measurement Uncertainty	6
1.7 Description Of Test Modes.....	6
2. TEST METHODOLOGY	7
2.1 EUT Configuration	7
2.2 EUT Exercise	7
2.3 General Test Procedures	7
3. SYSTEM TEST CONFIGURATION	8
3.1 Justification.....	8
3.2 EUT Exercise Software	8
3.3 Special Accessories.....	8
3.4 Block Diagram/Schematics.....	8
3.5 Equipment Modifications	8
3.6 Test Setup	8
4. ANTENNA PORT MEASUREMENT.....	9
4.1 Peak Power	9
4.2 Frequency Separation And 20 dB Bandwidth	10
4.3 Number Of Hopping Frequency	14
4.4 Time Of Occupancy (Dwell Time).....	16
4.5 Conducted Spurious Emissions And Band Edges Test.....	19
5. RADIATED MEASUREMENT	25
5.1 Test Equipment.....	25
5.2 Block Diagram of Test Setup.....	25
5.3 Radiated Emission Limit	26
5.4 Test Results.....	27
6. ANTENNA REQUIREMENT	32
6.1 Standard Applicable.....	32
6.2 Antenna Connected Construction	32
7. MANUFACTURER/ APPROVAL HOLDER DECLARATION	33

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT	: DLX Wii mote and nunchuk bundle
Model Number	: SL-1700+1703M
Power Supply	: DC 3.0V by 2*AA Batteries
Frequency Range	: 2402.00-2480.00MHz (Channel Frequency=2402+1(K-1), K=1, 2, 379)
Modulation Technology	: GFSK(1Mbps)
Module Channel	: 79
Channel Spacing	: 1MHz
Bluetooth Version	: Bluetooth V2.0 without EDR
Antenna Gain	: 2.0dBi(Max.)

1.2 Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
N/A	N/A	N/A	N/A	N/A

1.3 External I/O Cable

I/O Port Description	Quantity	Cable
N/A	N/A	N/A

1.4 Description of Test Facility

Site Description EMC Lab.

: Accredited by CNAS, June 04, 2010
The Certificate Registration Number. is L4595.
Accredited by FCC, July 14, 2011
The Certificate Registration Number. is 899208.
Accredited by Industry Canada, May. 02, 2011
The Certificate Registration Number. is 9642A-1

1.5 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty :	30MHz~200MHz	$\pm 2.96\text{dB}$	(1)
	200MHz~1000MHz	$\pm 3.10\text{dB}$	(1)
	1GHz~26.5GHz	$\pm 3.80\text{dB}$	(1)
Conduction Uncertainty :	150kHz~30MHz	$\pm 1.63\text{dB}$	(1)
Power disturbance :	30MHz~300MHz	$\pm 1.60\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.7 Description Of Test Modes

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. Without the introduction of the enhanced data rate (EDR) feature. An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using GFSK techniques, resulting in an increase of two to three times the number of bits per symbol. All 3axis have been tested. The following operating modes were applied for the related test items.

All test modes were tested, only the result of the worst case was recorded in the report.

Mode of Operations	Frequency Range (MHz)	Data Rate (Mbps)
GFSK	2402	1
	2441	1
	2480	1
For Conducted Emission		
Test Mode	N/A	
For Radiated Emission		
Test Mode	TX Mode	

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4, RSS-210, FCC CFR PART 15C 15.207, 15.209, 15.247 and DA 00-705.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.247 under the FCC Rules Part 15 Subpart C and RSS-210.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a continuous transmits condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

N/A.

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.


4. ANTENNA PORT MEASUREMENT

4.1 Peak Power

4.1.1 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Power Sensor	Agilent	E9327A	US40441788	2012-06-18	2013-06-17
2	Power Meter	Agilent	E4416A	QB41292714	2012-06-18	2013-06-17
3	DC Filter	MPE	23872C	N/A	2012-06-18	2013-06-17

4.1.2 Block Diagram of Test Setup



4.1.3 Limit

According to § 15.247(a)(1) or A8.4 (2), For frequency hopping systems operating in the band 2400-2483.5 MHz employing at least 75 hopping channels, the maximum peak conducted output power shall not exceed 125 W.

4.1.4 Test Procedure

The transmitter output is connected to the Power Meter.

4.1.5 Test Results

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (mW)	Result
GFSK	2402	-1.66	0.68	125	Pass
	2441	-1.41	0.72	125	Pass
	2480	-1.49	0.71	125	Pass

4.2 Frequency Separation And 20 dB Bandwidth


4.2.1 Limit

According to §15.247(c) or A8.1(a), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.2.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2012-06-18	2013-06-17
2	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2012-06-18	2013-06-17
3	DC Filter	MPE	23872C	N/A	2012-06-18	2013-06-17

4.2.3 Block Diagram of Test Setup





4.2.4 Test Procedure



- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- Set center frequency of Spectrum Analyzer = middle of hopping channel.
- Set the Spectrum Analyzer as RBW = 100kHz, VBW = 100kHz, Span = wide enough to capture the peaks of two adjacent channels, Sweep = auto.
- Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.

4.2.5 Test Results

The Measurement Result With 1Mbps For GFSK Modulation				
Channel	20dB Bandwidth (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low	1.012	1.000	≥ 25 KHz or 2/3 20 dB BW	Pass
Middle	1.049		≥ 25 KHz or 2/3 20 dB BW	Pass
High	1.105		≥ 25 KHz or 2/3 20 dB BW	Pass

The test data refer to the following page.

Test Plot Of Frequency Separation (GFSK)**Measurement of 20dB Bandwidth****Test frequency: 2402MHz(GFSK)**

Test frequency: 2441MHz(GFSK)**Test frequency: 2480MHz(GFSK)**

4.3 Number Of Hopping Frequency


4.3.1 Limit

According to § 15.247(a)(1)(ii) or A8.1 (d), Frequency hopping systems operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels.

4.3.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Last Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2012-06-18	2013-06-17
2	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2012-06-18	2013-06-17
3	DC Filter	MPE	23872C	N/A	2012-06-18	2013-06-17

4.3.3 Block Diagram of Test Setup





4.3.4 Test Procedure

- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- Set Spectrum Analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- Set the Spectrum Analyzer as RBW, VBW=1MHz.
- Max hold, view and count how many channel in the band.

4.3.5 Test Results

The Measurement Result With The Worst Case of 1Mbps For GFSK Modulation			
Total No. of Hopping Channel	Measurement Result (No. of Ch)	Limit (MHz)	Result
	79	≥ 15	Pass

The test data refer to the following page.

Test Plot-1 For Number of Hopping Channel**Test Plot-2 For Number of Hopping Channel**

4.4 Time Of Occupancy (Dwell Time)


4.4.1 Limit

According to § 15.247(a)(1)(iii) or A8.1 (d), Frequency hopping systems operating in the 2400MHz- 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

4.4.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2012-06-18	2013-06-17
2	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2012-06-18	2013-06-17
3	DC Filter	MPE	23872C	N/A	2012-06-18	2013-06-17

4.4.3 Block Diagram of Test Setup



4.4.4 Test Procedure

- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- Set center frequency of Spectrum Analyzer = operating frequency.
- Set the Spectrum Analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- Repeat above procedures until all frequency measured were complete.

4.5.5 Test Results

The Worst Test Result With 1Mbps For GFSK Modulation (Middle Channel)				
	Time of Pulse for (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
DH1	0.40	31.6	128.0	400
DH3	1.66	31.6	265.6	400
DH5	2.90	31.6	309.3	400

DH1

$$0.40 \times (1600/2) / 79 \times 31.6 = 128.0 \text{ms}$$

DH3


$$1.66 \times (1600/4) / 79 \times 31.6 = 265.6 \text{ms}$$

DH5


$$2.90 \times (1600/6) / 79 \times 31.6 = 309.3 \text{ms}$$

The test data refer to the following:


Test Plot of DH1, Middle Channel



Test Plot of DH3, Middle Channel



Test Plot of DH5, Middle Channel



4.5 Conducted Spurious Emissions And Band Edges Test


4.5.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.5.2 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY4144029 2	2012-06-18	2013-06-17
2	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2012-06-18	2013-06-17
3	DC Filter	MPE	23872C	N/A	2012-06-18	2013-06-17

4.5.3 Block Diagram of Test Setup



4.5.4 Test Procedure



Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.



The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.



Measurements are made over the 9kHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels

4.5.5 Test Results of Conducted Spurious Emissions

No non-compliance noted. Only record the worst test result (TX-GFSK) in this report. The test data refer to the following page.

Test Plot**9KHz-26.5GHz Low Channel(GFSK)**

9KHz-26.5GHz Middle Channel(GFSK)



9KHz-26.5GHz High Channel(GFSK)



4.5.5 Test Results of Band Edges Test

No non-compliance noted. Only record the worst test result in this report. The test data refer to the following page.

Test Plot

Hopping On - (GFSK)




Hopping Off - (GFSK)


5. RADIATED MEASUREMENT

5.1 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	2012-06-18	2013-06-17
2	Test Receiver	R& S	ESCS30	828985/018	2012-06-18	2013-06-17
3	Loop antenna	EMCO	6502	0042963	2012-06-18	2013-06-17
4	Log per Antenna	Schwarzbeck	VULB9163	142	2012-06-18	2013-06-17
5	Horn-antenna	Schwarzbeck	BBHA9120D	D:266	2012-06-18	2013-06-17
6	Horn-antenna	Schwarzbeck	BBHA9170	BBHA9170154	2012-06-18	2013-06-17
7	DC Filter	MPE	23872C	N/A	2012-06-18	2013-06-17

5.2 Block Diagram of Test Setup



**Above 1 GHz**

5.3 Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

Part 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector.

Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Part 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F (kHz)	300
0.490–1.705	24000/F (kHz)	30
1.705–30.0	30	30
30–88	100**	3
88–216	150**	3
216–960	200**	3
Above 960	500	3

5.4 Test Results

PASS.

Only record the worst test result in this report.


The test data please refer to following page:

Below 1GHz

Env. /Ins: 24°C/56%
 EUT: DLX Wii mote and nunchuk bundle
 M/N: SL-1700+1703M
 Power Rating: DC 3.0V
 Test Mode: Tx-2402
 Operator: Leo
 Memo:
 pol: VERTICAL

	Freq.	Reading	CabLos	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	44.55	3.19	0.41	13.55	0.00	17.15	40.00	-22.85	QP
2	62.98	5.29	0.48	11.51	0.00	17.28	40.00	-22.72	QP
3	100.81	4.26	0.60	13.09	0.00	17.95	43.50	-25.55	QP
4	292.87	11.37	1.08	12.92	0.00	25.37	46.00	-20.63	QP
5	630.43	4.29	1.60	18.56	0.00	24.45	46.00	-21.55	QP
6	942.77	3.81	1.94	21.37	0.00	27.12	46.00	-18.88	QP


Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.
 3. The emission levels that are 20dB below the official limit are not reported.



Env. /Ins: 24°C/56%
 EUT: DLX Wii mote and nunchuk bundle
 M/N: SL-1700+1703M
 Power Rating: DC 3.0V
 Test Mode: Tx-2402
 Operator: Leo
 Memo:
 pol: HORIZONTAL

	Freq.	Reading	CabLos	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	45.52	3.57	0.41	13.52	0.00	17.50	40.00	-22.50	QP
2	100.81	3.72	0.60	13.09	0.00	17.41	43.50	-26.09	QP
3	298.69	21.26	1.12	13.03	0.00	35.41	46.00	-10.59	QP
4	389.87	7.65	1.17	14.82	0.00	23.64	46.00	-22.36	QP
5	641.10	4.55	1.55	18.60	0.00	24.70	46.00	-21.30	QP
6	884.57	4.20	1.87	20.93	0.00	27.00	46.00	-19.00	QP


Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24°C/56%
 EUT: DLX Wii mote and nunchuk bundle
 M/N: SL-1700+1703M
 Power Rating: DC 3.0V
 Test Mode: Tx-2441
 Operator: Leo
 Memo:
 pol: VERTICAL

	Freq.	Reading	CabLos	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	62.98	6.29	0.48	11.51	0.00	18.28	40.00	-21.72	QP
2	100.81	5.26	0.60	13.09	0.00	18.95	43.50	-24.55	QP
3	292.87	10.37	1.08	12.92	0.00	24.37	46.00	-21.63	QP
4	494.63	4.36	1.50	16.44	0.00	22.30	46.00	-23.70	QP
5	630.43	5.29	1.60	18.56	0.00	25.45	46.00	-20.55	QP
6	809.88	5.94	1.71	20.16	0.00	27.81	46.00	-18.19	QP


Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24°C/56%
 EUT: DLX Wii mote and nunchuk bundle
 M/N: SL-1700+1703M
 Power Rating: DC 3.0V
 Test Mode: Tx-2441
 Operator: Leo
 Memo:
 pol: HORIZONTAL

	Freq.	Reading	CabLos	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	45.52	2.57	0.41	13.52	0.00	16.50	40.00	-23.50	QP
2	100.81	3.72	0.60	13.09	0.00	17.41	43.50	-26.09	QP
3	298.69	20.26	1.12	13.03	0.00	34.41	46.00	-11.59	QP
4	389.87	7.65	1.17	14.82	0.00	23.64	46.00	-22.36	QP
5	601.33	5.07	1.43	18.45	0.00	24.95	46.00	-21.05	QP
6	884.57	5.20	1.87	20.93	0.00	28.00	46.00	-18.00	QP


Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.
 3. The emission levels that are 20dB below the official limit are not reported.



Env. /Ins: 24°C/56%
 EUT: DLX Wii mote and nunchuk bundle
 M/N: SL-1700+1703M
 Power Rating: DC 3.0V
 Test Mode: Tx-2480
 Operator: Leo
 Memo:
 pol: VERTICAL

	Freq.	Reading	CabLos	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	62.98	6.29	0.48	11.51	0.00	18.28	40.00	-21.72	QP
2	100.81	4.26	0.60	13.09	0.00	17.95	43.50	-25.55	QP
3	292.87	13.37	1.08	12.92	0.00	27.37	46.00	-18.63	QP
4	494.63	5.36	1.50	16.44	0.00	23.30	46.00	-22.70	QP
5	630.43	5.29	1.60	18.56	0.00	25.45	46.00	-20.55	QP
6	942.77	4.81	1.94	21.37	0.00	28.12	46.00	-17.88	QP

Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.
 3. The emission levels that are 20dB below the official limit are not reported.



Env. /Ins: 24°C/56%
 EUT: DLX Wii mote and nunchuk bundle
 M/N: SL-1700+1703M
 Power Rating: DC 3.0V
 Test Mode: Tx-2480
 Operator: Leo
 Memo:
 pol: HORIZONTAL

	Freq.	Reading	CabLos	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	45.52	4.57	0.41	13.52	0.00	18.50	40.00	-21.50	QP
2	117.30	5.84	0.68	10.96	0.00	17.48	43.50	-26.02	QP
3	298.69	20.26	1.12	13.03	0.00	34.41	46.00	-11.59	QP
4	389.87	6.65	1.17	14.82	0.00	22.64	46.00	-23.36	QP
5	688.63	4.75	1.60	18.77	0.00	25.12	46.00	-20.88	QP
6	884.57	5.20	1.87	20.93	0.00	28.00	46.00	-18.00	QP

Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.
 3. The emission levels that are 20dB below the official limit are not reported.

Above 1GHz

The test result for Tx-Low Channel:

Freq. MHz	Reading dBuv	Ant. Fac dB/m	Pre.Fac dB	Cab.Los dB	Limit dBuv/m	Margin dB	Remark	Pol.
4804.07	45.66	33.06	35.04	3.94	74	-26.38	Peak	Horizontal
4804.13	33.41	33.06	35.04	3.94	54	-18.63	Average	Horizontal
4804.11	44.89	33.06	35.04	3.94	74	-27.15	Peak	Vertical
4804.15	33.64	33.06	35.04	3.94	54	-18.40	Average	Vertical

The test result for Tx-Middle Channel:

Freq. MHz	Reading dBuv	Ant. Fac dB/m	Pre.Fac dB	Cab.Los dB	Limit dBuv/m	Margin dB	Remark	Pol.
4882.11	44.71	33.16	35.15	3.96	74	-27.32	Peak	Horizontal
4882.16	33.26	33.16	35.15	3.96	54	-18.77	Average	Horizontal
4882.13	43.67	33.16	35.15	3.96	74	-28.36	Peak	Vertical
4882.16	33.07	33.16	35.15	3.96	54	-18.96	Average	Vertical

The test result for Tx-High Channel:

Freq. MHz	Reading dBuv	Ant. Fac dB/m	Pre.Fac dB	Cab.Los dB	Limit dBuv/m	Margin dB	Remark	Pol.
4960.10	44.16	33.26	35.14	3.98	74	-27.74	Peak	Horizontal
4960.13	33.11	33.26	35.14	3.98	54	-18.79	Average	Horizontal
4960.11	43.78	33.26	35.14	3.98	74	-28.12	Peak	Vertical
4960.09	32.71	33.26	35.14	3.98	54	-19.19	Average	Vertical

Notes:

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30 MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. 18~25GHz at least have 20dB margin. No recording in the test report.

6. ANTENNA REQUIREMENT

6.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Connected Construction

The directional gains of antenna used for transmitting is 2.0 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

.

7. MANUFACTURER/ APPROVAL HOLDER DECLARATION

The following identical model(s):

--	--	--
----	----	----

Belong to the tested device:

Product description : DLX Wii mote and nunchuk bundle

Model name : SL-1700+1703M

-----THE END OF REPORT-----