



120.00 mm

 **BLAUPUNKT**

Model: Philadelphia 835 (World)



Rear of Unit



| PIN | DEFINITION A PART | PIN | DEFINITION B PART |
|-----|-------------------|-----|-------------------|
| 1   | CAN-L             | 1   | Rear R+           |
| 2   | NC                | 2   | Rear R-           |
| 3   | CAN-H             | 3   | Front R+          |
| 4   | ACC               | 4   | Front R-          |
| 5   | NC                | 5   | Front L+          |
| 6   | NC                | 6   | Front L-          |
| 7   | BATT +12V         | 7   | Rear L+           |
| 8   | GND               | 8   | Rear L-           |

| DEFINITION C PART |              |             |         |
|-------------------|--------------|-------------|---------|
| PIN C1 PART       | PIN C2 PART  | PIN C3 PART |         |
| 1                 | Video GND    | 7           | NC      |
| 2                 | NC           | 8           | P.CONT* |
| 3                 | NC           | 9           | NC      |
| 4                 | Camera Video | 10          | NC      |
| 5                 | NC           | 11          | NC      |
| 6                 | NC           | 12          | NC      |
| ---               | ---          | ---         | ---     |
| ---               | ---          | ---         | ---     |

| PIN  | DEFINITION       |
|------|------------------|
| 1-20 | NC               |
| 21   | Front L          |
| 22   | Front R          |
| 23   | Audio GND        |
| 24   | Rear L           |
| 25   | Rear R           |
| 26   | Rear Video OUT 2 |
| 27   | SUB OUT          |
| 28   | Audio GND        |
| 29   | Rear L OUT       |
| 30   | Rear R OUT       |
| 31   | Rear Video OUT 1 |
| 32   | AUX IN Video     |
| 33   | Video GND        |
| 34   | AUX Audio GND    |
| 35   | AUX IN L         |
| 36   | AUX IN R         |

**Warnings:**  
 Warranty void if this unit is damaged due to misuse or unauthorized service attempting.  
 Before making any electrical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Owner's Manual.  
 Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 50-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle.  
 Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

This product was produced using lead free technology.  
 Help keep the world clean! Dispose properly!

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:  
 (1) This device may not cause harmful interference, and  
 (2) This device must accept any interference received, including interference that may cause undesired operation.



FCC ID: RPL-PHL835

IC: 10835A-PHL835

CE 2200



10R-032588

P/N:12707100XXXX

Remarks: (\*) Total max. 150 mA / Fuse: 15 Ampere

12V ⚡ GROUND --- 15A max

100.00 mm