




Rear of Unit

A



B



PIN DEFINITION A PART

1	NC
2	NC
3	NC
4	NC
5	NC
6	NC
7	NC
8	AUX_RCH
9	LINE_R
10	AUX_LCH
11	AUX_CVBS
12	GND
13	EVD_CVBS
14	LINE_FR/Red
15	GND
16	LINE_FL/White
17	LINE_RL/White
18	AGND
19	SUB_OUT/Blue
20	LINE_RR/Red

PIN DEFINITION B PART

1	KEY A/White
2	KEY_B/Red
3	VGND/Black
4	PCNT-/Blue with White
5	ACC/Red
6	CAMERA IN/Red
7	RU-/Green with Black
8	HE_VL/RSLP/Pink
9	RL-/+Green
10	SWR/Black
11	BRKE-/Green with White
12	Perm. +12V/Yellow
13	BR-/Purple with Black
14	PANT/Blue
15	BRL-/Purple
16	ILU/Brown
17	FR-/Grey
18	FL-/White with Black
19	FR-/Grey with Black
20	FL-/White

Warnings:

Warranty void if this unit is damaged due to misuse or unauthorized service attempting.

Before making any electrical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Owner's Manual.

Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 50-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle. Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

This product was produced using lead free technology. Help keep the world clean! Dispose properly!

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.



10R - 05 3318

FCC ID: RPL-SANANTO640

P/N: 127071009144

Remarks: (*) Total max. 150 mA / Fuse: 15 Ampere

12V GND 15A max USB Output: 6V 600mA

120.00 mm
100.00 mm