

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Email: ee.shenzhen@sgs.com

# **RF Exposure Evaluation Report**

Application No.: SZEM1307004092RF

Applicant: Create New Technology (HK) Limited

Manufacturer: Create New Technology (HK) Limited

Product Name: TVpad Model No.(EUT): M358

FCC ID: RPSTVPM358X

**Standards:** 47 CFR Part 1.1307(2012)

47 CFR Part 1.1310(2012)

**Date of Receipt:** 2013-07-30

**Date of Test:** 2013-08-15 to 2013-08-26

**Date of Issue:** 2013-09-02

Test Result : PASS\*

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM130700409202

Page: 2 of 6

### 2 Contents

		Fo	ige
1	С	COVER PAGE	1
2	С	CONTENTS	2
3	G	GENERAL INFORMATION	3
	3.1	CLIENT INFORMATION	3
	3.2	GENERAL DESCRIPTION OF EUT	3
	3.3	TEST LOCATION	4
	3.4	TEST FACILITY	4
	3.5	DEVIATION FROM STANDARDS	4
	3.6	ABNORMALITIES FROM STANDARD CONDITIONS	4
	3.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
4	R	RF EXPOSURE EVALUATION	5
	4.1	RF Exposure Compliance Requirement	5
	4.	l.1.1 Limits	5
	4	1.1.2 Test Procedure	5
		4.1.3 EUT RF Exposure Evaluation	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms and conditions.htm">www.sgs.com/terms and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms e-document.htm">www.sgs.com/terms e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130700409202

Page: 3 of 6

### 3 General Information

#### 3.1 Client Information

Applicant:	Create New Technology (HK) Limited		
Address of Applicant:	FLAT/RM 704 7/F BRIGHT WAY TOWER 33 MONG KOK ROAD		
	Hong Kong		
Manufacturer:	Create New Technology (HK) Limited		
Address of Manufacturer:	FLAT/RM 704 7/F BRIGHT WAY TOWER 33 MONG KOK ROAD		
	Hong Kong		

### 3.2 General Description of EUT

Name:	TVpad
Model No.	M358
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
	IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)
	IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
	IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Sample Type:	Fixed production
Test Power Grade:	44 (manufacturer declare )
Test Software of EUT:	adb shell (manufacturer declare )
Antenna Type and Gain:	Type :Integral
	Gain :1.42dBi
Adapter:	MODEL: MU10-Q050200-A1
·	Input: AC 100V-240V 50-60Hz 0.3A
	Output: DC 5.0V ==== 2.0A
Test Voltage:	120V 60Hz
DC Cable:	105cm
AV Cable:	105cm



Report No.: SZEM130700409202

Page: 4 of 6

#### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

#### 3.5 Deviation from Standards

None.

#### 3.6 Abnormalities from Standard Conditions

None.

### 3.7 Other Information Requested by the Customer

None.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms.e-document.htm">www.sgs.com/terms.e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130700409202

Page: 5 of 6

# 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### **4.1.1 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

			()	
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
(A) Lim	its for Occupationa	I/Controlled Exposu	res	
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6
(B) Limits	for General Populati	ion/Uncontrolled Exp	oosure	
0.3–1.34 1.34–30 30–300 300–1500	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500	30 30 30 30
1500-100.000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout\*G)/(4\*Pi\*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms and conditions.htm">www.sgs.com/terms and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms e-document.htm">www.sgs.com/terms e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130700409202

Page: 6 of 6

### 4.2 4.1.3 EUT RF Exposure Evaluation

Antenna Gain:1.42dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.387 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency	Max Conducted	Output Power	Power Density	Limit	Result
	(MHz)	Peak Output	to Antenna	at R = 20 cm		
		Power (dBm)	(mW)	(mW/cm <sup>2</sup> )		
Middle	2437	17.49	56.105	0.016	1.0	PASS

Note: Refer to report No. SZEM130700409201 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.