



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>



Dates of Tests: June 19 ~ 27, 2007
 Test Report S/N: LR500190706D
 Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

RQKSMARTRFGUNUHF

APPLICANT

SAMMI Information Systems Co., Ltd.

FCC Classification	:	FHSS Sequence Spread Spectrum (FHSS)
Manufacturing Description	:	UHF RFID Reader
Manufacturer	:	SAMMI Information Systems Co., Ltd.
Model name	:	Smart RF GUN
Test Device Serial No.:	:	P701SC0004
Rule Part(s)	:	FCC Part 15.247 Subpart C; ANSI C-63.4-2003
Frequency Range	:	902.3 ~ 927.7MHz
RF power	:	0.561 W - Conducted
Data of issue	:	June 27, 2007

This test report is issued under the authority of:

Dong-Min JUNG, Technical Manager

The test was supervised by:

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.

NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION'S -----	3
2. INFORMATION'S ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 TECHNICAL CHARACTERISTICS TEST -----	6
3.2.1 CARRIER FREQUENCY SEPARATION -----	6
3.2.2 NUMBER OF HOPPING FREQUENCIES -----	8
3.2.3 20 dB BANDWIDTH -----	11
3.2.4 TIME OF OCCUPANCY (Dwell Time) -----	13
3.2.5 TTANSMITTER OUTPUT POWER -----	15
3.2.6 BAND – EDGE (Conducted) -----	17
3.2.7 FIELD STRENGTH OF HARMONICS -----	23
3.2.8 AC CONDUCTED EMISSIONS -----	26

APPENDIX

APPENDIX TEST EQUIPMENT USED FOR TESTS -----	29
--	----

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2007-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2007-07-13	EMC accredited Lab.
FCC	U.S.A	610755	2008-03-28	FCC filing
VCCI	JAPAN	R2133, C2307	2008-06-22	VCCI registration
IC	CANADA	IC5799	2008-04-23	IC filing

2. Information's about test item

2-1 Client

Company name : SAMMI Information Systems Co., Ltd.
 Address : 496,wonchun-dong, yeongtong-ku, suwon, kyung ki-do, Korea
 Tel / Fax : +82-31-217-8252 / +82-31-217-8254

2-2 Manufacturer

Company name : SAMMI Information Systems Co., Ltd.
 Address : 7-9FL., Seo Jo Bldg, 103-5, Galwor-Dond, Yong San-Ku, Seoul, Korea

2-2 Equipment Under Test (EUT)

Trade name : UHF RFID Reader
 FCC ID : RQKSMARTRFGUNUHF
 Model name : Smart RF GUN (UHF)
 Serial number : P701SC0004
 Date of receipt : June 18, 2007
 EUT condition : Pre-production, not damaged
 Antenna type : Ceramic Patch Antenna Gain 1dBi
 Frequency Range : 902.3 ~ 927.7MHz
 RF output power : 27dBm
 Number of channels : 128
 Channel spacing : 200KHz
 Channel Access Protocol : Frequency Hopping
 Power Source : Adaptor: 100-240VAC/0.5A, 5VDC/3A
 Battery: Rechargeable Lithium Ion Battery 2200 mAh 3.7VDC

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	902.3	914.9	927.7

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
PDA	Smart Compact	N/A	SAMMI
-	-	-	-

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 50 hops		C
15.247(a)	20 dB Bandwidth	< 1 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1 Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

3.2 Transmitter requirements

3.2.1 Carrier Frequency Separation

Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 1 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more) Sweep = auto

VBW = 10 kHz Detector function = peak

Trace = max hold

Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
0.203	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency Separation



3.2.2 Number of Hopping Frequencies

Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 902 ~ 928 MHz FH band were examined.

The spectrum analyzer is set to:

Frequency range 1: Start = 900 MHz, Stop = 905 MHz

2: Start = 905 MHz, Stop = 910 MHz

3: Start = 910 MHz, Stop = 915 MHz

4: Start = 915 MHz, Stop = 920 MHz

5: Start = 920 MHz, Stop = 925 MHz

6: Start = 925 MHz, Stop = 930 MHz

RBW = 100 kHz (1% of the span or more) Sweep = auto

VBW = 100 kHz (VBW \geq RBW) Detector function = peak

Trace = max hold Span = 5MHz

Measurement Data: Complies

Total number of Hopping Channels	128
---	-----

- See next pages for actual measured spectrum plots.




Minimum Standard:

At least 50 hopes




Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Number of Hopping Frequencies



Number of Hopping Frequencies



3.2.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 1 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 10 kHz Sweep = auto

VBW = 10 kHz (VBW \geq RBW) Detector function = peak

Trace = max hold

Measurement Data:

Frequency (MHz)	Channel No.	Test Results	
		Measured Bandwidth (MHz)	Result
902.3	1	0.133	Complies
914.9	64	0.133	Complies
927.7	128	0.128	Complies

- See next pages for actual measured spectrum plots.




Minimum Standard:

The transmitter shall have a maximum 20dB bandwidth of 1 MHz.

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

20 dB Bandwidth



3.2.4 Time of Occupancy (Dwell Time)

Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 914.9 MHz

Span = zero

RBW = 10 MHz

VBW = 30 MHz (VBW \geq RBW)

Trace = max hold

Detector function = peak

Measurement Data:

Channel Number	Channel Frequency (MHz)	Test Results			
		Length (ms)	number	Dwell Time (ms)	Result
64	914.9	9.75	5	48.75	Complies



- See next pages for actual measured spectrum plots.

Minimum Standard:

0.4 seconds within a 10 second period per any frequency

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)



3.2.5 Transmitter Output Power

Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW \geq RBW)

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data:

Frequency (MHz)	Ch.	Test Results		
		dBm	W	Result
2402	0	27.49	0.561	Complies
2441	39	27.03	0.505	Complies
2480	78	27.10	0.513	Complies




- See next pages for actual measured spectrum plots.

Minimum Standard:	< 1W
--------------------------	------

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Peak Output Power



3.2.6 Band Edge

Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

VBW = 100 kHz

Span = 10 MHz

Detector function = peak



Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.



Minimum Standard:	> 20 dBc
--------------------------	----------

Measurement Setup



Same as the Chapter 3.2.1 (Figure 1)

Band - edge (with Hopping)



Band - edge (without Hopping)





**Band - edge (at 20 dB blow) – Low channel
Frequency Range = 30 MHz ~ 10th harmonic.**



Band - edge (at 20 dB blow) – Mid channel
Frequency Range = 30 MHz ~ 10th harmonic.



**Band - edge (at 20 dB blow) – High channel
Frequency Range = 30 MHz ~ 10th harmonic.**



3.2.7 Field Strength of Harmonics

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10th harmonic.

RBW = 100 kHz (30MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz

Trace = max hold

Peak mode: VBW = 1 MHz

Average mode: VBW = 10Hz

Detector function = Peak & average

Sweep = auto

Measurement Data:

→ Refer to the Next page

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data: Peak mode

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
1804.6	61.7	1829.8	64.1	1855.4	63.7
2706.9	49.3	2744.7	50.3	2783.1	55.2
-	-	-	-	-	-
-	-	-	-	-	-
Measurement uncertainty		± 6 dB			

Note: Emissions attenuated more than 20 dB below the permissible value are not reported.

Measurement Data: Average mode

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
1805	50.7	1829.8	52.7	1855.4	52.1
2733	38.3	2744.7	41.5	2783.1	45.8
-	-	-	-	-	-
-	-	-	-	-	-
Measurement uncertainty		± 6 dB			

Note: Emissions attenuated more than 20 dB below the permissible value are not reported.

Measurement Data:




243 Jukug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel: +82-31-3236008,9
Fax: +82-31-3236010

EUT/Model No.: Smart RF GUN(UHF)

TEST MODE:

Temp Humi : 33 / 50

Tested by: B. S. KIM



3.2.8 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency


AC Conducted Emissions –Line



243 Jukug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel +82-31-323-6008
Fax +82-31-323-6010

EUT / Model No. : Smart RF GUN(UHF) Phase : LINE
Test Mode : Test Power : 120 / 60
Temp./Humi. : 24 / 54 Test Engineer : B.S.KIM

Data: 541 File: E:\00_e3 EMI DATA\2007\LT A_Conduction_0706_1.EMI (542) Date: 2007-06-25
Level (dBuV)



Freq MHz	RD QP dBuV		RD AV dBuV		C. F		Result dBuV	Result dBuV	Limit dBuV	Limit dBuV	Margin dB	Margin dB
	QP	AV	QP	AV	QP	AV						
0.199	50.00	38.92	0.19	50.19	39.11	63.67	53.67	13.48	14.56			
0.330	40.20	35.33	0.31	40.51	35.64	59.44	49.44	18.93	13.80			
0.464	35.90	34.08	0.33	36.23	34.41	56.63	46.63	20.40	12.22			
0.595	28.10	27.20	0.29	28.39	27.49	56.00	46.00	27.61	18.51			
0.661	29.10	27.14	0.30	29.40	27.44	56.00	46.00	26.60	18.56			
1.331	27.30	26.63	0.35	27.65	26.98	56.00	46.00	28.35	19.02			
1.396	28.77	26.72	0.36	29.13	27.08	56.00	46.00	26.87	18.92			
5.031	22.87	21.24	0.55	23.42	21.79	60.00	50.00	36.58	28.21			
5.713	23.40	21.46	0.58	23.98	22.04	60.00	50.00	36.02	27.96			
6.951	22.54	20.16	0.54	23.08	20.70	60.00	50.00	36.92	29.30			

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


AC Conducted Emissions -Neutral



243 Jukug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel +82-31-323-6008
Fax +82-31-323-6010

EUT / Model No. : Smart RF GUN(UHF) Phase : NEUTRAL
Test Mode : Test Power : 120 / 60
Temp./Humi. : 24 / 54 Test Engineer : B.S.KIM

Data: 542 File: E:\00_e3 EMI DATA\2007\LT A_Conduction_0706_1.EMI (542) Date: 2007-06-25
Level (dBuV)



Freq MHz	RD QP	RD AV	C. F	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.198	44.13	40.63	0.20	44.33	40.83	63.71	53.71	19.38	12.88
0.264	40.99	38.15	0.24	41.23	38.39	61.29	51.29	20.06	12.90
0.330	36.93	34.76	0.31	37.24	35.07	59.44	49.44	22.20	14.37
0.529	---	33.35	0.28	0.00	33.63	0.00	46.00	0.00	12.37
0.529	35.04	---	0.28	35.32	0.00	56.00	0.00	20.68	0.00
0.661	30.11	28.85	0.29	30.40	29.14	56.00	46.00	25.60	16.86
1.388	28.74	27.21	0.34	29.08	27.55	56.00	46.00	26.92	18.45
2.448	27.66	26.78	0.51	28.17	27.29	56.00	46.00	27.83	18.71
6.488	22.74	21.88	0.53	23.27	22.41	60.00	50.00	36.73	27.59
6.627	---	21.29	0.52	0.00	21.81	0.00	50.00	0.00	28.19
20.924	15.21	8.43	1.35	16.56	9.78	60.00	50.00	43.44	40.22

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	8594E	3649A03649	HP	Apr-08
2	Signal Generator	8648C	3623A02597	HP	Apr-08
3	Attenuator (3dB)	8491A	37822	HP	Nov-07
4	Attenuator (10dB)	8491A	63196	HP	Nov-07
5	EMI Test Receiver	ESVD	843748/001	R&S	Jan-08
6	LISN	KNW-407	8-1430-1	Kyoritsu	Jan-08
7	Two-Line V-Network	ESH3-Z5	893045/017	R&S	Jan-08
8	RF Amplifier	8447D	2949A02670	HP	Jan-08
9	RF Amplifier	8447D	2439A09058	HP	Jan-08
10	RF Amplifier	8449B	3008A02126	HP	Apr-09
11	Test Receiver	ESHS10	828404009	R&S	Jan-08
12	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Jul-07
13	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-09
14	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-09
15	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-09
16	Horn Antenna	BBHA 9120D	0499	Schwarzbeck	Jun-07
17	Dipole Antenna	VHA9103	2116	Schwarzbeck	Nov-07
18	Dipole Antenna	VHA9103	2117	Schwarzbeck	Nov-07
19	Dipole Antenna	UHA9105	2261	Schwarzbeck	Nov-07
20	Dipole Antenna	UHA9105	2262	Schwarzbeck	Nov-07
21	Spectrum Analyzer	8591E	3649A05888	HP	Jan-08
22	Spectrum Analyzer	8563E	3425A02505	HP	Apr-08
23	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Feb-08
24	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	Jun-07
25	RF Switch	MP59B	6200414971	ANRITSU	Jun-07
26	RF Switch	MP59B	6200438565	ANRITSU	Jun-07
27	Power Divider	11636A	6243	HP	Nov-07
28	DC Power Supply	6622A	3448A03079	HP	Oct-07
29	Attenuator (30dB)	11636A	6243	HP	Nov-07
30	Frequency Counter	5342A	2826A12411	HP	Apr-08
31	Power Meter	EPM-441A	GB32481702	HP	Apr-08
32	Power Sensor	8481A	2702A64048	HP	Apr-08
33	Audio Analyzer	8903B	3729A18901	HP	Nov-07
34	Modulation Analyzer	8901B	3749A05878	HP	Nov-07
35	TEMP & HUMIDITY Chamber	YJ-500	L05022	Jin Young Tech	Oct-07
36	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-09