

Analysis Report

FCC ID: RQUTT-9913BT

The Equipment Under Test (EUT) is a Stereo Turntable with Bluetooth Receiver and Record Storage Compartment. It can accept input sources such as analog Aux-in (3.5mm phone jack), Phono (Long-Play Record), USB flash memory playback and wireless Bluetooth device. The Bluetooth module in the EUT is operating in the frequency range from 2402MHz to 2480MHz (79 channels with 1MHz channel spacing). The audio signal is amplified and fed to the built-in stereo loudspeakers. The EUT has an analog line-out. It is powered by 120VAC only.

2.4GHz Bluetooth Module:

Modulation Type: GFSK

Antenna Type: Integral, Internal (PCB Trace)

Frequency Range: 2402MHz - 2480MHz, 1MHz channel spacing, 79 channels

Nominal field strength is 90B μ V/m @ 3m

Production Tolerance of field strength is +/- 3dB

Antenna gain is 0dBi

According to the KDB 447498:

For Bluetooth:

Based on the Maximum allowed field strength of production tolerance was 93dB μ V/m at 3m in frequency 2.480GHz, thus;

The EIRP = $[(FS^2 * D) / 30] = 0.6\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.6mW.

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 * 5 / \sqrt{2.480} \text{ mW}$

= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.